

TurboNorm

October 25, 2011

methylation

CpG island DNA methylation array data

Description

CpG island DNA methylation array data of a neuro-ectodermal cell line that was treated with a demethylating agent

Usage

```
data(methylation)
```

Format

"RGList" as defined in the package limma containing data from CpG island DNA methylation array data of a neuro-ectodermal cell line that was treated with a demethylating agent. The element "weights" of the "RGList" contains the subset of invariant fragments, those without methylation-sensitive restriction sites, as a logical vector.

Details

The data is extracted from a larger experiment described in van Iterson et al. Because the data is from a high-dense tiling array a random subset of the data was chosen for convenience in making the vignette.

References

van Iterson et al. (2010) *in preparation*.

Examples

```
data(methylation)
```

normalize.pspline *Functions for single-colour microarray data normalization using the*

Description

Modified version of `normalize.loess` and `normalize.AffyBatch.pspline` from the `affy` package uses the P-spline smoother in stead of the loess algorithm

Usage

```
normalize.pspline(mat, epsilon = 10^-2, maxit = 1, log.it = TRUE,
  verbose = TRUE, weights = rep(1, nrow(mat)), ...)
normalize.AffyBatch.pspline(abatch,
  type=c("together", "pmonly", "mmonly", "separate"), ...)
```

Arguments

<code>mat</code>	a matrix with columns containing the values of the chips to normalize.
<code>abatch</code>	an <code>AffyBatch</code> object.
<code>epsilon</code>	a tolerance value (supposed to be a small value - used as a stopping criterion).
<code>maxit</code>	maximum number of iterations.
<code>log.it</code>	logical. If TRUE it takes the log2 of <code>mat</code>
<code>verbose</code>	logical. If TRUE displays current pair of chip being worked on.
<code>weights</code>	For weighted normalization. The default is NULL, so there are no weights used.
<code>type</code>	A string specifying how the normalization should be applied. See details for more.
<code>...</code>	Graphical parameters can be supplied.

Details

This function is a modified version of the function `normalize.loess` from the `affy` package. In stead of the loess algorithm the function uses the P-spline algorithm. The `type` argument should be one of `"separate"`, `"pmonly"`, `"mmonly"`, `"together"` which indicates whether to normalize only one probe type (PM,MM) or both together or separately.

Value

Normalized `AffyBatch`

Author(s)

Maarten van Iterson and Chantal van Leeuwen

References

Laurent Gautier, Leslie Cope, Benjamin M. Bolstad and Rafael A. Irizarry (2004). `affy` -analysis of Affymetrix GeneChip data at the probe level. *Bioinformatics*, Vol. 20, no. 3, 307-315.

Paul .H.C. Eilers and Brain D. Marx (1996). Flexible smoothing with B-splines and Penalties. *Statistical Science*, Vol 11, No. 2, 89-121.

See Also

[normalize.loess](#)

Examples

```
library(affydata)

data(Dilution)
PM <- log2(pm(Dilution[,c(1,3)]))
M <- PM[,1]-PM[,2]
A <- 0.5*(PM[,1]+PM[,2])

nPM <- log2(normalize.pspline(pm(Dilution[,c(1,3)])))
nM <- nPM[,1]-nPM[,2]
nA <- 0.5*(nPM[,1]+nPM[,2])

par(mfcol=c(2,1))
plot(M~A)
plot(nM~nA)

norm <- normalize.AffyBatch.pspline(Dilution, type="pmonly")
```

panel.pspline

Panel function for adding a P-spline smoothed curves to a lattice

Description

The function panel.pspline is similar to panel.loess but show the P-spline smoothed curve.

Usage

```
panel.pspline(x, y, weights = rep(1, length(y)), nintervals = 100, type, horizontal
```

Arguments

x, y	vectors giving the coordinates of the points in the scatter plot
weights	vector of weights of with same length as the data for a weighted smoothing. Default all weights are 1.
nintervals	an integer indicating the number of intervals equal to 1 + number of knots. Currently the intervals must be larger than 10.
type	see panel.loess
horizontal	see panel.loess
col.line, lty, lwd	line colour, type and width that will be used in the plots, defaults are col=1, lty=1 and lwd=1.
...	see panel.loess

Details`?panel.loess`**Author(s)**

Maarten van Iterson and Chantal van Leeuwen

References

Deepayan Sarkar (2009). `lattice`: Lattice Graphics. R package version 0.17-26. <http://CRAN.R-project.org/package=lattice> Paul .H.C. Eilers and Brain D. Marx (1996). Flexible smoothing with B-splines and Penalties. *Statistical Science*, Vol 11, No. 2, 89-121.

See Also[panel.loess](#)**Examples**

```
library(marray)
library(lattice)
data(swirl)
data <- data.frame(M=as.vector(maM(swirl)), A=as.vector(maA(swirl)), Sample=rep(paste("A", 1:100)))

xyplot(M~A|Sample, data=data,
       panel = function(x, y) {
         panel.grid(h=-1, v= 2)
         panel.xyplot(x, y)
         panel.loess(x, y, span=0.25, col="black")
         panel.pspline(x, y, col="red", lwd=2)})
```

`pspline`*Function for two-colour microarray data normalization using the*

Description

Wrapper function for two colour microarray data normalization using the P-spline smoother suitable for a `RGList`- or `MarrayRaw`-objects.

Usage

```
pspline(object, background = c("none", "subtract"), weights = NULL,
        nintervals = 100, subset=NULL, showArrays = 0, verbose=FALSE,
        line.col=2, line.lty=1, line.lwd=2, ...)
```

Arguments

<code>object</code>	either a RGList or an MarrayRaw-object.
<code>background</code>	for background subtraction use 'subtract'. Default is no background subtraction.
<code>weights</code>	vector of weights that will be used a for a weighted normalization. The default NULL assume equal weight 1 for all data points.
<code>nintervals</code>	number of bins in which the data will be divided. The default is 100 bins.
<code>showArrays</code>	either a integer(> 0) or a vector of integers indicating the arrays for which a MA-plot will be produced.
<code>subset</code>	subset of the data on which the normalization will be based. A special case of weighted normalization.
<code>verbose</code>	if TRUE gives additional information on the fit.
<code>line.col</code> , <code>line.lty</code> , <code>line.lwd</code>	line colour, type and width that will be used in the plots, defaults are <code>col=2</code> , <code>lty=1</code> and <code>lwd=2</code> .
<code>...</code>	additional graphical arguments for plotting.

Details

if necessary?

Value

The value that will be returned is either a MAList or MarrayNorm-object depending on the input type.

Author(s)

Chantal van Leeuwen and Maarten van Iterson

References

Paul .H.C. Eilers and Brain D. Marx (1996). Flexible smoothing with B-splines and Penalties. Statistical Science, Vol 11, No. 2, 89-121.

See Also

[normalizeWithinArrays](#), [maNormMain](#)

Examples

```
library(marray)
data(swirl)

x <- pspline(swirl, showArrays=2, pch=20, col="grey")
x <- pspline(swirl, showArrays=2:4, line.col="green")
```

TurboNorm-package *A fast scatterplot smoother with applications for microarray*

Description

A fast scatterplot smoother based on B-splines with second order difference penalty. Functions for microarray normalization of single-colour data i.e. Affymetrix/Illumina and two-colour data supplied as marray MarrayRaw-objects or limma RGList-objects are available.

Details

Package:	TurboNorm
Type:	Package
Version:	1.0
Date:	2010-09-15
License:	LGPL
LazyLoad:	yes

This package contains a implementation of piecewise constant P-splines of Eilers and Marx (1996) that can be used for normalization of either single- or two-colour data. For two-colour data objects of type RGList from the limma package and MarrayRaw from the package marray can be normalized using the function `pspline()`. For single colour microarray data wrapper functions are written based on the affy package functions `normalize.loess()` and `normalize.AffyBatch.loess()` namely `normalize.pspline()` and `normalize.AffyBatch.pspline()`. Also a `panel.pspline()` is available for adding the smoothed curve to lattice graphics panels.

Note

The package `pspline` (S original by Jim Ramsey, R port by Brian Ripley) implements the B-spline/Natural Cubic Spline smoother

Author(s)

Chantal van Leeuwen and Maarten van Iterson Maintainer: Maarten van Iterson<M.van_Iterson.HG@lumc.nl>

References

Paul .H.C. Eilers and Brain D. Marx (1996). Flexible smoothing with B-splines and Penalties. Statistical Science, Vol 11, No. 2, 89-121.

See Also

[turbotrend](#), [pspline](#), [normalize.pspline](#), [normalize.AffyBatch.pspline](#), [panel.pspline](#)

turbotrend

*turbotrend: a fast scatterplot smoother***Description**

A fast scatterplot smoother based on B-splines with second order difference penalty

Usage

```
turbotrend(x, y, w = rep(1, length(y)), n = 100,
           lambda=10^seq(-10, 10, length=1000),
           method=c("original", "demmler"))
```

Arguments

<code>x, y</code>	vectors giving the coordinates of the points in the scatter plot.
<code>w</code>	vector of weights of with same length as the data for a weighted smoothing. Default all weights are 1.
<code>n</code>	an integer indicating the number of intervals equal to 1 + number of knots. Currently the intervals must be larger than 10.
<code>lambda</code>	Optionally a user-defined penalty parameter can be provided, if not generalized cross-validation is used to find the optimal penalty parameter.
<code>method</code>	method for solving the system of linear equations either using the data in the original space or transformed to the Demmler-Reinsch basis.

Details

some details about implementation

Value

An object of type `pspline` is returned as a list with the following items:

<code>x</code>	original data vector <code>x</code>
<code>y</code>	fitted <code>y</code> -values with same length as vector <code>x</code>
<code>w</code>	vector of weights
<code>n</code>	number of bins
<code>ytrend</code>	binned fitted <code>y</code> -values
<code>xtrend</code>	binned <code>x</code> -values
<code>lambda</code>	if scalar penalty parameter used else if vector of two lower and upper bound of the grid
<code>gcv</code>	generalized cross-validation
<code>edf</code>	effective degrees of freedom (trace of the smoother matrix)
<code>call</code>	function call which produced this output

Author(s)

Maarten van Iterson, Chantal van Leeuwen

References

Paul .H.C. Eilers and Brain D. Marx (1996). Flexible smoothing with B-splines and Penalties. *Statistical Science*, Vol 11, No. 2, 89-121.

See Also

[loess](#), [lowess](#), [smooth](#), [smooth.spline](#) and [smooth.Pspline](#)

Examples

```
library(marray)
data(swirl)

x <- maA(swirl)[,1]
y <- maM(swirl)[,1]
xord <- x[order(x)]
yord <- y[order(x)]

plot(xord, yord, main = "data(swirl) & smoothing splines + lowess")
lines(turbotrend(xord, yord), col = "red", lwd=2)
lines(smooth.spline(xord, yord), col = "green", lwd=2)
lines(lowess(xord, yord), col = "purple", lwd=2)
legend("topleft", c("piecewise constant P-splines", "Cubic B-splines", "lowess"), text.co
```


Index

- *Topic **datasets**
 - methylation, 1
- *Topic **hplot**
 - panel.pspline, 3
- *Topic **package**
 - TurboNorm-package, 6
- *Topic **regression**
 - turbotrend, 7
- *Topic **smooth**
 - normalize.pspline, 2
 - pspline, 4
 - turbotrend, 7

- AffyBatch, 2

- loess, 8
- lowess, 8

- maNormMain, 5
- methylation, 1

- normalize.AffyBatch.pspline, 6
- normalize.AffyBatch.pspline
(*normalize.pspline*), 2
- normalize.loess, 2, 3
- normalize.pspline, 2, 6
- normalizeWithinArrays, 5

- panel.loess, 3, 4
- panel.pspline, 3, 6
- pspline, 4, 6

- smooth, 8
- smooth.Pspline, 8
- smooth.spline, 8

- TurboNorm-package, 6
- turbotrend, 6, 7