

Package ‘affycoretools’

October 7, 2014

Date 2008-12-15

Title Functions useful for those doing repetitive analyses with Affymetrix GeneChips.

Version 1.36.1

Author James W. MacDonald

Description Various wrapper functions that have been written to streamline the more common analyses that a core Biostatistician might see.

Maintainer James W. MacDonald <jmacdon@u.washington.edu>

License Artistic-2.0

Depends affy, Biobase, GO.db

Imports biomaRt, limma, GOSTats, annotate, annaffy, genefilter, gcrma, splines, xtable, AnnotationDbi, lattice, gplots, R2HTML, oligoClasses, ReportingTools, hwriter

Suggests affydata, hgfocscdf, rgl, BiocStyle, knitr

biocViews ReportWriting, Microarray, OneChannel, GeneExpression

VignetteBuilder knitr

Collate 'affystart.R' 'biomartfuns.R' 'foldFilt.R' 'geneSetTables.R' 'getfdfil.R' 'hyperGtable.R' 'limma2annaffy.R' 'mirnaFuns.R' 'plotma.R' 'probes2table.R' 'reportingTools.R' 'vennSelect.R' 'zzz.R' 'affycoretools.R'

R topics documented:

affycoretools	2
affystart	3
annBM	4
dataAndHeatmapPage	5
entrezLinks	6
foldFilt	7
foldFiltBM	8

geneSetPage	10
getMainProbes	12
getUniqueLL	12
gsHeatmap	13
hyperG2annaffy	14
hyperGoutput	15
limma2annaffy	18
limma2biomaRt	19
makeHmap	21
makeImages	23
makeVenn	24
maplot	26
mirna2mrna	27
outputRomer	28
plotDeg	29
plotPCA	30
probes2table	32
probes2tableBM	33
runRomer	34
venn4Way	36
vennCounts2	37
vennPage	38
vennSelect	39
vennSelect2	41
vennSelectBM	43
vennSelectFC	45
writeFit	46

Index **48**

affycoretools	<i>Make repetitive analyses of microarray and RNA-Seq data simpler with affycoretools.</i>
---------------	--

Description

The affycoretools package is primarily intended to make analyses of Affymetrix GeneChip data simpler and more straightforward. There are any number of packages designed for preprocessing or analyzing Affy data, but there are not so many that help streamline the analysis to help create useful output that can be given to collaborators.

Details

The affycoretools package is primarily intended to be used as a way to do reproducible research, where the analysis and documentation are all held in a single file, that is then processed by R to create the output data, as well as a nicely formatted pdf that documents the analysis. The affycoretools package can be used with either Sweave or knitr documents, although these days knitr is really the way to go.

In addition, affycoretools can be used with either annaffy or ReportingTools to create useful output in HTML or text format to share with your collaborators. However, ReportingTools is being actively developed and maintained, whereas annaffy is not, so the intention is to slowly convert all the functions to primarily use ReportingTools.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

affystart

Pre-processing for Affymetrix Data

Description

This function is designed to automatically read in all cel files in a directory, make all pre-processing QC plots and compute expression measures.

Usage

```
affystart(..., filenames = NULL, groups = NULL,
  groupnames = NULL, plot = TRUE, pca = TRUE,
  squarepca = FALSE, plottype = "pdf",
  express = c("rma", "mas5", "gcrma"), addname = NULL,
  output = "txt", annotate = FALSE,
  ann.vec = c("SYMBOL", "GENENAME", "ENTREZID", "UNIGENE", "REFSEQ"))
```

Arguments

...	Requires that all variables be named.
filenames	If not all cel files in a directory will be used, pass a vector of filenames.
groups	An integer vector indicating the group assignments for the PCA plot.
groupnames	A character vector with group names for PCA legend.
plottype	What type of plot to save. Can be "pdf", "postscript", "png", "jpeg", or "bmp". Defaults to "pdf". Note that "png" and "jpeg" may not be available on a given computer. See the help page for capabilities and png for more information.
plot	Should density and degradation plots be made? Defaults to TRUE.
pca	Should a PCA plot be made? Defaults to TRUE.
squarepca	Should the y-axis of the PCA plot be made comparable to the x-axis? This may aid in interpretation of the PCA plot. Defaults to FALSE.
express	One of either rma, mas5, gcrma. Defaults to rma. Partial matching OK.
addname	Used to append something to the name of the pca plot and the expression values output file (e.g., if function is run twice using different methods to compute expression values).
output	What format to use for the output of expression values. Currently only supports text format.
annotate	Boolean. Add annotation data to the output file?
ann.vec	A character vector of annotation data to add to the output file.

Value

Returns an ExpressionSet.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

plotHist, plotDeg, plotPCA

annBM

Select Available Annotation from a Biomart

Description

These functions are designed to do two things that are useful for an end user. If called with no arguments, they will output a character vector of annotation sources that are typically available from a Biomart database. If called with a 'mart' connection (typically created by a call to [useMart](#)), they will return a character vector of annotation sources that exist for that particular Biomart and species. If called with a 'mart' connection and a character vector of annotation sources, they will return a list that is intended to be used by other functions for creating HTML pages. This last function doesn't have any real utility for the end user.

Usage

```
annBM(mart, annot, species)
```

Arguments

mart	A 'mart' connection, typically created by a call to useMart .
annot	A character vector of annotation sources. This is not typically useful for an end user to specify.
species	A species name, of the form e.g., 'hsapiens'

Details

The purpose of these functions is to either give an example of typical annotation sources that may be available at a particular Biomart, or to output those sources that are known to exist at a Biomart.

linksBM is intended to list those annotation sources that may be turned into hyperlinks whereas annBM is intended to list those annotation sources that will not be linked.

These functions have only a few of the possible annotation sources, and currently there is no simple way to extend these sources. Additions to the list are possible, however. Please contact me if there is something in particular that should be included in either list.

Value

Normally called by an end user to output a character vector of annotation sources.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
annBM()
```

dataAndHeatmapPage	<i>A function to create an annotated HTML table for all genes in a significant gene set as well as a heatmap of these data.</i>
--------------------	---

Description

This is intended to be an internal function to runRomer. It is documented here only because it may be necessary to pass alternative arguments to this function from runRomer.

Usage

```
dataAndHeatmapPage(eset, fit, ind, columns = NULL,
  annot = NULL, fname, heatmap, title, key = TRUE,
  fitind = NULL)
```

Arguments

eset	An ExpressionSet containing normalized, summarized gene expression data.
fit	An MArrayLM object.
ind	Numeric vector indicating which rows of the ExpressionSet to use.
columns	Numeric vector indicating which columns of the ExpressionSet to use. If NULL, all columns will be used.
annot	Character. The name of the annotation package for the array used. If NULL, data will be output without any additional annotation.
fname	The filename of the resulting output, without the 'html' file extension.
heatmap	Character. The filename of the heatmap to append to the bottom of the HTML page.
title	Title to be placed at the top of the resulting HTML page.
key	Character. The filename of the heatmap key to append to the bottom of the HTML page.
fitind	Numeric. Which column of the MArrayLM object to use for output in the HTML table.

Details

This function creates an annotation table using `probes2table` if an annotation file is used, otherwise data will be output in a simple HTML table. A heatmap showing the expression values for all the genes in the gene set is then placed below this table, along with a key that indicates the range of the expression values.

Author(s)

James W. MacDonald

entrezLinks

Add links to data when using ReportingTools

Description

These functions are intended to add links to the Affymetrix, Entrez Gene, and AmiGO databases when creating HTML tables using ReportingTools.

Usage

```
entrezLinks(df, ...)
```

Arguments

<code>df</code>	A data.frame, usually created using the <code>select</code> function of the AnnotationDbi package. For Entrez ID data, the column name must be <code>ENTREZID</code> . For Affy data, the column name must be <code>PROBEID</code> , and for GO data the column name must be <code>Term</code> . Any other names will fail.
<code>...</code>	Allows one to pass arbitrary arguments to lower level functions. Currently unsupported.

Details

These functions are not actually intended to be called directly. Instead, they are used as targets for the `.modifyDF` argument of the `publish` function of ReportingTools. See the example below for more detail.

Value

A data.frame is returned, with links included.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
## Not run:
## say we have an ExpressionSet from HuGene 1.0 ST array
## and fit a model using limma
fit <- lmFit(eset, design)
fit2 <- eBayes(fit)
## now annotate the genes using select()
fit2$genes <- select(hugene10sttranscriptcluster.db, featureNames(eset),
c("ENTREZID", "SYMBOL"))
## and create an HTML page with links to Affy and Entrez
out <- topTable(fit2, coef=2)
htab <- HTMLReport("The title", "a_short_name")
publish(out, htab, .modifyDF = list(affyLinks, entrezLinks))
finish(htab)
## End(Not run)
```

foldFilt

Output Fold Change Data

Description

This function is designed to take an ExpressionSet and some comparisons and output either HTML tables, text files, or both.

Usage

```
foldFilt(object, fold = 1, groups, comps, compnames,
save = FALSE, text = TRUE, html = TRUE,
filterfun = NULL)
```

Arguments

object	An ExpressionSet object
fold	The log fold change cutoff to use. Note that this is log base two.
groups	A vector of group identifiers. Probably easiest to use a numeric vector
comps	A list containing all the comparisons to be made. Each list item should be a vector of length two. See details for more information.
compnames	A character vector of the names for each of the comparisons to be made. This will be the name of the resulting HTML or text file.
save	Boolean. If TRUE, a list will be returned. The first item in the list will be a vector showing the number of 'significant' genes for each comparison. The second item will be a matrix of -1's, 0's and 1's indicating a significant difference, and the direction of the difference. The first item is useful for creating Sweave - based reports and the second is useful for making Venn diagrams using the vennDiagram from the limma package.
html	Boolean - if TRUE, output HTML tables

text	Boolean - if TRUE, output text tables
filterfun	A filtering function, created by genefilter to filter the data using additional criteria. See details for more information

Details

This function is useful for outputting annotated gene lists for multiple fold change comparisons. The genes will be ordered by the absolute fold change. Note that this function is essentially a wrapper to call `annaffy`, so is only useful for Affymetrix GeneChips for which there is an annotation package.

Without attaching a data file to this package, it is not possible to give a working example. Instead, here is a 'for instance'.

Say you have an `ExpressionSet` containing four Affy HG-U133Plus2 chips. There is no replication, and you simply want to output genes with a two-fold or greater difference between the first chip and each of the last three (the first chip is the control, and the other three are experimentals). The `ExpressionSet` is called `eset`.

Additionally, say we don't want any genes called significant if both of the samples have very low expression. We can set up a filter using the `genefilter` package.

```
f1 <- kOverA(1,6)
```

```
filt <- filterfun(f1)
```

```
foldFilt(eset, groups=1:4, comps=list(c(2, 1), c(3, 1), c(4, 1)), compnames=c("Expt1-Cont", "Expt2-Cont", "Expt3-Cont"), filterfun = filt)
```

This will output three HTML tables called 'Expt1-Cont.html', etc., each containing sorted genes that have two-fold or greater differences between the two samples.

Value

Returns a list; see above for the elements of the list. This function is mainly called for the side effect of outputting HTML or text files containing annotated 'significant' gene lists.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

foldFiltBM

Output Fold Change Data using biomaRt

Description

This function is designed to take an `ExpressionSet` and some comparisons and output HTML tables. It is very similar to `foldFilt` except it uses the `biomaRt` package to annotate genes and the `annotate` package to create the HTML table(s).

Usage

```
foldFiltBM(object, fold = 1, groups, comps, compnames,
           species, links = linksBM()[1:3],
           otherann = annBM()[1:3], filterfun = NULL,
           ann.source = "entrezgene", affyid = FALSE, html = TRUE,
           text = TRUE, save = FALSE)
```

Arguments

object	An ExpressionSet object
fold	The log fold change cutoff to use. Note that this is log base two.
groups	A vector of group identifiers. Probably easiest to use a numeric vector
comps	A list containing all the comparisons to be made. Each list item should be a vector of length two. See details for more information.
compnames	A character vector of the names for each of the comparisons to be made. This will be the name of the resulting HTML or text file.
species	The species name. This must be in a particular format for biomaRt. An example for human is "hsapiens" or for mouse is "mmusculus".
links	A character vector of things to annotate with hyperlinks to online databases. See linksBM for possible values.
otherann	A character vector of things to annotate with text only (i.e., no hyperlinks). See annBM for possible values.
filterfun	A filtering function created by genefilter to filter the data using additional criteria. See details for more information
ann.source	The annotation source of the IDs that will be used to annotate the genes. The default value is "entrezgene". See details for other possibilities.
affyid	Boolean. Are the IDs used to annotate these data Affymetrix IDs?
html	Boolean. Output HTML tables? Defaults to TRUE
text	Boolean. Output text tables? Defaults to TRUE
save	Boolean. If TRUE, a list will be returned. The first item in the list will be a vector showing the number of 'significant' genes for each comparison. The second item will be a matrix of -1's, 0's and 1's indicating a significant difference, and the direction of the difference. The first item is useful for creating Sweave - based reports and the second is useful for making Venn diagrams using vennDiagram from the limma package.

Details

This function is useful for outputting annotated gene lists for multiple fold change comparisons. The genes will be ordered by the absolute fold change.

This function currently only supports Affymetrix data. It is designed for Affymetrix chips that don't have an annotation package, which includes data that have been analyzed using the 're-mapped' CDFs supplied to BioC by MBNI at University of Michigan.

The IDs that will be used to annotate the genes depend on the source of the data. If, for example, one is using an Affymetrix chip that doesn't have a BioC annotation package, then the IDs will be Affymetrix IDs. To find out the correct name to use for the `ann.source` argument, one can create a connection to a Biomart database using `useMart` and then get a list of available Affy arrays using `getAffyArrays`.

If one is using one of the re-mapped CDFs from MBNI at University of Michigan, then the IDs to use depend on the mapping used to create the CDF. At this time, only three types of CDFs can be used; EntrezGene, UniGene, and RefSeq. One can determine the correct `ann.source` argument by creating a connection to a Biomart database, and then calling `linksBM(mart, linksBM()[[3]])`.

One can also protect against selecting probesets that have very small expression values for all samples (which likely have a large fold change due to noise, rather than signal) by using the `filterfun` argument. An example would be:

```
f <- kOverA(1, 6)
filt <- filterfun(f)
```

Then add `filterfun = filt` as an argument to the call to `foldFilt`.

Value

Returns a list; see above for the elements of the list. This function is mainly called for the side effect of outputting HTML or text files containing annotated 'significant' gene lists.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

geneSetPage	<i>A function to create an HTML page for each gene set, as well as the HTML pages for each significant gene set.</i>
-------------	--

Description

This is intended to be an internal function to `runRomer`, and is not intended to be called by end users. However, the `...` argument to `runRomer` allows one to pass arguments to lower level functions, so the arguments are described here.

Usage

```
geneSetPage(rsalts, genesets, eset, fit, file,
  cutoff = 0.05, dir = ".", subdir = ".", columns = NULL,
  colnames = NULL, col = NULL, caption = NULL,
  annot = NULL, nam = NULL, fitind = NULL, bline = NULL,
  ...)
```

Arguments

rslts	The results from running romer on one gene set.
genesets	Character. A vector of gene symbols for one gene set.
eset	An ExpressionSet containing normalized, summarized gene expression data.
fit	An MArrayLM object, containing the fitted data.
file	Filename for the resulting HTML page.
cutoff	Numeric. The cutoff for significance for a given gene set. Defaults to 0.05.
dir	The directory to write the results. Defaults to the working directory.
subdir	The subdirectory to write the individual gene set results. Defaults to the working directory.
columns	Numeric. The columns of the ExpressionSet to use for the individual gene set output pages. See dataAndHeatmapPage for more information.
colnames	Character. Alternative column names for the resulting heatmap. See dataAndHeatmapPage for more information.
col	A vector of colors for the heatmap. Defaults to bluered .
caption	Caption to put at the top of the HTML page.
annot	Character. The name of the annotation package for the array used. If NULL, the row names of the heatmap will be the probeset IDs unless the 'nam' argument below is used.
nam	Character. The row names for the resulting heatmap. If NULL and no 'annot' argument is used, the probeset IDs will be used for the row names.
fitind	Numeric. The columns of the MArrayLM object to use for the individual HTML tables.
bline	Defaults to NULL. Otherwise, a numeric vector indicating which columns of the data are the baseline samples. The data used for the heatmap will be centered by subtracting the mean of these columns from all data.
...	Allows arguments to be passed to lower-level functions. See dataAndHeatmapPage and gsHeatmap for available arguments.

Details

This function creates a 'midlevel' HTML table that contains each gene set that was significant, with a link to an HTML table that shows data for each gene in that gene set (with annotation), as well as a heatmap showing the expression levels. Normally this is not run by end users, but is called as part of the [runRomer](#) function.

Value

Nothing is returned. Called only for the side effect of creating HTML tables.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

getMainProbes	<i>Remove control probesets from ST arrays</i>
---------------	--

Description

This function is designed to remove all but the 'main' type of probesets from the Gene ST array types.

Usage

```
getMainProbes(input)
```

Arguments

input	Either a character string (e.g., "pd.hugene.1.0.st.v1") or a FeatureSet object.
-------	---

Value

If the argument is a character string, returns a data.frame containing probeset IDs along with the probeset type, that can be used to subset e.g., an ExpressionSet of Gene ST data, or an MArrayLM object created from Gene ST data. Note that the order of the probesets is not guaranteed to match the order in your ExpressionSet or MArrayLM object, so that should be checked first. If the argument is a FeatureSet object, it returns a FeatureSet object with only main probes remaining.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

getUniqueLL	<i>Subset a Vector of Probesets</i>
-------------	-------------------------------------

Description

This function will take a vector of Affy IDs and return a vector of Entrez IDs that have replicated IDs removed. The resulting vector will still have the corresponding Affy IDs appended as names, which is important for some functions.

Usage

```
getUniqueLL(probes, annot)
```

Arguments

probes	A vector of probe IDs
annot	The annotation package for the chip used

Details

Subsetting a set of Affy IDs to unique Entrez Gene IDs is a common thing to do prior to doing a hypergeometric test. Functions such as [hyperGTest](#) can use un-named vectors of Entrez IDs (e.g., `unique(getLL(probeIDs, annot))`), but there is some functionality that requires the Entrez Gene IDs to be in a named vector, with the names being the associated Probeset IDs.

As an example, `hyperGoutput` will only work correctly if the input Entrez ID vector is named with the associated Probeset IDs.

Value

A named vector of unique Entrez IDs

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

 gsHeatmap

A function to create a simple heatmap and key.

Description

This is an internal function called by `runRomer` and is not intended to be used directly. It is documented here only because arguments may be passed down via the `dots` argument.

Usage

```
gsHeatmap(eset, ind, filename, columns = NULL,
          colnames = NULL, col = NULL, annot = NULL, nam = NULL,
          scale.row = FALSE, key = TRUE, bline = NULL)
```

Arguments

<code>eset</code>	An ExpressionSet containing normalized, summarized gene expression data.
<code>ind</code>	Numeric vector indicating which rows of the ExpressionSet to use.
<code>filename</code>	The filename for the heatmap and associated key.
<code>columns</code>	Numeric vector indicating which columns of the ExpressionSet to use. If <code>NULL</code> , all columns will be used.
<code>colnames</code>	Character. Substitute column names for the heatmap. If <code>NULL</code> , the <code>sampleNames</code> will be used.
<code>col</code>	A vector of colors to use for the heatmap. If <code>NULL</code> , the bluered function will be used.
<code>annot</code>	Character. The name of the array annotation package to use to convert probeset IDs to gene symbols. If <code>NULL</code> , either the probeset IDs will be used, or the input from the <code>'nam'</code> argument below will be used.

nam	Character. A vector of row.names to use for the heatmap. If NULL, and the above 'annot' argument is NULL as well, probeset IDs will be used.
scale.row	Boolean. Should the data be scaled by row? Defaults to FALSE.
key	Boolean. Should a key be produced that shows the numeric range for the colors of the heatmap? Defaults to TRUE.
bline	A numeric vector, usually extracted from a contrast matrix, used to 'sweep' the mean baseline sample means from the heatmap data. The end result will be a heatmap in which the colors correspond to log fold changes from the baseline samples.

Details

As noted above, this is only intended to be called indirectly by runRomer. However, certain arguments such as scale.row, or col, etc, can be passed down to this function via the dots argument, allowing the end user to have more control over the finished product.

Value

Nothing is returned. Called only for the side effect of creating heatmaps in 'png' format.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

hyperG2annaffy

HTML tables from GOIDs

Description

Output HTML tables containing the 'enriched' genes for each GO term resulting from a call to hyperGtable.

Usage

```
hyperG2annaffy(probids, lib, eset, fit = NULL,
               subset = NULL, comp = 1, type = "MF", pvalue = 0.05,
               min.count = 10)
```

Arguments

probids	A vector of Affymetrix probe IDs
lib	An annotation package (e.g., hgu95av2)
eset	An ExpressionSet
fit	An lmFit object. Only necessary if statistics are desired in the resulting table. Defaults to NULL.

subset	A numeric vector used to select GO terms to output (see description for more information). Defaults to NULL
comp	Which contrast/parameter estimate should be used to extract the relevant statistics? Only used if <code>fit</code> is not NULL. See description for more information.
type	One of "MF", "CC", "BP", indicating molecular function, cellular component, or biological process, respectively.
pvalue	The significance level used to choose GO terms
min.count	The minimum number of a given GO term that must be on the chip in order to choose that GO term. This protects against very low p-values that result from the situation where there are very few genes with a given GO term on the chip, but one or two are found in the set of significant genes.

Details

This function is used to create HTML tables based on the output of `hyperGtable`. The basic idea is as follows; as part of an analysis, say `hyperGtable` was used to create a table of 'enriched' GO terms. Unfortunately, the table only lists GO terms and the number of probesets that are annotated to those GO terms, and the client may be interested in knowing what probesets are enriched for each (or some) GO term.

The default behaviour is to output an HTML table for each GO term, containing the probesets that are annotated at that term (and that are in the set of significant genes). If only some of the GO terms are of interest, one may use the `subset` argument to select only particular rows. In addition, if the relevant t-statistics, p-values and fold changes are of interest, one can also use the `fit` argument to point to an `lmFit` object that contains these data, as well as the `comp` argument to indicate which parameter or contrast to use. Note that the `comp` argument defaults to 1, so the first parameter or contrast will be extracted by default.

Value

This function is used only for the side effect of creating HTML tables.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

hyperGoutput

Output Tables Based on Hypergeometric Test

Description

This function will output various tables containing probesets that are annotated to a particular GO, KEGG, or PFAM term. The tables are based on the results from a call to `hyperGtest`.

Usage

```
hyperGoutput(hyptObj, eset, pvalue, categorySize,
             sigProbesets, fit = NULL, subset = NULL, comp = 1,
             output = c("significant", "all", "split"),
             statistics = c("tstat", "pval", "FC"), html = TRUE,
             text = TRUE, ...)
```

Arguments

hyptObj	A HyperGResult object, usually produced by a call to hyperGTest
eset	An ExpressionSet object
pvalue	The p-value cutoff used for selecting significant GO terms. If not specified, it will be extracted from the HyperGResult object
categorySize	Number of terms in the universe required for a term to be significant. See details for more information
sigProbesets	Vector of probeset IDs that were significant in the original analysis.
fit	An MArrayLM object, produced from a call to eBayes
subset	Numeric vector used to select particular tables to output. The default is to output tables for all terms. See details for more information
comp	Numeric vector of length one, used to indicate which comparison in the MArrayLM object to use for extracting relevant statistics. See details for more information
output	One of 'selected', 'all', or 'split'. See details for more information
statistics	Which statistics to output in the resulting tables. Choices include 'tstat', 'pval', or 'FC', corresponding to t-statistics, p-values, and fold change, respectively
html	Boolean. Output HTML tables? Defaults to TRUE
text	Boolean. Output text tables? Defaults to TRUE
...	Allows end user to pass further arguments. The most notable would be an <code>anncols</code> argument, passed to <code>probes2table</code> to control the hyperlinked annotation columns. See aaf.handler for more information

Details

This function is designed to be used to output the results from a hypergeometric test for over-represented terms. This function would be used at the end of an analysis such as:

1.) Compute expression values 2.) Fit a model using `limma` 3.) Output significant probesets using `limma2annaffy` 4.) Perform hypergeometric test using [hyperGTest](#)

At step 4, one can output a list of the over-represented terms using [htmlReport](#). One might then be interested in knowing which probesets contributed to the significance of a particular term, which is what this function is designed to do.

One argument that can be passed to [htmlReport](#) (and also to `hyperGoutput`) is `categorySize`, which gives a lower bound for the number of probesets with a particular term in the universe. In other words, assume that a particular GO term is annotated to three probesets on a given chip. If, after doing a t-test to detect differentially expressed probesets, one of those probesets were found to be significantly differentially expressed and was then used to do a hypergeometric test, that GO

term would be significant, with a small p-value. However, this is probably not very strong evidence that the GO term is actually over-represented, since there were only three to begin with. By setting `categorySize` to a sensible value (such as 10), this situation can be avoided.

This function will output HTML and/or text tables containing annotation information about each probeset as well as the expression values. In addition, if `limma` were used to fit the model, the relevant statistics (t-statistic, p-value, fold change) can also be output in the table by passing the `MArrayLM` object that resulted from a

call to `eBayes`. The `statistics` argument can

be used to control which statistics are output.

By default `hyperGoutput` will output tables for all significant terms, which may end up being quite a few tables. Usually only a few terms are of interest, so there is a `subset` argument that can be used to select only those terms. This argument follows directly from the order of the table output by `htmlReport` or `summary`. For instance, if the first, third and fifth terms in the HTML table output by `htmlReport` were of interest, one would use `subset=c(1,3,5)`.

One critical step prior to the hypergeometric test is to subset the probesets to unique Entrez Gene IDs. It should be noted however, that the functions used by `hyperGoutput` will output all the probesets annotated to a particular term. The `output` argument is used to control this behavior. If `output = "significant"` (the default), then only those probesets that correspond to the original subsetting will be output. If `output = "all"`, then all probesets will be output (grouped by Entrez ID), with the 'significant' probeset first. If `output = "split"`, then all the probesets will be output, with all the 'significant' probesets first, followed by the other probesets, grouped by Entrez ID.

Note that the 'significant' probesets come from one of two sources. First, one can pass a character vector of probeset IDs corresponding to those that were significant in the original analysis (recommended). Second, if the `geneIds` slot of the `GOHyperGParams` object contains a named vector of Entrez Gene IDs, then the names from that vector will be used. This can be accomplished by using either `findLargest` or `getUniqueLL`.

Since the `geneIds` are by definition a unique set of Entrez Gene IDs, any duplicate probeset IDs will have been removed, so the first method is to be preferred for accuracy.

Value

This function returns no value, and is called solely for the side effect of outputting HTML and/or text tables.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[hyperGTest](#), [htmlReport](#), [probeSetSummary](#)

limma2annaffy

Function to Create HTML Tables from limma Objects

Description

This function is designed to take an `ExpressionSet` and an `lmFit`, `model.matrix`, and contrast object from `limma` and convert into HTML tables using `annaffy`. The alternate function `limma2annaffy.na` is designed to be run without user intervention.

Usage

```
limma2annaffy(eset, fit, design, contrast, lib,
  adjust = "fdr",
  anncols = aaf.handler()[c(1:3, 6:7, 9:12)],
  number = 30, pfilt = NULL, fldfilt = NULL,
  tstat = TRUE, pval = TRUE, FC = TRUE,
  expression = TRUE, html = TRUE, text = FALSE,
  save = FALSE, addname = NULL, addtitle = NULL,
  interactive = TRUE, natFC = FALSE)
```

Arguments

<code>eset</code>	An <code>ExpressionSet</code> containing affymetrix expression values.
<code>fit</code>	An <code>lmFit</code> object.
<code>design</code>	A <code>model.matrix</code> object.
<code>contrast</code>	A contrasts matrix from <code>limma</code> .
<code>lib</code>	An annotation package for the Affy chips used.
<code>adjust</code>	Multiplicity adjustment. Choices are "fdr", "holm", "hommel", "bonferroni", or "none". Partial matching allowed.
<code>anncols</code>	A vector of things to annotate, produced by a call to <code>aaf.handler()</code> .
<code>number</code>	Number of genes to output to table. See details for more information.
<code>pfilt</code>	A p-value to filter output. See details for more information.
<code>fldfilt</code>	A fold change to filter output. See details for more information.
<code>tstat</code>	Boolean: Output t-statistics in table? Defaults to FALSE.
<code>pval</code>	Boolean: Output (adjusted) p-values in table? Defaults to FALSE.
<code>FC</code>	Boolean: Output fold changes in table? Defaults to FALSE.
<code>expression</code>	Boolean: Output expression values in table? Defaults to TRUE.
<code>html</code>	Boolean: Output data in HTML tables? Defaults to TRUE.
<code>text</code>	Boolean: Output data in text tables? Defaults to TRUE.
<code>save</code>	Boolean: Save tables as R objects for further processing? Defaults to FALSE.

addname	A character vector to add to the end of the automatically generated output file names. Useful for multiple calls to eliminate over-writing of existing HTML or text tables.
addtitle	A character vector to add to the title for the HTML table. By default the title will be the same as the filename. If the addname argument is not NULL, then that will be appended to the filename (and will be used as the HTML title). If addtitle is not NULL, it will be appended to the filename and that will then be used as the HTML table title.
interactive	Boolean: Is this an interactive call, or run as part of a script (e.g., in an Sweave document)? Defaults to TRUE
natFC	Boolean: Add 'unlogged' fold change to output? This is intended for people who don't understand logs or fractions. If the fold change is positive, it is simply exponentiated (e.g., 2^x where x is the log fold change). If negative, we use 2^{-x} , so e.g., a log fold change of -2 will result in a -4.

Details

This function is designed to automatically output HTML or text tables, with filenames taken from the column names of the contrast matrix. The number of genes output can be controlled several different ways. First, if `pfilt` and `fldfilt` are both NULL, the top genes will be output based on the number variable. Otherwise, the genes are filtered based on p-value, fold change, or both. If the genes are filtered this way, the number of genes to be output will be listed and the filter(s) can then be adjusted if necessary.

This function currently only supports Affymetrix data.

Value

If `save` is TRUE, a list of tables from `topTable` will be output.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[topTable](#), [aafTableAnn](#)

limma2biomaRt

Function to Create HTML Tables from limma Objects using biomaRt for Annotation

Description

This function is designed to take an ExpressionSet and an `lmFit`, `model.matrix`, and contrast object from limma and convert into HTML and text tables using biomaRt. The alternate function `limma2biomaRt.na` is designed to be run without user intervention.

Usage

```
limma2biomaRt(eset, fit, design, contrast, species,
  links = linksBM()[1:3], otherdata = annBM()[1:3],
  ann.source = "entrezgene", adjust = "fdr", number = 30,
  pfilt = NULL, fldfilt = NULL, tstat = TRUE,
  pval = TRUE, FC = TRUE, expression = TRUE, html = TRUE,
  text = TRUE, save = FALSE, addname = NULL,
  interactive = TRUE, affyid = FALSE)
```

Arguments

<code>eset</code>	An ExpressionSet containing affymetrix expression values.
<code>fit</code>	An lmFit object.
<code>design</code>	A model.matrix object.
<code>contrast</code>	A contrasts matrix from limma.
<code>species</code>	The species name. This must be in a particular format for biomaRt. An example for human is "hsapiens", or for mouse "mmusculus".
<code>links</code>	A character vector of things to annotate with hyperlinks to online databases. See linksBM for possible values.
<code>otherdata</code>	A character vector of things to annotate with text only (i.e., no hyperlinks). See annBM for possible values.
<code>ann.source</code>	The annotation source of the IDs that will be used to annotate the genes. The default value is "entrezgene". See details for other possibilities.
<code>adjust</code>	Multiplicity adjustment. Choices are "fdr", "holm", "hommel", "bonferroni", or "none". Partial matching allowed.
<code>number</code>	Number of genes to output to table. See details for more information.
<code>pfilt</code>	A p-value to filter output. See details for more information.
<code>fldfilt</code>	A fold change to filter output. See details for more information.
<code>tstat</code>	Boolean: Output t-statistics in table? Defaults to FALSE.
<code>pval</code>	Boolean: Output (adjusted) p-values in table? Defaults to FALSE.
<code>FC</code>	Boolean: Output fold changes in table? Defaults to FALSE.
<code>expression</code>	Boolean: Output expression values in table? Defaults to TRUE.
<code>html</code>	Boolean: Output data in HTML tables? Defaults to TRUE.
<code>text</code>	Boolean: Output data in text tables? Defaults to TRUE
<code>save</code>	Boolean: Save tables as R objects for further processing? Defaults to FALSE.
<code>addname</code>	A character vector to add to the end of the automatically generated output file names. Useful for multiple calls to eliminate over-writing of existing HTML or text tables.
<code>interactive</code>	Boolean: Is this an interactive call, or run as part of a script (e.g., in an Sweave document)? Defaults to TRUE
<code>affyid</code>	Boolean. Are the IDs used to annotate these data Affymetrix IDs?

Details

This function is designed to automatically output HTML tables, with filenames taken from the column names of the contrast matrix. The number of genes output can be controlled several different ways. First, if `pflt` and `fldflt` are both `NULL`, the top genes will be output based on the number variable. Otherwise, the genes are filtered based on p-value, fold change, or both. If the genes are filtered this way, the number of genes to be output will be listed and the filter(s) can then be adjusted if necessary.

This function currently only supports Affymetrix data. It is designed for Affymetrix chips that don't have an annotation package, which includes data that have been analyzed using the 're-mapped' CDFs supplied to BioC by MBNI at University of Michigan.

The IDs that will be used to annotate the genes depend on the source of the data. If, for example, one is using an Affymetrix chip that doesn't have a BioC annotation package, then the IDs will be Affymetrix IDs. To find out the correct name to use for the `ann.source` argument, one can create a connection to a Biomart database using [useMart](#) and then get a list of available Affy arrays using [listFilters](#).

If one is using one of the re-mapped CDFs from MBNI at University of Michigan, then the IDs to use depend on the mapping used to create the CDF. At this time, only three types of CDFs can be used; EntrezGene, UniGene, and RefSeq. One can determine the correct `ann.source` argument by creating a connection to a Biomart database, and then calling `linksBM(mart, linksBM()[[3]])`.

Value

If `save` is `TRUE`, a list of tables from [topTable](#) will be output.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[topTable](#), [aafTableAnn](#)

makeHmap

A function to create a heatmap-like object or matrix of correlations between miRNA and mRNA data.

Description

This function is intended for use when both miRNA and mRNA data are available for the same samples. In this situation it may be advantageous to compute correlations between the two RNA types, in order to detect mRNA transcripts that are targeted by miRNA.

Usage

```
makeHmap(mRNAdat, miRNAdat, mRNA1st, mRNAvec = NULL,
         miRNAvec = NULL, chipPkg, header, plot = TRUE,
         out = TRUE)
```

Arguments

mRNA <code>dat</code>	An <code>ExpressionSet</code> , <code>data.frame</code> or matrix of mRNA expression values. The <code>row.names</code> for these data should correspond to the manufacturer's probe ID. Currently, the only manufacturer supported is Affymetrix.
miRNA <code>dat</code>	An <code>ExpressionSet</code> , <code>data.frame</code> or matrix of mRNA expression values. The <code>row.names</code> for these data should correspond to the manufacturer's probe ID. Currently, the only manufacturer supported is Affymetrix.
mRNA <code>lst</code>	A list of mRNA probe IDs where the names of each list item are mirBase miRNA IDs. Usually this will be the output from <code>mirna2mrna</code> .
mRNA <code>vec</code>	A numeric vector used to subset or reorder the mRNA data, by column. If <code>NULL</code> , this will simply be <code>1:ncol(mRNA<code>dat</code>)</code> .
miRNA <code>vec</code>	A numeric vector used to subset or reorder the miRNA data, by column. If <code>NULL</code> , this will simply be <code>1:ncol(miRNA<code>dat</code>)</code> .
chipPkg	Character. The name of the chip-specific annotation package (e.g., "hgu133plus2.db").
header	Character. The plot title if a heatmap is output.
plot	Boolean. Should a heatmap be generated?
out	Boolean. Should the matrix of correlation coefficients be output?

Details

As noted above, this function is intended to generate output from simultaneous analyses of miRNA and mRNA data for the same samples, the goal being either a heatmap like plot of correlations, or the data (or both).

If creating a plot, note that if the number of significant mRNA probes is large, the resulting heatmap will have many rows and will not plot correctly on the usual graphics device within R. In order to visualize, it is almost always better to output as a pdf. In addition, the dimensions of this pdf will have to be adjusted so the row names for the heatmap will be legible. As an example, a heatmap with 10 miRNA transcripts and 100 mRNA transcripts will likely need a pdf with a width argument of 6 and a height argument of 25 or 30. It may require some experimentation to get the correct arguments to the pdf function.

Also please note that this function by necessity outputs rectangular data. However, there will be many instances in which a given miRNA isn't thought to target a particular mRNA. Whenever this occurs, the heatmap will have a white cell, and the output data for that combination will be `NA`.

Value

This function will output a numeric matrix if the 'out' argument is `TRUE`.

Author(s)

James W. MacDonald

See Also

`mirna2mrna`

makeImages	<i>Add dotplot images</i>
------------	---------------------------

Description

A function to add dotplot glyphs and links to HTML tables

Usage

```
makeImages(df, eset, grp.factor, design, contrast,
           colind, repdir = "./reports", extraname = NULL)
```

Arguments

df	A data.frame from calling topTable. Note that the row.names for this data.frame must be consistent with the "eset" object. In other words, if "eset" is an ExpressionSet, then the row.names of the data.frame must consistent with the featureNames of the ExpressionSet.
eset	A matrix, data.frame, or ExpressionSet. If using RNA-Seq data, use voom from edgeR to create an EList object, and then pass in the "E" list item.
grp.factor	A factor that indicates which group ALL of the samples belong to. This will be subsetted internally, so do not subset yourself.
design	The design matrix used by limma or edgeR to fit the model.
contrast	The contrast matrix used by limma or edgeR to make comparisons.
colind	Which column of the contrast matrix are we using? In other words, for which comparison are we creating a table?
repdir	A directory in which to put the HTML tables. Defaults to a "reports" directory in the working directory.
extraname	By default, the tables will go in a "reports" subdirectory, and will be named based on the column name of the contrast that is specified by the colind argument (after replacing any spaces with an underscore). If this will result in name collisions (e.g., a previous file will be over-written because the resulting names are the same), then an extraname can be appended to ensure uniqueness.

Details

This function is intended to create little dotplot glyphs that can be added to an HTML table of results from e.g., a microarray or RNA-Seq experiment, showing graphically how much the different groups are changing. The glyphs have unlabeled axes to make them small enough to fit in an HTML table, and clicking on a glyph will result in a new page loading with a full sized dotplot, complete with axis labels.

This function is very similar to the stock functions in the ReportingTools package, but the standard glyphs for that package consist of a dotplot on top of a boxplot, which seems too busy to me. In addition, for most microarray analyses there are not enough replicates to make a boxplot useful.

Value

A list, two items. The first item is the input data.frame with the glyphs included, ready to be used with ReportingTools to create an HTML table. The second item is a pdf of the most differentially expressed comparison. This is useful for those who are using e.g., knitr or Sweave and want to be able to automatically insert an example dotplot in the document to show clients what to expect.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

makeVenn

High-level function for making Venn diagrams and outputting the results from the diagrams in HTML and CSV files.

Description

This function is designed to output CSV and HTML tables based on an analysis using the limma package, with output generated using the ReportingTools package.

Usage

```
makeVenn(fit, contrast, design, eset, groups = NULL,
         collist = NULL, p.value = 0.05, lfc = 0,
         method = "both", adj.meth = "BH", titleadd = NULL,
         fileadd = NULL, baseUrl = ".",
         reportDirectory = "./venns", ...)
```

Arguments

fit	An <code>MArrayLM</code> object, from a call to <code>eBayes</code> .
contrast	A contrasts matrix, produced either by hand, or by a call to <code>makeContrasts</code>
design	A design matrix.
eset	An <code>ExpressionSet</code> object.
groups	This argument is used when creating a legend for the resulting HTML pages. If <code>NULL</code> , the groups will be generated using the column names of the design matrix. In general it is best to leave this <code>NULL</code> .
collist	A list containing numeric vectors indicating which columns of the fit, contrast and design matrix to use. If <code>NULL</code> , all columns will be used.
p.value	A p-value to filter the results by.
lfc	A log fold change to filter the results by.
method	One of "same", "both", "up", "down", "sameup", or "samedown". See details for more information.
adj.meth	Method to use for adjusting p-values. Default is 'BH', which corresponds to 'fdr'. Ideally one would set this value to be the same as was used for <code>decideTests</code> .

<code>titleadd</code>	Additional text to add to the title of the HTML tables. Default is NULL, in which case the title of the table will be the same as the filename.
<code>fileadd</code>	Additional text to add to the name of the HTML and CSV tables. Default is NULL.
<code>baseUrl</code>	A character string giving the location of the page in terms of HTML locations. Defaults to "."
<code>reportDirectory</code>	A character string giving the location that the results will be written. Defaults to "./venns"
<code>...</code>	Used to pass other arguments to <code>probes2table</code> , in particular, to change the argument to <code>anncols</code> which controls the columns of hyperlinks to online databases (e.g., Entrez Gene, etc.). See aaf.handler for more information.

Details

The purpose of this function is to output HTML and text tables with lists of genes that fulfill the criteria of a call to `decideTests` as well as the direction of differential expression. This is a high-level function that calls `vennSelect2` internally, and is intended to be used with `vennPage` to create a set of Venn diagrams (on an HTML page) that have clickable links in each cell of the diagram. The links will then pass the end user to individual HTML pages that contain the genes that are represented by the counts in a given cell of the Venn diagram.

In general, the only thing that is needed to create a set of Venn diagrams is a list of numeric vectors that indicate the columns of the contrast matrix that are to be used for a given diagram. See the example below for a better explanation.

Some important things to note: First, the names of the HTML and text tables are extracted from the `colnames` of the `TestResults` object, which come from the contrasts matrix, so it is important to use something descriptive. Second, the method argument is analogous to the `include` argument from `vennCounts` or `vennDiagram`. Choosing "both" will select genes that are differentially expressed in one or more comparisons, regardless of direction. Choosing "up" or "down" will select genes that are only differentially expressed in one direction. Choosing "same" will select genes that are differentially expressed in the same direction. Choosing "sameup" or "samedown" will select genes that are differentially expressed in the same direction as well as 'up' or 'down'.

Note that this is different than sequentially choosing "up" and then "down". For instance, a gene that is upregulated in one comparison and downregulated in another comparison will be listed in the intersection of those two comparisons if "both" is chosen, it will be listed in only one comparison for both the "up" and "down" methods, and it will be listed in the union (e.g., not selected) if "same" is chosen.

Unlike `vennSelect`, this function automatically creates both HTML and CSV output files.

Value

A list containing the output from calling `vennSelect2` on the columns specified by the `collist` argument. This is intended as input to `vennPage`, which will use those data to create the HTML page with Venn diagrams with clickable links.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
## Not run:
mat <- matrix(rnorm(1e6), ncol = 20)
design <- model.matrix(~factor(1:4, each=5))
colnames(design) <- LETTERS[1:4]
contrast <- matrix(c(1,-1,0,0,1,0,-1,0,1,0,0,-1,0,1,-1,0,0,1,0,-1),
ncol = 5)
colnames(contrast) <- paste(LETTERS[c(1,1,1,2,2)],
LETTERS[c(2,3,4,3,4)], sep = " vs ")
fit <- lmFit(mat, design)
fit2 <- contrasts.fit(fit, contrast)
fit2 <- eBayes(fit2)
## two Venn diagrams - a 3-way Venn with the first three contrasts
## and a 2-way Venn with the last two contrasts
collist <- list(1:3,4:5)
venn <- makeVenn(fit2, contrast, design, eset, collist = collist)
vennPage(venn, "index.html", "Venn diagrams")

## End(Not run)
```

maplot

A Function to make MA plots from all arrays.

Description

This function creates an MA plot for all arrays in either an ExpressionSet or a matrix. A 'baseline' array is created using the median expression for each gene, and each array is then compared to the baseline array.

Usage

```
maplot(object, layout = NULL, ...)
```

Arguments

object	An ExpressionSet or matrix containing log-transformed array data.
layout	A numeric vector, length two. Best results will be obtained if both values are the same, and between 2 and 5 (e.g., c(3,3))
...	Other arguments that will be passed down to the xypLOT function from the lattice package.

Value

No output. Used only for the side effect of creating MA plots.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

 mirna2mrna

A function to map miRNA to mRNA.

Description

This function is intended use when there are miRNA and mRNA data for the same subjects, and the goal is to detect mRNAs that appear to be targeted by the miRNA.

Usage

```
mirna2mrna(miRNAids, miRNAannot, mRNAids, orgPkg,
  chipPkg, sanger = TRUE, miRNAcol = NULL,
  mRNAcol = NULL, transType = "ensembl")
```

Arguments

miRNAids	A character vector of miRNA IDs. Currently only supports Affymetrix platform.
miRNAannot	Character. The filename (including path if not in working directory) for the file containing miRNA to mRNA mappings.
mRNAids	A character vector of mRNA IDs. Currently only supports Affymetrix platform.
orgPkg	Character. The Bioconductor organism package (e.g., org.Hs.eg.db) to be used for mapping.
chipPkg	Character. The Bioconductor chip-specific package (e.g., hgu133plus2.db) to be used for mapping.
sanger	Boolean. Is the miRNAannot file a Sanger miRBase targets file? These can be downloaded from http://www.ebi.ac.uk/enright-srv/microcosm/cgi-bin/targets/v5/download.pl
miRNAcol	Numeric. If using a Sanger miRBase targets file, leave NULL. Otherwise, use this to indicate which column of the miRNAannot file contains miRNA IDs.
mRNAcol	Numeric. If using Sanger miRBase targets file, leave NULL. Otherwise, use this to indicate which column of the miRNAannot file contains mRNA IDs.
transType	Character. Designates the type of transcript ID for mRNA supplied by the miRNAannot file. If using the Sanger miRBase files, this is ensembl. Other choices include refseq and accnum.

Details

This function is intended to take a vector of miRNA IDs that are significantly differentially expressed in a given experiment and then map those IDs to putative mRNA transcripts that the mRNAs are supposed to target. The mRNA transcript IDs are then mapped to chip-specific probeset IDs, which are then subsetted to only include those probesets that were also significantly differentially expressed.

The output from this function is intended as input for [makeHmap](#).

Value

A list with names that correspond to each significant miRNA, and the mRNA probeset IDs that are targeted by that miRNA.

Author(s)

James W. MacDonald

See Also

makeHmap

outputRomer	<i>A function to create HTML output from the results of running romer on a set of contrasts.</i>
-------------	--

Description

This function is actually intended to be a sub-function of runRomer, but can hypothetically run by itself if the `romer` step has already been done.

Usage

```
outputRomer(rs1st, geneset1st, eset, fit,
  design = NULL, contrast = NULL, changenames = TRUE,
  dir = "genesets", explanation = NULL, annot = NULL,
  baseline.hmap = TRUE, file = "indexRomer.html", ...)
```

Arguments

rs1st	A list of results, generated by the <code>romer</code> function. See discussion for more information.
geneset1st	A list of genesets, usually created by loading in the RData files that can be downloaded from http://bioinf.wehi.edu.au/software/MSigDB/ . See details for more information.
eset	An <code>ExpressionSet</code> containing normalized, summarized gene expression data.
fit	An <code>MArrayLM</code> object, containing the fitted data.
design	A design matrix describing the model.
contrast	A contrast matrix describing the contrasts that were fit. This matrix should have colnames, which will be used to name subdirectories containing results.
changenames	Boolean. When creating heatmaps of the gene sets, should the columns be appended with the colnames from the design matrix? If FALSE, the sampleNames will be used.
dir	Character. The subdirectory to use for the output data. Defaults to 'genesets'.

explanation	If NULL, a generic paragraph will be placed at the top of the indexRomer.html page, giving a brief explanation of the analysis. Alternatively, this can be replaced with other text. Please note that this text should conform to HTML standards (e.g., will be pasted into the HTML document as-is, so should contain any required HTML markup).
annot	Character. The name of the annotation package for the array being used. This is used to add annotation data to the data tables for each gene set. If NULL (the default), the tables will only contain probeset IDs and statistics.
baseline.hmap	Boolean. If TRUE, then the resulting heatmaps will be centered by subtracting the mean of the baseline sample. As an example, in a contrast of treatment A - treatment B, the mean of the treatment B samples will be subtracted. The heatmap colors then represent the fold change between the A and B samples.
file	Character. The filename to output. Defaults to 'indexRomer.html'.
...	Arguments to be passed to lower-level functions. See geneSetPage, dataAndHeatmapPage and gsHeatmap for available arguments.

Details

This function is intended to be an internal function for runRomer. However, it is possible that runRomer errored out after saving the results from running `romer` on a set of contrasts, and all that remains is to create the output HTML.

Please note that the first two arguments to this function have certain expectations. The `rsltlst` should be the output from running `romer`. If using the saved output from runRomer, one should first load the 'romer.Rdata' file, which will introduce a list object with the name 'romerlst' into the working directory, so the first argument should be `rsltlst = romerlst`.

Second, see the code for runRomer, specifically the line that creates the 'sets' object, which will show how to create the correct `genesetlst` object.

Value

Nothing is returned. The function is run only for the side effect of creating HTML tables with output for each significant gene set.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

plotDeg

Functions to Plot Density and RNA Degradation Plots

Description

These functions make density and RNA degradation plots with automatic placement of legends.

Usage

```
plotDeg(dat, filenames = NULL)
```

Arguments

dat	An AffyBatch object, or in the case of plotHist, a matrix (e.g., from a call to read.probematrix. Note that plotDeg requires an AffyBatch object to work correctly.
filenames	Filenames that will be used in the legend of the resulting plot. If NULL (the default), these names will be extracted from the sampleNames slot of the AffyBatch object.

Value

These functions are called only for the side effect of making the plots. Nothing else is returned.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
library("affydata")
data(Dilution)
plotDeg(Dilution)
plotHist(Dilution)
```

plotPCA

A Function to Make a PCA Plot from an ExpressionSet

Description

This function makes a PCA plot from an ExpressionSet or matrix

Usage

```
plotPCA(object, groups = NULL, groupnames = NULL,
  addtext = NULL, x.coord = NULL, y.coord = NULL,
  screeplot = FALSE, squarepca = FALSE, pch = NULL,
  col = NULL, pcs = c(1, 2), legend = TRUE,
  main = "Principal Components Plot", plot3d = FALSE,
  outside = FALSE, ...)
```

Arguments

object	An ExpressionSet, matrix or prcomp object.
groups	A numeric vector delineating group membership for samples. Default is NULL, in which case default plotting symbols and colors will be used.
groupnames	A character vector describing the different groups. Default is NULL, in which case the sample names will be used.
addtext	A character vector of additional text to be placed just above the plotting symbol for each sample. This is helpful if there are a lot of samples for identifying e.g., outliers.
x.coord	Pass an x-coordinate if automatic legend placement fails
y.coord	Pass a y-coordinate if automatic legend placement fails.
screepplot	Boolean: Plot a screepplot instead of a PCA plot? Defaults to FALSE.
squarepca	Should the y-axis of the PCA plot be made comparable to the x-axis? This may aid in interpretation of the PCA plot. Defaults to FALSE.
pch	A numeric vector indicating what plotting symbols to use. Default is NULL, in which case default plotting symbols will be used. Note that this argument will override the 'groups' argument.
col	A numeric or character vector indicating what color(s) to use for the plotting symbols. Default is NULL in which case default colors will be used. Note that this argument will override the 'groups' argument.
pcs	A character vector of length two (or three if plot3d is TRUE), indicating which principal components to plot. Defaults to the first two principal components.
legend	Boolean. Should a legend be added to the plot? Defaults to TRUE.
main	A character vector for the plot title.
plot3d	Boolean. If TRUE, then the PCA plot will be rendered in 3D using the rgl package. Defaults to FALSE. Note that the pcs argument should have a length of three in this case.
outside	Boolean. If TRUE the legend will be placed outside the plotting region, at the top right of the plot.
...	Further arguments to be passed to plot. See the help page for plot for further information.

Value

This function returns nothing. It is called only for the side effect of producing a PCA plot or screepplot.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
library("affy")
data(sample.ExpressionSet)
plotPCA(sample.ExpressionSet, groups =
  as.numeric(pData(sample.ExpressionSet)[,2]), groupnames =
  levels(pData(sample.ExpressionSet)[,2]))
```

probes2table

*Convert Affy Probe ids to Annotated HTML Table***Description**

A function to convert a vector of Affy ids to an annotated HTML table.

Usage

```
probes2table(eset, probids, lib, otherdata = NULL,
  anncols = aaf.handler()[c(1:3, 6:7, 9:12)],
  html = TRUE, text = FALSE, express = TRUE,
  save = FALSE, filename, title = NULL)
```

Arguments

eset	An ExpressionSet containing Affy expression values.
probids	A vector of probe ids.
lib	An annotation package for the Affy chips used.
otherdata	A <i>*named*</i> list of additional information to include in the resulting table. Examples would be t-statistics, p-values, fold change, etc. Each list item should be a vector the same length as the probids vector. The name associated with each list item will be used as the column name in the resulting table.
anncols	A vector of things to annotate, produced by a call to aaf.handler().
html	Output data in HTML tables? Defaults to TRUE.
text	Output data in text tables? Defaults to TRUE.
express	Output expression values in table? Defaults to TRUE.
save	Should tables be saved as R objects for further processing? Defaults to FALSE.
filename	Filename of the resulting HTML table.
title	Title for HTML table. If NULL, the filename will be used.

Value

If save is TRUE, a data.frame is saved containing the data.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[topTable](#), [aafTableAnn](#)

probes2tableBM *Convert Affy Probe ids to Annotated HTML Table using biomaRt*

Description

A function to convert a vector of Affy ids to an annotated HTML or text table. This function is very similar to `probes2table`, except it uses the `biomaRt` package to annotate genes, and the `annotate` package to create the HTML table.

Usage

```
probes2tableBM(eset, probids, species, filename,
  otherdata = NULL, links = linksBM()[1:3],
  otherann = annBM()[1:3], ann.source = "entrezgene",
  express = TRUE, html = TRUE, text = TRUE,
  affyid = FALSE)
```

Arguments

<code>eset</code>	An ExpressionSet containing Affy expression values.
<code>probids</code>	A vector of probe ids.
<code>species</code>	The species name. This must be in a particular format for <code>biomaRt</code> . An example for human is "hsapiens" or for mouse is "mmusculus".
<code>filename</code>	File name of the resulting HTML table.
<code>otherdata</code>	A *named* list of additional information to include in the resulting table. Examples would be t-statistics, p-values, fold change, etc. Each list item should be a vector the same length as the <code>probids</code> vector. The name associated with each list item will be used as the column name in the resulting table.
<code>links</code>	A character vector of things to annotate with hyperlinks to online databases. See <code>linksBM</code> for possible values.
<code>otherann</code>	A character vector of things to annotate with text only (i.e., no hyperlinks). See <code>annBM</code> for possible values.
<code>ann.source</code>	The annotation source of the IDs that will be used to annotate the genes. The default value is "entrezgene". See details for other possibilities.
<code>express</code>	Output expression values in table? Defaults to TRUE.
<code>html</code>	Boolean. Output HTML table? Defaults to TRUE
<code>text</code>	Boolean. Output text table? Defaults to TRUE
<code>affyid</code>	Boolean. Are the IDs used to annotate these data Affymetrix IDs?

Details

This function is designed to output HTML tables based on a set of IDs. This function currently only supports Affymetrix data. It is designed for Affymetrix chips that don't have an annotation package, which includes data that have been analyzed using the 're-mapped' CDFs supplied to BioC by MBNI at University of Michigan.

The IDs that will be used to annotate the genes depend on the source of the data. If, for example, one is using an Affymetrix chip that doesn't have a BioC annotation package, then the IDs will be Affymetrix IDs. To find out the correct name to use for the `ann.source` argument, one can create a connection to a Biomart database using [useMart](#) and then get a list of available Affy arrays using [listFilters](#).

If one is using one of the re-mapped CDFs from MBNI at University of Michigan, then the IDs to use depend on the mapping used to create the CDF. At this time, only three types of CDFs can be used; EntrezGene, UniGene, and RefSeq. One can determine the correct `ann.source` argument by creating a connection to a Biomart database, and then calling `linksBM(mart, linksBM()[[3]])`.

Value

This function is only used for the side effect of outputting an HTML table.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[topTable](#)

runRomer

A function to run the romer function on a set of contrasts.

Description

This function automates both running [romer](#) on a set of contrasts as well as the creation of output HTML tables that can be used to explore the results. The basic idea here is that one might have used `limma` to fit a model and compute some contrasts, and then want to do a GSEA using [romer](#).

Usage

```
runRomer(setloc, annot = NULL, eset, design = NULL,  
         contrast = NULL, fit, wts = NULL, save = TRUE,  
         baseline.hmap = TRUE, ...)
```

Arguments

setloc	A character vector giving the path for gene set RData files (see description for more information).
annot	Character. The name of the array annotation package.
eset	An ExpressionSet containing normalized expression data.
design	A design matrix describing the model fit to the data.
contrast	A contrast matrix describing the contrasts that were computed from the data. This contrast should have colnames, which will be used to create parts of the resulting directory structure.
fit	An MArrayLM object, containing the fitted model data.
wts	Optional weights vector - if array weights were used to fit the model, they should be supplied here as well.
save	Boolean. If true, after running the romer step, the results will be saved in a file 'romer.Rdata', which can be used as input for outputRomer to create HTML tables. Since romer can take a long time to run, it is advantageous to keep the default.
baseline.hmap	Boolean. If TRUE, then the resulting heatmaps will be centered by subtracting the mean of the baseline sample. As an example, in a contrast of treatment A - treatment B, the mean of the treatment B samples will be subtracted. The heatmap colors then represent the fold change between the A and B samples.
...	Used to pass arguments to lower-level functions. See outputRomer geneSetPage , dataAndHeatmapPage and gsHeatmap for available arguments.

Details

The [romer](#) expects as input a list or lists of gene symbols that represent individual gene sets. One example is the various gene sets from the Broad Institute that are available at <http://bioinf.wehi.edu.au/software/MSigDB/>, which are distributed as RData files. The default assumption for this function is that the end user will have downloaded these files, and the setloc argument simply tells runRomer where to find them.

Alternatively, user-based gene sets could be created (these should consist of lists of character vectors of gene symbols - see one of the Broad gene sets for an example).

This function will run [romer](#) using all the gene sets in the referenced directory, on all the contrasts supplied, and then output the results in a (default) 'genesets' subdirectory. There will be an HTML file in the working directory with a (default) filename of 'indexRomer.html' that will point to individual HTML files in the genesets subdirectory, which will point to individual files in subdirectories within the genesets subdirectory (named after the colnames of the contrast matrix).

Value

Nothing is returned. This function is called only for the side-effects of creating output HTML files in the working and sub-directories.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

`venn4Way`*4-way Venn Diagrams*

Description

A function to create a 4-way Venn diagram

Usage

```
venn4Way(fit, contrast, p.value, lfc, adj.meth,  
         baseUrl = ".", reportDirectory = "./venns", ...)
```

Arguments

<code>fit</code>	An MArrayLM object, created by the limma package.
<code>contrast</code>	A contrasts matrix, used by limma to generate the comparisons made.
<code>p.value</code>	A p-value cutoff for significance
<code>lfc</code>	A log fold change cutoff
<code>adj.meth</code>	The method used to adjust for multiple comparisons.
<code>baseUrl</code>	The base directory for the tables generated. Defaults to ".", meaning the current directory.
<code>reportDirectory</code>	The directory in which to put the results. Defaults to a "venns" subdirectory.
<code>...</code>	Allows arbitrary arguments to be passed to lower level functions

Details

This function is an internal function and not really intended to be called by the end user. It is generally called by the `vennPage` function. The goal is to create a 4-way Venn diagram in an HTML page with clickable links to tables of the genes found in a given cell. In addition, the numbers in each cell are underlined with colored bars that help end users tell what contrasts are captured by that cell.

Value

Returns a list. The first item is a (list of) `HTMLReportRef` objects that can be used by Reporting-Tools to create HTML links. The second item is the output from the `venn` function in `gtools`, and the third item is the name of the contrasts used to generate the Venn diagram.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Description

This function is designed to compute counts for a Venn diagram. It is slightly different from [vennCounts](#) in the additional ability to compute counts for genes that are differentially expressed in the same direction.

Usage

```
vennCounts2(x, method = "same", fit = NULL,  
            foldFilt = NULL)
```

Arguments

x	A TestResults object, produced by a call to decideTests or foldFilt .
method	One of "same", "both", "up", "down". See details for more information.
fit	An MArrayLM object, produced by a call to lmFit and eBayes . Only necessary if 'foldFilt' = TRUE.
foldFilt	A fold change to filter samples. This is primarily here for consistency with the corresponding argument in vennSelect .

Details

The function [vennCounts](#) will return identical results except for the "same" method. This will only select those genes that both pass the criteria of [decideTests](#) as well as being differentially expressed in the same direction. Note that this is different from the "both" method, which simply requires that a given gene be differentially expressed in e.g., two different comparisons without any requirement that the direction be the same.

Value

A [VennCounts](#) object.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
library("limma")  
tstat <- matrix(rt(300,df=10),100,3)  
tstat[1:33,] <- tstat[1:33,]+2  
clas <- classifyTestsF(tstat,df=10,p.value=0.05)  
a <- vennCounts2(clas)  
print(a)  
vennDiagram(a)
```

vennPage	<i>High-level function for making Venn diagrams with clickable links to HTML pages with the underlying genes.</i>
----------	---

Description

This function is designed to be used in conjunction with the `makeVenn` function, to first create a set of HTML pages containing the genes that are represented by the cells of a Venn diagram, and then create an HTML page with the same Venn diagrams, with clickable links that will point the end user to the HTML pages.

Usage

```
vennPage(vennlst, pagename, pagetitle, cex.venn = 1,
         shift.title = FALSE, baseUrl = ".",
         reportDirectory = NULL, ...)
```

Arguments

vennlst	The output from <code>makeVenn</code> .
pagename	Character. The file name for the resulting HTML page. Something like 'venns' is reasonable. Note that the .html will automatically be appended.
pagetitle	Character. The heading for the HTML page.
cex.venn	Numeric. Adjusts the size of the font in the Venn diagram. Usually the default is OK.
shift.title	Boolean. Should the right contrast name of the Venn diagram be shifted down? Useful for long contrast names. If a two-way Venn diagram, this will shift the right name down so they don't overlap. If a three-way Venn diagram, this will shift the top right name down.
baseUrl	Character. The base URL for the resulting HTML page. The default of "." is usually optimal.
reportDirectory	If NULL, the <code>reportDirectory</code> will be extracted from the <code>vennlst</code> . This is usually what one should do.
...	To allow passing other arguments to lower level functions. Currently not used.

Details

This function is intended to be used as part of a pipeline, by first calling `makeVenn` and then using the output from that function as input to this function to create the HTML page with clickable links.

Value

An `HTMLReport` object. If used as input to the `ReportingTools` `publish` function, this will create a link on an index page to the Venn diagram HTML page. See e.g., the microarray analysis vignette for `ReportingTools` for more information.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Examples

```
## Not run:
mat <- matrix(rnorm(1e6), ncol = 20)
design <- model.matrix(~factor(1:4, each=5))
colnames(design) <- LETTERS[1:4]
contrast <- matrix(c(1,-1,0,0,1,0,-1,0,1,0,0,-1,0,1,-1,0,0,1,0,-1),
  ncol = 5)
colnames(contrast) <- paste(LETTERS[c(1,1,1,2,2)],
  LETTERS[c(2,3,4,3,4)], sep = " vs ")
fit <- lmFit(mat, design)
fit2 <- contrasts.fit(fit, contrast)
fit2 <- eBayes(fit2)
## two Venn diagrams - a 3-way Venn with the first three contrasts
## and a 2-way Venn with the last two contrasts
collist <- list(1:3,4:5)
venn <- makeVenn(fit2, contrast, design, eset, collist = collist)
vennreport <- vennPage(venn, "index.html", "Venn diagrams")
indexPage <- HTMLReport("index", "My results", reportDirectory =
  ".", baseUrl = ".")
publish(vennreport)
finish(indexPage)

## End(Not run)
```

 vennSelect

Select and Output Genelists Based on Venn Diagrams

Description

This function is designed to output text and/or HTML tables based on the results of a call to [decideTests](#).

Usage

```
vennSelect(eset, design, x, contrast, fit,
  method = "same", adj.meth = "BH", stat = "fstat",
  otherstats = c("pval", "FC"), order.by = "pval",
  foldFilt = NULL, save = FALSE, titleadd = NULL, ...)
```

Arguments

eset	An ExpressionSet object.
design	A design matrix.
x	A TestResults object, usually from a call to decideTests .

contrast	A contrasts matrix, produced either by hand, or by a call to makeContrasts
fit	An MArrayLM object, from a call to eBayes .
method	One of "same", "both", "up", "down", "sameup", or "samedown". See details for more information.
adj.meth	Method to use for adjusting p-values. Default is 'BH', which corresponds to 'fdr'. Ideally one would set this value to be the same as was used for decideTests .
stat	The statistic to report in the resulting HTML tables. Choices are 'fstat', 'tstat', and NULL. Ideally, the statistic chosen would correspond to the method used in decideTests . In other words, if one used methods such as 'separate' or 'hierarchical', which are based on a t-statistic, one should choose 'tstat', however, if one used 'nestedF', the logical choice would be 'fstat'.
otherstats	Other statistics to be included in the HTML tables. Choices include 'pval' and 'FC'.
order.by	Which statistic should be used to order the probesets? Choices include 'fstat', 'tstat', 'pval', and 'FC'. Note that if 'FC' is chosen and there are more than one set of fold changes, the first will be used.
foldFilt	A log fold change to filter results.
save	Boolean. Save the results for further processing?
titleadd	Additional text to add to the title of the HTML tables. Default is NULL, in which case the title of the table will be the same as the filename.
...	Used to pass other arguments to <code>probes2table</code> , in particular, to change the argument to <code>anncols</code> which controls the columns of hyperlinks to online databases (e.g., Entrez Gene, etc.). See aaf.handler for more information.

Details

The purpose of this function is to output HTML and text tables with lists of genes that fulfill the criteria of a call to [decideTests](#) as well as the direction of differential expression.

Some important things to note: First, the names of the HTML and text tables are extracted from the `colnames` of the `TestResults` object, which come from the contrasts matrix, so it is important to use something descriptive. Second, the `method` argument is analogous to the `include` argument from [vennCounts](#) or [vennDiagram](#). Choosing "both" will select genes that are differentially expressed in one or more comparisons, regardless of direction. Choosing "up" or "down" will select genes that are only differentially expressed in one direction. Choosing "same" will select genes that are differentially expressed in the same direction. Choosing "sameup" or "samedown" will select genes that are differentially expressed in the same direction as well as 'up' or 'down'.

Note that this is different than sequentially choosing "up" and then "down". For instance, a gene that is upregulated in one comparison and downregulated in another comparison will be listed in the intersection of those two comparisons if "both" is chosen, it will be listed in only one comparison for both the "up" and "down" methods, and it will be listed in the union (e.g., not selected) if "same" is chosen.

Calling the function normally will result in the output of HTML and text tables:

```
vennSelect(eset, fit, design, x)
```


Calling the function with `save` set to `TRUE` will output both HTML and text tables as well as a vector of counts for each comparison. This is useful when using the function programmatically (e.g., when making reports using Sweave).

```
out <- vennSelect(eset, fit, design, x, save = TRUE)
```

An alternative would be to use `vennCounts2` and `vennDiagram` to output a Venn diagram, which is probably more reasonable since the tables being output are supposed to be based on a Venn diagram.

Value

Normally called only for the side effect of producing HTML and text tables. However, setting `save` to `TRUE` will output a vector of counts that can be used for making Sweave-style reports.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

vennSelect2

Select and Output Genelists Based on Venn Diagrams

Description

This function is designed to output text and/or HTML tables based on the results of a call to `decideTests`, using the ReportingTools package.

Usage

```
vennSelect2(fit, contrast, design, eset, groups = NULL,
  cols = NULL, p.value = 0.05, lfc = 0, method = "same",
  adj.meth = "BH", titleadd = NULL, fileadd = NULL,
  baseUrl = ".", reportDirectory = "./venns", ...)
```

Arguments

<code>fit</code>	An <code>MArrayLM</code> object, from a call to <code>eBayes</code> .
<code>contrast</code>	A contrasts matrix, produced either by hand, or by a call to <code>makeContrasts</code>
<code>design</code>	A design matrix.
<code>eset</code>	An <code>ExpressionSet</code> object.
<code>groups</code>	This argument is used when creating a legend for the resulting HTML pages. If <code>NULL</code> , the groups will be generated using the column names of the design matrix.
<code>cols</code>	A numeric vector indicating which columns of the fit, contrast and design matrix to use. If <code>NULL</code> , all columns will be used.
<code>p.value</code>	A p-value to filter the results by.
<code>lfc</code>	A log fold change to filter the results by.

method	One of "same", "both", "up", "down", "sameup", or "samedown". See details for more information.
adj.meth	Method to use for adjusting p-values. Default is 'BH', which corresponds to 'fdr'. Ideally one would set this value to be the same as was used for decideTests .
titleadd	Additional text to add to the title of the HTML tables. Default is NULL, in which case the title of the table will be the same as the filename.
fileadd	Additional text to add to the name of the HTML and CSV tables. Default is NULL.
baseUrl	A character string giving the location of the page in terms of HTML locations. Defaults to "."
reportDirectory	A character string giving the location that the results will be written. Defaults to "./venns"
...	Used to pass other arguments to <code>probes2table</code> , in particular, to change the argument to <code>anncols</code> which controls the columns of hyperlinks to online databases (e.g., Entrez Gene, etc.). See aaf.handler for more information.

Details

The purpose of this function is to output HTML and text tables with lists of genes that fulfill the criteria of a call to [decideTests](#) as well as the direction of differential expression.

Some important things to note: First, the names of the HTML and text tables are extracted from the `colnames` of the `TestResults` object, which come from the contrasts matrix, so it is important to use something descriptive. Second, the method argument is analogous to the `include` argument from [vennCounts](#) or [vennDiagram](#). Choosing "both" will select genes that are differentially expressed in one or more comparisons, regardless of direction. Choosing "up" or "down" will select genes that are only differentially expressed in one direction. Choosing "same" will select genes that are differentially expressed in the same direction. Choosing "sameup" or "samedown" will select genes that are differentially expressed in the same direction as well as 'up' or 'down'.

Note that this is different than sequentially choosing "up" and then "down". For instance, a gene that is upregulated in one comparison and downregulated in another comparison will be listed in the intersection of those two comparisons if "both" is chosen, it will be listed in only one comparison for both the "up" and "down" methods, and it will be listed in the union (e.g., not selected) if "same" is chosen.

Unlike `vennSelect`, this function automatically creates both HTML and CSV output files.

Value

A list with two items. First, a list of `HTMLReport` objects from the `ReportingTools` package, which can be used to create an index page with links to the HTML pages created by this function. See the help page for `HTMLReport` in `ReportingTools` as well as the vignettes for more information. The second item is a `vennCounts` object from `limma`, which can be used to create a Venn diagram, e.g., in a report if this function is called within a Sweave or knitr pipeline.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

Description

This function is designed to output HTML and text tables based on the results of a call to [decideTests](#). This function is very similar to `vennSelect`, except it uses the `biomaRt` package to annotate genes, and the `annotate` package to create the HTML table.

Usage

```
vennSelectBM(eset, design, x, contrast, fit,
             method = "same", adj.meth = "BH", stat = "fstat",
             otherstats = c("pval", "FC"), order.by = "pval",
             foldFilt = NULL, save = FALSE, species,
             links = linksBM()[1:3], otherdata = annBM()[1:3],
             ann.source = "entrezgene", html = TRUE, text = TRUE,
             affyid = FALSE, ...)
```

Arguments

<code>eset</code>	A ExpressionSet object.
<code>design</code>	A design matrix, usually from a call to <code>model.matrix</code> . See details for more information.
<code>x</code>	A TestResults object, usually from a call to decideTests .
<code>contrast</code>	A contrasts matrix, produced either by hand, or by a call to makeContrasts
<code>fit</code>	An MArrayLM object, from a call to eBayes .
<code>method</code>	One of "same", "both", "up", "down", "sameup", or "samedown". See details for more information.
<code>adj.meth</code>	Method to use for adjusting p-values. Default is 'BH', which corresponds to 'fdr'. Ideally one would set this value to be the same as was used for decideTests .
<code>stat</code>	The statistic to report in the resulting HTML tables. Choices are 'fstat', 'tstat', and NULL. Ideally, the statistic chosen would correspond to the method used in decideTests . In other words, if one used methods such as 'separate' or 'hierarchical', which are based on a t-statistic, one should choose 'tstat', however, if one used 'nestedF', the logical choice would be 'fstat'.
<code>otherstats</code>	Other statistics to be included in the HTML tables. Choices include 'pval' and 'FC'.
<code>order.by</code>	Which statistic should be used to order the probesets? Choices include 'fstat', 'tstat', 'pval', and 'FC'. Note that if 'FC' is chosen and there are more than one set of fold changes, the first will be used.
<code>foldFilt</code>	A fold change to use for filtering. Default is NULL, meaning no filtering will be done.

save	Boolean - If TRUE, output a count of genes that fulfill the criteria. Useful for e.g., Sweave-type reports.
species	The species name. This must be in a particular format for biomaRt. An example for human is "hsapiens", or for mouse "mmusculus".
links	A character vector of things to annotate with hyperlinks to online databases. See linksBM for possible values.
otherdata	A character vector of things to annotate with text only (i.e., no hyperlinks). See annBM for possible values.
ann.source	The annotation source of the IDs that will be used to annotate the genes. The default value is "entrezgene". See details for other possibilities.
html	Boolean. Output HTML tables? Defaults to TRUE
text	Boolean. Output text tables? Defaultst to TRUE
affyid	Boolean. Are the IDs used to annotate these data Affymetrix IDs?
...	Used to pass other variables to e.g., htmlpage.

Details

The purpose of this function is to output HTML tables with lists of genes that fulfill the criteria of a call to [decideTests](#) as well as the direction of differential expression.

The IDs that will be used to annotate the genes depend on the source of the data. If, for example, one is using an Affymetrix chip that doesn't have a BioC annotation package, then the IDs will be Affymetrix IDs. To find out the correct name to use for the `ann.source` argument, one can create a connection to a Biomart database using [useMart](#) and then deduce the correct argument by the output from `listFilters(mart)`. It will usually be something starting with 'affy', and contain the name of the chip.

If one is using one of the re-mapped CDFs from MBNI at University of Michigan, then the IDs to use depend on the mapping used to create the CDF. At this time, only three types of CDFs can be used; EntrezGene, UniGene, and RefSeq. One can determine the correct `ann.source` argument by creating a connection to a Biomart database, and then calling `linksBM(mart, linksBM())[[3]]`.

Some important things to note: First, the names of the HTML tables are extracted from the `colnames` of the `TestResults` object, which come from the contrasts matrix, so it is important to use something descriptive. Second, the `method` argument is analogous to the `include` argument from [vennCounts](#) or [vennDiagram](#). Choosing "both" will select genes that are differentially expressed in one or more comparisons, regardless of direction. Choosing "up" or "down" will select genes that are only differentially expressed in one direction. Choosing "same" will select genes that are differentially expressed in the same direction. Choosing "sameup" or "samedown" will select genes that are differentially expressed in the same direction as well as 'up' or 'down'.

Note that this is different than sequentially choosing "up" and then "down". For instance, a gene that is upregulated in one comparison and downregulated in another comparison will be listed in the intersection of those two comparisons if "both" is chosen, it will be listed in only one comparison for both the "up" and "down" methods, and it will be listed in the union (e.g., not selected) if "same" is chosen.

Calling the function normally will result in the output of HTML tables.

Calling the function with `save` set to `TRUE` will output HTML tables as well as a vector of counts for each comparison. This is useful when using the function programmatically (e.g., when making reports using Sweave).

```
out <- vennSelectBM(eset, fit, design, x, <other arguments>, save = TRUE)
```

An alternative would be to use `vennCounts2` and `vennDiagram` to output a Venn diagram, which is probably more reasonable since the tables being output are supposed to be based on a Venn diagram.

Value

Normally called only for the side effect of producing HTML tables. However, setting `save` to `TRUE` will output a vector of counts that can be used for making Sweave-style reports.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

vennSelectFC

Select and Output Gene Lists Based on Venn Diagrams

Description

This function is designed to output text and/or HTML tables based on the results of a call to `foldFilt`. The general idea being that one might want to create a Venn diagram showing probesets that are unique to particular comparisons, or consistent between comparisons, and then might want to output the probesets that are contained in each cell of the Venn diagram.

Usage

```
vennSelectFC(eset, x, comps, order.by = "sum",
             method = "same", text = TRUE, html = TRUE, ...)
```

Arguments

<code>eset</code>	A ExpressionSet object.
<code>x</code>	An indicator matrix showing up or down regulation based on fold change, usually from a call to <code>foldFilt</code> . See details for more information.
<code>comps</code>	A list containing all the comparisons to be made. Each list item should be a vector of length two. This should be identical to the <code>'comps'</code> argument used in the call to <code>foldFilt</code> . See details for more information.
<code>order.by</code>	One of <code>'sum'</code> , <code>'max'</code> , <code>'median'</code> , or <code>'mean'</code> . This orders the output for those tables that have multiple fold change values based on the summary statistic chosen. Defaults to <code>'sum'</code> .
<code>method</code>	One of <code>"same"</code> , <code>"both"</code> , <code>"up"</code> , <code>"down"</code> , <code>"sameup"</code> , or <code>"samedown"</code> . See details for more information.
<code>text</code>	Boolean. Output text tables? Defaults to <code>TRUE</code>

html Boolean. Output HTML tables? Defaults to TRUE
 ... Used to pass other arguments to `probes2table`, in particular, to change the argument to `anncols` which controls the columns of hyperlinks to online databases (e.g., Entrez Gene, etc.). See [aaf.handler](#) for more information.

Details

The purpose of this function is to output the probesets listed in a Venn diagram that has been produced by a call to `foldFilt`. A small example would be as follows:

Assume an `ExpressionSet` exists that contains expression values for three Affymetrix chips, say a control, and two experimentals. One might want to know what probesets are different between each of the experimentals and the control, and those that are different between both of the experimentals and the control. We first make the comparisons, based on a fold change of 2 (or a difference of 1 on the log scale).

```
comps <- list(c(1,2), c(1,3))
```

This list indicates what comparisons we want. In this case 1vs2 and 1vs3.

```
out <- foldFilt(eset, fold = 1, groups = 1:3, comps = comps, compnames=c("Control vs experimental1", "Control vs experimental2"), save = TRUE)
```

By setting `save = TRUE`, we are saving a list, the first item being a vector of the number of probesets in each comparison, the second item being an indicator matrix showing up or down regulation based on a two-fold difference. We could make a Venn diagram using this matrix with `vennCounts2` and [vennDiagram](#). If we then wanted to output the probesets in each cell of that Venn diagram, we could use `vennSelectFC` as follows:

```
vennSelectFC(eset, out[[2]], comps)
```

One thing to note here is that the names of the resulting tables as well as the columns containing the fold change values will be extracted from the column names of the indicator matrix. This matrix will get its column names from the 'compnames' argument to `foldFilt`, so it is best to use reasonable names here. Also note that any character used in the 'compnames' argument that is not a valid character for a file name will be stripped out.

Value

Called only for the side effect of outputting HTML and/or text tables.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

writeFit

Function to output annotated fit data from limma

Description

This function is designed to take an `ExpressionSet` an annotation package and an `lmFit` object, and output an annotated text file containing t-statistics, p-values, and fold change data for all contrasts.

Usage

```
writeFit(fit, annotation = NULL, eset,  
         touse = c("symbol", "genename", "accnum", "entrezid", "unigene"))
```

Arguments

fit	A <code>lmFit</code> object, created by the <code>limma</code> package.
annotation	An annotation package, specific for the chip used in the analysis.
eset	An <code>ExpressionSet</code> object containing expression values.
touse	Character vector of BiMaps from annotation package. As an example, if the annotation package is the <code>hgu133plus2.db</code> package, then 'symbol' refers to the <code>hgu133plus2SYMBOL</code> BiMap.

Details

This function is designed to output annotation data as well as statistics (p-values, fold change, t-statistics) for all probes on a chip.

Value

A `data.frame` is returned.

Author(s)

James W. MacDonald <jmacdon@u.washington.edu>

See Also

[write.fit](#)

Index

*Topic **hplot**

affystart, 3
maplot, 26
plotDeg, 29
plotPCA, 30
vennCounts2, 37

*Topic **htest**

hyperG2annaffy, 14

*Topic **manip**

affystart, 3
annBM, 4
entrezLinks, 6
foldFilt, 7
foldFiltBM, 8
getMainProbes, 12
getUniqueLL, 12
hyperG2annaffy, 14
hyperGoutput, 15
limma2annaffy, 18
limma2biomaRt, 19
makeHmap, 21
makeVenn, 24
mirna2mrna, 27
probes2table, 32
probes2tableBM, 33
vennCounts2, 37
vennPage, 38
vennSelect, 39
vennSelect2, 41
vennSelectBM, 43
vennSelectFC, 45
writeFit, 46

aaf.handler, 16, 25, 40, 42, 46

aafTableAnn, 19, 21, 33

affycoretools, 2

affycoretools-package (affycoretools), 2

affyLinks (entrezLinks), 6

affystart, 3

annBM, 4

bluered, 11, 13

dataAndHeatmapPage, 5

decideTests, 24, 25, 37, 39–44

eBayes, 16, 17, 24, 37, 40, 41, 43

entrezLinks, 6

ExpressionSet, 5, 11, 13, 28, 35, 43, 45

findLargest, 17

foldFilt, 7

foldFiltBM, 8

genefilter, 8, 9

geneSetPage, 10

getMainProbes, 12

getUniqueLL, 12

goLinks (entrezLinks), 6

gsHeatmap, 13

htmlReport, 16, 17

hyperG2annaffy, 14

hyperGoutput, 15

hyperGTest, 13, 16, 17

limma2annaffy, 18

limma2biomaRt, 19

linksBM (annBM), 4

listFilters, 21, 34

lmFit, 14, 15, 37

makeContrasts, 24, 40, 41, 43

makeHmap, 21, 27

makeImages, 23

makeVenn, 24

maplot, 26

MArrayLM, 16, 17, 24, 37, 40, 41, 43

mirna2mrna, 22, 27

outputRomer, 28

plotDeg, 29

plotHist (plotDeg), [29](#)
plotPCA, [30](#)
probes2table, [32](#)
probes2tableBM, [33](#)
probeSetSummary, [17](#)

romer, [11](#), [28](#), [29](#), [34](#), [35](#)
runRomer, [34](#)

screepLOT, [31](#)
summary, [17](#)

TestResults, [37](#), [39](#), [43](#)
topTable, [19](#), [21](#), [33](#), [34](#)

useMart, [4](#), [10](#), [21](#), [34](#), [44](#)

venn4Way, [36](#)
VennCounts, [37](#)
vennCounts, [25](#), [37](#), [40](#), [42](#), [44](#)
vennCounts2, [37](#)
vennDiagram, [25](#), [40–42](#), [44–46](#)
vennPage, [38](#)
vennSelect, [39](#)
vennSelect2, [41](#)
vennSelectBM, [43](#)
vennSelectFC, [45](#)

write.fit, [47](#)
writeFit, [46](#)