FDb.InfiniumMethylation.hg19

October 7, 2014

getPlatform Retrieve annotations for HumanMethylation27 or HumanMethylation450 chips

Description

FDb.InfiniumMethylation.hg19 is an omnibus package that merges all of the existing Illumina Infinium DNA methylation probe annotations into one FDb. However, most users will be analyzing one of the two chips at any given time. The utility functions getPlatform(platform), get450k(), and get27k() retrieve a compact GenomicRanges form of the annotations for the requested platform.

Author(s)

Tim Triche, Jr.

Examples

hm450.hg19 <- getPlatform(platform=HM450, genome=hg19)
show(hm450.hg19)</pre>

hm27.hg19 <- get27k()
genome(hm27.hg19)</pre>

hg19.islands

Description

This GRanges object was constructed from the data provided at http://rafalab.jhsph.edu/CGI/model-based-cpg-islands-hg19.txt

Additional species and software to run the model can be found at http://rafalab.jhsph.edu/CGI/index.html

Author(s)

Tim Triche, Jr. (with data from Wu, Irizarry, and Feinberg)

Examples

```
data(hg19.islands)
split(hg19.islands, seqnames(hg19.islands))
```

miscData

miscellaneous data used in the construction of this FeatureDb package

Description

In the subdirectory inst/build/, there are several scripts that rebuild this FeatureDb from scratch. A handful of intermediate results from dbSNP and comparison of existing datasets are required to patch small gaps in the Illumina manifests. These datasets supply those intermediate results.

Author(s)

Tim Triche, Jr.

Examples

```
data(hm450.rsProbes)
data(hm27.SNP.colors)
```

FDb.InfiniumMethylation.hg19

Annotation package for Illumina Infinium DNA methylation probes

Description

This package loads one or more FeatureDb objects. Such FeatureDb objects are an R interface to prefabricated databases contained by this package. In the case of the Infinium methylation FDb, it is FDb.InfiniumMethylation.hg19 (for the moment; hg18 may come later, or alternatively users can use liftOver() from rtracklayer to do it).

Author(s)

Tim Triche, Jr.

See Also

features makeFeatureDbFromUCSC import.bed getPlatform get450k get27k

Examples

load the library
library(FDb.InfiniumMethylation.hg19)

list the contents that are loaded into memory ls(package:FDb.InfiniumMethylation.hg19)

```
## show the db object that is loaded by calling its name
FDb.InfiniumMethylation.hg19
```

extract features for use in constructing SummarizedExperiments
or comparing chip features against other data (e.g. ChIP-seq)
InfiniumMethylation <- features(FDb.InfiniumMethylation.hg19)</pre>

wed prefer if R would stop us from comparing across assemblies: met <- metadata(FDb.InfiniumMethylation.hg19) ## need to fetch genome genome(InfiniumMethylation) <- met[which(met[,name]==Genome),value]</pre>

```
## last but not least, sort the probes in genomic order
InfiniumMethylation <- sort(InfiniumMethylation)
show(InfiniumMethylation)
```

```
## Example: probes that overlap Irizarrys HMM CpG islands
data(hg19.islands)
CGI.probes <- subsetByOverlaps(InfiniumMethylation, hg19.islands)
head(CGI.probes)
tail(CGI.probes)
```

```
## The same logic works for overlapping probes with other data.
## For example, we can easily do this for old 27k data as well:
hm27 <- get27k()
hm27.shores <- subsetByOverlaps(hm27, hg19.shores)</pre>
```

```
## The same logic applies to overlapping ChIP-seq peaks, DNAseI footprints, etc.
## Much more data is available via GenomicFeatures and rtracklayer:
help(makeFeatureDbFromUCSC)
```

4

Index

*Topic data FDb.InfiniumMethylation.hg19, 3 hg19.islands, 2miscData, 2 *Topic package FDb.InfiniumMethylation.hg19,3 FDb.InfiniumMethylation.hg19,3 FDb.InfiniumMethylation.hg19-package (FDb.InfiniumMethylation.hg19), 3 features, 3 get27k, 3 get27k (getPlatform), 1 get450k, 3 get450k (getPlatform), 1 getPlatform, 1, 3 hg18ToHg19 (miscData), 2 hg19.islands, 2 hm27.controls(miscData), 2 hm27.SNP.colors(miscData), 2 hm450.controls(miscData), 2 hm450k.rsProbes (miscData), 2 import.bed, 3 makeFeatureDbFromUCSC, 3

miscData,2