

Package ‘microbiomeMarker’

January 18, 2022

Title microbiome biomarker analysis toolkit

Version 1.0.1

Description To date, a number of methods have been developed for microbiome marker discovery based on metagenomic profiles, e.g. LEfSe. However, all of these methods have its own advantages and disadvantages, and none of them is considered standard or universal. Moreover, different programs or softwares may be development using different programming languages, even in different operating systems. Here, we have developed an all-in-one R package microbiomeMarker that integrates commonly used differential analysis methods as well as three machine learning-based approaches, including Logistic regression, Random forest, and Support vector machine, to facilitate the identification of microbiome markers.

License GPL-3

biocViews Metagenomics, Microbiome, DifferentialExpression

URL <https://github.com/yiluheihei/microbiomeMarker>

BugReports <https://github.com/yiluheihei/microbiomeMarker/issues>

Depends R (>= 4.1.0)

Imports dplyr, phyloseq, magrittr, purrr, MASS, utils, ggplot2, tibble, rlang, stats, coin, ggtree, tidytree, methods, IRanges, tidy, patchwork, ggsignif, metagenomeSeq, DESeq2, edgeR, BiocGenerics, Biostrings, yaml, biomformat, S4Vectors, Biobase, ComplexHeatmap, ANCOMBC, caret, limma, ALDEx2, multtest, plotROC

Encoding UTF-8

RoxygenNote 7.1.2

Roxygen list(markdown = TRUE)

Suggests testthat, covr, glmnet, Matrix, kernlab, e1071, ranger, knitr, rmarkdown, BiocStyle

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/microbiomeMarker>

git_branch RELEASE_3_14

git_last_commit d4852b9

git_last_commit_date 2021-11-08

Date/Publication 2022-01-18

Author Yang Cao [aut, cre]

Maintainer Yang Cao <caoyang.name@gmail.com>

R topics documented:

| | |
|-------------------------------------|----|
| microbiomeMarker-package | 3 |
| abundances | 3 |
| aggregate_taxa | 4 |
| assign-otu_table | 5 |
| data-caporaso | 6 |
| data-cid_ying | 6 |
| data-ecam | 7 |
| data-enterotypes_arumugam | 7 |
| data-kostic_crc | 8 |
| data-oxygen | 8 |
| data-pediatric_ibd | 9 |
| data-spontaneous_colitis | 9 |
| extract_posthoc_res | 10 |
| get_treedata_phyloseq | 11 |
| import_dada2 | 11 |
| import_qiime2 | 12 |
| marker_table | 14 |
| marker_table-class | 14 |
| marker_table<- | 15 |
| microbiomeMarker | 16 |
| microbiomeMarker-class | 17 |
| nmarker | 18 |
| normalize_phyloseq-method | 18 |
| phyloseq2DESeq2 | 21 |
| phyloseq2edgeR | 22 |
| phyloseq2metagenomeSeq | 23 |
| plot_abundance | 24 |
| plot_cladogram | 24 |
| plot_ef_bar | 26 |
| plot_heatmap | 27 |
| plot_postHocTest | 28 |
| plot_sl_roc | 29 |
| postHocTest | 30 |
| postHocTest-class | 31 |
| run_aldex | 32 |
| run_ancom | 34 |
| run_ancombc | 37 |
| run_deseq2 | 40 |

run_edger 42
 run_lefse 45
 run_limma_voom 48
 run_marker 50
 run_metagenomeseq 52
 run_posthoc_test 54
 run_simple_stat 56
 run_sl 58
 run_test_multiple_groups 61
 run_test_two_groups 63
 subset_marker 65
 summarize_taxa 65
 transform_abundances 66
 [. 67

Index **69**

microbiomeMarker-package
microbiomeMarker: A package for microbiome biomarker discovery

Description

The microbiomeMarker package provides several methods to identify microbiome biomarker, such as lefse, deseq2.

abundances *Extract taxa abundances*

Description

Extract taxa abundances from phyloseq objects.

Usage

```
abundances(object, transform = c("identity", "log10", "log10p"), norm = FALSE)

## S4 method for signature 'otu_table'
abundances(object, transform = c("identity", "log10", "log10p"), norm = FALSE)

## S4 method for signature 'phyloseq'
abundances(object, transform = c("identity", "log10", "log10p"), norm = FALSE)

## S4 method for signature 'microbiomeMarker'
abundances(object, transform = c("identity", "log10", "log10p"))
```

Arguments

| | |
|-----------|---|
| object | otu_table , phyloseq , or microbiomeMarker . |
| transform | transformation to apply, the options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation. • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | logical, indicating whether or not to return the normalized taxa abundances. |

Value

abundance matrix with taxa in rows and samples in columns.

See Also

[otu_table](#), [phyloseq](#), [microbiomeMarker](#), [transform_abundances](#)

Examples

```
data(caporaso)
abd <- abundances(caporaso)
```

| | |
|----------------|-----------------------|
| aggregate_taxa | <i>Aggregate Taxa</i> |
|----------------|-----------------------|

Description

Summarize phyloseq data into a higher phylogenetic level.

Usage

```
aggregate_taxa(x, level, verbose = FALSE)
```

Arguments

| | |
|---------|---|
| x | phyloseq-class object |
| level | Summarization level (from <code>rank_names(pseq)</code>) |
| verbose | verbose |

Details

This provides a convenient way to aggregate phyloseq OTUs (or other taxa) when the phylogenetic tree is missing. Calculates the sum of OTU abundances over all OTUs that map to the same higher-level group. Removes ambiguous levels from the taxonomy table. Returns a phyloseq object with the summarized abundances.

Value

Summarized phyloseq object

Author(s)

Contact: Leo Lahti <microbiome-admin@googlegroups.com>

References

See citation('microbiome')

Examples

```
data(caporaso)
caporaso_phylum <- aggregate_taxa(caporaso, "Phylum")
```

| | |
|------------------|-------------------------------|
| assign-otu_table | <i>Assign a new OTU table</i> |
|------------------|-------------------------------|

Description

Assign a new OTU table in microbiomeMarker object

Usage

```
## S4 replacement method for signature 'microbiomeMarker,otu_table'
otu_table(x) <- value

## S4 replacement method for signature 'microbiomeMarker,phyloseq'
otu_table(x) <- value

## S4 replacement method for signature 'microbiomeMarker,microbiomeMarker'
otu_table(x) <- value
```

Arguments

| | |
|-------|--|
| x | microbiomeMarker |
| value | otu_table , phyloseq , or microbiomeMarker |

Value

a [microbiomeMarker](#) object.

data-caporaso

16S rRNA data from "Moving pictures of the human microbiome"

Description

16S read counts and phylogenetic tree file of 34 Illumina samples derived from Moving Pictures of the Human Microbiome (Caporaso et al.) Group label: gut, left palm, right palm, and tongue - indicating different sampled body sites.

Format

a [phyloseq::phyloseq](#) object

Author(s)

Yang Cao

Source

Data was downloaded from <https://www.microbiomeanalyst.ca>

References

Caporaso, et al. Moving pictures of the human microbiome. *Genome Biol* 12, R50 (2011).
<https://doi.org/10.1186/gb-2011-12-5-r50>

data-cid_ying

16S rRNA data of 94 patients from CID 2012

Description

Data from a cohort of 94 Bone Marrow Transplant patients previously published on in CID

Format

a [phyloseq::phyloseq](#) object

Author(s)

Yang Cao

Source

<https://github.com/ying14/yingtools2/tree/master/data>

References

Ying, et al. Intestinal Domination and the Risk of Bacteremia in Patients Undergoing Allogeneic Hematopoietic Stem Cell Transplantation, *Clinical Infectious Diseases*, Volume 55, Issue 7, 1 October 2012, Pages 905–914,

<https://academic.oup.com/cid/article/55/7/905/428203>

data-ecam

Data from Early Childhood Antibiotics and the Microbiome (ECAM) study

Description

The data from a subset of the Early Childhood Antibiotics and the Microbiome (ECAM) study, which tracked the microbiome composition and development of 43 infants in the United States from birth to 2 years of age, identifying microbiome associations with antibiotic exposure, delivery mode, and diet.

Format

a `phyloseq::phyloseq` object

References

Bokulich, Nicholas A., et al. "Antibiotics, birth mode, and diet shape microbiome maturation during early life." *Science translational medicine* 8.343 (2016): 343ra82-343ra82.

<https://github.com/FrederickHuangLin/ANCOM/tree/master/data>

data-enterotypes_arumugam

Enterotypes data of 39 samples

Description

The data contains 22 European metagenomes from Danish, French, Italian, and Spanish individuals, and 13 Japanese and 4 American.

Format

a `phyloseq::phyloseq` object

Author(s)

Yang Cao

References

Arumugam, Manimozhiyan, et al. Enterotypes of the human gut microbiome. *nature* 473.7346 (2011): 174-180.

data-kostic_crc *Data from a study on colorectal cancer (kostic 2012)*

Description

The data from a study on colorectal cancer. Samples that had no DIAGNOSIS attribute assigned and with less than 500 reads (counts) were removed, and 191 samples remains (91 healthy and 86 Tumors).

Format

a `phyloseq::phyloseq` object

Author(s)

Yang Cao

References

Kostic et al. Genomic analysis identifies association of *Fusobacterium* with colorectal carcinoma. *Genome research*, 2012, 22(2), 292-298.

data-oxygen *Oxygen availability 16S dataset, of which taxa table has been summarized for python lefse input*

Description

A small subset of the HMP 16S dataset for finding biomarkers characterizing different level of oxygen availability in different bodysites

Format

a `phyloseq::phyloseq` object

Author(s)

Yang Cao

Source

http://huttenhower.sph.harvard.edu/webfm_send/129

data-pediatric_ibd *IBD stool samples*

Description

43 pediatric IBD stool samples obtained from the Integrative Human Microbiome Project Consortium (iHMP). Group label: CD and Controls.

Format

a `phyloseq::phyloseq` object

Author(s)

Yang Cao

Source

<https://www.microbiomeanalyst.ca/MicrobiomeAnalyst/resources>

data-spontaneous_colitis

This is a sample data from lefse python script, a 16S dataset for studying the characteristics of the fecal microbiota in a mouse model of spontaneous colitis.

Description

The dataset contains 30 abundance profiles (obtained processing the 16S reads with RDP) belonging to 10 rag2 (control) and 20 truc (case) mice.

Format

a `phyloseq::phyloseq` object

Author(s)

Yang Cao

Source

http://www.huttenhower.org/webfm_send/73

extract_posthoc_res *Extract results from a posthoc test*

Description

This function extracts the results of posthoc test.

Usage

```
extract_posthoc_res(object, features = NULL)
```

Arguments

object a `postHocTest` object.
features either `NULL` extracts results of all features, or a character vector to specify the test results of which features are extracted.

Value

a `IRanges::SimpleDataFrameList` object.

Examples

```
require(IRanges)
pht <- postHocTest(
  result = DataFrameList(
    featureA = DataFrame(
      comparisons = c("group2-group1",
                     "group3-group1",
                     "group3-group2"),
      diff_mean = runif(3),
      pvalue = rep(0.01, 3),
      ci_lower = rep(0.01, 3),
      ci_upper = rep(0.011, 3)
    ),
    featureB = DataFrame(
      comparisons = c("group2-group1",
                     "group3-group1",
                     "group3-group2"),
      diff_mean = runif(3),
      pvalue = rep(0.01, 3),
      ci_lower = rep(0.01, 3),
      ci_upper = rep(0.011, 3)
    )
  ),
  abundance = data.frame(
    featureA = runif(3),
    featureB = runif(3),
    group = c("group1", "group2", "grou3")
  )
)
```

```
)  
)  
extract_posthoc_res(pht, "featureA")[[1]]
```

get_treedata_phyloseq *Generate tree data from phyloseq object*

Description

Generate tree data from phyloseq object

Usage

```
get_treedata_phyloseq(ps, sep = "|")
```

Arguments

ps a `phyloseq::phyloseq` object
sep character, separate between different levels of taxa, default |

Value

a `tidytree::treedata` object

Author(s)

Yang Cao

import_dada2 *Import function to read the the output of dada2 as phyloseq object*

Description

Import the output of dada2 into phyloseq object

Usage

```
import_dada2(  
  seq_tab,  
  tax_tab = NULL,  
  sam_tab = NULL,  
  phy_tree = NULL,  
  keep_taxa_rows = TRUE  
)
```

Arguments

| | |
|----------------|---|
| seq_tab | matrix-like, ASV table, the output of <code>dada2::removeBimeraDenovo</code> . |
| tax_tab | matrix, taxonomy table, the output of <code>dada2::assignTaxonomy</code> or <code>dada2::addSpecies</code> . |
| sam_tab | data.frame or <code>phyloseq::sample_data</code> , sample data |
| phy_tree | <code>ape::phylo</code> class or character represents the path of the tree file |
| keep_taxa_rows | logical, whether keep taxa in rows or not in the <code>otu_table</code> of the returned <code>phyloseq</code> object, default TRUE. |

Details

The output of the `dada2` pipeline is a feature table of amplicon sequence variants (an ASV table): A matrix with rows corresponding to samples and columns to ASVs, in which the value of each entry is the number of times that ASV was observed in that sample. This table is analogous to the traditional OTU table. Conveniently, taxa names are saved as ASV1, ASV2, ..., in the returned `phyloseq` object.

Value

`phyloseq::phyloseq` object hold the taxonomy info, sample metadata, number of reads per ASV.

Examples

```
seq_tab <- readRDS(system.file("extdata", "dada2_seqtab.rds",
  package = "microbiomeMarker"
))
tax_tab <- readRDS(system.file("extdata", "dada2_taxtab.rds",
  package = "microbiomeMarker"
))
sam_tab <- read.table(system.file("extdata", "dada2_samdata.txt",
  package = "microbiomeMarker"
), sep = "\t", header = TRUE, row.names = 1)
ps <- import_dada2(seq_tab = seq_tab, tax_tab = tax_tab, sam_tab = sam_tab)
ps
```

import_qiime2

Import function to read the the output of dada2 as phyloseq object

Description

Import the `qiime2` artifacts, including feature table, taxonomic table, phylogenetic tree, representative sequence and sample metadata into `phyloseq` object.

Usage

```
import_qiime2(  
  otu_qza,  
  taxa_qza = NULL,  
  sam_tab = NULL,  
  refseq_qza = NULL,  
  tree_qza = NULL  
)
```

Arguments

| | |
|------------|---|
| otu_qza | character, file path of the feature table from qiime2. |
| taxa_qza | character, file path of the taxonomic table from qiime2, default NULL. |
| sam_tab | character, file path of the sample metadata in tsv format, default NULL. |
| refseq_qza | character, file path of the representative sequences from qiime2, default NULL. |
| tree_qza | character, file path of the phylogenetic tree from qiime2, default NULL. |

Value

[phyloseq::phyloseq](#) object.

Examples

```
otuqza_file <- system.file(  
  "extdata", "table.qza",  
  package = "microbiomeMarker"  
)  
taxaqza_file <- system.file(  
  "extdata", "taxonomy.qza",  
  package = "microbiomeMarker"  
)  
sample_file <- system.file(  
  "extdata", "sample-metadata.tsv",  
  package = "microbiomeMarker"  
)  
treeqza_file <- system.file(  
  "extdata", "tree.qza",  
  package = "microbiomeMarker"  
)  
ps <- import_qiime2(  
  otu_qza = otuqza_file, taxa_qza = taxaqza_file,  
  sam_tab = sample_file, tree_qza = treeqza_file  
)  
ps
```

| | |
|--------------|---|
| marker_table | <i>Build or access the marker_table</i> |
|--------------|---|

Description

This is the recommended function for both building and accessing microbiome marker table ([marker_table](#)).

Usage

```
marker_table(object)

## S4 method for signature 'data.frame'
marker_table(object)

## S4 method for signature 'microbiomeMarker'
marker_table(object)
```

Arguments

object an object among the set of classes defined by the microbiomeMarker package that contain marker_table

Value

a [marker_table](#) object.

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.05,
  p_adjust = "fdr"
)
marker_table(mm)
```

| | |
|--------------------|---|
| marker_table-class | <i>The S4 class for storing microbiome marker information</i> |
|--------------------|---|

Description

This Class is inherit from data.frame. Rows represent the microbiome markers and variables represents feature of the marker.

Fields

names, row.names a character vector, inherited from the input data.frame
 .data a list, each element corresponding the each column of the input data.frame
 .S3Class character, the S3 class marker_table inherited from: "data.frame"

Author(s)

Yang Cao

marker_table<- *Assign marker_table to object*

Description

This function replace the marker_table slot of object with value.

Usage

```
marker_table(object) <- value
```

Arguments

object a [microbiomeMarker](#) object to modify.
 value new value to replace the marker_table slot of object. Either a marker_table-class,
 a data.frame that can be coerced into marker_table-class.

Value

a [microbiomeMarker](#) object.

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.1,
  p_adjust = "fdr"
)
mm_marker <- marker_table(mm)
mm_marker
marker_table(mm) <- mm_marker[1:2, ]
marker_table(mm)
```

microbiomeMarker *Build microbiomeMarker-class objects*

Description

This the constructor to build the `microbiomeMarker` object, don't use the `new()` constructor.

Usage

```
microbiomeMarker(  
  marker_table = NULL,  
  norm_method = NULL,  
  diff_method = NULL,  
  ...  
)
```

Arguments

`marker_table` a `marker_table` object differential analysis.
`norm_method` character, method used to normalize the input phyloseq object.
`diff_method` character, method used for microbiome marker identification.
... arguments passed to `phyloseq::phyloseq()`

Value

a `microbiomeMarker` object.

See Also

`phyloseq::phyloseq()`

Examples

```
microbiomeMarker(  
  marker_table = marker_table(data.frame(  
    feature = c("speciesA", "speciesB"),  
    enrich_group = c("groupA", "groupB"),  
    ef_logFC = c(-2, 2),  
    pvalue = c(0.01, 0.01),  
    padj = c(0.01, 0.01),  
    row.names = c("marker1", "marker2")  
  )),  
  norm_method = "TSS",  
  diff_method = "DESeq2",  
  otu_table = otu_table(matrix(  
    c(4, 1, 1, 4),  
    nrow = 2, byrow = TRUE,  
    dimnames = list(c("speciesA", "speciesB"), c("sample1", "sample2"))  
  ))
```



```

    ),
    taxa_are_rows = TRUE
  ),
  tax_table = tax_table(matrix(
    c("speciesA", "speciesB"),
    nrow = 2,
    dimnames = list(c("speciesA", "speciesB"), "Species")
  )),
  sam_data = sample_data(data.frame(
    group = c("groupA", "groupB"),
    row.names = c("sample1", "sample2")
  ))
)

```

microbiomeMarker-class

The main class for microbiomeMarker data

Description

microbiomeMarker-class is inherited from the [phyloseq::phyloseq](#) by adding a custom slot `microbiome_marker` to save the differential analysis results. And it provides a seamless interface with **phyloseq**, which makes **microbiomeMarker** simple and easy to use. For more details on see the document of [phyloseq::phyloseq](#).

Usage

```
## S4 method for signature 'microbiomeMarker'
show(object)
```

Arguments

object a microbiomeMarker-class object

Value

a `microbiomeMarker` object.

Slots

marker_table a data.frame, a [marker_table](#) object.

norm_method character, method used to normalize the input phyloseq object.

diff_method character, method used for marker identification.

See Also

[phyloseq::phyloseq](#), [marker_table](#), [summarize_taxa\(\)](#)

| | |
|---------|---|
| nmarker | <i>Get the number of microbiome markers</i> |
|---------|---|

Description

Get the number of microbiome markers

Usage

```
nmarker(object)

## S4 method for signature 'microbiomeMarker'
nmarker(object)

## S4 method for signature 'marker_table'
nmarker(object)
```

Arguments

object a [microbiomeMarker](#) or [marker_table](#) object

Value

an integer, the number of microbiome markers

Examples

```
mt <- marker_table(data.frame(
  feature = c("speciesA", "speciesB"),
  enrich_group = c("groupA", "groupB"),
  ef_logFC = c(-2, 2),
  pvalue = c(0.01, 0.01),
  padj = c(0.01, 0.01),
  row.names = c("marker1", "marker2")
))
nmarker(mt)
```

normalize,phyloseq-method

Normalize the microbial abundance data

Description

It is critical to normalize the feature table to eliminate any bias due to differences in the sampling sequencing depth. This function implements six widely-used normalization methods for microbial compositional data.

For rarefying, reads in the different samples are randomly removed until the same predefined number has been reached, to assure all samples have the same library size. Rarefying normalization method is the standard in microbial ecology. Please note that the authors of phyloseq do not advocate using this rarefying a normalization procedure, despite its recent popularity

TSS simply transforms the feature table into relative abundance by dividing the number of total reads of each sample.

CSS is based on the assumption that the count distributions in each sample are equivalent for low abundant genes up to a certain threshold. Only the segment of each sample's count distribution that is relatively invariant across samples is scaled by CSS

RLE assumes most features are not differential and uses the relative abundances to calculate the normalization factor.

TMM calculates the normalization factor using a robust statistics based on the assumption that most features are not differential and should, in average, be equal between the samples. The TMM scaling factor is calculated as the weighted mean of log-ratios between each pair of samples, after excluding the highest count OTUs and OTUs with the largest log-fold change.

In CLR, the log-ratios are computed relative to the geometric mean of all features.

norm_cpm: This normalization method is from the original LefSe algorithm, recommended when very low values are present (as shown in the LefSe galaxy).

Usage

```
## S4 method for signature 'phyloseq'
normalize(object, method = "TSS", ...)

## S4 method for signature 'otu_table'
normalize(object, method = "TSS", ...)

## S4 method for signature 'data.frame'
normalize(object, method = "TSS", ...)

## S4 method for signature 'matrix'
normalize(object, method = "TSS", ...)

norm_rarefy(
  object,
  size = min(sample_sums(object)),
  rng_seed = FALSE,
  replace = TRUE,
  trim_otus = TRUE,
  verbose = TRUE
)
```

```

norm_tss(object)

norm_css(object, sl = 1000)

norm_rle(
  object,
  locfunc = stats::median,
  type = c("poscounts", "ratio"),
  geo_means = NULL,
  control_genes = NULL
)

norm_tmm(
  object,
  ref_column = NULL,
  logratio_trim = 0.3,
  sum_trim = 0.05,
  do_weighting = TRUE,
  Acutoff = -1e+10
)

norm_clr(object)

norm_cpm(object)

```

Arguments

| | |
|--------|---|
| object | a phyloseq::phyloseq or phyloseq::otu_table |
| method | the methods used to normalize the microbial abundance data. Options includes: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to 1e+06. |
| ... | other arguments passed to the corresponding normalization methods. |

| | |
|---|---|
| size, rng_seed, replace, trim_otus, verbose | extra arguments passed to <code>phyloseq::rarefy_even_depth()</code> . |
| s1 | The value to scale. |
| locfunc | a function to compute a location for a sample. By default, the median is used. |
| type | method for estimation: either "ratio" or "poscounts" (recommend). |
| geo_means | default NULL, which means the geometric means of the counts are used. A vector of geometric means from another count matrix can be provided for a "frozen" size factor calculation. |
| control_genes | default NULL, which means all taxa are used for size factor estimation, numeric or logical index vector specifying the taxa used for size factor estimation (e.g. core taxa). |
| ref_column | column to use as reference |
| logratio_trim | amount of trim to use on log-ratios |
| sum_trim | amount of trim to use on the combined absolute levels ("A" values) |
| do_weighting | whether to compute the weights or not |
| Acutoff | cutoff on "A" values to use before trimming |

Value

the same class with object.

See Also

`edgeR::calcNormFactors()`, `DESeq2::estimateSizeFactorsForMatrix()`, `metagenomeSeq::cumNorm()`
`phyloseq::rarefy_even_depth()`
`metagenomeSeq::calcNormFactors()`
`DESeq2::estimateSizeFactorsForMatrix()`
`edgeR::calcNormFactors()`

Examples

```
data(caporaso)
normalize(caporaso, "TSS")
```

phyloseq2DESeq2

Convert phyloseq-class object to DESeqDataSet-class object

Description

This function convert [phyloseq::phyloseq-class] to [DESeq2::DESeqDataSet-class], which can then be tested using [DESeq2::DESeq()].

Usage

```
phyloseq2DESeq2(ps, design, ...)
```

Arguments

ps the [phyloseq::phyloseq-class] object to convert, which must have a [phyloseq::sample_data()] component.

design a formula or matrix, the formula expresses how the counts for each gene depend on the variables in colData. Many R formula are valid, including designs with multiple variables, e.g., ~ group + condition. This argument is passed to [DESeq2::DESeqDataSetFromMatrix\(\)](#).

... additional arguments passed to [DESeq2::DESeqDataSetFromMatrix\(\)](#), Most users will not need to pass any additional arguments here.

Value

a [DESeq2::DESeqDataSet](#) object.

See Also

[DESeq2::DESeqDataSetFromMatrix\(\)](#), [DESeq2::DESeq\(\)](#)

Examples

```
data(caporaso)
phyloseq2DESeq2(caporaso, ~SampleType)
```

phyloseq2edgeR

Convert phyloseq data to edgeR DGEList object

Description

This function convert [phyloseq::phyloseq](#) object to [edgeR::DGEList](#) object, can then can be used to perform differential analysis using the methods in **edgeR**.

Usage

```
phyloseq2edgeR(ps, ...)
```

Arguments

ps a [phyloseq::phyloseq](#) object.

... optional, additional named arguments passed to [edgeR::DGEList\(\)](#). Most users will not need to pass any additional arguments here.

Value

A [edgeR::DGEList](#) object.

Examples

```
data(caporaso)
dge <- phyloseq2edgeR(caporaso)
```

phyloseq2metagenomeSeq

Convert phyloseq data to MetagenomeSeq MRexperiment object

Description

The phyloseq data is converted to the relevant `metagenomeSeq::MRexperiment` object, which can then be tested in the zero-inflated mixture model framework in the `metagenomeSeq` package.

Usage

```
phyloseq2metagenomeSeq(ps, ...)
otu_table2metagenomeSeq(ps, ...)
```

Arguments

`ps` `phyloseq::phyloseq` object for `phyloseq2metagenomeSeq()`, or `phyloseq::otu_table` object for `otu_table2metagenomeSeq()`.

`...` optional, additional named arguments passed to `metagenomeSeq::newMRexperiment()`. Most users will not need to pass any additional arguments here.

Value

A `metagenomeSeq::MRexperiment` object.

See Also

`metagenomeSeq::fitTimeSeries()`, `metagenomeSeq::fitLogNormal()`, `metagenomeSeq::fitZig()`, `metagenomeSeq::MRtable()`, `metagenomeSeq::MRfulltable()`

Examples

```
data(caporaso)
phyloseq2metagenomeSeq(caporaso)
```

| | |
|----------------|---------------------------------------|
| plot_abundance | <i>plot the abundances of markers</i> |
|----------------|---------------------------------------|

Description

plot the abundances of markers

Usage

```
plot_abundance(mm, label_level = 1, max_label_len = 60, markers = NULL, group)
```

Arguments

| | |
|---------------|--|
| mm | a microbiomeMarker object |
| label_level | integer, number of label levels to be displayed, default 1, 0 means display the full name of the feature |
| max_label_len | integer, maximum number of characters of feature label, default 60 |
| markers | character vector, markers to display, default NULL, indicating plot all markers. |
| group | character, the variable to set the group |

Value

a [ggplot2::ggplot](#) object.

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.01,
  p_adjust = "none"
)
plot_abundance(mm, group = "Enterotype")
```

| | |
|----------------|---|
| plot_cladogram | <i>plot cladogram of micobiomeMaker results</i> |
|----------------|---|

Description

plot cladogram of micobiomeMaker results

Usage

```
plot_cladogram(
  mm,
  color,
  only_marker = FALSE,
  branch_size = 0.2,
  alpha = 0.2,
  node_size_scale = 1,
  node_size_offset = 1,
  clade_label_level = 4,
  annotation_shape = 22,
  annotation_shape_size = 5,
  group_legend_param = list(),
  marker_legend_param = list()
)
```

Arguments

| | |
|---|--|
| mm | a microbiomeMarker object |
| color | a color vector, used to highlight the clades of microbiome biomarker. The values will be matched in order (usually alphabetical) with the groups. If this is a named vector, then the colors will be matched based on the names instead. |
| only_marker | logical, whether show all the features or only markers in the cladogram, default FALSE. |
| branch_size | numeric, size of branch, default 0.2 |
| alpha | alpha parameter for shading, default 0.2 |
| node_size_scale | the parameter 'a' controlling node size: $node_size = a * \log(\text{relative_abundance}) + b$ |
| node_size_offset | the parameter 'b' controlling node size: $node_size = a * \log(\text{relative_abundance}) + b$ |
| clade_label_level | max level of taxa used to label the clade, other level of taxa will be shown on the side |
| annotation_shape | shape used for annotation, default 22 |
| annotation_shape_size | size used for annotation shape, default 5 |
| group_legend_param, marker_legend_param | a list specifying extra parameters of group legend and marker legend, such as direction (the direction of the guide), nrow (the desired number of rows of legends). See ggplot2::guide_legend() for more details. |

Value

a ggtree object

Author(s)

Chenhao Li, Guangchuang Yu, Chenghao Zhu, Yang Cao

References

This function is modified from `clada.anno` from `microbiomeViz`.

See Also

`ggtree::ggtree()`

Examples

```
data(kostic_crc)
kostic_crc_small <- phyloseq::subset_taxa(
  kostic_crc,
  Phylum %in% c("Firmicutes")
)
mm_lefse <- run_lefse(
  kostic_crc_small,
  wilcoxon_cutoff = 0.01,
  group = "DIAGNOSIS",
  kw_cutoff = 0.01,
  multigrp_strat = TRUE,
  lda_cutoff = 4
)
plot_cladogram(mm_lefse, color = c("darkgreen", "red"))
```

plot_ef_bar

bar and dot plot of effect size of microbiomeMarker data

Description

bar and dot plot of effect size microbiomeMarker data. This function returns a `ggplot2` object that can be saved or further customized using `ggplot2` package.

Usage

```
plot_ef_bar(mm, label_level = 1, max_label_len = 60, markers = NULL)
```

```
plot_ef_dot(mm, label_level = 1, max_label_len = 60, markers = NULL)
```

Arguments

| | |
|----------------------------|--|
| <code>mm</code> | a <code>microbiomeMarker</code> object |
| <code>label_level</code> | integer, number of label levels to be displayed, default 1, 0 means display the full name of the feature |
| <code>max_label_len</code> | integer, maximum number of characters of feature label, default 60 |
| <code>markers</code> | character vector, markers to display, default NULL, indicating plot all markers. |

Value

a ggplot project

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.01,
  p_adjust = "none"
)
plot_ef_bar(mm)
```

plot_heatmap

Heatmap of microbiome marker

Description

Display the microbiome marker using heatmap, in which rows represents the marker and columns represents the samples.

Usage

```
plot_heatmap(
  mm,
  transform = c("log10", "log10p", "identity"),
  cluster_marker = FALSE,
  cluster_sample = FALSE,
  markers = NULL,
  label_level = 1,
  max_label_len = 60,
  sample_label = FALSE,
  group,
  ...
)
```

Arguments

| | |
|-----------|---|
| mm | a <code>microbiomeMarker</code> object |
| transform | transformation to apply, for more details see <code>transform_abundances()</code> : <ul style="list-style-type: none">• "identity", return the original data without any transformation.• "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$.• "log10p", the transformation is $\log_{10}(1 + \text{object})$. |

| | |
|--------------------------------|--|
| cluster_marker, cluster_sample | logical, controls whether to perform clustering in markers (rows) and samples (cols), default FALSE. |
| markers | character vector, markers to display, default NULL, indicating plot all markers. |
| label_level | integer, number of label levels to be displayed, default 1, 0 means display the full name of the feature |
| max_label_len | integer, maximum number of characters of feature label, default 60 |
| sample_label | logical, controls whether to show the sample labels in the heatmap, default FALSE. |
| group | character, the variable to set the group |
| ... | extra arguments passed to <code>ComplexHeatmap::Heatmap()</code> . |

Value

a `ComplexHeatmap::Heatmap` object.

See Also

`transform_abundances, ComplexHeatmap::Heatmap()`

Examples

```
data(kostic_crc)
kostic_crc_small <- phyloseq::subset_taxa(
  kostic_crc,
  Phylum %in% c("Firmicutes")
)
mm_lefse <- run_lefse(
  kostic_crc_small,
  wilcoxon_cutoff = 0.01,
  group = "DIAGNOSIS",
  kw_cutoff = 0.01,
  multigrp_strat = TRUE,
  lda_cutoff = 4
)
plot_heatmap(mm_lefse, group = "DIAGNOSIS")
```

plot_postHocTest postHocTest *plot*

Description

Visualize the result of post-hoc test using ggplot2

Usage

```
plot_postHocTest(pht, feature, step_increase = 0.12)
```

Arguments

pht a `postHocTest` object
feature character, to plot the post-toc test result of this feature
step_increase numeric vector with the increase in fraction of total height for every additional comparison to minimize overlap, default 0.12.

Value

a `ggplot` object

Examples

```

data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2", "Enterotype 1")
) %>%
  phyloseq::subset_taxa(Phylum == "Bacteroidetes")
pht <- run_posthoc_test(ps, group = "Enterotype")
plot_postHocTest(pht, feature = "p__Bacteroidetes|g__Alistipes")
  
```

plot_sl_roc

ROC curve of microbiome marker from supervised learning methods

Description

Show the ROC curve of the microbiome marker calculated by `run_sl`.

Usage

```
plot_sl_roc(mm, group, nfolds = 3, nrepeats = 3, tune_length = 5, ...)
```

Arguments

mm a `microbiomeMarker` object.
group, nfolds, nrepeats, tune_length, ...
 same with the `run_sl()`.

Value

a `ggplot2::ggplot` object.

See Also

[run_sl\(\)](#)

Examples

```
data(enterotypes_arumugam)
# small example phyloseq object for test
ps_s <- phyloseq::subset_taxa(
  enterotypes_arumugam,
  Phylum %in% c("Firmicutes", "Bacteroidetes")
)

set.seed(2021)
mm <- run_sl(
  ps_s,
  group = "Gender",
  taxa_rank = "Genus",
  nfolds = 2,
  nrepeats = 1,
  top_n = 15,
  norm = "TSS",
  method = "LR",
)
plot_sl_roc(mm, group = "Gender")
```

postHocTest

Build postHocTest object

Description

This function is used to create postHocTest object, and is only used for developers.

Usage

```
postHocTest(
  result,
  abundance,
  conf_level = 0.95,
  method = "tukey",
  method_str = paste("Posthoc multiple comparisons of means: ", method)
)
```

Arguments

| | |
|------------|---|
| result | a <code>IRanges::SimpleDFrameList</code> object. |
| abundance | data.frame. |
| conf_level | numeric, confidence level. |
| method | character, method for posthoc test. |
| method_str | character, illustrates which method is used for posthoc test. |

Value

a `postHocTest` object.

Examples

```
require(IRanges)
pht <- postHocTest(
  result = DataFrameList(
    featureA = DataFrame(
      comparisons = c("group2-group1",
        "group3-group1",
        "group3-group2"),
      diff_mean = runif(3),
      pvalue = rep(0.01, 3),
      ci_lower = rep(0.01, 3),
      ci_upper = rep(0.011, 3)
    ),
    featureB = DataFrame(
      comparisons = c("group2-group1",
        "group3-group1",
        "group3-group2"),
      diff_mean = runif(3),
      pvalue = rep(0.01, 3),
      ci_lower = rep(0.01, 3),
      ci_upper = rep(0.011, 3)
    )
  ),
  abundance = data.frame(
    featureA = runif(3),
    featureB = runif(3),
    group = c("group1", "group2", "grou3")
  )
)
pht
```

| | |
|-------------------|---|
| postHocTest-class | <i>The postHocTest Class, represents the result of post-hoc test result among multiple groups</i> |
|-------------------|---|

Description

The postHocTest Class, represents the result of post-hoc test result among multiple groups

Usage

```
## S4 method for signature 'postHocTest'
show(object)
```

Arguments

object a postHocTest-class object

Value

a `postHocTest` object.

Slots

result a `IRanges::DataFrameList`, each `DataFrame` consists of five variables:

- comparisons: character, specify which two groups to test (the group names are separated by "_")
- diff_mean: numeric, difference in mean abundances
- pvalue: numeric, p values
- ci_lower and ci_upper: numeric, lower and upper confidence interval of difference in mean abundances

abundance abundance of each feature in each group

conf_level confidence level

method method used for post-hoc test

method_str method illustration

Author(s)

Yang Cao

run_aldex

Perform differential analysis using ALDEx2

Description

Perform differential analysis using ALDEx2

Usage

```
run_aldex(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "none",
  norm_para = list(),
  method = c("t.test", "wilcox.test", "kruskal", "glm_anova"),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  mc_samples = 128,
```



```

    denom = c("all", "iqlr", "zero", "lvha"),
    paired = FALSE
  )

```

Arguments

| | |
|---------------|--|
| ps | a <code>phyloseq::phyloseq</code> object |
| group | character, the variable to set the group |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See <code>transform_abundances()</code> for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation (default). "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See <code>normalize()</code> for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. "rarefy": random subsampling counts to the smallest library size in the data set. "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. "CLR": centered log-ratio normalization. "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | arguments passed to specific normalization methods |
| method | test method, options include: "t.test" and "wilcox.test" for two groups comparison, "kruskal" and "glm_anova" for multiple groups comparison. |
| p_adjust | method for multiple test correction, default none, for more details see <code>stats::p.adjust</code> . |
| pvalue_cutoff | cutoff of p value, default 0.05. |
| mc_samples | integer, the number of Monte Carlo samples to use for underlying distributions estimation, 128 is usually sufficient. |

| | |
|--------|---|
| denom | character string, specify which features used to as the denominator for the geometric mean calculation. Options are: <ul style="list-style-type: none"> • "all", with all features. • "iqlr", accounts for data with systematic variation and centers the features on the set features that have variance that is between the lower and upper quartile of variance. • "zero", a more extreme case where there are many non-zero features in one condition but many zeros in another. In this case the geometric mean of each group is calculated using the set of per-group non-zero features. • "lvha", with house keeping features. |
| paired | logical, whether to perform paired tests, only worked for method "t.test" and "wilcox.test". |

Value

a `microbiomeMarker` object.

References

Fernandes, A.D., Reid, J.N., Macklaim, J.M. et al. Unifying the analysis of high-throughput sequencing datasets: characterizing RNA-seq, 16S rRNA gene sequencing and selective growth experiments by compositional data analysis. *Microbiome* 2, 15 (2014).

See Also

[ALDEx2::aldex\(\)](#)

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_aldex(ps, group = "Enterotype")
```

run_ancom

Perform differential analysis using ANCOM

Description

Perform significant test by comparing the pairwise log ratios between all features.

Usage

```
run_ancom(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "TSS",
  norm_para = list(),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  W_cutoff = 0.75,
  test = c("aov", "wilcox.test", "kruskal.test"),
  ...
)
```

Arguments

| | |
|-----------|--|
| ps | a phyloseq-class object. |
| group | character, the variable to set the group. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation. "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. "rarefy": random subsampling counts to the smallest library size in the data set. "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. |

| | |
|---------------|--|
| | <ul style="list-style-type: none"> • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to 1e+06. |
| norm_para | named list. other arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| p_adjust | method for multiple test correction, default none, for more details see stats::p.adjust . |
| pvalue_cutoff | significance level for each of the statistical tests, default 0.05. |
| W_cutoff | lower bound for the proportion for the W-statistic, default 0.7. |
| test | character, the test to determine the p value of log ratio, one of "aov", "wilcox.test", "kruskal.test". |
| ... | additional arguments passed to the test function. |

Details

In an experiment with only two treatments, this tests the following hypothesis for feature i :

$$H_{0i} : E(\log(\mu_i^1)) = E(\log(\mu_i^2))$$

where μ_i^1 and μ_i^2 are the mean abundances for feature i in the two groups.

The developers of this method recommend the following significance tests if there are 2 groups, use non-parametric Wilcoxon rank sum test [stats::wilcox.test\(\)](#). If there are more than 2 groups, use nonparametric [stats::kruskal.test\(\)](#) or one-way ANOVA [stats::aov\(\)](#).

Value

a [microbiomeMarker](#) object, in which the slot of marker_table contains four variables:

- feature, significantly different features.
- enrich_group, the class of the differential features enriched.
- effect_size, differential means for two groups, or F statistic for more than two groups.
- W, the W-statistic, number of features that a single feature is tested to be significantly different against.

Author(s)

Huang Lin, Yang Cao

References

Mandal et al. "Analysis of composition of microbiomes: a novel method for studying microbial composition", *Microbial Ecology in Health & Disease*, (2015), 26.

Examples

```

data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_ancom(ps, group = "Enterotype")

```

run_ancombc

Differential analysis of compositions of microbiomes with bias correction (ANCOM-BC).

Description

Differential abundance analysis for microbial absolute abundance data. This function is a wrapper of `ANCOMBC::ancombc()`.

Usage

```

run_ancombc(
  ps,
  group,
  formula,
  contrast = NULL,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "none",
  norm_para = list(),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  zero_cut = 0.9,
  lib_cut = 0,
  struc_zero = FALSE,
  neg_lb = FALSE,
  tol = 1e-05,
  max_iter = 100,
  conserve = FALSE,
  pvalue_cutoff = 0.05
)

```

Arguments

`ps` a `phyloseq::phyloseq` object, which consists of a feature table, a sample metadata and a taxonomy table.

`group` the name of the group variable in metadata. Specifying group is required for detecting structural zeros and performing global test.

| | |
|-----------|---|
| formula | the character string expresses how the microbial absolute abundances for each taxon depend on the variables in metadata. |
| contrast | this parameter only used for two groups comparison while there are multiple groups. For more please see the following details. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | named list. other arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| p_adjust | method to adjust p-values by. Default is "holm". Options include "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none". See stats::p.adjust() for more details. |
| zero_cut | a numerical fraction between 0 and 1. Taxa with proportion of zeroes greater than zero_cut will be excluded in the analysis. Default is 0.90. |
| lib_cut | a numerical threshold for filtering samples based on library sizes. Samples with library sizes less than lib_cut will be excluded in the analysis. Default is 0, i.e. do not filter any sample. |

| | |
|---------------|---|
| struc_zero | whether to detect structural zeros. Default is FALSE. |
| neg_lb | whether to classify a taxon as a structural zero in the corresponding study group using its asymptotic lower bound. Default is FALSE. |
| tol | the iteration convergence tolerance for the E-M algorithm. Default is 1e-05. |
| max_iter | the maximum number of iterations for the E-M algorithm. Default is 100. |
| conserve | whether to use a conservative variance estimate of the test statistic. It is recommended if the sample size is small and/or the number of differentially abundant taxa is believed to be large. Default is FALSE. |
| pvalue_cutoff | level of significance. Default is 0.05. |

Details

contrast must be a two length character or NULL (default). It is only required to set manually for two groups comparison when there are multiple groups. The order determines the direction of comparison, the first element is used to specify the reference group (control). This means that, the first element is the denominator for the fold change, and the second element is used as baseline (numerator for fold change). Otherwise, users do not need to concern this parameter (set as default NULL), and if there are two groups, the first level of groups will be set as the reference group; if there are multiple groups, it will perform an ANOVA-like testing to find markers which differ in any of the groups.

Value

a `microbiomeMarker` object.

References

Lin, Huang, and Shyamal Das Peddada. "Analysis of compositions of microbiomes with bias correction." *Nature communications* 11.1 (2020): 1-11.

See Also

[ANCOMBC::ancombc](#)

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_ancombc(ps, group = "Enterotype", formula = "Enterotype")
```

run_deseq2

*Perform DESeq differential analysis***Description**

Differential expression analysis based on the Negative Binomial distribution using **DESeq2**.

Usage

```
run_deseq2(
  ps,
  group,
  contrast = NULL,
  taxa_rank = "all",
  norm = "RLE",
  norm_para = list(),
  transform = c("identity", "log10", "log10p"),
  fitType = c("parametric", "local", "mean", "glmGamPoi"),
  sfType = "poscounts",
  betaPrior = FALSE,
  modelMatrixType,
  useT = FALSE,
  minmu = ifelse(fitType == "glmGamPoi", 1e-06, 0.5),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  ...
)
```

Arguments

| | |
|-----------|--|
| ps | ps a <code>phyloseq::phyloseq</code> object. |
| group | character, the variable to set the group, must be one of the var of the sample metadata. |
| contrast | this parameter only used for two groups comparison while there are multiple groups. For more please see the following details. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code> , e.g., OTU or ASV). |
| norm | the methods used to normalize the microbial abundance data. See <code>normalize()</code> for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. "rarefy": random subsampling counts to the smallest library size in the data set. |

| | |
|--|---|
| | <ul style="list-style-type: none"> • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. |
| norm_para | arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| fitType, sfType, betaPrior, modelMatrixType, useT, minmu | these seven parameters are inherited from DESeq2::DESeq() . <ul style="list-style-type: none"> • fitType, either "parametric", "local", "mean", or "glmGamPoi" for the type of fitting of dispersions to the mean intensity. • sfType, either "ratio", "poscounts", or "iterate" for the type of size factor estimation. We recommend to use "poscounts". • betaPrior, whether or not to put a zero-mean normal prior on the non-intercept coefficients. • modelMatrixType, either "standard" or "expanded", which describe how the model matrix, • useT, logical, where Wald statistics are assumed to follow a standard Normal. • minmu, lower bound on the estimated count for fitting gene-wise dispersion. For more details, see DESeq2::DESeq() . Most users will not need to set this arguments (just use the defaults). |
| p_adjust | method for multiple test correction, default none, for more details see stats::p.adjust . |
| pvalue_cutoff | pvalue_cutoff numeric, p value cutoff, default 0.05. |
| ... | extra parameters passed to DESeq2::DESeq() . |

Details

Note: DESeq2 requires the input is raw counts (un-normalized counts), as only the counts values allow assessing the measurement precision correctly. For more details see the vignette of DESeq2 (`vignette("DESeq2")`).

Thus, this function only supports "none", "rarefy", "RLE", "CSS", and "TMM" normalization methods. We strongly recommend using the "RLE" method (default normalization method in the DESeq2 package). The other normalization methods are used for expert users and comparisons among different normalization methods.

For two groups comparison, this function utilizes the Wald test (defined by `DESeq2::nbinomWaldTest()`) for hypothesis testing. A Wald test statistic is computed along with a probability (p-value) that a test statistic at least as extreme as the observed value were selected at random. `contrasts` are used to specify which two groups to compare. The order of the names determines the direction of fold change that is reported.

Likelihood ratio test (LRT) is used to identify the genes that significantly changed across all the different levels for multiple groups comparisons. The LRT identified the significant features by comparing the full model to the reduced model. It is testing whether a feature removed in the reduced model explains a significant variation in the data.

`contrast` must be a two length character or NULL (default). It is only required to set manually for two groups comparison when there are multiple groups. The order determines the direction of comparison, the first element is used to specify the reference group (control). This means that, the first element is the denominator for the fold change, and the second element is used as baseline (numerator for fold change). Otherwise, users do not need to concern this parameter (set as default NULL), and if there are two groups, the first level of groups will set as the reference group; if there are multiple groups, it will perform an ANOVA-like testing to find markers which difference in any of the groups.

Value

a `microbiomeMarker` object.

References

Love, Michael I., Wolfgang Huber, and Simon Anders. "Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2." *Genome biology* 15.12 (2014): 1-21.

See Also

`DESeq2::results()`, `DESeq2::DESeq()`

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
) %>%
  phyloseq::subset_taxa(Phylum %in% c("Firmicutes"))
run_deseq2(ps, group = "Enterotype")
```

run_edger

Perform differential analysis using edgeR

Description

Differential expression analysis based on the Negative Binomial distribution using **edgeR**.

Usage

```
run_edger(
  ps,
  group,
  contrast = NULL,
  taxa_rank = "all",
  method = c("LRT", "QLFT"),
  transform = c("identity", "log10", "log10p"),
  norm = "TMM",
  norm_para = list(),
  disp_para = list(),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  ...
)
```

Arguments

| | |
|-----------|--|
| ps | ps a phyloseq::phyloseq object. |
| group | character, the variable to set the group, must be one of the var of the sample metadata. |
| contrast | this parameter only used for two groups comparison while there are multiple groups. For more please see the following details. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| method | character, used for differential analysis, please see details below for more info. |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation (default). "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. "rarefy": random subsampling counts to the smallest library size in the data set. "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. |

| | |
|---------------|--|
| | <ul style="list-style-type: none"> • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to 1e+06. |
| norm_para | arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| disp_para | additional arguments passed to <code>edgeR::estimateDisp()</code> used for dispersions estimation. Most users will not need to pass any additional arguments here. |
| p_adjust | method for multiple test correction, default none, for more details see <code>stats::p.adjust</code> . |
| pvalue_cutoff | numeric, p value cutoff, default 0.05 |
| ... | extra arguments passed to the model. See <code>edgeR::glmQLFit()</code> and <code>edgeR::glmFit()</code> for more details. |

Details

Note that edgeR is designed to work with actual counts. This means that transformation is not required in any way before inputting them to edgeR.

There are two test methods for differential analysis in **edgeR**, likelihood ratio test (LRT) and quasi-likelihood F-test (QLFT). The QLFT method is recommended as it allows stricter error rate control by accounting for the uncertainty in dispersion estimation.

contrast must be a two length character or NULL (default). It is only required to set manually for two groups comparison when there are multiple groups. The order determines the direction of comparison, the first element is used to specify the reference group (control). This means that, the first element is the denominator for the fold change, and the second element is used as baseline (numerator for fold change). Otherwise, users do not need to concern this parameter (set as default NULL), and if there are two groups, the first level of groups will set as the reference group; if there are multiple groups, it will perform an ANOVA-like testing to find markers which difference in any of the groups.

Value

a `microbiomeMarker` object.

Author(s)

Yang Cao

References

Robinson, Mark D., and Alicia Oshlack. "A scaling normalization method for differential expression analysis of RNA-seq data." *Genome biology* 11.3 (2010): 1-9.

Robinson, Mark D., Davis J. McCarthy, and Gordon K. Smyth. "edgeR: a Bioconductor package for differential expression analysis of digital gene expression data." *Bioinformatics* 26.1 (2010): 139-140.

See Also

[edgeR::glmFit\(\)](#), [edgeR::glmQLFit\(\)](#), [edgeR::estimateDisp\(\)](#), [normalize\(\)](#)

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_edger(ps, group = "Enterotype")
```

run_lefse

Liner discriminant analysis (LDA) effect size (LEFSe) analysis

Description

Perform Metagenomic LEFSe analysis based on phyloseq object.

Usage

```
run_lefse(
  ps,
  group,
  subgroup = NULL,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "CPM",
  norm_para = list(),
  kw_cutoff = 0.05,
  lda_cutoff = 2,
  bootstrap_n = 30,
  bootstrap_fraction = 2/3,
  wilcoxon_cutoff = 0.05,
  multigrp_strat = FALSE,
  strict = c("0", "1", "2"),
  sample_min = 10,
  only_same_subgrp = FALSE,
  curv = FALSE
)
```

Arguments

| | |
|----------|--|
| ps | a phyloseq-class object |
| group | character, the column name to set the group |
| subgroup | character, the column name to set the subgroup |

| | |
|--------------------|---|
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | named list. other arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| kw_cutoff | numeric, p value cutoff of kw test, default 0.05 |
| lda_cutoff | numeric, lda score cutoff, default 2 |
| bootstrap_n | integer, the number of bootstrap iteration for LDA, default 30 |
| bootstrap_fraction | numeric, the subsampling fraction value for each bootstrap iteration, default 2/3 |
| wilcoxon_cutoff | numeric, p value cutoff of wilcoxon test, default 0.05 |
| multigrp_strat | logical, for multiple group tasks, whether the test is performed in a one-against one (more strict) or in a one-against all setting, default FALSE. |
| strict | multiple testing options, 0 for no correction (default), 1 for independent comparisons, 2 for independent comparison. |

| | |
|------------------|---|
| sample_min | integer, minimum number of samples per subclass for performing wilcoxon test, default 10 |
| only_same_subgrp | logical, whether perform the wilcoxon test only among the subgroups with the same name, default FALSE |
| curv | logical, whether perform the wilcoxon test using the Curtis's approach, default FALSE |

Value

a [microbiomeMarker](#) object, in which the slot of marker_table contains four variables:

- feature, significantly different features.
- enrich_group, the class of the differential features enriched.
- lda, logarithmic LDA score (effect size)
- pvalue, p value of kw test.

Author(s)

Yang Cao

References

Segata, Nicola, et al. Metagenomic biomarker discovery and explanation. *Genome biology* 12.6 (2011): R60.

See Also

[normalize](#)

Examples

```
data(kostic_crc)
kostic_crc_small <- phyloseq::subset_taxa(
  kostic_crc,
  Phylum == "Firmicutes"
)
mm_lefse <- run_lefse(
  kostic_crc_small,
  wilcoxon_cutoff = 0.01,
  group = "DIAGNOSIS",
  kw_cutoff = 0.01,
  multigrp_strat = TRUE,
  lda_cutoff = 4
)
```

run_limma_voom *Differential analysis using limma-voom*

Description

Differential analysis using limma-voom

Usage

```
run_limma_voom(
  ps,
  group,
  contrast = NULL,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "none",
  norm_para = list(),
  voom_span = 0.5,
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  ...
)
```

Arguments

| | |
|-----------|---|
| ps | ps a phyloseq::phyloseq object. |
| group | character, the variable to set the group, must be one of the var of the sample metadata. |
| contrast | this parameter only used for two groups comparison while there are multiple groups. For more please see the following details. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation (default). "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. |

- "rarefy": random subsampling counts to the smallest library size in the data set.
- "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference.
- "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference.
- "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold.

| | |
|---------------|---|
| norm_para | arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| voom_span | width of the smoothing window used for the lowess mean-variance trend for <code>limma::voom()</code> . Expressed as a proportion between 0 and 1. |
| p_adjust | method for multiple test correction, default none, for more details see <code>stats::p.adjust</code> . |
| pvalue_cutoff | cutoff of p value, default 0.05. |
| ... | extra arguments passed to <code>limma::eBayes()</code> . |

Details

contrast must be a two length character or NULL (default). It is only required to set manually for two groups comparison when there are multiple groups. The order determines the direction of comparison, the first element is used to specify the reference group (control). This means that, the first element is the denominator for the fold change, and the second element is used as baseline (numerator for fold change). Otherwise, users do not need to concern this parameter (set as default NULL), and if there are two groups, the first level of groups will set as the reference group; if there are multiple groups, it will perform an ANOVA-like testing to find markers which difference in any of the groups.

Value

a `microbiomeMarker` object.

References

Law, C. W., Chen, Y., Shi, W., & Smyth, G. K. (2014). voom: Precision weights unlock linear model analysis tools for RNA-seq read counts. *Genome biology*, 15(2), 1-17.

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.01,
```

```

    p_adjust = "none"
  )
mm

```

run_marker

Find makers (differentially expressed metagenomic features)

Description

run_marker is a wrapper of all differential analysis functions.

Usage

```

run_marker(
  ps,
  group,
  da_method = c("lefse", "simple_t", "simple_welch", "simple_white", "simple_kruskal",
    "simple_anova", "edger", "deseq2", "metagenomeseq", "ancom", "ancombc", "aldex",
    "limma_voom", "sl_lr", "sl_rf", "sl_svm"),
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "none",
  norm_para = list(),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  ...
)

```

Arguments

| | |
|-----------|--|
| ps | a <code>phyloseq::phyloseq</code> object |
| group | character, the variable to set the group |
| da_method | character to specify the differential analysis method. The options include: <ul style="list-style-type: none"> "lefse", linear discriminant analysis (LDA) effect size (LEfSe) method, for more details see <code>run_lefse()</code>. "simple_t", "simple_welch", "simple_white", "simple_kruskal", and "simple_anova", simple statistic methods; "simple_t", "simple_welch" and "simple_white" for two groups comparison; "simple_kruskal", and "simple_anova" for multiple groups comparison. For more details see <code>run_simple_stat()</code>. "edger", see <code>run_edger()</code>. "deseq2", see <code>run_deseq2()</code>. "metagenomeseq", differential expression analysis based on the Zero-inflated Log-Normal mixture model or Zero-inflated Gaussian mixture model using metagenomeSeq, see <code>run_metagenomeseq()</code>. "ancom", see <code>run_ancom()</code>. |

| | |
|---------------|---|
| | <ul style="list-style-type: none"> • "ancombc", differential analysis of compositions of microbiomes with bias correction, see run_ancombc(). • "aldex", see run_aldex(). • "limma_voom", see run_limma_voom(). • "sl_lr", "sl_rf", and "sl_svm", three supervised learning (SL) methods: logistic regression (lr), random forest (rf), or support vector machine (svm). For more details see run_sl(). |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | arguments passed to specific normalization methods |
| p_adjust | method for multiple test correction, default none, for more details see stats::p.adjust . |
| pvalue_cutoff | numeric, p value cutoff, default 0.05. |
| ... | extra arguments passed to the corresponding differential analysis functions, e.g. run_lefse() . |

Details

This function is only a wrapper of all differential analysis functions, We recommend to use the corresponding function, since it has a better default arguments setting.

Value

a `microbiomeMarker` object.

See Also

`run_lefse()`, `run_simple_stat()`, `run_test_two_groups()`, `run_test_multiple_groups()`, `run_edger()`, `run_deseq2()`, `run_metagenomeseq()`, `run_ancom()`, `run_ancombc()`, `run_aldex()`, `run_limma_voom()`, `run_sl()`

| | |
|-------------------|--|
| run_metagenomeseq | <i>metagenomeSeq differential analysis</i> |
|-------------------|--|

Description

Differential expression analysis based on the Zero-inflated Log-Normal mixture model or Zero-inflated Gaussian mixture model using `metagenomeSeq`.

Usage

```
run_metagenomeseq(
  ps,
  group,
  contrast = NULL,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "CSS",
  norm_para = list(),
  method = c("ZILN", "ZIG"),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  ...
)
```

Arguments

| | |
|----------|--|
| ps | ps a <code>phyloseq::phyloseq</code> object. |
| group | character, the variable to set the group, must be one of the var of the sample metadata. |
| contrast | this parameter only used for two groups comparison while there are multiple groups. For more please see the following details. |

| | |
|---------------|---|
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(ps)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(ps)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | arguments passed to specific normalization methods. |
| method | character, which model used for differential analysis, "ZILN" (Zero-inflated Log-Normal mixture model) or "ZIG" (Zero-inflated Gaussian mixture model). And the zero-inflated log-normal model is preferred due to the high sensitivity and low FDR. |
| p_adjust | method for multiple test correction, default none, for more details see stats::p.adjust . |
| pvalue_cutoff | numeric, p value cutoff, default 0.05 |
| ... | extra arguments passed to the model. more details see metagenomeSeq::fitFeatureModel() and metagenomeSeq::fitZig() , e.g. control (can be setted using metagenomeSeq::zigControl() for metagenomeSeq::fitZig()). |

Details

metagenomeSeq provides two differential analysis methods, zero-inflated log-normal mixture model (implemented in [metagenomeSeq::fitFeatureModel\(\)](#)) and zero-inflated Gaussian mixture model

(implemented in `metagenomeSeq::fitZig()`). We recommend `fitFeatureModel` over `fitZig` due to high sensitivity and low FDR. Both `metagenomeSeq::fitFeatureModel()` and `metagenomeSeq::fitZig()` require the abundance profiles before normalization.

For `metagenomeSeq::fitZig()`, the output column is the coefficient of interest, and `logFC` column in the output of `metagenomeSeq::fitFeatureModel()` is analogous to coefficient. Thus, `logFC` is really just the estimate the coefficient of interest in `metagenomeSeq::fitFeatureModel()`. For more details see these question [Difference between fitFeatureModel and fitZIG in metagenomeSeq](#).

`contrast` must be a two length character or `NULL` (default). It is only required to set manually for two groups comparison when there are multiple groups. The order determines the direction of comparison, the first element is used to specify the reference group (control). This means that, the first element is the denominator for the fold change, and the second element is used as baseline (numerator for fold change). Otherwise, users do required to concern this parameter (set as default `NULL`), and if there are two groups, the first level of groups will set as the reference group; if there are multiple groups, it will perform an ANOVA-like testing to find markers which difference in any of the groups.

Of note, `metagenomeSeq::fitFeatureModel()` is not allows for multiple groups comparison.

Value

a `microbiomeMarker` object.

Author(s)

Yang Cao

References

Paulson, Joseph N., et al. "Differential abundance analysis for microbial marker-gene surveys." *Nature methods* 10.12 (2013): 1200-1202.

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_metagenomeseq(ps, group = "Enterotype")
```

run_posthoc_test

Post hoc pairwise comparisons for multiple groups test.

Description

Multiple group test, such as anova and Kruskal-Wallis rank sum test, can be used to uncover the significant feature among all groups. Post hoc tests are used to uncover specific mean differences between pair of groups.

Usage

```
run_posthoc_test(
  ps,
  group,
  transform = c("identity", "log10", "log10p"),
  norm = "TSS",
  norm_para = list(),
  conf_level = 0.95,
  method = c("tukey", "games_howell", "scheffe", "welch_uncorrected")
)
```

Arguments

| | |
|------------|--|
| ps | a <code>phyloseq::phyloseq</code> object |
| group | character, the variable to set the group |
| transform | character, the methods used to transform the microbial abundance. See <code>transform_abundances()</code> for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See <code>normalize()</code> for more details. Options include: <ul style="list-style-type: none"> • a integer, e.g. 1e6 (default), indicating pre-sample normalization of the sum of the values to 1e6. • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. |
| norm_para | arguments passed to specific normalization methods |
| conf_level | confidence level, default 0.95 |
| method | one of "tukey", "games_howell", "scheffe", "welch_uncorrected", defining the method for the pairwise comparisons. See details for more information. |

Value

a `postHocTest` object

See Also

`postHocTest`, `run_test_multiple_groups()`

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2", "Enterotype 1")
) %>%
  phyloseq::subset_taxa(Phylum == "Bacteroidetes")
pht <- run_posthoc_test(ps, group = "Enterotype")
pht
```

`run_simple_stat`*Simple statistical analysis of metagenomic profiles*

Description

Perform simple statistical analysis of metagenomic profiles. This function is a wrapper of `run_test_two_groups` and `run_test_multiple_groups`.

Usage

```
run_simple_stat(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "TSS",
  norm_para = list(),
  method = c("welch.test", "t.test", "white.test", "anova", "kruskal"),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  diff_mean_cutoff = NULL,
  ratio_cutoff = NULL,
  eta_squared_cutoff = NULL,
  conf_level = 0.95,
  nperm = 1000,
  ...
)
```


Arguments

| | |
|--------------------------------|--|
| ps | a <code>phyloseq::phyloseq</code> object |
| group | character, the variable to set the group |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See <code>transform_abundances()</code> for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation (default). "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See <code>normalize()</code> for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. "rarefy": random subsampling counts to the smallest library size in the data set. "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. "CLR": centered log-ratio normalization. "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | arguments passed to specific normalization methods |
| method | test method, options include: "welch.test", "t.test" and "white.test" for two groups comparison, "anova" and "kruskal" for multiple groups comparison. |
| p_adjust | method for multiple test correction, default none, for more details see <code>stats::p.adjust</code> . |
| pvalue_cutoff | numeric, p value cutoff, default 0.05 |
| diff_mean_cutoff, ratio_cutoff | only used for two groups comparison, cutoff of different means and ratios, default NULL which means no effect size filter. |
| eta_squared_cutoff | only used for multiple groups comparison, numeric, cutoff of effect size (eta squared) default NULL which means no effect size filter. |

`conf_level` only used for two groups comparison, numeric, confidence level of interval.
`nperm` integer, only used for two groups comparison, number of permutations for white non parametric t test estimation
`...` only used for two groups comparison, extra arguments passed to `t.test()` or `fisher.test()`.

Value

a `microbiomeMarker` object.

See Also

`run_test_two_groups()`, `run_test_multiple_groups()`

Examples

```

data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2")
)
run_simple_stat(ps, group = "Enterotype")

```

run_sl

Identify biomarkers using supervised learning (SL) methods

Description

Identify biomarkers using logistic regression, random forest, or support vector machine.

Usage

```

run_sl(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "none",
  norm_para = list(),
  nfolds = 3,
  nrepeats = 3,
  sampling = NULL,
  tune_length = 5,
  top_n = 10,
  method = c("LR", "RF", "SVM"),
  ...
)

```

Arguments

| | |
|-------------|---|
| ps | a phyloseq-class object. |
| group | character, the variable to set the group. |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. • "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference. • "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference. • "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold. • "CLR": centered log-ratio normalization. • "CPM": pre-sample normalization of the sum of the values to $1e+06$. |
| norm_para | named list. other arguments passed to specific normalization methods. Most users will not need to pass any additional arguments here. |
| nfolds | the number of splits in CV. |
| nrepeats | the number of complete sets of folds to compute. |
| sampling | a single character value describing the type of additional sampling that is conducted after resampling (usually to resolve class imbalances). Values are "none", "down", "up", "smote", or "rose". For more details see caret::trainControl() . |
| tune_length | an integer denoting the amount of granularity in the tuning parameter grid. For more details see caret::train() . |

| | |
|--------|--|
| top_n | an integer denoting the top n features as the biomarker according the importance score. |
| method | supervised learning method, options are "LR" (logistic regression), "RF" (random forest), or "SVM" (support vector machine). |
| ... | extra arguments passed to the classification. e.g., importance for randomForest::randomForest. |

Details

Only support two groups comparison in the current version. And the marker was selected based on its importance score. Moreover, The hyper-parameters are selected automatically by a grid-search based method in the N-time K-fold cross-validation. Thus, the identified biomarker based can be biased due to model overfitting for small datasets (e.g., with less than 100 samples).

The argument top_n is used to denote the number of markers based on the importance score. There is no rule or principle on how to select top_n, however, usually it is very useful to try a different top_n and compare the performance of the marker predictions for the testing data.

Value

a [microbiomeMarker](#) object.

Author(s)

Yang Cao

See Also

[caret::train\(\)](#), [caret::trainControl\(\)](#)

Examples

```
data(enterotypes_arumugam)
# small example phyloseq object for test
ps_small <- phyloseq::subset_taxa(
  enterotypes_arumugam,
  Phylum %in% c("Firmicutes", "Bacteroidetes")
)

set.seed(2021)
mm <- run_sl(
  ps_small,
  group = "Gender",
  taxa_rank = "Genus",
  nfolds = 2,
  nrepeats = 1,
  top_n = 15,
  norm = "TSS",
  method = "LR",
)
mm
```

```
run_test_multiple_groups
    Statistical test for multiple groups
```

Description

Statistical test for multiple groups

Usage

```
run_test_multiple_groups(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "TSS",
  norm_para = list(),
  method = c("anova", "kruskal"),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  effect_size_cutoff = NULL
)
```

Arguments

| | |
|-----------|---|
| ps | a phyloseq::phyloseq object |
| group | character, the variable to set the group |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code>), e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation (default). • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> • "none": do not normalize. • "rarefy": random subsampling counts to the smallest library size in the data set. • "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size. |

- "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference.
- "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference.
- "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold.
- "CLR": centered log-ratio normalization.
- "CPM": pre-sample normalization of the sum of the values to 1e+06.

| | |
|--------------------|---|
| norm_para | arguments passed to specific normalization methods |
| method | test method, must be one of "anova" or "kruskal" |
| p_adjust | method for multiple test correction, default none, for more details see stats::p.adjust . |
| pvalue_cutoff | numeric, p value cutoff, default 0.05. |
| effect_size_cutoff | numeric, cutoff of effect size default NULL which means no effect size filter. The eta squared is used to measure the effect size for anova/kruskal test. |

Value

a `microbiomeMarker` object.

See Also

[run_posthoc_test\(\)](#), [run_test_two_groups\(\)](#), [run_simple_stat\(\)](#)

Examples

```
data(enterotypes_arumugam)
ps <- phyloseq::subset_samples(
  enterotypes_arumugam,
  Enterotype %in% c("Enterotype 3", "Enterotype 2", "Enterotype 1")
)
mm_anova <- run_test_multiple_groups(
  ps,
  group = "Enterotype",
  method = "anova"
)
```

run_test_two_groups *Statistical test between two groups*

Description

Statistical test between two groups

Usage

```
run_test_two_groups(
  ps,
  group,
  taxa_rank = "all",
  transform = c("identity", "log10", "log10p"),
  norm = "TSS",
  norm_para = list(),
  method = c("welch.test", "t.test", "white.test"),
  p_adjust = c("none", "fdr", "bonferroni", "holm", "hochberg", "hommel", "BH", "BY"),
  pvalue_cutoff = 0.05,
  diff_mean_cutoff = NULL,
  ratio_cutoff = NULL,
  conf_level = 0.95,
  nperm = 1000,
  ...
)
```

Arguments

| | |
|-----------|---|
| ps | a phyloseq::phyloseq object |
| group | character, the variable to set the group |
| taxa_rank | character to specify taxonomic rank to perform differential analysis on. Should be one of <code>phyloseq::rank_names(phyloseq)</code> , or "all" means to summarize the taxa by the top taxa ranks (<code>summarize_taxa(ps, level = rank_names(ps)[1])</code>), or "none" means perform differential analysis on the original taxa (<code>taxa_names(phyloseq)</code> , e.g., OTU or ASV). |
| transform | character, the methods used to transform the microbial abundance. See transform_abundances() for more details. The options include: <ul style="list-style-type: none"> "identity", return the original data without any transformation (default). "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. "log10p", the transformation is $\log_{10}(1 + \text{object})$. |
| norm | the methods used to normalize the microbial abundance data. See normalize() for more details. Options include: <ul style="list-style-type: none"> "none": do not normalize. |

- "rarefy": random subsampling counts to the smallest library size in the data set.
- "TSS": total sum scaling, also referred to as "relative abundance", the abundances were normalized by dividing the corresponding sample library size.
- "TMM": trimmed mean of m-values. First, a sample is chosen as reference. The scaling factor is then derived using a weighted trimmed mean over the differences of the log-transformed gene-count fold-change between the sample and the reference.
- "RLE", relative log expression, RLE uses a pseudo-reference calculated using the geometric mean of the gene-specific abundances over all samples. The scaling factors are then calculated as the median of the gene counts ratios between the samples and the reference.
- "CSS": cumulative sum scaling, calculates scaling factors as the cumulative sum of gene abundances up to a data-derived threshold.
- "CLR": centered log-ratio normalization.
- "CPM": pre-sample normalization of the sum of the values to 1e+06.

norm_para arguments passed to specific normalization methods
 method test method, must be one of "welch.test", "t.test" or "white.test"
 p_adjust method for multiple test correction, default none, for more details see [stats::p.adjust](#).
 pvalue_cutoff numeric, p value cutoff, default 0.05
 diff_mean_cutoff, ratio_cutoff
 cutoff of different means and ratios, default NULL which means no effect size filter.
 conf_level numeric, confidence level of interval.
 nperm integer, number of permutations for white non parametric t test estimation
 ... extra arguments passed to [t.test\(\)](#) or [fisher.test\(\)](#)

Value

a [microbiomeMarker](#) object.

Author(s)

Yang Cao

See Also

[run_test_multiple_groups\(\)](#), [run_simple_stat](#)

Examples

```
data(enterotypes_arumugam)
mm_welch <- run_test_two_groups(
  enterotypes_arumugam,
  group = "Gender",
  method = "welch.test"
)
mm_welch
```

| | |
|---------------|----------------------------------|
| subset_marker | <i>Subset microbiome markers</i> |
|---------------|----------------------------------|

Description

Subset markers based on an expression related to the columns and values within the `marker_table` slot of `mm`.

Usage

```
subset_marker(mm, ...)
```

Arguments

`mm` a `microbiomeMarker` or `marker_table` object.
`...` the subsetting expression passed to `base::subset()`.

Value

a subset object in the same class with `mm`.

Examples

```
data(enterotypes_arumugam)
mm <- run_limma_voom(
  enterotypes_arumugam,
  "Enterotype",
  contrast = c("Enterotype 3", "Enterotype 2"),
  pvalue_cutoff = 0.01,
  p_adjust = "none"
)
subset_marker(mm, enrich_group == "Enterotype 3")
```

| | |
|----------------|---|
| summarize_taxa | <i>Summarize taxa into a taxonomic level within each sample</i> |
|----------------|---|

Description

Provides summary information of the representation of a taxonomic levels within each sample.

Usage

```
summarize_taxa(ps, level = rank_names(ps)[1], absolute = TRUE, sep = "|")
```

Arguments

| | |
|----------|--|
| ps | a phyloseq-class object. |
| level | taxonomic level to summarize, default the top level rank of the ps. |
| absolute | logical, whether return the absolute abundance or relative abundance, default FALSE. |
| sep | a character string to separate the taxonomic levels. |

Value

a [phyloseq:phyloseq](#) object, where each row represents a taxa, and each col represents the taxa abundance of each sample.

Examples

```
data(enterotypes_arumugam)
summarize_taxa(enterotypes_arumugam)
```

transform_abundances *Transform the taxa abundances in otu_table sample by sample*

Description

Transform the taxa abundances in otu_table sample by sample, which means the counts of each sample will be transformed individually.

Usage

```
transform_abundances(object, transform = c("identity", "log10", "log10p"))
```

Arguments

| | |
|-----------|---|
| object | otu_table , phyloseq , or microbiomeMarker . |
| transform | transformation to apply, the options include: <ul style="list-style-type: none"> • "identity", return the original data without any transformation. • "log10", the transformation is $\log_{10}(\text{object})$, and if the data contains zeros the transformation is $\log_{10}(1 + \text{object})$. • "log10p", the transformation is $\log_{10}(1 + \text{object})$. |

Value

A object matches the class of argument object with the transformed otu_table.

See Also

[abundances\(\)](#)

Examples

```

data(oxygen)
x1 <- transform_abundances(oxygen)
head(otu_table(x1), 10)
x2 <- transform_abundances(oxygen, "log10")
head(otu_table(x2), 10)
x3 <- transform_abundances(oxygen, "log10p")
head(otu_table(x3), 10)

```

[*Extract marker_table object*]

Description

Operators acting on `marker_table` to extract parts.

Usage

```

## S4 method for signature 'marker_table,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

```

Arguments

x object from which to extract element(s) or in which to replace element(s).

i indices specifying elements to extract or replace. Indices are numeric or character vectors or empty (missing) or NULL. Numeric values are coerced to integer as by `as.integer` (and hence truncated towards zero). Character vectors will be matched to the `names` of the object (or for matrices/arrays, the `dimnames`): see ‘Character indices’ below for further details.

For [-indexing only: `i, j, ...` can be logical vectors, indicating elements/slices to select. Such vectors are recycled if necessary to match the corresponding extent. `i, j, ...` can also be negative integers, indicating elements/slices to leave out of the selection.

When indexing arrays by [a single argument `i` can be a matrix with as many columns as there are dimensions of `x`; the result is then a vector with elements corresponding to the sets of indices in each row of `i`.

An index value of NULL is treated as if it were `integer(0)`.

j indices specifying elements to extract or replace. Indices are numeric or character vectors or empty (missing) or NULL. Numeric values are coerced to integer as by `as.integer` (and hence truncated towards zero). Character vectors will be matched to the `names` of the object (or for matrices/arrays, the `dimnames`): see ‘Character indices’ below for further details.

For [-indexing only: `i, j, ...` can be logical vectors, indicating elements/slices to select. Such vectors are recycled if necessary to match the corresponding extent. `i, j, ...` can also be negative integers, indicating elements/slices to leave out of the selection.

When indexing arrays by [a single argument *i* can be a matrix with as many columns as there are dimensions of *x*; the result is then a vector with elements corresponding to the sets of indices in each row of *i*.

An index value of `NULL` is treated as if it were `integer(0)`.

... see [base::Extract\(\)](#).
drop ignored now.

Value

a `marker_table` object.

See Also

[base::Extract\(\)](#)

Index

* utilities

- aggregate_taxa, 4
- [, 67
- [,marker_table,ANY,ANY,ANY-method ([], 67
- abundances, 3
- abundances(), 66
- abundances, (abundances), 3
- abundances,microbiomeMarker-method (abundances), 3
- abundances,otu_table-method (abundances), 3
- abundances,phyloseq-method (abundances), 3
- aggregate_taxa, 4
- ALDEx2::aldex(), 34
- ANCOMBC::ancombc, 39
- ANCOMBC::ancombc(), 37
- ape::phylo, 12
- as.integer, 67
- assign-marker_table (marker_table<-), 15
- assign-otu_table, 5
- base::Extract(), 68
- base::subset(), 65
- caporaso (data-caporaso), 6
- caret::train(), 59, 60
- caret::trainControl(), 59, 60
- cid_ying (data-cid_ying), 6
- ComplexHeatmap::Heatmap, 28
- ComplexHeatmap::Heatmap(), 28
- data-caporaso, 6
- data-cid_ying, 6
- data-ecam, 7
- data-enterotypes_arumugam, 7
- data-kostic_crc, 8
- data-oxygen, 8
- data-pediatric_ibd, 9
- data-spontaneous_colitis, 9
- DESeq2::DESeq(), 22, 41, 42
- DESeq2::DESeqDataSet, 22
- DESeq2::DESeqDataSetFromMatrix(), 22
- DESeq2::estimateSizeFactorsForMatrix(), 21
- DESeq2::nbinomWaldTest(), 42
- DESeq2::results(), 42
- dimnames, 67
- ecam (data-ecam), 7
- edgeR::calcNormFactors(), 21
- edgeR::DGEList, 22
- edgeR::DGEList(), 22
- edgeR::estimateDisp(), 44, 45
- edgeR::glmFit(), 44, 45
- edgeR::glmQLFit(), 44, 45
- ef-barplot,ef-dotplot (plot_ef_bar), 26
- enterotypes_arumugam (data-enterotypes_arumugam), 7
- extract_posthoc_res, 10
- fisher.test(), 58, 64
- get_treedata_phyloseq, 11
- ggplot2::ggplot, 24, 29
- ggplot2::guide_legend(), 25
- ggtree::ggtree(), 26
- import_dada2, 11
- import_qiime2, 12
- IRanges::DataFrameList, 32
- IRanges::SimpleDFrameList, 10, 30
- kostic_crc (data-kostic_crc), 8
- limma::eBayes(), 49
- limma::voom(), 49
- marker_table, 14, 14, 16–18, 65

- marker_table, data.frame-method
(marker_table), 14
- marker_table, microbiomeMarker-method
(marker_table), 14
- marker_table-class, 14
- marker_table<-, 15
- metagenomeSeq::calcNormFactors(), 21
- metagenomeSeq::cumNorm(), 21
- metagenomeSeq::fitFeatureModel(), 53, 54
- metagenomeSeq::fitLogNormal(), 23
- metagenomeSeq::fitTimeSeries(), 23
- metagenomeSeq::fitZig(), 23, 53, 54
- metagenomeSeq::MRexperiment, 23
- metagenomeSeq::MRfulltable(), 23
- metagenomeSeq::MRtable(), 23
- metagenomeSeq::newMRexperiment(), 23
- metagenomeSeq::zigControl(), 53
- microbiomeMarker, 4, 5, 15, 16, 16, 17, 18, 24–27, 29, 34, 36, 39, 42, 44, 47, 49, 52, 54, 58, 60, 62, 64–66
- microbiomeMarker-class, 17
- microbiomeMarker-package, 3
- names, 67
- nmarker, 18
- nmarker, marker_table-method (nmarker), 18
- nmarker, microbiomeMarker-method (nmarker), 18
- norm_clr (normalize, phyloseq-method), 18
- norm_cpm (normalize, phyloseq-method), 18
- norm_css (normalize, phyloseq-method), 18
- norm_rarefy
(normalize, phyloseq-method), 18
- norm_rle (normalize, phyloseq-method), 18
- norm_tmm (normalize, phyloseq-method), 18
- norm_tss (normalize, phyloseq-method), 18
- normalize, 47
- normalize (normalize, phyloseq-method), 18
- normalize(), 33, 35, 38, 40, 43, 45, 46, 48, 51, 53, 55, 57, 59, 61, 63
- normalize, data.frame-method
(normalize, phyloseq-method), 18
- normalize, matrix-method
(normalize, phyloseq-method), 18
- normalize, otu_table-method
(normalize, phyloseq-method), 18
- normalize, phyloseq-method, 18
- otu_table, 4, 5, 66
- otu_table-method (abundances), 3
- otu_table2metagenomeSeq
(phyloseq2metagenomeSeq), 23
- otu_table<-, microbiomeMarker, microbiomeMarker-method
(assign-otu_table), 5
- otu_table<-, microbiomeMarker, otu_table-method
(assign-otu_table), 5
- otu_table<-, microbiomeMarker, phyloseq-method
(assign-otu_table), 5
- oxygen (data-oxygen), 8
- pediatric_ibd (data-pediatric_ibd), 9
- phyloseq, 4, 5, 66
- phyloseq2DESeq2, 21
- phyloseq2edgeR, 22
- phyloseq2metagenomeSeq, 23
- phyloseq::otu_table, 20, 23
- phyloseq::phyloseq, 6–9, 11–13, 17, 20, 22, 23, 33, 37, 40, 43, 48, 50, 52, 55, 57, 61, 63, 66
- phyloseq::phyloseq(), 16
- phyloseq::rarefy_even_depth(), 21
- phyloseq::sample_data, 12
- plot_abundance, 24
- plot_cladogram, 24
- plot_ef_bar, 26
- plot_ef_dot (plot_ef_bar), 26
- plot_heatmap, 27
- plot_postHocTest, 28
- plot_sl_roc, 29
- postHocTest, 10, 29, 30, 31, 32, 56
- postHocTest-class, 31
- postHocTest-method (postHocTest-class), 31
- run_aldex, 32
- run_aldex(), 51, 52
- run_ancom, 34
- run_ancom(), 50, 52
- run_ancombc, 37
- run_ancombc(), 51, 52
- run_deseq2, 40
- run_deseq2(), 50, 52
- run_edger, 42
- run_edger(), 50, 52
- run_lefse, 45

run_lefse(), 50–52
run_limma_voom, 48
run_limma_voom(), 51, 52
run_marker, 50
run_metagenomeseq, 52, 52
run_metagenomeseq(), 50
run_posthoc_test, 54
run_posthoc_test(), 62
run_simple_stat, 56, 64
run_simple_stat(), 50, 52, 62
run_sl, 58
run_sl(), 29, 51, 52
run_test_multiple_groups, 61
run_test_multiple_groups(), 52, 56, 58,
64
run_test_two_groups, 63
run_test_two_groups(), 52, 58, 62

show, (postHocTest-class), 31
show, microbiomeMarker-method
 (microbiomeMarker-class), 17
show, postHocTest-method
 (postHocTest-class), 31
spontaneous_colitis
 (data-spontaneous_colitis), 9
stats::aov(), 36
stats::kruskal.test(), 36
stats::p.adjust, 33, 36, 41, 44, 49, 51, 53,
57, 62, 64
stats::p.adjust(), 38
stats::wilcox.test(), 36
subset_marker, 65
summarize_taxa, 65
summarize_taxa(), 17

t.test(), 58, 64
tidytree::treedata, 11
transform_abundances, 4, 28, 66
transform_abundances(), 27, 33, 35, 38, 41,
43, 46, 48, 51, 53, 55, 57, 59, 61, 63