

# lmdme: Linear Models on Designed Multivariate Experiments in R

**Cristóbal Fresno**  
Universidad Católica de Córdoba

**Mónica G Balzarini**  
Universidad Nacional de Córdoba

**Elmer A Fernández**  
Universidad Católica de Córdoba

---

## Abstract

This introduction to linear model on designed multivariate experiments of the R package **lmdme** is a (slightly) modified version of Fresno *et al.* (2014), published in the *Journal of Statistical Software*.

The **lmdme** package (Fresno and Fernández 2013a) decomposes analysis of variance (ANOVA) through linear models on designed multivariate experiments, allowing ANOVA-principal component analysis (APCA) and ANOVA-simultaneous component analysis (ASCA) in R (R Development Core Team 2012). It also extends both methods with the application of partial least squares (PLS) through the specification of a desired output matrix. The package is freely available on the Bioconductor website (Gentleman *et al.* 2004), licensed under GNU general public license.

ANOVA decomposition methods for designed multivariate experiments are becoming popular in “omics” experiments (transcriptomics, metabolomics, etc.), where measurements are performed according to a predefined experimental design (Smilde *et al.* 2005), with several experimental factors or including subject-specific clinical covariates, such as those present in current clinical genomic studies. ANOVA-PCA and ASCA are well-suited methods for studying interaction patterns on multidimensional datasets. However, current R implementation of APCA is only available for *Spectra* data in **ChemoSpec** package (Hanson 2012), whereas ASCA (Nueda *et al.* 2007) is based on average calculations on the indices of up to three design matrices. Thus, no statistical inference on estimated effects is provided. Moreover, ASCA is not available in R package format.

Here, we present an R implementation for ANOVA decomposition with PCA/PLS analysis that allows the user to specify (through a flexible `formula` interface), almost any linear model with the associated inference on the estimated effects, as well as to display functions to explore results both of PCA and PLS. We describe the model, its implementation and one high-throughput *microarray* example applied to interaction pattern analysis.

*Keywords:* linear model, ANOVA decomposition, PCA, PLS, designed experiments, R.

---

## 1. Introduction

Current “omics” experiments (proteomics, transcriptomics, metabolomics or genomics) are multivariate in nature. Modern technology allows us to explore the whole genome or a big subset of the proteome, where each gene/protein is in essence a variable explored to elucidate its relationship with an outcome. In addition, these experiments are including an increasing number of experimental factors (time, dose, etc.) from design or subject-specific information, such as age, gender and lineage, and are available for analysis. Hence, to decipher experimental design or subject-specific patterns, some multivariate approaches should be applied, with principal component analysis (PCA) and partial least squares regression (PLS) being the most common. However, it is known that working with raw data might mask information of interest. Therefore, analysis of variance (ANOVA)-based decomposition is becoming popular to split variability sources before applying such multivariate approaches. Seminal works on genomics were that of De Haan *et al.* (2007) on ANOVA-PCA (APCA) and of Smilde *et al.* (2005) on ANOVA-SCA (ASCA) models. However, to the best of our knowledge R implementation of APCA is only available for *Spectra* data, **ChemoSpec** R package by Hanson (2012). Regarding ASCA, as there is no R package for this model, it can only be used by uploading script-function files resulting from a MATLAB code translation (Nueda *et al.* 2007). In addition, ASCA only accepts up to three design matrices, which limits its use and makes it difficult. Moreover, coefficient estimations are based on average calculations using binary design matrices, without any statistical inference over them.

Here, we provide a flexible linear model-based decomposition framework. Almost any model can be specified, according to the experimental design, by means of a flexible `formula` interface. Because coefficient estimation is carried out by means of maximum likelihood, statistical significance is naturally given. The framework also provides both capacity to perform PCA and PLS analysis on appropriate ANOVA decomposition results, as well as graphical representations. The implementation is well-suited for direct analysis of gene expression matrices (variables on rows) from high-throughput data such as *microarray* or *RNA-seq* experiments. Below we provide an examples to introduce the user to the package applications, through the exploration of interaction patterns on a microarray experiment.

## 2. The model

A detailed explanation of ANOVA decomposition and multivariate analysis can be found in Smilde *et al.* (2005) and Zwanenburg *et al.* (2011). Briefly and without the loss of generality, let us assume a *microarray* experiment where the expression of  $(G_1, G_2, \dots, G_g)$  genes are arrayed in a chip. In this context, let us consider an experimental design with two main factors:  $A$ , with  $a$  levels  $(A_1, A_2, \dots, A_i, \dots, A_a)$  and  $B$ , with  $b$  levels  $(B_1, B_2, \dots, B_j, \dots, B_b)$ , with replicates  $R_1, R_2, \dots, R_k, \dots, R_r$  for each  $A \times B$  combination levels. After preprocessing steps are performed as described in (Smyth 2004), each chip is represented by a column vector of gene expression measurements of  $g \times 1$ . Then, the whole experimental data is arranged into a  $g \times n$  expression matrix  $(X)$ , where  $n = a \times b \times r$ . In this data scheme, single gene measurements across the different treatment combinations  $(A_i \times B_j)$  are presented in a row on the  $X$  matrix, as depicted in Figure 1. An equivalent  $X$  matrix structure needs to be obtained for *2D-DIGE* or *RNA-seq* experiments and so forth.




Figure 1: Data representation of microarray gene expression. A) Genes are spotted on the chip. Then, expression levels for each combination of treatment factor levels  $A_i B_j$  and their replicates  $R_k$  can be measured on the chips, yielding a total of  $n = a \times b \times r$  microarrays. B) Gene expression of each chip (microarray) is then interpreted as a column vector of expression levels. C) Then, these column vectors will be combined by columns producing the experiment gene expression matrix  $X$ . Expression measurements under all treatment combinations for a gene are represented by the  $X$  matrix rows. Thus, measurements on a row are subjected to the ANOVA model of (1).

Regardless of data generation, the ANOVA model for each gene (row) in  $X$  can be expressed as (1):

$$x_{ijk} = \mu + \alpha_i + \beta_j + \alpha_i \times \beta_j + \varepsilon_{ijk} \quad (1)$$

Where  $x_{ijk}$  is the measured expression for “some” gene, at combination “ $ij$ ” of factors  $A$  and  $B$  for the  $k$  replicate;  $\mu$  is the overall mean;  $\alpha, \beta$  and  $\alpha \times \beta$  are the main and interaction effects respectively; and the error term  $\varepsilon_{ijk} \sim N(0, \sigma^2)$ . In addition, (1) can also be expressed in matrix form for all genes into (2):

$$X = X_\mu + X_\alpha + X_\beta + X_{\alpha\beta} + E = \sum_{l \in \{\mu, \alpha, \beta, \alpha\beta\}} X_l + E \quad (2)$$

Where  $X_l, E$  matrices are of dimension  $g \times n$  and contain the level means of the corresponding  $l$ -th term and the random error respectively. However, in the context of linear models  $X_l$  can also be written as a linear combination of two matrix multiplications in the form of (3):

$$X = \sum_{l \in \{\mu, \alpha, \beta, \alpha\beta\}} X_l + E = \sum_{l \in \{\mu, \alpha, \beta, \alpha\beta\}} B_l Z_l^T + E = B_\mu Z_\mu^T + \dots + B_{\alpha\beta} Z_{\alpha\beta}^T + E = \mu \mathbf{1}^T + B_\alpha Z_\alpha^T + \dots + B_{\alpha\beta} Z_{\alpha\beta}^T + E \quad (3)$$

Where  $B_l$  and  $Z_l$  are referenced in the literature as *coefficient* and *model* matrices of dimensions  $g \times m_{(l)}$  and  $n \times m_{(l)}$ , respectively, and  $m_{(l)}$  is the number of levels of factor  $l$ . The first term is usually called *intercept*, with  $B_\mu = \mu$  and  $Z_\mu = \mathbf{1}$  being of dimension  $g \times 1$  and  $n \times 1$ , respectively. In this example, all  $Z_l$  are binary matrices, identifying whether a measurement belongs (“1”) or not (“0”) to the corresponding factor.

In the implementations provided by [Smilde et al. \(2005\)](#) and [Nueda et al. \(2007\)](#), the estimation of the coefficient matrices is based on calculations of *averages* using the design matrix (up to three design matrices  $Z_{\alpha, \beta, \alpha\beta}$ ), to identify the average samples. In theory, these authors fully decompose the original matrix as shown in (1). On the contrary, in this package the model coefficients are estimated, iteratively, by the *maximum likelihood* approach, using the `lmFit` function provided by `limma` package ([Smyth et al. 2011](#)). Consequently, three desirable features are also incorporated:

1. *Flexible formula interface* to specify any potential model. The user only needs to provide: i) The gene expression matrix ( $X$ ), ii) The experimental `data.frame` (`design`) with treatment structure, and iii) The model in a `formula` style, just as in an ordinary `lm` R function. Internal `model.matrix` call, will automatically build the appropriate  $Z$  matrices, overcoming the constraint on factorial design size, and tedious model matrix definitions.
2. *Hypothesis tests* on coefficient  $B_l$  matrices. A  $T$  test is automatically carried out for the  $s$ -th gene model, to test whether or not the  $o$ -th coefficient is equal to zero, i.e.,  $H_0 : b_{so} = 0$  vs  $H_1 : b_{so} \neq 0$ . In addition, an  $F$  test is performed to simultaneously determine whether or not all  $b_{so}$  are equal to zero.
3. *Empirical Bayes correction* can also be achieved through the `eBayes` `limma` function. It uses an empirical Bayes method to shrink the row/gene-wise sample variances towards a common value and to augment the degrees of freedom for the individual variances ([Smyth 2004](#)).



when one or several dependent variables (outputs -  $O$ ) must be predicted from a large and potentially highly correlated set of independent variables (inputs). In our implementation, the input can be either the *coefficient* matrix  $\hat{B}_l$  or the *residual*  $\hat{E}_{l-1}$ . According to the choice, the respective output matrix will be a diagonal  $O = \text{diag}(\text{nrow}(\hat{B}_l))$  or design matrix  $O = Z_l$ . In addition, users can specify their own output matrix,  $O$ , to verify a particular hypothesis. For instance, in functional genomics it could be the Gene Ontology class matrix as used in gene set enrichment analysis (GSEA) by [Subramanian et al. \(2005\)](#).

When working with the *coefficient* matrix, the user will not have to worry about the expected number of components in  $X$  (rank of the matrix, given the number of replicates per treatment level), as suggested by [Smilde et al. \(2005\)](#), because the components are directly summarized in the coefficient  $\hat{B}_l$  matrix. In addition, for both PCA/PLS, the **lmdme** package ([Fresno and Fernández 2013a](#)) also offers different methods to visualize results, e.g., `biplot`, `loadingplot` and `screepplot` or `leverage` calculation, in order to filter out rows/genes as in [Tarazona et al. \(2012\)](#).

### 3. Example

In this section we provide an overview of **lmdme** package by [Fresno and Fernández \(2013a\)](#). The example consists of an application of the analysis of gene expression interaction pattern, where we address: How to define the model, undertake ANOVA decomposition, perform PCA/PLS analysis and visualize the results.

From here onwards, some outputs were removed for reasons of clarity and the examples were performed with `options(digits=4)`.

#### 3.1. Package overview

The original data files for the first example are available at Gene Expression Omnibus ([Edgar et al. 2002](#)), with accession GSE37761 and **stemHypoxia** package ([Fresno and Fernández 2013b](#)) on the Bioconductor website. In this dataset, [Prado-Lopez et al. \(2010\)](#) studied differentiation of human embryonic stem cells under hypoxia conditions. They measured gene expression at different time points under controlled oxygen levels. This experiment has a typical two-way ANOVA structure, where factor  $A$  stands for “*time*” with  $a = 3$  levels  $\{0.5, 1, 5 \text{ days}\}$ , factor  $B$  stands for “*oxygen*” with  $b = 3$  levels  $\{1, 5, 21\%\}$  and  $r = 2$  replicates, yielding a total of 18 samples. The remainder of the dataset was excluded in order to have a balanced design, as suggested by [Smilde et al. \(2005\)](#) to fulfil orthogonality assumptions in ANOVA decomposition.

First, we need to load **stemHypoxia** package to access R objects calling `data("stemHypoxia")`, which will then load the experimental `design` and gene expression intensities `M`.

```
R> library("stemHypoxia")
R> data("stemHypoxia")
```

Now we manipulate the `design` object to maintain only those treatment levels which create a balanced dataset. Then, we change `rownames(M)` of each gene in `M`, with their corresponding `M$Gene_ID`.

```
R> timeIndex<-design$time %in% c(0.5, 1, 5)
R> oxygenIndex<-design$oxygen %in% c(1, 5, 21)
R> design<-design[timeIndex & oxygenIndex, ]
R> design$time<-as.factor(design$time)
R> design$oxygen<-as.factor(design$oxygen)
R> rownames(M)<-M$Gene_ID
R> M<-M[, colnames(M) %in% design$samplename]
```

Now we can explore microarray gene expression data present on the M matrix, with  $g = 40736$  rows (individuals/genes) and  $n = 18$  columns (samples/microarrays). In addition, the experimental `design` data.frame contains main effect columns (e.g., `time` and `oxygen`) and the sample names (`samplename`). A brief summary of these objects is shown using `head` function:

```
R> head(design)
```

```
  time oxygen samplename
3  0.5      1   12h_1_1
4  0.5      1   12h_1_2
5  0.5      5   12h_5_1
6  0.5      5   12h_5_2
7  0.5     21  12h_21_1
8  0.5     21  12h_21_2
```

```
R> head(M)[, 1:3]
```

```
           12h_1_1 12h_1_2 12h_5_1
A_24_P66027   7.182   7.512   8.225
A_32_P77178   6.385   6.035   6.440
A_23_P212522  9.562   9.390   9.211
A_24_P934473  6.288   6.397   6.265
A_24_P9671    12.007  11.995  12.282
A_32_P29551  10.176   9.273   9.360
```

Once the preprocessing of the experiment data is completed, `library("lmdme")` should be loaded. This instruction will automatically load the required packages: `limma` (Smyth *et al.* 2011) and `pIs` (Mevik *et al.* 2011). Once the data are loaded, the ANOVA decomposition of Section 2.1 can be carried out using (4) calling `lmdme` function with the `model` formula, actual data and experimental `design`.

```
R> library("lmdme")
R> fit<-lmdme(model=~time*oxygen, data=M, design=design)
R> fit
```

```
lmdme object:
Data dimension: 40736 x 18
Design (head):
```

```

  time oxygen samplename
3  0.5      1    12h_1_1
4  0.5      1    12h_1_2
5  0.5      5    12h_5_1
6  0.5      5    12h_5_2
7  0.5     21    12h_21_1
8  0.5     21    12h_21_2

```

```
Model:~time * oxygen
```

```
Model decomposition:
```

Step	Names	Formula	CoefCols
1	1 (Intercept)	~ 1	1
2	time	~ -1 + time	3
3	oxygen	~ -1 + oxygen	3
4	time:oxygen	~ -1 + time:oxygen	9

The results of `lmdme` will be stored inside the `fit` object, which is an S4 R class. By invoking the `fit` object, a brief description of the *data* and *design* used are shown as well as the `Model` applied and a summary of the decomposition. This `data.frame` describes the applied `Formula` and `Names` for each `Step`, as well as the amount of estimated coefficients for each gene (`CoefCols`).

At this point, we can choose those subjects/genes in which at least one interaction coefficient is statistically different from zero ( $F$  test on the coefficients) with a threshold  $p$  value of 0.001 and perform ASCA on the interaction *coefficient* term, and PLS against the identity matrix (default option).

```

R> id<-F.p.values(fit, term="time:oxygen")<0.001
R> decomposition(fit, decomposition="pca", type="coefficient",
+   term="time:oxygen", subset=id, scale="row")
R> fit.plsr<-fit
R> decomposition(fit.plsr, decomposition="plsr", type="coefficient",
+   term="time:oxygen", subset=id, scale="row")

```

These instructions will perform ASCA and PLS decomposition over the `scale="row"` version of the 305 selected subjects/genes (`subset=id`) on `fit` and `fit.plsr` object, respectively. The results will be stored inside these objects. In addition, we have explicitly indicated the decomposition `type="coefficient"` (default value) in order to apply it to the `coefficient` matrix, on "time:oxygen" interaction term ( $\hat{B}_{\alpha\beta}$ ).

Now, we can visualize the associated biplots (see Figure 2 (a) and (b)).


```

R> biplot(fit, xlabs="o", expand=0.7)
R> biplot(fit.plsr, which="loadings", xlabs="o",
+   ylabs=colnames(coefficients(fit.plsr, term="time:oxygen")),
+   var.axes=TRUE)

```

For visual clarity, `xlabs` are changed with the "o" symbol, instead of using the `rownames(M)` with manufacturer ids, and second axis with the `expand=0.7` option to avoid cutting off





(a) ANOVA simultaneous component analysis

(b) ANOVA partial least squares

Figure 2: Biplot on the decomposed interaction coefficients ( $time \times oxygen$ ) on genes satisfying the  $F$  test with  $p$  value  $< 0.001$ . Notice that the interaction matrix in the ASCA model is of rank 9. Thus, 9 arrows are expected and the score of the 305 selected subjects are projected onto the space spanned by the first two principal components in Figure 2(a).

loading labels. In addition, PLS biplot is modified from the default `pls` behavior to obtain a graph similar to ASCA output (`which="loadings"`). Accordingly, `ylabs` is changed to match the corresponding coefficients of the interaction term and `var.axes` is set to `TRUE`. The ASCA biplot of the first two components (see Figure 2(a)), explain over 70% of the coefficient variance. The genes are arranged in an elliptical shape. Thus, it can be observed that some genes tend to interact with different combinations of time and oxygen. A similar behavior is observed in PLS biplot of Figure 2(b).

The interaction effect on the `fit` object can also be displayed using the `loadingplot` function (see Figure 3). For every combination of two consecutive levels of factors (time and oxygen), the figure shows an interaction effect on the first component, which explains 50.61% of the total variance of the “time:oxygen” term.

```
R> loadingplot(fit, term.x="time", term.y="oxygen")
```




Figure 3: ANOVA simultaneous component analysis `loadingplot` on genes satisfying the  $F$  test with  $p$  value  $< 0.001$  on the interaction coefficients ( $time \times oxygen$ ).

In the case of an ANOVA-PCA/PLS analysis, the user only needs to change the `type="residuals"` parameter in the `decomposition` function and perform a similar exploration.

## Acknowledgements

*Funding:* This work was supported by the National Agency for Promoting Science and Technology, Argentina (PICT00667/07 to E.A.F. and PICT 2008-0807 BID to E.A.F.), Córdoba Ministry of Science and Technology, Argentina (PID2008 to E.A.F and PIP2009 to M.G.B.), Catholic University of Córdoba, Argentina and National Council of Scientific and Technical Research (CONICET), Argentina.

## References

- Abdi H, Williams L (2010). “Principal Component Analysis.” *Wiley Interdisciplinary Reviews: Computational Statistics*, **2**(4), 433–459.
- De Haan J, Wehrens R, Bauerschmidt S, Piek E, Van Schaik R, Buydens L (2007). “Interpretation of ANOVA Models for Microarray Data Using PCA.” *Bioinformatics*, **23**(2), 184–190.
- Edgar R, Domrachev M, Lash AE (2002). “Gene Expression Omnibus: NCBI Gene Expression and Hybridization Array Data Repository.” *Nucleic Acids Research*, **30**(1), 207–210. ISSN 1362-4962. doi:10.1093/nar/30.1.207. URL <http://dx.doi.org/10.1093/nar/30.1.207>.
- Fresno C, Balzarini MG, Fernández EA (2014). “lmdme: Linear Models on Designed Multivariate Experiments in R.” *Journal of Statistical Software*, **56**(7), 1–16. URL <http://www.jstatsoft.org/v56/i07/>.
- Fresno C, Fernández EA (2013a). **lmdme**: *Linear Model Decomposition for Designed Multivariate Experiments*. R package version 1.2.1, URL <http://www.bioconductor.org/packages/release/bioc/html/lmdme.html>.
- Fresno C, Fernández EA (2013b). **stemHypoxia**: *Differentiation of Human Embryonic Stem Cells Under Hypoxia Gene Expression Dataset by Prado-Lopez et al. (2010)*. R package version 0.99.3, URL <http://www.bioconductor.org/packages/release/data/experiment/html/stemHypoxia.html>.
- Gentleman RC, Carey VJ, Bates DM, others (2004). “Bioconductor: Open Software Development for Computational Biology and Bioinformatics.” *Genome Biology*, **5**, R80. URL <http://genomebiology.com/2004/5/10/R80>.
- Hanson BA (2012). **ChemoSpec**: *Exploratory Chemometrics for Spectroscopy*. R package version 1.51-2, URL <http://CRAN.R-project.org/package=ChemoSpec>.
- Harrington PdB, Vieira N, Espinoza J, Nien J, Romero R, Yergey A (2005). “Analysis of Variance–Principal Component Analysis: A Soft Tool for Proteomic Discovery.” *Analytica Chimica Acta*, **544**(1), 118–127.
- Mevik BH, Wehrens R, Liland KH (2011). **pls**: *Partial Least Squares and Principal Component Regression*. R package version 2.3-0, URL <http://CRAN.R-project.org/package=pls>.

- Nueda M, Conesa A, Westerhuis J, Hoefsloot H, Smilde A, Talón M, Ferrer A (2007). “Discovering Gene Expression Patterns in Time Course Microarray Experiments by ANOVA–SCA.” *Bioinformatics*, **23**(14), 1792–1800.
- Prado-Lopez S, Conesa A, Armiñán A, Martínez-Losa M, Escobedo-Lucea C, Gandia C, Tarazona S, Melguizo D, Blesa D, Montaner D, *et al.* (2010). “Hypoxia Promotes Efficient Differentiation of Human Embryonic Stem Cells to Functional Endothelium.” *Stem Cells*, **28**(3), 407–418.
- R Development Core Team (2012). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria. ISBN 3-900051-07-0, URL <http://www.R-project.org>.
- Shawe-Taylor J, Cristianini N (2004). *Kernel Methods for Pattern Analysis*. Cambridge University Press. ISBN 9780521813976. URL <http://books.google.com.ar/books?id=9i0vg12lti4C>.
- Smilde A, Jansen J, Hoefsloot H, Lamers R, Van Der Greef J, Timmerman M (2005). “ANOVA-Simultaneous Component Analysis (ASCA): A New Tool for Analysing Designed Metabolomics Data.” *Bioinformatics*, **21**(13), 3043–3048.
- Smyth GK (2004). “Linear Models and Empirical Bayes Methods for Assessing Differential Expression in Microarray Experiments.” *Statistical Applications in Genetics and Molecular Biology*, **3**(1), Article 3.
- Smyth GK, Ritchie M, Silver J, Wettenhall J, Thorne N, Langaas M, Ferkingstad E, Davy M, Pepin F, Choi D, McCarthy D, Wu D, Oshlack A, de Graaf C, Hu Y, Shi W, Phipson B (2011). *limma: Linear Models for Microarray Data*. R package version 3.12.1, URL <http://www.bioconductor.org/packages/2.10/bioc/html/limma.html>.
- Subramanian A, Tamayo P, Mootha V, Mukherjee S, Ebert B, Gillette M, Paulovich A, Pomeroy S, Golub T, Lander E, *et al.* (2005). “Gene Set Enrichment Analysis: A Knowledge-Based Approach for Interpreting Genome-Wide Expression Profiles.” *Proceedings of the National Academy of Sciences of the United States of America*, **102**(43), 15545–15550.
- Tarazona S, Prado-López S, Dopazo J, Ferrer A, Conesa A (2012). “Variable Selection for Multifactorial Genomic Data.” *Chemometrics and Intelligent Laboratory Systems*, **110**(1), 113–122.
- Zwanenburg G, Hoefsloot H, Westerhuis J, Jansen J, Smilde A (2011). “ANOVA-Principal Component Analysis and ANOVA-Simultaneous Component Analysis: A Comparison.” *Journal of Chemometrics*, **25**(10), 561–567.

## Session Info

```
R> sessionInfo()
```

```
R version 4.2.1 (2022-06-23)
```

```
Platform: x86_64-pc-linux-gnu (64-bit)
```

```
Running under: Ubuntu 20.04.5 LTS
```

```
Matrix products: default
```

```
BLAS: /home/biocbuild/bbs-3.16-bioc/R/lib/libRblas.so
```

```
LAPACK: /home/biocbuild/bbs-3.16-bioc/R/lib/libRlapack.so
```

```
locale:
```

```
[1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
[3] LC_TIME=en_GB            LC_COLLATE=C
[5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
[7] LC_PAPER=en_US.UTF-8    LC_NAME=C
[9] LC_ADDRESS=C            LC_TELEPHONE=C
[11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C
```

```
attached base packages:
```

```
[1] stats      graphics  grDevices  utils      datasets  methods
[7] base
```

```
other attached packages:
```

```
[1] lmdme_1.40.0      pls_2.8-1          stemHypoxia_1.33.0
```

```
loaded via a namespace (and not attached):
```

```
[1] compiler_4.2.1  limma_3.54.0     tools_4.2.1
```

### Affiliation:

Cristóbal Fresno & Elmer A Fernández

Bioscience Data Mining Group

Faculty of Engineering

Universidad Católica de Córdoba

X5016DHK Córdoba, Argentina

E-mail: [cfresno@bdmg.com.ar](mailto:cfresno@bdmg.com.ar), [efernandez@bdmg.com.ar](mailto:efernandez@bdmg.com.ar)

URL: <http://www.bdmg.com.ar/>

Mónica G Balzarini

Biometry Department

Faculty of Agronomy

Universidad Nacional de Córdoba

X5000JVP Córdoba, Argentina

E-mail: [mbalzari@gmail.com](mailto:mbalzari@gmail.com)

URL: <http://www.infostat.com.ar/>