

Package ‘pengls’

May 25, 2023

Type Package

Title Fit Penalised Generalised Least Squares models

Version 1.6.0

Description Combine generalised least squares methodology from the nlme package for dealing with autocorrelation with penalised least squares methods from the glmnet package to deal with high dimensionality. This pengls packages glues them together through an iterative loop. The resulting method is applicable to high dimensional datasets that exhibit autocorrelation, such as spatial or temporal data.

License GPL-2

Encoding UTF-8

RoxygenNote 7.2.1

Imports glmnet, nlme, stats, BiocParallel

Suggests knitr,rmarkdown,testthat

VignetteBuilder knitr

Depends R (>= 4.2.0)

biocViews Transcriptomics, Regression, TimeCourse, Spatial

BugReports <https://github.com/sthawinke/pengls>

git_url <https://git.bioconductor.org/packages/pengls>

git_branch RELEASE_3_17

git_last_commit 993ff65

git_last_commit_date 2023-04-25

Date/Publication 2023-05-25

Author Stijn Hawinkel [cre, aut] (<<https://orcid.org/0000-0002-4501-5180>>)

Maintainer Stijn Hawinkel <stijn.hawinkel@psb.ugent.be>

R topics documented:

coef.cv.pengls	2
coef.pengls	2

cv.pengls	3
getCorMat	5
getLoss	6
makeFolds	6
pengls	7
predict.cv.pengls	9
predict.pengls	9
print.cv.pengls	10
print.pengls	10

Index	12
--------------	-----------

coef.cv.pengls	<i>Extract coefficients from a cv.pengls model</i>
----------------	--

Description

Extract coefficients from a cv.pengls model

Usage

```
## S3 method for class 'cv.pengls'
coef(object, which = "lambda.1se", ...)
```

Arguments

object	A cv.pengls object
which	a character string, for which lambda should coefficients be returned
...	further arguments, currently ignored

Value

The vector of coefficients

coef.pengls	<i>Extract coefficients from a pengls model</i>
-------------	---

Description

Extract coefficients from a pengls model

Usage

```
## S3 method for class 'pengls'
coef(object, ...)
```

Arguments

object A pengls object
 ... further arguments, currently ignored

Value

The vector of coefficients

cv.pengls *Perform cross-validation pengls*

Description

Perform cross-validation pengls

Usage

```
cv.pengls(
  data,
  glsSt,
  xNames,
  outVar,
  corMat,
  nfolds,
  foldid,
  scale = FALSE,
  center = FALSE,
  cvType = "blocked",
  lambdas,
  transFun = "identity",
  transFunArgs = list(),
  loss = c("R2", "MSE"),
  ...
)
```

Arguments

data A data matrix or data frame
 glsSt a covariance structure, as supplied to nlme::gls as "correlation"
 xNames names of the regressors in data
 outVar name of the outcome variable in data
 corMat a starting value for the correlation matrix. Taken to be a diagonal matrix if missing
 nfolds an integer, the number of folds used in cv.glmnet to find lambda
 foldid An optional vector defining the fold

scale, center	booleans, should regressors be scaled to zero mean and variance 1? Defaults to TRUE
cvType	A character vector defining the type of cross-validation. Either "random" or "blocked", ignored if foldid is provided
lambdas	an optional lambda sequence
transFun	a transformation function to apply to predictions and outcome in the cross-validation
transFunArgs	Additional arguments passed onto transFun
loss	a character vector, currently either 'R2' or 'MSE' indicating the loss function (although R2 is not a proper loss...)
...	passed onto glmnet::glmnet

Value

A list with components

lambda	The series of lambdas
cvm	The vector of mean R2's
cvsd	The standard error of R2 at the maximum
cvOpt	The R2 according to the 1 standard error rule
coefs	The matrix of coefficients for every lambda value
bestFit	The best fitting pengls model according to the 1 standard error rule
lambda.min	Lambda value with maximal R2
lambda.1se	Smallest lambda value within 1 standard error from the maximum
foldid	The folds
glsSt	The nlme correlation object
loss	The loss function used

Examples

```
library(nlme)
library(BiocParallel)
n <- 20 #Sample size
p <- 50 #Number of features
g <- 10 #Size of the grid
#Generate grid
Grid <- expand.grid("x" = seq_len(g), "y" = seq_len(g))
# Sample points from grid without replacement
GridSample <- Grid[sample(nrow(Grid), n, replace = FALSE),]
#Generate outcome and regressors
b <- matrix(rnorm(p*n), n , p)
a <- rnorm(n, mean = b %*% rbinom(p, size = 1, p = 0.2)) #20% signal
#Compile to a matrix
df <- data.frame("a" = a, "b" = b, GridSample)
# Define the correlation structure (see ?nlme::gls), with initial nugget 0.5 and range 5
corStruct = corGaus(form = ~ x + y, nugget = TRUE,
```

```

value = c("range" = 5, "nugget" = 0.5)
#Fit the pengls model, for simplicity for a simple lambda
register(MulticoreParam(3)) #Prepare multithreading
penglsFitCV = cv.pengls(data = df, outVar = "a", xNames = grep(names(df),
pattern = "b", value = TRUE),
glsSt = corStruct, nfolds = 5)
penglsFitCV$lambda.1se #Lambda for 1 standard error rule
penglsFitCV$cvOpt #Corresponding R2
coef(penglsFitCV)
penglsFitCV$foldid #The folds used
#With MSE as loss function
penglsFitCVmse = cv.pengls(data = df, outVar = "a",
xNames = grep(names(df), pattern = "b", value =TRUE),
glsSt = corStruct, nfolds = 5, loss = "MSE")
penglsFitCVmse$lambda.1se #Lambda for 1 standard error rule
penglsFitCVmse$cvOpt #Corresponding MSE
coef(penglsFitCVmse)
predict(penglsFitCVmse)

```

getCorMat

Get the (square root of the inverse of the) correlation matrix

Description

Get the (square root of the inverse of the) correlation matrix

Usage

```
getCorMat(data, glsSt, Coef = c(coef(glsSt)), control, outVar)
```

Arguments

data	The data frame
glsSt	The correlation object for gls
Coef	optional vector of coefficients to glsSt
control	the list of control arguments for gls
outVar	the name of the outcome variable

Value

A list with components

corMat	The square root of the inverse correlation matrix
Coef	The coefficients of the correlation object

getLoss	<i>Calculate the loss given predicted and observed values</i>
---------	---

Description

Calculate the loss given predicted and observed values

Usage

```
getLoss(preds, obs, loss)
```

Arguments

preds	Matrix of predicted values
obs	vector of observed values
loss	a character vector indicating the loss type, see ?cv.pengls

Value

the evaluated loss

makeFolds	<i>Divide observations into folds</i>
-----------	---------------------------------------

Description

Divide observations into folds

Usage

```
makeFolds(nfolds, data, cvType, coords)
```

Arguments

nfolds	The number of folds
data	the dataset
cvType	a character vector, indicating the type of cross-validation required, either blocked or random
coords	the names of the coordinates in data

Value

the vector of folds

Examples

```

n folds <- 10
data <- expand.grid("x" = seq_len(10), "y" = seq_len(10))
randomFolds <- makeFolds(nfolds = nfolds, data, "random", c("x", "y"))
blockedFolds <- makeFolds(nfolds = nfolds, data, "blocked", c("x", "y"))

```

pengls

Iterative estimation of penalised generalised least squares

Description

Iterative estimation of penalised generalised least squares

Usage

```

pengls(
  data,
  glsSt,
  xNames,
  outVar,
  corMat,
  lambda,
  foldid,
  maxIter = 30,
  tol = 0.05,
  verbose = FALSE,
  scale = FALSE,
  center = FALSE,
  optControl = lmeControl(opt = "optim", maxIter = 500, msVerbose = verbose, msMaxIter =
    500, niterEM = 1000, msMaxEval = 1000),
  nfolds = 10,
  penalty.factor = c(0, rep(1, length(xNames))),
  ...
)

```

Arguments

data	A data matrix or data frame
glsSt	a covariance structure, as supplied to nlme::gls as "correlation"
xNames	names of the regressors in data
outVar	name of the outcome variable in data
corMat	a starting value for the correlation matrix. Taken to be a diagonal matrix if missing
lambda	The penalty value for glmnet. If missing, the optimal value of vanilla glmnet without autocorrelation component is used

foldid	An optional vector defining the fold
maxIter	maximum number of iterations between glmnet and gls
tol	A convergence tolerance
verbose	a boolean, should output be printed?
scale, center	booleans, should regressors be scaled to zero mean and variance 1? Defaults to TRUE
optControl	control arguments, passed onto nlme::gls' control argument
nfolds	an integer, the number of folds used in cv.glmnet to find lambda
penalty.factor	passed onto glmnet:glmnet. The first entry is zero by default for the intercept, which is not shrunk
...	passed onto glmnet::glmnet

Value

A list with components

glmnet	The glmnet fit, which can be manipulated as such
gls	A list with info on the estimated correlation matrix
iter	The iterations needed
conv	A boolean, indicating whether the iteration between mean model and covariance estimation converged
xNames, data, glsSt, outVar	As provided
lambda	The lambda penalty parameter used

See Also

cv.pengls

Examples

```
### Example 1: spatial data
# Define the dimensions of the data
library(nlme)
n <- 50 #Sample size
p <- 100 #Number of features
g <- 10 #Size of the grid
#Generate grid
Grid <- expand.grid("x" = seq_len(g), "y" = seq_len(g))
# Sample points from grid without replacement
GridSample <- Grid[sample(nrow(Grid), n, replace = FALSE),]
#Generate outcome and regressors
b <- matrix(rnorm(p*n), n , p)
a <- rnorm(n, mean = b %*% rbinom(p, size = 1, p = 0.2)) #20% signal
#Compile to a matrix
df <- data.frame("a" = a, "b" = b, GridSample)
# Define the correlation structure (see ?nlme::gls), with initial nugget 0.5 and range 5
```



```

corStruct <- corGaus(form = ~ x + y, nugget = TRUE, value = c("range" = 5, "nugget" = 0.5))
#Fit the pengls model, for simplicity for a simple lambda
penglsFit <- pengls(data = df, outVar = "a", xNames = grep(names(df), pattern = "b", value =TRUE),
glsSt = corStruct, nfolds = 5)

### Example 2: timecourse data
dfTime <- data.frame("a" = a, "b" = b, "t" = seq_len(n))
dfTime$a[-1] = dfTime$a[-n]*0.25 #Some temporal signal
corStructTime <- corAR1(form = ~ t, value = 0.5)
penglsFitTime <- pengls(data = dfTime, outVar = "a",
xNames = grep(names(dfTime), pattern = "b", value =TRUE),
glsSt = corStructTime, nfolds = 5)

```

predict.cv.pengls *Make predictions from a cv.pengls model*

Description

Make predictions from a cv.pengls model

Usage

```
## S3 method for class 'cv.pengls'
predict(object, ...)
```

Arguments

object	A cv.pengls object
...	further arguments, currently ignored

Value

A vector with predicted values

predict.pengls *Make predictions from a pengls model*

Description

Make predictions from a pengls model

Usage

```
## S3 method for class 'pengls'
predict(object, newx, ...)
```

Arguments

object	A pengls object
newx	The test data
...	further arguments, currently ignored

Value

A vector with predicted values

print.cv.pengls	<i>Print a summary of a cv.pengls model</i>
-----------------	---

Description

Print a summary of a cv.pengls model

Usage

```
## S3 method for class 'cv.pengls'  
print(x, ...)
```

Arguments

x	A cv.pengls object
...	further arguments, currently ignored

Value

Prints output to console

print.pengls	<i>Print a summary of a pengls model</i>
--------------	--

Description

Print a summary of a pengls model

Usage

```
## S3 method for class 'pengls'  
print(x, ...)
```

Arguments

x	A pengls object
...	further arguments, currently ignored

print.pengls

11

Value

Prints output to console

Index

`coef.cv.pengls`, 2
`coef.pengls`, 2
`cv.pengls`, 3

`getCorMat`, 5
`getLoss`, 6

`makeFolds`, 6

`pengls`, 7
`predict.cv.pengls`, 9
`predict.pengls`, 9
`print.cv.pengls`, 10
`print.pengls`, 10