

From the Genepix data files to RGList to NChannelSet

Audrey Kauffmann, Wolfgang Huber

April 27, 2023

Load the required packages

```
> library("Biobase")
> library("limma")
> library("CCl4")
```

Read the data and convert them into an RGList

The Genepix (.gpr) data files are in the `extdata` directory of the *CCl4* package. If you have the package installed, we can locate them on your filesystem with the function `system.file`. If the files are somewhere else, please adapt the below assignment to `datapath`.

```
> datapath = system.file("extdata", package="CCl4")

> p = read.AnnotatedDataFrame("samplesInfo.txt", path=datapath)
> CCl4_RGList = read.maimages(files=sampleNames(p),
+   path = datapath,
+   source = "genepix",
+   columns = list(R = "F635 Median", Rb = "B635 Median",
+                 G = "F532 Median", Gb = "B532 Median"))
```

If this code is run in the `inst/doc` directory of the *CCl4* (source) package, the output data files will be written directly into the `data` directory of the package. Otherwise, just write into a temporary directory.

```
> outdir = file.path("../", "../", "data")
> if(!isTRUE(file.info(outdir)$isdir))
+   outdir = tempdir()
> save(CCl4_RGList, file = file.path(outdir, "CCl4_RGList.RData"))
```

The function `read.maimages` from the *limma* package reads the .gpr files and builds an *RGList* object from it.

The output is written to

```
> outdir

[1] "/tmp/RtmpJCZpUF"
```

Build an NChannelSet from the RGList

Once the *RGList* object has been created, we can build an *NChannelSet*.

```

> sessionInfo()

R version 4.3.0 RC (2023-04-13 r84269)
Platform: x86_64-pc-linux-gnu (64-bit)
Running under: Ubuntu 22.04.2 LTS

Matrix products: default
BLAS: /home/biocbuild/bbs-3.17-bioc/R/lib/libRblas.so
LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.10.0

locale:
 [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
 [3] LC_TIME=en_GB             LC_COLLATE=C
 [5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
 [7] LC_PAPER=en_US.UTF-8     LC_NAME=C
 [9] LC_ADDRESS=C              LC_TELEPHONE=C
[11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C

time zone: America/New_York
tzcode source: system (glibc)

attached base packages:
[1] stats      graphics  grDevices  utils      datasets  methods   base

other attached packages:
[1] CCL14_1.38.0      limma_3.56.0      Biobase_2.60.0
[4] BiocGenerics_0.46.0

loaded via a namespace (and not attached):
[1] compiler_4.3.0 tools_4.3.0

```

Table 1: The output of `sessionInfo` on the build system after running this vignette.

```

> featureData = new("AnnotatedDataFrame", data = CCL14_RGList$genes)
> assayData = with(CCL14_RGList, assayDataNew(R=R, G=G, Rb=Rb, Gb=Gb))
> varMetadata(p)$channel=factor(c("G", "R", "G", "R"),
+                               levels=c(ls(assayData), "_ALL_"))
> CCL14 <- new("NChannelSet",
+             assayData = assayData,
+             featureData = featureData,
+             phenoData = p)
> save(CCL14, file = file.path(outdir, "CCL14.RData"))

```