

# Package ‘omicRexposome’

April 16, 2024

**Title** Exposome and omic data associatin and integration analysis

**Version** 1.24.3

**Maintainer** Xavier Escribà Montagut <xavier.escriba@isglobal.org>

**Description** omicRexposome systematizes the association evaluation between exposures and omic data, taking advantage of MultiDataSet for coordinated data management, rexposome for exposome data definition and limma for association testing. Also to perform data integration mixing exposome and omic data using multi co-inherent analysis (omicade4) and multi-canonical correlation analysis (PMA).

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.0.1

**VignetteBuilder** knitr

**Depends** R (>= 3.4), Biobase

**Imports** stats, utils, grDevices, graphics, methods, rexposome, limma, sva, ggplot2, ggrepel, PMA, omicade4, gridExtra, MultiDataSet, SmartSVA, isva, parallel, SummarizedExperiment, stringr

**Suggests** BiocStyle, knitr, rmarkdown, snpStats, brgedata

**biocViews** ImmunoOncology, WorkflowStep, MultipleComparison, Visualization, GeneExpression, DifferentialExpression, DifferentialMethylation, GeneRegulation, Epigenetics, Proteomics, Transcriptomics, StatisticalMethod, Regression

**git\_url** <https://git.bioconductor.org/packages/omicRexposome>

**git\_branch** RELEASE\_3\_18

**git\_last\_commit** 7937bee

**git\_last\_commit\_date** 2024-02-12

**Repository** Bioconductor 3.18

**Date/Publication** 2024-04-15

**Author** Carles Hernandez-Ferrer [aut, cre],  
Juan R. González [aut]

## R topics documented:

add_cls . . . . .	2
add_exp . . . . .	3
asr . . . . .	4
association . . . . .	4
crossomics . . . . .	6
crs . . . . .	7
getIntegration . . . . .	8
mds . . . . .	8
omicRexposome . . . . .	9
plotAssociation . . . . .	9
plotHits . . . . .	10
plotIntegration . . . . .	11
plotLambda . . . . .	12
snpToContinuous . . . . .	13
tableHits . . . . .	13
tableLambda . . . . .	14
<b>Index</b>	<b>15</b>

---

add_cls	<i>Method to add an ExposomeClust to a MultiDataSet</i>
---------	---

---

### Description

This method allows to insert an object of class [ExposomeClust](#) as an independent dataset into an object of class [MultiDataSet](#).

### Usage

```
add_cls(object, clsSet, ...)

## S4 method for signature 'MultiDataSet,ExposomeClust'
add_cls(object, clsSet, ...)
```

### Arguments

object	An object of class <a href="#">MultiDataSet</a> .
clsSet	An object of class <a href="#">ExposomeClust</a> .
...	Arguments given to <a href="#">add_eset</a> from <a href="#">MultiDataSet</a> .

### Value

A [MultiDataSet](#) with the [ExpressionSet](#) added as an independent dataset.

### Examples

```
data("eclust", package = "rexposome")
library(MultiDataSet)
md <- new("MultiDataSet")
names(md)
md <- add_cls(md, expo_c)
names(md)
```

---

add\_exp

*Method to add an ExposomeSet to a MultiDataSet*

---

### Description

This method allows to insert an object of class [ExposomeSet](#) as an independent dataset into an object of class [MultiDataSet](#).

### Usage

```
add_exp(object, expoSet, warnings = TRUE, ...)

## S4 method for signature 'MultiDataSet,ExposomeSet'
add_exp(object, expoSet, warnings = TRUE,
        ...)
```

### Arguments

object	An object of class <a href="#">MultiDataSet</a> .
expoSet	An object of class <a href="#">ExposomeSet</a> .
warnings	(default TRUE) If set to FALSE warnings will not be displayed.
...	Arguments given to <a href="#">add_eset</a> from <a href="#">MultiDataSet</a> .

### Value

A [MultiDataSet](#) with the [ExpressionSet](#) added as an independent dataset.

### Examples

```
data("exposome", package = "rexposome")
library(MultiDataSet)
md <- new("MultiDataSet")
names(md)
md <- add_exp(md, expo)
names(md)
```

---

asr	ResultSet for testing and illustration purposes
-----	---

---

### Description

ResultSet created using [association](#) method, testing proteome association to exposome ("mds"), adjusted by sex and age.

### Usage

```
data("asr")
```

### Format

An object of class `ResultSet` of length 15.

### Value

A `ResultSet` object.

### Examples

```
data("asr", package = "omicRexposome")
asr
```

---

association	# <i>Method to perform an association study between transcriptome and exposom</i>
-------------	---

---

### Description

This function allows to perform an association study between gene expression from microarray and the exposome. An `ExpressionSet` is the object storing the gene expression and an `ExposomeSet` the one storing the exposome. Both of them needs to be encapsulated in a `MultiDataSet`. The association study is perform through standard `limma` pipeline. The function allows to perform multiple tests using the argument `exposures`.

### Usage

```
association(object, formula, expset, omicset, set = "exposures",
  method = "ls", ..., baselevels, sva = "none", vfilter = NULL,
  verbose = FALSE, warnings = TRUE)
```

```
## S4 method for signature 'MultiDataSet'
association(object, formula, expset, omicset,
  set = "exposures", method = "ls", ..., baselevels, sva = "none",
  vfilter = NULL, verbose = FALSE, warnings = TRUE)
```

**Arguments**

object	A MultiDataSet object containing at least one omic data-sets like ExpressionSet, MethylationSet... and, at last, one ExposomeSet.
formula	formula to be evaluated by each exposure (or phenotype, see set argument). It should not contain any exposures (or phenotype), it will be added automatically when evaluated.
expset	Name of the ExposomeSet in object.
omicset	Name of the omic data-set in object.
set	(default "exposures") Can take value "exposures" to test the association of the exposures in the ExposomeSet vs. the features in the omic data-set. If takes "phenotypes" all phenotypes in ExposomeSet are tested.
method	(default "lm") Check limma help pages.
...	Arguments passed to limma's lmFit.
baselevels	(optional) If set, must be a labeled vector with the default base level for categorical exposures.
sva	(default "none"). This argument can take value "none" to do not apply SVA. Value "fast" will run SVA using isva and SmartSVA. Value "slow" will run SVA using sva.
vfilter	(default NULL). Only used when sva = "slow". Numeric number of probes used in <a href="#">sva</a> . Recommended ~10% of real probes.
verbose	(default FALSE) If set to TRUE, a series of messages describing the process are shown.
warnings	(default TRUE) If set to TRUE, a series of warnings are shown when required user attention.

**Value**

An object of class [ResultSet](#).

**Examples**

```
library(MultiDataSet)
data(brge_prot, package = "brgedata")
data(brge_expo, package = "brgedata")
mds <- createMultiDataSet()
mds <- add_eset(mds, brge_prot, dataset.type = "proteines")
mds <- add_eset(mds, brge_expo, dataset.type = "exposures", GRanges = NA)

asr <- association(mds, formula = Asthma ~ Sex + Age,
  expset = "exposures", omicset = "proteines")
asr
```

---

crossomics

*Function to perform a Transcriptome-Wide Association Study*


---

## Description

This function allows to perform a Transcriptome-Wide Association Study by using an `ExposmeSet` and an `ExpressionSet`. It allows to perform an adjustment using Surrogate Variable Analysis (from R package `sva`).

## Usage

```
crossomics(object, method = "mcca", ncomponents = 2, ..., na.rm = FALSE,
           permute = c(100, 3), verbose = FALSE, warnings = TRUE)
```

```
## S4 method for signature 'MultiDataSet'
crossomics(object, method = "mcca",
           ncomponents = 2, ..., na.rm = FALSE, permute = c(100, 3),
           verbose = FALSE, warnings = TRUE)
```

## Arguments

<code>object</code>	A <code>MultiDataSet</code> object containing at last two data-sets like <code>ExposomeSet</code> , <code>ExpressionSet</code> , <code>MethylationSet</code> ...
<code>method</code>	(default "mcca") It can takes values "mcca" for Multiple Canonical Correlation Analysis or "mca" for Multiple Co-Inertia Analysis.
<code>ncomponents</code>	(default 2) Number of components to be estimated.
<code>...</code>	Other arguments given to <code>mca</code> (from <code>omicade4</code> ) or to <code>MultiCCA</code> (from <code>PMA</code> ).
<code>na.rm</code>	(default FALSE) If method was set to "mcca" and <code>na.rm</code> was set to TRUE, features containing missing values are removed.
<code>permute</code>	(default <code>c(100, 3)</code> ). If <code>method="mcca"</code> and this argument is set to NULL no permutation test to tune-up the parameters for <code>MultiCCA</code> . When filled, <code>permute[1]</code> corresponds to the number permutations (default in <code>MultiCCA.permute</code> is 25) and <code>permute[2]</code> the number of iterations (default in <code>MultiCCA.permute</code> is 3).
<code>verbose</code>	(default FALSE) If set to TRUE, a series of messages describing the process are shown.
<code>warnings</code>	(default TRUE) If set to TRUE, a series of warnings are shown when required user attention.

## Value

An object of class `ResultSet`.

## Examples

```
library(MultiDataSet)
library(rexposome)
data(brge_prot, package = "brgedata")
data(brge_expo, package = "brgedata")
mds <- createMultiDataSet()
mds <- add_eset(mds, brge_prot, dataset.type = "proteines")
mds <- add_eset(mds, imputation(brge_expo),
  dataset.type = "exposures", GRanges = NA)

crs <- crossomics(mds, method = "mcia")
crs
```

---

crs

*ResultSet for testing and illustration purposes*

---

## Description

ResultSet created using [crossomics](#) method, selecting "mcia" method. Result from the integration of proteome and exposome data ("mds").

## Usage

```
data("crs")
```

## Format

An object of class `ResultSet` of length 1.

## Value

A `ResultSet` object.

## Examples

```
data("crs", package = "omicRexposome")
crs
```

---

getIntegration	<i>Method to extrat integration-feature result from a ResultSet</i>
----------------	---

---

### Description

Homologous methods from `MultiDataSet` (`getAssociation`) but for `ResultSet` created by `crossomics`. It Returns a `data.frame` with the result from `mcia` (`omicade4`) or from `MultiCCA` (PMA).

### Usage

```
getIntegration(object, ...)

## S4 method for signature 'ResultSet'
getIntegration(object, ...)
```

### Arguments

<code>object</code>	An object of class <code>ResultSet</code> obtained from
<code>...</code>	NOT USED

### Value

A `data.frame`

### Examples

```
data("crs", package = "omicRexposome")
class(getIntegration(crs))
```

---

mds	<i>MultiDataSet for testing and illustration purpouses</i>
-----	--

---

### Description

`MultiDataSet` containing both proteome data-set and exposome data-set.

### Usage

```
data("mds")
```

### Format

An object of class `MultiDataSet` of length 2.

### Value

A `MultiDataSet` object.



**Examples**

```
data("mds", package = "omicRexposome")
mds
```

---

omicRexposome	<i>omicRexposome: Package for exposome and omic data associatin and integration</i>
---------------	---

---

**Description**

omicRexposome: Package for exposome and omic data associatin and integration

**exposome-omic data association study**

The packages offers the function [association](#) that allows to perform an association study using transcriptome, methylome, etc. as dependent variable and exposome data as independent variable. The function relies on limma pipeline and generates an object of class `ResultSet`, that can be plotted using [plotAssociation](#).

**exposome-omic data integration study**

The packages offers the function [crossomics](#) that allows to perform two types of integration study: Multi Canonical Correlation Analysis and Multi Co-Inertia Analysis. The function allos to use any type and number of datasets (aka. exposome transcriptome, methylome, etc.). The function generates an object of class `ResultSet`, that can be plotted using [plotIntegration](#).

---

plotAssociation	<i>Function to draw de result of an association study</i>
-----------------	---

---

**Description**

This function draws two type of plots for the `ResultSet` from association functions

**Usage**

```
plotAssociation(object, rid = 1, coef = 2, contrast = 1,
  type = c("manhattan", "qq", "volcano"), tPV = NULL, tFC = NULL,
  show.effect = FALSE)

## S4 method for signature 'ResultSet'
plotAssociation(object, rid = 1, coef = 2,
  contrast = NULL, type = c("manhattan", "qq", "volcano"), tPV = NULL,
  tFC = NULL, show.effect = FALSE)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a> obtained from <code>assoc_*</code> functions.
rid	(default 1) Index or name of the test to be plotted.
coef	(default 2) Index of the coefficient to be extracted.
contrast	(default 1) When code corresponds to a multicategorical variable, <code>contrast</code> selects the comparison.
type	Can take "volcano", "qq", "manhattan" and "protein". "protein" plot is a type of Manhattan plot designed for protein association analysis.
tPV	(optional) Threshold for P.Value when <code>type="volcano"</code> .
tFC	(optional) Threshold for Fold Change or Effect when <code>type="volcano"</code> .
show.effect	(default FALSE) If set to TRUE, when <code>type="volcano"</code> the X-axis will show $2^{\logFC}$ instead of $\logFC$ .

**Value**

A ggplot2 object

**See Also**

[plotIntegration](#) for plotting integration results. [association](#) to create a `ResultSet` to be passed to this function.

**Examples**

```
data("asr", package = "omicRexposome")
plotAssociation(asr, type = "qq")
plotAssociation(asr, type = "volcano")
```

---

plotHits

*Plot number of hits per result in ResultSet*

---

**Description**

This method draws a barplot with the number of hits in each result stored in the given [ResultSet](#).

**Usage**

```
plotHits(object, th = 0.05, width = 0.75)

## S4 method for signature 'ResultSet'
plotHits(object, th = 0.05, width = 0.75)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a>
th	(default 0.05) Threshold (p-value) to considere a result as a hit.
width	(default 0.70) width of the bar

**Value**

A ggplot2 object

**See Also**

[plotLambda](#) for a graphical representation of the lambda score per analysys, [tableLambda](#) for the lambda score per analysys, [tableHits](#) for the hists per analysys

**Examples**

```
data(asr, package = "omicRexposome")
plotHits(asr)
```

---

plotIntegration	<i>Function to draw de result of an integration study</i>
-----------------	---

---

**Description**

This function draws a plots for the ResultSet from integration function

**Usage**

```
plotIntegration(object, cmpX = 1, cmpY = 2, lb.th = 0.2,
  legend.show = TRUE, colors, ...)
```

```
## S4 method for signature 'ResultSet'
plotIntegration(object, cmpX = 1, cmpY = 2,
  lb.th = 0.2, legend.show = TRUE, colors, ...)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a> obtained from <a href="#">crossomics</a> .
cmpX	(default 1) Value of the X-axis when plotting results from <a href="#">mcia</a> .
cmpY	(default 2) Value of the Y-axis when plotting results from <a href="#">mcia</a> .
lb.th	(default 0.20) Threshold to place labels on radar chart drawn when plotting results from <a href="#">MultiCCA</a> .
legend.show	(default TRUE) If set to FALSE, right legend of radar plot is hidden when plotting results from <a href="#">MultiCCA</a> .
colors	(optional) Names vector with the colors sued to draw each dataset. Used when plotting results from <a href="#">MultiCCA</a> . If missing, random colores are chosen.
...	Optional arguments are given to plot from <a href="#">omicade4</a> package (argument axes is filled with values from cmpX and cmpY).

**Value**

A ggplot2 object

**See Also**

[plotAssociation](#) for plotting association results. [crossomics](#) to create a `ResultSet` to be passed to this function.

**Examples**

```
data("crs", package = "omicRexposome")
plotIntegration(crs)
```

---

plotLambda	<i>Plot lambda score for all results in a ResultSet</i>
------------	---

---

**Description**

This method draws a barplot with the lambda score of each result in the given [ResultSet](#).

**Usage**

```
plotLambda(object, width = 0.75)

## S4 method for signature 'ResultSet'
plotLambda(object, width = 0.75)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a>
width	(default 0.70) width of the bar

**Value**

A ggplot2 object

**See Also**

[plotHits](#) for a graphical representation of the hits per analysis, [tableLambda](#) for the lambda score per analysis, [tableHits](#) for the hits per analysis

**Examples**

```
data("asr", package = "omicRexposome")
plotLambda(asr)
```

---

snpToContinuous	<i>Transforms the discrete genotype from a snpSet to a matrix of a continuous variable.</i>
-----------------	---

---

**Description**

The function converts the categorical variable of SNPs to a continuous variable by normalizing each SNP as described in Abraham G. and Inouye M. 2014 (DOI: 10.1371/journal.pone.0093766).

**Usage**

```
snpToContinuous(snpSet, verbose = FALSE)
```

**Arguments**

snpSet	An object of class snpSet with set calls slot .
verbose	If set to TRUE, messages will be shown.

**Value**

An matrix of the calls of the SNPs converted to a continuous variable.

**See Also**

[crossomics](#) use this function

---

tableHits	<i>Counts the number of hits on the results stored in a ResultSet</i>
-----------	---

---

**Description**

Given a threshold it counts the number of hits in each result in the given [ResultSet](#).

**Usage**

```
tableHits(object, th = 0.05)

## S4 method for signature 'ResultSet'
tableHits(object, th = 0.05)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a>
th	(default 0.05) Threshold (p-value) to considere a result as a hit.

**Value**

A labeled numeric vector with the exposures and the number of hits.

**See Also**

[tableLambda](#) for the lambda score per analysis, [plotLambda](#) for a graphical representation of the lambda score per analysis, [plotHits](#) for a graphical representation of the hits per analysis

**Examples**

```
data("asr", package = "omicRexposome")
tableHits(asr)
```

---

tableLambda	<i>Compute a lambda score on the results stored in a ResultSet</i>
-------------	--

---

**Description**

Compute lambda score on each result in the given [ResultSet](#) by using [lambdaClayton](#).

**Usage**

```
tableLambda(object, trim = 0.5)

## S4 method for signature 'ResultSet'
tableLambda(object, trim = 0.5)
```

**Arguments**

object	An object of class <a href="#">ResultSet</a>
trim	(default 0.5) percentage of right omitted values for <a href="#">lambdaClayton</a> .

**Value**

Returns a data.frame having the exposures and the computed lambda score.

A labeled numeric vector with the lambda score for each exposure.

**See Also**

[tableHits](#) for the number of hits per analysis, [plotHits](#) for a graphical representation of the hits per analysis, [plotLambda](#) for a graphical representation of the lambda score per analysis

**Examples**

```
data("asr", package = "omicRexposome")
tableLambda(asr)
```

# Index

- \* **datasets**
  - asr, [4](#)
  - crs, [7](#)
  - mds, [8](#)
- add\_cls, [2](#)
- add\_cls, MultiDataSet, ExposomeClust-method (add\_cls), [2](#)
- add\_eset, [2, 3](#)
- add\_exp, [3](#)
- add\_exp, MultiDataSet, ExposomeSet-method (add\_exp), [3](#)
- asr, [4](#)
- association, [4, 4, 9, 10](#)
- association, MultiDataSet-method (association), [4](#)
- crossomics, [6, 7–9, 11–13](#)
- crossomics, MultiDataSet-method (crossomics), [6](#)
- crs, [7](#)
- ExposomeClust, [2](#)
- ExposomeSet, [3](#)
- ExpressionSet, [2, 3](#)
- getIntegration, [8](#)
- getIntegration, ResultSet-method (getIntegration), [8](#)
- lambdaClayton, [14](#)
- mcia, [11](#)
- mds, [8](#)
- MultiCCA, [11](#)
- MultiDataSet, [2, 3](#)
- omicade4, [11](#)
- omicRexposome, [9](#)
- omicRexposome-package (omicRexposome), [9](#)
- plotAssociation, [9, 9, 12](#)
- plotAssociation, ResultSet-method (plotAssociation), [9](#)
- plotHits, [10, 12, 14](#)
- plotHits, ResultSet-method (plotHits), [10](#)
- plotIntegration, [9, 10, 11](#)
- plotIntegration, ResultSet-method (plotIntegration), [11](#)
- plotLambda, [11, 12, 14](#)
- plotLambda, ResultSet-method (plotLambda), [12](#)
- ResultSet, [5, 6, 8, 10–14](#)
- snpToContinuous, [13](#)
- snpToContinuous, SnpSet-method (snpToContinuous), [13](#)
- sva, [5](#)
- tableHits, [11, 12, 13, 14](#)
- tableHits, ResultSet-method (tableHits), [13](#)
- tableLambda, [11, 12, 14, 14](#)
- tableLambda, ResultSet-method (tableLambda), [14](#)