

Package ‘BiocStyle’

November 21, 2024

Title Standard styles for vignettes and other Bioconductor documents

Description Provides standard formatting styles for Bioconductor PDF and HTML documents. Package vignettes illustrate use and functionality.

Version 2.35.0

Imports bookdown, knitr (>= 1.30), rmarkdown (>= 1.2), stats, utils, yaml, BiocManager

Suggests BiocGenerics, RUnit, htmltools

biocViews Software

License Artistic-2.0

VignetteBuilder knitr

Encoding UTF-8

URL <https://github.com/Bioconductor/BiocStyle>

BugReports <https://github.com/Bioconductor/BiocStyle/issues>

RoxygenNote 6.1.0

git_url <https://git.bioconductor.org/packages/BiocStyle>

git_branch devel

git_last_commit 40286b4

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-11-21

Author Andrzej Oleś [aut] (ORCID: <<https://orcid.org/0000-0003-0285-2787>>),
Mike Smith [ctb] (ORCID: <<https://orcid.org/0000-0002-7800-3848>>),
Martin Morgan [ctb],
Wolfgang Huber [ctb],
Bioconductor Package Maintainer [cre]

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

Contents

BiocStyle-defunct	2
helpers	2
html_document	3
latex	4
macros	5
markdown	7
md_document	8
output	9
pdf_document	10
use_vignette_html	11
Index	12

BiocStyle-defunct	<i>Defunct functions in package ‘BiocStyle’</i>
-------------------	---

Description

These functions are defunct and no longer available.

Details

The following functions are no longer available; use the replacement indicated below:

- latex_old, latex2: [latex](#)
- pdf_document_old, pdf_document2: [pdf_document](#)
- html_document_old, html_document2: [html_document](#)

helpers	<i>Specify Rmarkdown document metadata</i>
---------	--

Description

Helper functions for including metadata in the document header.

Usage

```
pkg_ver(pkg)
```

```
doc_date()
```

Arguments

```
pkg          character(1), package name
```

Details

Use `doc_date` to include document compilation date in the document metadata field `'date'`, and `pkg_ver` for package version specification in the `'package'` field.

Value

Markdown-formatted character string.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2015

Examples

```
## current date
doc_date()

## package name with version
pkg_ver("BiocStyle")
```

html_document	<i>Use Bioconductor style to format R Markdown HTML output</i>
---------------	--

Description

Format for converting from R Markdown to an Bioconductor HTML document.

Usage

```
html_document(toc = TRUE, number_sections = TRUE, fig_width = NA,
  fig_height = NA, self_contained = TRUE, css = NULL,
  pandoc_args = NULL, ..., titlecaps = TRUE)
```

Arguments

<code>toc</code>	logical(1), TRUE to include a table of contents in the output
<code>number_sections</code>	logical(1), TRUE to number section headings
<code>fig_width</code>	numeric(1), default width (in inches) for figures
<code>fig_height</code>	numeric(1), default width (in inches) for figures
<code>self_contained</code>	numeric(1), TRUE to produce a standalone HTML file with no external dependencies, using data: URIs to incorporate the contents of linked scripts, stylesheets, images, and videos. Note that even for self contained documents MathJax is still loaded externally (this is necessary because of it's size).

css	character, one or more css files to include
pandoc_args	character, additional command line options to pass to pandoc
...	Additional arguments passed to html_document
titlecaps	logical(1), TRUE to use the emphasize the first sentence in figure and table captions as title

Details

`BiocStyle::html_document` format extends the [html_document](#) format. See the [online documentation](#) and the package vignette "Authoring R Markdown Vignettes" for additional details on using the format,

Value

R Markdown output format to pass to [render](#)

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2017

See Also

[pdf_document](#), [md_document](#)

Examples

```
## Not run:

# simple invocation
render("input.Rmd", BiocStyle::html_document())

# specify options
render("input.Rmd", BiocStyle::html_document(toc = FALSE))

## End(Not run)
```

latex

Use Bioconductor style to format LaTeX vignettes

Description

This function inserts code into a document preamble to provide a consistent style to Bioconductor vignettes.

Usage

```
latex(..., width, titlecaps = TRUE, short.fignames = FALSE, fig.path,
       use.unsrurl = TRUE, relative.path = FALSE)
```

Arguments

<code>...</code>	Additional arguments, passed to options .
<code>width</code>	integer(1), maximum number of columns on a line used in printing. See options .
<code>titlecaps</code>	logical(1), emphasize the first sentence of float captions
<code>short.fignames</code>	logical(1), indicates whether <code>\incfig</code> figures should be inserted and referred to using short names equal to corresponding code chunk labels without any additional prefix.
<code>fig.path</code>	character(1), custom prefix to be used for figure file names when used with <code>knitr</code> ; has no effect when compiled with Sweave. For details see opts_chunk .
<code>use.unsrurl</code>	logical(1), indicating that the 'unsrurl' style will be used (<code>\bibliographystyle</code> command <i>not</i> required).
<code>relative.path</code>	logical(1), copy supporting LaTeX files and use relative paths rather than absolute paths to system files.

Details

Use is described in the 'Bioconductor LaTeX Style 2.0' vignette.

By default the 'unsrurl' bibliography style is used, which automatically creates links to URL, DOIs, etc. Use a different `bibliographystyle` with `use.unsrurl=FALSE` and standard LaTeX commands for styling bibliographies.

Value

The return value is a character string directing LaTeX to use the Bioconductor style file.

A side effect is setting any options specified as arguments.

Author(s)

Andrzej Oleś, Martin Morgan, Wolfgang Huber

Examples

```
## location of the .sty file
BiocStyle:::bioconductor.sty
```

macros

Link to packages on Bioconductor, CRAN and GitHub

Description

Functions for adding links to Bioconductor, CRAN and GitHub packages into R Markdown documents.

Usage

```
Biocpkg(pkg, vignette = NULL, label = NULL)
```

```
Biocbook(pkg, label = NULL)
```

```
Biocannopkg(pkg)
```

```
Biocexptpkg(pkg)
```

```
CRANpkg(pkg)
```

```
Rpackage(pkg)
```

```
Githubpkg(repo, pkg)
```

Arguments

pkg	character(1), package name
vignette	character(1), basename of vignette link, including html or pdf extension, e.g., "work-0-intro.html".
label	character(1) label used to identify the package or vignette. If NULL, defaults to pkg.
repo	Repository address in the format username/repo[/subdir]

Details

Use `Biocpkg` for Bioconductor software, annotation, experiment data, and workflow packages. When `vignette=NULL`, the function automatically includes a link to the package landing page, the version of which depends on the current Bioconductor version (i.e. if run in a devel environment, it will point towards the devel landing page; otherwise it will point to the release landing page).

Use `Biocbook` for Bioconductor webbooks. This will create a link to the index page of the book rather than to the landing page of the package used for the book's deployment.

Use `CRANpkg` for R packages available on CRAN. The function automatically includes a link to the master CRAN landing page.

Use `Githubpkg` for R packages available on GitHub. The `repo` should include the repository address in the format `username/repo[/subdir]`. If package is missing, the package name is assumed to be equal the repository name and is extracted from `repo`.

For R packages which are not available on Bioconductor, CRAN or GitHub, use `Rpackage`.

Value

Markdown-formatted character vector containing a hyperlinked package name. If `vignette != NULL`, the address of the specified vignette is returned.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2015

Examples

```
## link to a Bioconductor software package
Biocpkg("IRanges")

## link to a Bioconductor annotation package
Biocpkg("org.Mm.eg.db")

## link to a Bioconductor experiment data package
Biocpkg("affydata")

## link to a Bioconductor workflow
Biocpkg("simpleSingleCell")
Biocpkg(
  "simpleSingleCell",
  vignette = "work-0-intro.html",
  label = "Episode 1: analyzing scRNA-seq data with R/Bioconductor"
)

## link to a CRAN package
CRANpkg("data.table")

## link to an R package on GitHub
Githubpkg("rstudio/rmarkdown")
```

markdown

Use Bioconductor CSS style to format HTML vignettes

Description

This function sets the Bioconductor style sheet to provide a consistent style across Bioconductor HTML vignettes.

Usage

```
markdown(css.files, self.contained = TRUE, links.target = TRUE)
```

Arguments

`css.files` character vector containing the location of additional .css files.

`self.contained` logical(1), should the content of the CSS stylesheet files be included into the html file or should they be saved as separate files.

`links.target` logical(1), should external links open in new browser tab/window.

Details

Use is described in the ‘Bioconductor CSS Style’ vignette.

Value

No value is returned. The function is called for its side effect of setting the markdown and/or knitr specific options controlling the inclusion of the Bioconductor CSS style file in the HTML output.

Author(s)

Andrzej Oles <andrzej.oles@embl.de>, 2014-2015

Examples

```
## location of the .css file
BiocStyle:::bioconductor.css
```

md_document

Convert to a BiocStyle markdown document

Description

Enable BiocStyle macros and author affiliations in markdown documents.

Usage

```
md_document(toc = TRUE, ...)
```

Arguments

toc	TRUE to include a table of contents in the output
...	Additional function arguments to pass to the base R Markdown md_document output formatter

Details

The `BiocStyle::md_document` format extends the base [md_document](#) format by means of specifying complex author affiliations. It also loads the BiocStyle package namespace to enable the use of helper functions, such as [Biocpkg](#).

Value

R Markdown output format to pass to [render](#)

Author(s)

Andrzej Oles <andrzej.oles@embl.de>, 2015-2016

See Also

[html_document](#), [pdf_document](#)

Examples

```
## Not run:  
  
rmarkdown::render("input.Rmd", BiocStyle::md_document())  
  
## End(Not run)
```

output

Output format of an R Markdown document

Description

Helper function to determine the document's current pandoc output format.

Usage

```
output()
```

Details

The function is useful for defining different behavior depending on the output format, e.g. figure settings.

Value

A character string specifying the pandoc output format.

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2016

Examples

```
## Not run:  
## Switch between SVG and PDF figures depending on document output format  
knitr::opts_chunk$set(  
  dev = switch(output(), html = "svg", latex = "pdf")  
)  
  
## End(Not run)
```

`pdf_document`*Use Bioconductor style to format R Markdown PDF output*

Description

This function sets the Bioconductor style in PDF documents rendered using R Markdown v2.

Usage

```
pdf_document(toc = TRUE, number_sections = TRUE, fig_width = NA,  
             fig_height = NA, includes = NULL, ..., titlecaps = TRUE,  
             toc_newpage = FALSE, use_unsrurl = TRUE, relative_path = FALSE)
```

Arguments

<code>toc</code>	logical(1), TRUE to include a table of contents in the output
<code>number_sections</code>	logical(1), TRUE to number section headings
<code>fig_width</code>	numeric(1), default width (in inches) for figures
<code>fig_height</code>	numeric(1), default width (in inches) for figures
<code>includes</code>	Named list of additional content to include within the document (typically created using the includes function).
<code>...</code>	Additional arguments passed to pdf_document .
<code>titlecaps</code>	logical(1), TRUE to use the emphasize the first sentence in figure and table captions as title
<code>toc_newpage</code>	logical(1), TRUE to start the table of contents on a new page.
<code>use_unsrurl</code>	logical(1), indicating that the ‘unsrurl’ style will be used (<code>\bibliographystyle</code> command <i>not</i> required).
<code>relative_path</code>	logical(1), copy supporting LaTeX files and use relative paths rather than absolute paths to system files.

Value

R Markdown output format to pass to [render](#).

Author(s)

Andrzej Oleś <andrzej.oles@embl.de>, 2014-2017

See Also

[html_document](#), [md_document](#)

Examples

```
## Not run:  
  
# simple invocation  
render("input.Rmd", BiocStyle::pdf_document())  
  
# specify an option for latex engine  
render("input.Rmd", BiocStyle::pdf_document(toc = FALSE))  
  
## End(Not run)
```

use_vignette_html *Create 'Rmd' vignette templates for HTML or PDF output*

Description

Create 'Rmd' vignette templates for HTML or PDF output

Usage

```
use_vignette_html(destination = tempfile(fileext = ".Rmd"))  
  
use_vignette_pdf(destination = tempfile(fileext = ".Rmd"))
```

Arguments

destination character(1) file path to destination. The directory of the destination must already exist, and the file must not. The default creates a file in the temporary directory, and so is removed when the R session ends.

Examples

```
use_vignette_html()
```

Index

* **manip**

- helpers, [2](#)
- latex, [4](#)
- markdown, [7](#)
- pdf_document, [10](#)

Biocannopkg (macros), [5](#)

Biocbook (macros), [5](#)

Biocexptpkg (macros), [5](#)

Biocpkg, [8](#)

Biocpkg (macros), [5](#)

BiocStyle-defunct, [2](#)

CRANpkg (macros), [5](#)

doc_date (helpers), [2](#)

Githubpkg (macros), [5](#)

helpers, [2](#)

html_document, [2](#), [3](#), [4](#), [8](#), [10](#)

includes, [10](#)

latex, [2](#), [4](#)

macros, [5](#)

markdown, [7](#)

md_document, [4](#), [8](#), [8](#), [10](#)

options, [5](#)

opts_chunk, [5](#)

output, [9](#)

pdf_document, [2](#), [4](#), [8](#), [10](#), [10](#)

pkg_ver (helpers), [2](#)

render, [4](#), [8](#), [10](#)

Rpackage (macros), [5](#)

use_vignette_html, [11](#)

use_vignette_pdf (use_vignette_html), [11](#)