

Package ‘BrowserViz’

January 10, 2025

Type Package

Title BrowserViz: interactive R/browser graphics using websockets and JSON

Version 2.29.0

Date 2023-09-12

Author Paul Shannon

Maintainer Arkadiusz Gladki <gladki.arkadiusz@gmail.com>

Depends R (>= 3.5.0), jsonlite (>= 1.5), httpuv(>= 1.5.0)

Imports methods, BiocGenerics

Suggests RUnit, BiocStyle, knitr, rmarkdown

Description Interactive graphics in a web browser from R, using websockets and JSON.

License GPL-2

URL <https://gladkia.github.io/BrowserViz/>

BugReports <https://github.com/gladkia/BrowserViz/issues>

LazyLoad yes

biocViews Visualization, ThirdPartyClient

NeedsCompilation no

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.2.1

git_url <https://git.bioconductor.org/packages/BrowserViz>

git_branch devel

git_last_commit 0acee92

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2025-01-10

Contents

| | |
|---|-----------|
| addRMessageHandler | 2 |
| browserResponseReady,BrowserViz-method | 3 |
| BrowserViz constructor | 3 |
| BrowserViz-class | 4 |
| closeWebSocket,BrowserViz-method | 5 |
| dispatchMessage | 5 |
| displayHTMLInDiv,BrowserViz-method | 6 |
| fromJSON | 6 |
| getBrowserInfo,BrowserViz-method | 7 |
| getBrowserResponse,BrowserViz-method | 7 |
| getBrowserWindowSize,BrowserViz-method | 8 |
| getBrowserWindowTitle,BrowserViz-method | 8 |
| handleResponse | 9 |
| port,BrowserViz-method | 9 |
| ready,BrowserViz-method | 10 |
| roundTripTest,BrowserViz-method | 10 |
| send,BrowserViz-method | 11 |
| setBrowserWindowTitle,BrowserViz-method | 11 |
| show,BrowserViz-method | 12 |
| toJSON | 12 |
| wait,BrowserViz-method | 13 |
| webBrowserAvailableForTesting | 13 |
| Index | 14 |

| | |
|--------------------|---|
| addRMessageHandler | <i>Supply the name of a function to call, identified by its key</i> |
|--------------------|---|

Description

Supply the name of a function to call, identified by its key

Usage

```
addRMessageHandler(key, functionName)
```

Arguments

| | |
|--------------|--------------------|
| key | A character string |
| functionName | A character string |

browserResponseReady, BrowserViz-method
browserResponseReady

Description

browserResponseReady

Usage

```
## S4 method for signature 'BrowserViz'  
browserResponseReady(obj)
```

Arguments

obj An object of class BrowserViz

BrowserViz constructor
Constructor for BrowserViz

Description

This constructor function:

- creates the BrowserViz object
- initializes the httpuv web server
- prepares that web server to additionally handle websocket traffic
- loads a "browserFile" - an html/javascript/css web page to communicate with in your web browser
- opens websocket communication between your R session and your browser
- installs an optional "httpQueryProcessingFunction" to handle http (non-websocket) requests.

Usage

```
BrowserViz(  
  host = "localhost",  
  portRange = 10000:10100,  
  title = "BrowserViz",  
  browserFile,  
  quiet = TRUE,  
  httpQueryProcessingFunction = NULL  
)
```

Arguments

| | | |
|-----------------------------|-----------|---|
| host | character | The constructor will open an http/websocket port here for web browsers to connect to. localhost by default |
| portRange | | The constructor looks for a free websocket port in this range. 10000:10100 by default |
| title | | Used for the web browser window, "igvR" by default |
| browserFile | | The full path to the bundled html, js and libraries, and css which constitute the browser app |
| quiet | | A logical variable controlling verbosity during execution |
| httpQueryProcessingFunction | | a function, default NULL, provides subclasses with the opportunity to execute code on the http server created here. |

Value

An object of the BrowserViZ class

| | |
|------------------|---|
| BrowserViz-class | <i>BrowserViz: a base class providing simple, extensible message passing between your R session and your web browser, for interactive data visualization.</i> |
|------------------|---|

Description

Many of the best interactive graphics capabilities available today are written in Javascript and run in a web browser. BrowserViz makes these capabilities available in R, using websockets for message passing back and forth between R and the browser. This class connects your R session to your web browser via websockets, using the R httpuv library, which in turn uses the Rook webserver.

BrowserViz is a concrete base class, in that instances can be constructed and run - which we do for testing. The primary use of this BrowserViz is to be subclassed: to facilitate the creation of new browser-based, R-connected interactive graphics capabilities embodied in R packages, written by programmers with some skill in both R and Javascript. Two examples of this can be found in these Bioconductor packages <https://bioconductor.org/packages/devel/bioc/html/igvR.html> and <https://bioconductor.org/packages/devel/bioc/html/RCyjs.html>.

Slots

| | |
|---------------------|--|
| uri | The http location at which this modest webserver runs |
| port | An integer port number for the http connection |
| websocketConnection | An environment managed by the httpuv library on our behalf |
| quiet | Logical variable controlling verbosity during execution |

See Also

[BrowserViz](#)

An S4 class to create and manage a modest webserver for websocket message passing between R and Javascript running in your web browser

closeWebSocket,BrowserViz-method

Close the websocket connection - between your R session and your web browser.

Description

Close the websocket connection - between your R session and your web browser.

Usage

```
## S4 method for signature 'BrowserViz'  
closeWebSocket(obj)
```

Arguments

obj An object of class BrowserViz

dispatchMessage *Route the message coming in from the browser to the appropriate R function.*

Description

Route the message coming in from the browser to the appropriate R function.

Usage

```
dispatchMessage(ws, msg, quiet)
```

Arguments

ws a websocket connectin
msg the JSON-encoded message from the browser
quiet logical TRUE or FALSE

displayHTMLInDiv, BrowserViz-method

Ask the browser to display html markup in the specified div

Description

Ask the browser to display html markup in the specified div

Usage

```
## S4 method for signature 'BrowserViz'  
displayHTMLInDiv(obj, htmlText, div.id)
```

Arguments

| | |
|----------|-------------------------------------|
| obj | An object of class BrowserViz |
| htmlText | A character string with HTML markup |
| div.id | A character string |

fromJSON

Transform JSON string into a native R object

Description

Transform JSON string into a native R object

Usage

```
fromJSON(...)
```

Arguments

... Extra arguments passed to this function

Value

a native R data structure

Examples

```
fromJSON(toJSON(data.frame(a=8:10, b=LETTERS[8:10], stringsAsFactors=FALSE)))
```

getBrowserInfo,BrowserViz-method

Retrieve basic attributes of the attached web browser.

Description

Retrieve basic attributes of the attached web browser.

Usage

```
## S4 method for signature 'BrowserViz'  
getBrowserInfo(obj)
```

Arguments

obj An object of class BrowserViz

getBrowserResponse,BrowserViz-method

Retrieve the response sent by the browser

Description

Retrieve the response sent by the browser

Usage

```
## S4 method for signature 'BrowserViz'  
getBrowserResponse(obj)
```

Arguments

obj An object of class BrowserViz

getBrowserWindowSize,BrowserViz-method

Supply the name of a function to call, identified by its key

Description

Supply the name of a function to call, identified by its key

Usage

```
## S4 method for signature 'BrowserViz'  
getBrowserWindowSize(obj)
```

Arguments

obj An object of class BrowserViz

getBrowserWindowTitle,BrowserViz-method

Supply the name of a function to call, identified by its key

Description

Supply the name of a function to call, identified by its key

Usage

```
## S4 method for signature 'BrowserViz'  
getBrowserWindowTitle(obj)
```

Arguments

obj An object of class BrowserViz

handleResponse *handleResponse*

Description

handleResponse

Usage

handleResponse(ws, msg)

Arguments

| | |
|-----|---|
| ws | websocket connection |
| msg | the JSON-encoded character string returned by the browser |

port, BrowserViz-method
Get the port number

Description

Get the port number

Usage

```
## S4 method for signature 'BrowserViz'  
port(obj)
```

Arguments

| | |
|-----|-------------------------------|
| obj | An object of class BrowserViz |
|-----|-------------------------------|

Value

the port number use in the websocket connection, a numeric value.

ready,BrowserViz-method

Is the websocket connection to the browser ready for use?

Description

Is the websocket connection to the browser ready for use?

Usage

```
## S4 method for signature 'BrowserViz'  
ready(obj)
```

Arguments

obj An object of class BrowserViz

roundTripTest,BrowserViz-method

Send data to the browser, ensure that it is returned accurately.

Description

Send data to the browser, ensure that it is returned accurately.

Usage

```
## S4 method for signature 'BrowserViz'  
roundTripTest(obj, ...)
```

Arguments

obj An object of class BrowserViz
... other arguments

send,BrowserViz-method

Send the specified message to the browser

Description

Send the specified message to the browser

Usage

```
## S4 method for signature 'BrowserViz'  
send(obj, msg)
```

Arguments

| | |
|-----|---|
| obj | An object of class BrowserViz |
| msg | A list with four fields: cmd: "someCommand", status: "request", callback: "someFunction", payload: "someData" |

setBrowserWindowTitle,BrowserViz-method

Supply the name of a function to call, identified by its key

Description

Supply the name of a function to call, identified by its key

Usage

```
## S4 method for signature 'BrowserViz'  
setBrowserWindowTitle(obj, newTitle)
```

Arguments

| | |
|----------|-------------------------------|
| obj | An object of class BrowserViz |
| newTitle | A character string |

show, BrowserViz-method

Display the core attributes of the BrowserViz object to stdout

Description

Display the core attributes of the BrowserViz object to stdout

Usage

```
## S4 method for signature 'BrowserViz'
show(object)
```

Arguments

object An object of class BrowserViz

toJSON

Transform an R data structure into JSON

Description

The semantics of toJSON changed between RJSONIO and jsonlite: in the latter, scalars are promoted to arrays of length 1. rather than change our javascript code, and since such promotion – while sensible in the context of R – strikes me as gratuitous, I follow jeroen ooms suggestion, creating this wrapper

Usage

```
toJSON(..., auto_unbox = TRUE)
```

Arguments

... Extra arguments passed to this function
 auto_unbox Logical

Value

a character string with the JSON representation of the R object

Examples

```
toJSON(data.frame(a=8:10, b=LETTERS[8:10], stringsAsFactors=FALSE))
```

wait, BrowserViz-method

Pause for the specified number of milliseconds

Description

Pause for the specified number of milliseconds

Usage

```
## S4 method for signature 'BrowserViz'  
wait(obj, msec)
```

Arguments

| | |
|------|-------------------------------|
| obj | An object of class BrowserViz |
| msec | Numeric |

webBrowserAvailableForTesting

Is there a web browser available for testing?

Description

This package's unit tests require a web browser to connect to. our heuristic, though not bullet proof, is that one of three conditions must be met Supply the name of a function to call, identified by its key

Usage

```
webBrowserAvailableForTesting()
```

Value

Logical TRUE or FALSE

Index

.BrowserViz (BrowserViz-class), 4

addMessageHandler, 2

browserResponseReady
(browserResponseReady, BrowserViz-method), 3

browserResponseReady, BrowserViz-method, 3

BrowserViz, 5

BrowserViz (BrowserViz constructor), 3

BrowserViz constructor, 3

BrowserViz-class, 4

closeWebSocket
(closeWebSocket, BrowserViz-method), 5

closeWebSocket, BrowserViz-method, 5

dispatchMessage, 5

displayHTMLInDiv
(displayHTMLInDiv, BrowserViz-method), 6

displayHTMLInDiv, BrowserViz-method, 6

fromJSON, 6

getBrowserInfo
(getBrowserInfo, BrowserViz-method), 7

getBrowserInfo, BrowserViz-method, 7

getBrowserResponse
(getBrowserResponse, BrowserViz-method), 7

getBrowserResponse, BrowserViz-method, 7

getBrowserWindowSize
(getBrowserWindowSize, BrowserViz-method), 8

getBrowserWindowSize, BrowserViz-method, 8

getBrowserWindowTitle
(getBrowserWindowTitle, BrowserViz-method), 8

getBrowserWindowTitle, BrowserViz-method, 8

handleResponse, 9

port (port, BrowserViz-method), 9

port, BrowserViz-method, 9

ready (ready, BrowserViz-method), 10

ready, BrowserViz-method, 10

roundTripTest
(roundTripTest, BrowserViz-method), 10

roundTripTest, BrowserViz-method, 10

send (send, BrowserViz-method), 11

send, BrowserViz-method, 11

setBrowserWindowTitle
(setBrowserWindowTitle, BrowserViz-method), 11

setBrowserWindowTitle, BrowserViz-method, 11

show (show, BrowserViz-method), 12

show, BrowserViz-method, 12

toJSON, 12

wait (wait, BrowserViz-method), 13

wait, BrowserViz-method, 13

webBrowserAvailableForTesting, 13