

Package ‘escheR’

November 5, 2024

Title Unified multi-dimensional visualizations with Gestalt principles

Version 1.7.0

Description The creation of effective visualizations is a fundamental component of data analysis. In biomedical research, new challenges are emerging to visualize multi-dimensional data in a 2D space, but current data visualization tools have limited capabilities. To address this problem, we leverage Gestalt principles to improve the design and interpretability of multi-dimensional data in 2D data visualizations, layering aesthetics to display multiple variables. The proposed visualization can be applied to spatially-resolved transcriptomics data, but also broadly to data visualized in 2D space, such as embedding visualizations. We provide this open source R package escheR, which is built off of the state-of-the-art ggplot2 visualization framework and can be seamlessly integrated into genomics toolboxes and workflows.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

biocViews Spatial, SingleCell, Transcriptomics, Visualization,
Software

Depends ggplot2, R (>= 4.3)

Imports SpatialExperiment (>= 1.6.1), SingleCellExperiment, rlang,
SummarizedExperiment

BugReports <https://github.com/boyigu01/escheR/issues>

URL <https://github.com/boyigu01/escheR>

Suggests STexampleData, BumpyMatrix, knitr, rmarkdown, BiocStyle,
ggpubr, scran, scater, scuttle, Seurat, hexbin

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/escheR>

git_branch devel

git_last_commit 6c6c207**git_last_commit_date** 2024-10-29**Repository** Bioconductor 3.21**Date/Publication** 2024-11-05

Author Boyi Guo [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2950-2349>>),
 Stephanie C. Hicks [aut] (ORCID:
 <<https://orcid.org/0000-0002-7858-0231>>),
 Erik D. Nelson [ctb] (ORCID: <<https://orcid.org/0000-0001-8477-0982>>)

Maintainer Boyi Guo <boyi.guo.work@gmail.com>

Contents

| | |
|---|----------|
| <code>.contain_reserved_col_name</code> | 2 |
| <code>add_fill</code> | 3 |
| <code>add_ground</code> | 4 |
| <code>add_symbol</code> | 5 |
| <code>make_escheR</code> | 5 |
| Index | 8 |

`.contain_reserved_col_name`

Check if `rowData(spe)` contains reserved name

Description

Internal Funciton

Usage

`.contain_reserved_col_name(col_name)`

Arguments

`col_name` the colnames

Value

TRUE when `col_name` contains reserved names, FALSE

| | |
|----------|---|
| add_fill | <i>Adding fill to highlight the figure in the spatial map</i> |
|----------|---|

Description

Adding fill to highlight the figure in the spatial map

Usage

```
add_fill(p, var, point_size = 2, ...)
```

```
add_fill_bin(p, var, bins = 30, point_size = 2.8, fun = sum, ...)
```

Arguments

| | |
|------------|---|
| p | a spatial map created by <code>make_escheR()</code> , with or without other layers of aesthetics. |
| var | A <code>character(1)</code> with the name of the <code>colData(spe)</code> column that has the values to be used as the background. |
| point_size | A <code>numeric(1)</code> specifying the size of the spot in the <code>ggplot</code> . Defaults to 2. |
| ... | Reserved for future arguments. |
| bins | numeric vector giving number of bins in both vertical and horizontal directions. Set to 30 by default. |
| fun | function for summary. See more detail in stat_summary_hex |

Value

an `ggplot` object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

make_escheR(spe) |>
  add_fill(var = "ground_truth")
```

| | |
|------------|---|
| add_ground | <i>Adding border to highlight the ground in the spatial map</i> |
|------------|---|

Description

Adding border to highlight the ground in the spatial map

Usage

```
add_ground(p, var, stroke = 0.5, point_size = 2, ...)
```

```
add_ground_bin(p, var, bins = 30, stroke = 1, point_size = 3, ...)
```

Arguments

| | |
|-------------------------|--|
| <code>p</code> | a spatial map created by <code>make_escheR()</code> , with or without other layers of aesthetics. |
| <code>var</code> | A character(1) with the name of the <code>colData(spe)</code> column that has the values to be used as the background. |
| <code>stroke</code> | A numeric(1) specifying the thickness of the border. |
| <code>point_size</code> | A numeric(1) specifying the size of the spot in the ggplot. Defaults to 2. |
| <code>...</code> | Reserved for future arguments. |
| <code>bins</code> | numeric vector giving number of bins in both vertical and horizontal directions. Set to 30 by default. |

Value

an ggplot object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

make_escheR(spe) |>
  add_ground(var = "ground_truth")
```

| | |
|------------|---|
| add_symbol | <i>Adding symbols to each spot in the spatial map</i> |
|------------|---|

Description

Adding symbols to each spot in the spatial map

Usage

```
add_symbol(p, var, size = 1, ...)
```

Arguments

| | |
|------|---|
| p | a spatial map created by <code>make_escheR()</code> , with or without other layers of aesthetics. |
| var | A <code>character(1)</code> with the name of the <code>colData(spe)</code> column that has the values to be used as the background. |
| size | A <code>numeric(1)</code> specifying the size of the symbols in the ggplot. Defaults to 1. |
| ... | Reserved for future arguments. |

Value

an ggplot object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

# Convert a continuous variable to categorical
spe$in_tissue <- factor(spe$in_tissue)

make_escheR(spe) |>
  add_ground(var = "ground_truth") |>
  add_symbol(var = "in_tissue", size = 0.5)
```

| | |
|-------------|--|
| make_escheR | <i>Create a new spatial map for spatial transcriptomics data</i> |
|-------------|--|

Description

`make_escheR()` is a generic function to initialize a ggplot object that contains a spatial map. Because the ggplot object saves the input spatial transcriptomics data, the transcriptomics data will be used in the following layering process to add more aesthetic components in the plot following the grammar of graphics and ggplot2 syntax.

Usage

```

make_escheR(object, spot_size = 2, ...)

## S3 method for class 'SingleCellExperiment'
make_escheR(object, spot_size = 2, dimred = "PCA", ...)

## S3 method for class 'SpatialExperiment'
make_escheR(object, spot_size = 2, dimred = NULL, y_reverse = TRUE, ...)

## S3 method for class 'data.frame'
make_escheR(object, spot_size = 2, .x, .y, ...)

```

Arguments

| | |
|-----------|--|
| object | a data object that contains the spatial transcriptomics data. Currently only working for spatial transcriptomics data as <code>SpatialExperiment</code> objects. |
| spot_size | A numeric(1) specifying the size of the spot in the ggplot. Defaults to 2. |
| ... | Reserved for future arguments. |
| dimred | String or integer scalar specifying the existing dimensionality reduction results to use. |
| y_reverse | (logical) Whether to reverse y coordinates, which is often required for 10x Genomics Visium data. Default = TRUE. |
| .x | the X-coordinate |
| .y | the Y-coordinate |

Value

an ggplot object that contains the spatial transcriptomics data.

References

Guo B, Huuki-Myers LA, Grant-Peters M, Collado-Torres L, Hicks SC (2023). escheR: Unified multi-dimensional visualizations with Gestalt principles. *Bioinformatics Advances*, Volume 3, Issue 1, vbad179, doi:10.1093/bioadv/vbad179

Examples

```

library(STexampleData)
# SpatialExperiment Object
spe <- Visium_humanDLPFC()
make_escheR(spe)

# SingleCellExperiment Object
sce <- SingleCellExperiment(counts(spe))
reducedDims(sce) <- list(
  # Example embedding
  EG = matrix(seq.int(1, ncol(spe)*2), ncol = 2)
)

```

```
make_escheR(sce, dimred = "EG")

# data.frame Object
x <- spatialCoords(spe)[,1]
y <- spatialCoords(spe)[,2]
df <- colData(spe) |> data.frame()
make_escheR(object = df, .x = x , .y = y)
```

Index

`.contain_reserved_col_name`, [2](#)

`add_fill`, [3](#)

`add_fill_bin (add_fill)`, [3](#)

`add_ground`, [4](#)

`add_ground_bin (add_ground)`, [4](#)

`add_symbol`, [5](#)

`make_escheR`, [5](#)

`stat_summary_hex`, [3](#)