

# Package ‘poem’

March 20, 2025

**Title** POpulation-based Evaluation Metrics

**Version** 0.99.7

## Description

This package provides a comprehensive set of external and internal evaluation metrics. It includes metrics for assessing partitions or fuzzy partitions derived from clustering results, as well as for evaluating subpopulation identification results within embeddings or graph representations. Additionally, it provides metrics for comparing spatial domain detection results against ground truth labels, and tools for visualizing spatial errors.

**BugReports** <https://github.com/RoseYuan/poem/issues>

**License** GPL (>= 3)

**URL** <https://roseyuan.github.io/poem/>

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Depends** R (>= 4.0)

**Imports** aricode, BiocNeighbors, BiocParallel, bluster, clevr, clue, cluster, elsa, fclust, igraph, Matrix, mclustcomp, methods, sp, spdep, stats, utils, SpatialExperiment, SummarizedExperiment

**Suggests** testthat (>= 3.0.0), BiocStyle, knitr, DT, dplyr, kableExtra, scico, cowplot, ggnetwork, ggplot2, tidyr, STexampleData

**VignetteBuilder** knitr

**biocViews** DimensionReduction, Clustering, GraphAndNetwork, Spatial, ATACSeq, SingleCell, RNASeq, Software, Visualization

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/poem>

**git\_branch** devel

**git\_last\_commit** 7e621fc

**git\_last\_commit\_date** 2025-01-17

**Repository** Bioconductor 3.21

**Date/Publication** 2025-03-19

**Author** Siyuan Luo [cre, aut] (ORCID: <<https://orcid.org/0009-0007-6404-3244>>),  
 Pierre-Luc Germain [aut, ctb] (ORCID:  
 <<https://orcid.org/0000-0003-3418-4218>>)

**Maintainer** Siyuan Luo <roseluosy@gmail.com>

## Contents

.check_duplicated_samples . . . . .	3
.compute_cluster_core_distance . . . . .	4
.compute_mutual_reach_dists . . . . .	4
.compute_pair_to_pair_dists . . . . .	5
.convert_singleton_clusters_to_noise . . . . .	5
.fn_density_separation . . . . .	6
.fn_density_sparseness . . . . .	6
.get_internal_objects . . . . .	7
.get_submatrix . . . . .	8
CDbw . . . . .	8
CHAOS . . . . .	10
dbcv . . . . .	10
ELSA . . . . .	12
emb2knn . . . . .	13
emb2snn . . . . .	13
findSpatialKNN . . . . .	14
FMeasure . . . . .	15
fuzzyHardMetrics . . . . .	16
fuzzyHardMetrics2 . . . . .	18
fuzzyHardSpotConcordance . . . . .	19
fuzzyPartitionMetrics . . . . .	21
fuzzySpotConcordance . . . . .	22
getEmbeddingClassMetrics . . . . .	23
getEmbeddingElementMetrics . . . . .	24
getEmbeddingGlobalMetrics . . . . .	25
getEmbeddingMetrics . . . . .	25
getFuzzyLabel . . . . .	27
getFuzzyPartitionElementMetrics . . . . .	27
getFuzzyPartitionMetrics . . . . .	29
getGraphClassMetrics . . . . .	31
getGraphElementMetrics . . . . .	33
getGraphMetrics . . . . .	34
getNeighboringPairConcordance . . . . .	36
getPairConcordance . . . . .	37
getPartitionClassMetrics . . . . .	37
getPartitionElementMetrics . . . . .	38
getPartitionGlobalMetrics . . . . .	39
getPartitionMetrics . . . . .	40

<code>.check_duplicated_samples</code>	3
<code>getSpatialClassExternalMetrics</code>	42
<code>getSpatialClassInternalMetrics</code>	43
<code>getSpatialElementExternalMetrics</code>	43
<code>getSpatialElementInternalMetrics</code>	44
<code>getSpatialExternalMetrics</code>	45
<code>getSpatialGlobalExternalMetrics</code>	48
<code>getSpatialGlobalInternalMetrics</code>	49
<code>getSpatialInternalMetrics</code>	50
<code>knnComposition</code>	52
<code>matchSets</code>	53
<code>metric_info</code>	53
<code>mockData</code>	54
<code>nnWeightedAccuracy</code>	55
<code>noisy_moon</code>	55
<code>PAS</code>	56
<code>setMatchingAccuracy</code>	56
<code>sp_toys</code>	57
<code>toyExamples</code>	57
<b>Index</b>	<b>59</b>

---

`.check_duplicated_samples`  
*Check Duplicated Samples*

---

### Description

Checks for duplicated samples in matrix  $X$ .

### Usage

```
.check_duplicated_samples(X, threshold = 1e-09)
```

### Arguments

<code>X</code>	Numeric matrix of samples.
<code>threshold</code>	Numeric, the distance threshold to consider samples as duplicates.

### Value

None

---

`.compute_cluster_core_distance`  
*Compute Cluster Core Distance*

---

**Description**

Computes the core distance for each point in a cluster.

**Usage**

```
.compute_cluster_core_distance(dists, d)
```

**Arguments**

<code>dists</code>	Numeric matrix of distances.
<code>d</code>	Integer, the dimensionality.

**Value**

Numeric vector of core distances for each point.

---

`.compute_mutual_reach_dists`  
*Compute Mutual Reachability Distances*

---

**Description**

Computes the mutual reachability distances between points.

**Usage**

```
.compute_mutual_reach_dists(dists, d)
```

**Arguments**

<code>dists</code>	Numeric matrix of distances.
<code>d</code>	Float, the dimensionality.

**Value**

A list containing core distances and mutual reachability distances.

---

`.compute_pair_to_pair_dists`  
*Compute Pair to Pair Distances*

---

**Description**

Compute the pairwise distances between points in matrix  $X$ .

**Usage**

```
.compute_pair_to_pair_dists(X, distance = "euclidean")
```

**Arguments**

<code>X</code>	Numeric matrix.
<code>distance</code>	String specifying the metric to compute the distances.

**Value**

Numeric matrix of pairwise distances with self-distances set to Inf.

---

`.convert_singleton_clusters_to_noise`  
*Convert Singleton Clusters to Noise*

---

**Description**

Converts clusters containing a single instance to noise.

**Usage**

```
.convert_singleton_clusters_to_noise(labels, noise_id)
```

**Arguments**

<code>labels</code>	Integer vector of cluster IDs.
<code>noise_id</code>	Integer, the ID for noise.

**Value**

Integer vector with singleton clusters converted to noise.

---

`.fn_density_separation`

*Density Separation of a Pair of Clusters*

---

### **Description**

Computes the density separation between two clusters.

### **Usage**

```
.fn_density_separation(  
  cls_i,  
  cls_j,  
  dists,  
  internal_core_dists_i,  
  internal_core_dists_j  
)
```

### **Arguments**

<code>cls_i</code>	Integer, first cluster index.
<code>cls_j</code>	Integer, second cluster index.
<code>dists</code>	Numeric matrix of distances.
<code>internal_core_dists_i</code>	Numeric vector of core distances for cluster i.
<code>internal_core_dists_j</code>	Numeric vector of core distances for cluster j.

### **Value**

A list containing the cluster indices and their density separation.

---

`.fn_density_sparseness`

*Density Sparseness of a Cluster*

---

### **Description**

Computes the density sparseness for a given cluster.

### **Usage**

```
.fn_density_sparseness(cls_inds, dists, d, use_igraph_mst)
```

**Arguments**

- `cls_inds` Integer vector of cluster indices.
- `dists` Numeric matrix of distances.
- `d` Integer, the dimensionality.
- `use_igraph_mst` Logical flag to use MST implementation in igraph. Currently only mst from igraph is implemented.

**Value**

A list containing the density sparseness, internal core distances, and internal node indices.

---

`.get_internal_objects` *Get Internal Objects*

---

**Description**

Computes the internal nodes and edges using Minimum Spanning Tree.

**Usage**

```
.get_internal_objects(mutual_reach_dists, use_igraph_mst = TRUE)
```

**Arguments**

- `mutual_reach_dists` Numeric matrix representing mutual reachability distances.
- `use_igraph_mst` Logical flag to use MST implementation in igraph. Currently only mst from igraph is implemented.

**Value**

A list containing the indices of internal nodes and their edge weights.

`.get_submatrix`      *Get Sub matrix*

---

### Description

Extract a sub matrix from a matrix based on optional row and column indices.

### Usage

```
.get_submatrix(arr, inds_a = NULL, inds_b = NULL)
```

### Arguments

`arr`                  Numeric matrix.  
`inds_a`                Optional integer vector for row indices.  
`inds_b`                Optional integer vector for column indices.

### Value

Numeric matrix representing the sub matrix.

---

`CDBw`                  *Calculate CDBw index*

---

### Description

Computes the CDBw-index (Halkidi and Vazirgiannis 2008; Halkidi, Vazirgiannis and Hennig, 2015). This function is directly copied from the `fpc` CRAN package and was written by Christian Hennig. It is included here to reduce the package dependencies (since `fpc` has a few not-so-light dependencies that aren't required here).

### Usage

```
CDBw(  
  x,  
  labels,  
  r = 10,  
  s = seq(0.1, 0.8, by = 0.1),  
  clusterstdev = TRUE,  
  trace = FALSE  
)
```



**Arguments**

x	Something that can be coerced into a numerical matrix, with elements as rows.
labels	A vector of integers with length =nrow(x) indicating the cluster for each observation.
r	Number of cluster border representatives.
s	Vector of shrinking factors.
clusterstdev	Logical. If TRUE, the neighborhood radius for intra-cluster density is the within-cluster estimated squared distance from the mean of the cluster; otherwise it is the average of these over all clusters.
trace	Logical; whether to print processing info.

**Value**

A vector with the following values (see refs for details):

cdbw	value of CDbw index (the higher the better).
cohesion	cohesion.
compactness	compactness.
sep	separation.

**Author(s)**

Christian Hennig

**References**

Halkidi, M. and Vazirgiannis, M. (2008) A density-based cluster validity approach using multi-representatives. *Pattern Recognition Letters* 29, 773-786.

Halkidi, M., Vazirgiannis, M. and Hennig, C. (2015) Method-independent indices for cluster validation. In C. Hennig, M. Meila, F. Murtagh, R. Rocci (eds.) *Handbook of Cluster Analysis*, CRC Press/Taylor & Francis, Boca Raton.

**Examples**

```
d1 <- mockData()
CDbw(d1[,seq_len(2)], d1[,3])
```

---

**CHAOS***Calculate CHAOS score*

---

**Description**

CHAOS score measures the clustering performance by calculating the mean length of the graph edges in the 1-nearest neighbor (1NN) graph for each cluster, averaged across clusters. Lower CHAOS score indicates better spatial domain clustering performance.

**Usage**

```
CHAOS(labels, location, BNPARAM = NULL)
```

**Arguments**

labels	Cluster labels.
location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
BNPARAM	BNPARAM object passed to <code>findKNN</code> specifying the kNN approximation method to use. Defaults to exact for small datasets, and Annoy for larger ones.

**Value**

A numeric value for CHAOS score.

**Examples**

```
data(sp_toys)
data <- sp_toys
CHAOS(data$label, data[,c("x", "y")])
CHAOS(data$p1, data[,c("x", "y")])
CHAOS(data$p2, data[,c("x", "y")])
```

---

**dbcv***Calculate DBCV Metric*

---

**Description**

Compute the DBCV (Density-Based Clustering Validation) metric.

**Usage**

```

dbcv(
  X,
  labels,
  distance = "euclidean",
  noise_id = -1,
  check_duplicates = FALSE,
  use_igraph_mst = TRUE,
  BPPARAM = BiocParallel::SerialParam(),
  ...
)

```

**Arguments**

<code>X</code>	Numeric matrix of samples.
<code>labels</code>	Integer vector of cluster IDs.
<code>distance</code>	String specifying the distance metric. "sqeuclidean", or possible method in <code>stats::dist()</code> . By default "euclidean".
<code>noise_id</code>	Integer, the cluster ID in <code>y</code> for noise (default -1).
<code>check_duplicates</code>	Logical flag to check for duplicate samples.
<code>use_igraph_mst</code>	Logical flag to use <code>igraph</code> 's MST implementation. Currently only <code>mst</code> from <code>igraph</code> is implemented.
<code>BPPARAM</code>	<code>BiocParallel</code> params for multithreading (default none)
<code>...</code>	Ignored

**Details**

This implementation will not fully reproduce the results of other existing implementations (e.g. <https://github.com/FelSiq/DBCv>) due to the different algorithms used for computing the Minimum Spanning Tree.

**Value**

A list:

<code>vcs</code>	Numeric vector of validity index for each cluster.
<code>dbcv</code>	Numeric value representing the overall DBCV metric.

**References**

Davoud Moulavi, et al. 2014; 10.1137/1.9781611973440.96.

**Examples**

```
data(noisy_moon)
data <- noisy_moon
dbcv(data[, c("x", "y")], data$kmeans_label)
dbcv(data[, c("x", "y")], data$hdbscan_label)
```

---

 ELSA

---

*Calculate ELSA scores*


---

**Description**

Calculating the Entropy-based Local indicator of Spatial Association (ELSA) scores, which consist of Ea, Ec and the overall ELSA.

**Usage**

```
ELSA(labels, location, k = 10)
```

**Arguments**

labels	Cluster labels.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	Number of nearest neighbors.

**Value**

A dataframe containing the Ea, Ec and ELSA for all samples in the dataset.

**References**

Naimi, Babak, et al., 2019; 10.1016/j.spasta.2018.10.001

**Examples**

```
data(sp_toys)
data <- sp_toys
ELSA(data$label, data[,c("x", "y")], k=6)
ELSA(data$p1, data[,c("x", "y")], k=6)
ELSA(data$p2, data[,c("x", "y")], k=6)
```

---

emb2knn	<i>Computes k nearest neighbors from embedding</i>
---------	--

---

**Description**

Computes k nearest neighbors from embedding.

**Usage**

```
emb2knn(x, k, BNPARAM = NULL)
```

**Arguments**

x	A numeric matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
k	The number of nearest neighbors.
BNPARAM	A BiocNeighbors parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

**Value**

A knn list.

**Examples**

```
d1 <- mockData()
emb2knn(as.matrix(d1[, seq_len(2)]), k=5)
```

---

emb2snn	<i>Computes shared nearest neighbors from embedding</i>
---------	---

---

**Description**

computes shared nearest neighbors from embedding.

**Usage**

```
emb2snn(x, k, type = "rank", BNPARAM = NULL)
```

**Arguments**

x	A numeric matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
k	The number of nearest neighbors.
type	A string specifying the type of weighting scheme to use for shared neighbors. Possible choices include "rank", "number", and "jaccard". See type in <a href="#">bluster::neighborsToSNNGraph</a> for details.
BNPARAM	A BiocNeighbors parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

**Value**

An igraph object.

**Examples**

```
d1 <- mockData()
emb2snn(as.matrix(d1[, seq_len(2)]), k=5)
```

---

findSpatialKNN

*Find the k nearest spatial neighbors*

---

**Description**

For a given dataset, find the k nearest neighbors for each object based on their spatial locations, with the option of handling ties.

**Usage**

```
findSpatialKNN(
  location,
  k,
  keep_ties = TRUE,
  useMedianDist = FALSE,
  BNPARAM = NULL
)
```

**Arguments**

location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
k	The number of nearest neighbors to look at.
keep_ties	A Boolean indicating if ties are counted once or not. If TRUE, neighbors of the same distances will be included even if it means returning more than k neighbors.

- `useMedianDist` Use the median distance of the k nearest neighbor as maximum distance to be included. Ignored if `keep_ties=FALSE`.
- `BNPARAM` BNPARAM object passed to `findKNN` specifying the kNN approximation method to use. Defaults to exact for small datasets, and Annoy for larger ones.

**Value**

A list of indices.

**Examples**

```
data(sp_toys)
data <- sp_toys
findSpatialKNN(data[,c("x", "y")], k=6)
```

---

FMeasure

*Calculate F measure*


---

**Description**

Compute the F measure between two clustering results. This is directly copied from the package FlowSOM.

**Usage**

```
FMeasure(true, pred, silent = TRUE)
```

**Arguments**

- `true` Array containing real cluster labels for each sample
- `pred` Array containing predicted cluster labels for each sample
- `silent` Logical, if FALSE, print some information about precision and recall

**Value**

F measure score

fuzzyHardMetrics

*Compute fuzzy-hard versions of pair-sorting partition metrics***Description**

Computes fuzzy-hard versions of pair-sorting partition metrics to compare a hard clustering with both a fuzzy and hard truth. This was especially designed for cases where the fuzzy truth represents an uncertainty of a hard truth. Briefly put, the maximum of the pair concordance between the clustering and either the hard or the fuzzy truth is used, and the hard truth is used to compute completeness. See [fuzzyPartitionMetrics](#) for the more standard implementation of the metrics.

**Usage**

```
fuzzyHardMetrics(
  hardTrue,
  fuzzyTrue,
  hardPred,
  nperms = NULL,
  returnElementPairAccuracy = FALSE,
  lowMemory = NULL,
  verbose = TRUE,
  BPPARAM = BiocParallel::SerialParam()
)
```

**Arguments**

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels. Must have the same length as hardPred.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue. Also note that the columns of fuzzyTrue should be in the order of the levels (or integer values) of hardTrue.
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
lowMemory	Logical; whether to use the slower, low-memory algorithm. By default this is enabled if the projected memory usage is higher than ~2GB.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
BPPARAM	BiocParallel params for multithreading (default none)



**Value**

A list of metrics:

NDC	Hullermeier's NDC (fuzzy rand index)
ACI	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
fuzzyWH	Fuzzy Wallace Homogeneity index
fuzzyWC	Fuzzy Wallace Completeness index
fuzzyAWH	Adjusted fuzzy Wallace Homogeneity index
fuzzyAWC	Adjusted fuzzy Wallace Completeness index

**Author(s)**

Pierre-Luc Germain

**References**

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
 D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

**See Also**

[poem::FuzzyPartitionMetrics\(\)](#).

**Examples**

```
# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue,1,FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
fuzzyHardMetrics(hardTrue, fuzzyTrue, hardPred, nperms=3)
```

---

fuzzyHardMetrics2      *Compute fuzzy-hard metrics with lower memory requirement*

---

### Description

This is a slightly slower, but low-memory version of [fuzzyHardMetrics](#).

### Usage

```
fuzzyHardMetrics2(
  hardTrue,
  fuzzyTrue,
  hardPred,
  nperms = 10,
  returnElementPairAccuracy = FALSE,
  verbose = TRUE,
  BPPARAM = BiocParallel::SerialParam()
)
```

### Arguments

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels. Must have the same length as hardPred.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue. Also note that the columns of fuzzyTrue should be in the order of the levels (or integer values) of hardTrue.
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
BPPARAM	BiocParallel params for multithreading (default none)

### Value

A list of metrics:

NDC	Hullermeier's NDC (fuzzy rand index)
-----	--------------------------------------

ACI	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
fuzzyWH	Fuzzy Wallace Homogeneity index
fuzzyWC	Fuzzy Wallace Completeness index
fuzzyAWH	Adjusted fuzzy Wallace Homogeneity index
fuzzyAWC	Adjusted fuzzy Wallace Completeness index

**Author(s)**

Pierre-Luc Germain

**References**

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

**See Also**

[poem::fuzzyHardMetrics\(\)](#).

**Examples**

```
# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue,1,FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
poem::fuzzyHardMetrics2(hardTrue, fuzzyTrue, hardPred, nperms=3)
```

---

fuzzyHardSpotConcordance

*Per-element maximal concordance between a hard and a fuzzy partition*

---

**Description**

Per-element maximal concordance between a hard clustering and hard and fuzzy ground truth labels.

**Usage**

```
fuzzyHardSpotConcordance(
  hardTrue,
  fuzzyTrue,
  hardPred,
  useNegatives = TRUE,
  verbose = TRUE
)
```

**Arguments**

hardTrue	A vector of true cluster labels
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of hardTrue.
hardPred	A vector of predicted cluster labels
useNegatives	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
verbose	Logical; whether to print expected memory usage for large datasets.

**Value**

A numeric vector of concordance scores for each element of hardPred

**Examples**

```
# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue,1,FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
fuzzyHardSpotConcordance(hardTrue, fuzzyTrue, hardPred)
```

---

fuzzyPartitionMetrics *Compute fuzzy-fuzzy versions of pair-sorting partition metrics*

---

### Description

Computes fuzzy versions of pair-sorting partition metrics. This is largely based on the permutation-based implementation by Antonio D'Ambrosio from the ConsRankClass package, modified to also compute the fuzzy versions of the adjusted Wallace indices, implement multithreading, and adjust the number of permutations according to their variability.

### Usage

```
fuzzyPartitionMetrics(
  P,
  Q,
  computeWallace = TRUE,
  nperms = NULL,
  verbose = TRUE,
  returnElementPairAccuracy = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  tnorm = c("product", "min", "lukasiewicz")
)
```

### Arguments

P	A object coercible to a numeric matrix with membership probability of elements (rows) in ground-truth classes (columns).
Q	A object coercible to a numeric matrix with membership probability of elements (rows) in predicted clusters (columns). Must have the same number of rows as P.
computeWallace	Logical; whether to compute the individual fuzzy versions of the Wallace indices (increases running time).
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).
returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
BPPARAM	BiocParallel params for multithreading (default none)
tnorm	Which type of t-norm operation to use for class membership of pairs (either product, min, or lukasiewicz) when calculating the Wallace indices. Does not influence the NDC/ACI metrics.

**Value**

When returnElementPairAccuracy is FALSE, return a list of metrics:

NDC	Hullermeier's NDC (fuzzy rand index)
ACI	Ambrosio's Adjusted Concordance Index (ACI), i.e. a permutation-based fuzzy version of the adjusted Rand index.
fuzzyWH	Fuzzy Wallace Homogeneity index
fuzzyWC	Fuzzy Wallace Completeness index
fuzzyAWH	Adjusted fuzzy Wallace Homogeneity index
fuzzyAWC	Adjusted fuzzy Wallace Completeness index

**Author(s)**

Pierre-Luc Germain

**References**

Hullermeier et al. 2012; 10.1109/TFUZZ.2011.2179303;  
D'Ambrosio et al. 2021; 10.1007/s00357-020-09367-0

**Examples**

```
# generate fuzzy partitions:
```

---

```
fuzzySpotConcordance Per-element concordance between two fuzzy partitions
```

---

**Description**

Per-element concordance between two fuzzy partitions

**Usage**

```
fuzzySpotConcordance(P, Q)
```

**Arguments**

P	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns)
Q	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as P

**Value**

A numeric vector of concordance scores for each row of P.

**Examples**

```
# generate fuzzy partitions:
m1 <- matrix(c(0.95, 0.025, 0.025,
              0.98, 0.01, 0.01,
              0.96, 0.02, 0.02,
              0.95, 0.04, 0.01,
              0.95, 0.01, 0.04,
              0.99, 0.005, 0.005,
              0.025, 0.95, 0.025,
              0.97, 0.02, 0.01,
              0.025, 0.025, 0.95),
            ncol = 3, byrow=TRUE)
m2 <- matrix(c(0.95, 0.025, 0.025,
              0.98, 0.01, 0.01,
              0.96, 0.02, 0.02,
              0.025, 0.95, 0.025,
              0.02, 0.96, 0.02,
              0.01, 0.98, 0.01,
              0.05, 0.05, 0.95,
              0.02, 0.02, 0.96,
              0.01, 0.01, 0.98),
            ncol = 3, byrow=TRUE)
colnames(m1) <- colnames(m2) <- LETTERS[seq_len(3)]
fuzzySpotConcordance(m1,m2)
```

---

```
getEmbeddingClassMetrics
```

```
getEmbeddingClassMetrics
```

---

**Description**

Computes class-level, embedding-based metrics.

**Usage**

```
getEmbeddingClassMetrics(
  x,
  labels,
  metrics = c("meanSW", "minSW", "pnSW", "dbcv"),
  distance = "euclidean",
  ...
)
```

**Arguments**

<code>x</code>	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
<code>labels</code>	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.

metrics	The metrics to compute.
distance	The distance metric to use (default euclidean).
...	Optional arguments. See details.

**Value**

A data.frame of metrics for each node/element of *x*.

---

```
getEmbeddingElementMetrics
      getEmbeddingElementMetrics
```

---

**Description**

Computes element-level, embedding-based metrics.

**Usage**

```
getEmbeddingElementMetrics(
  x,
  labels,
  metrics = c("SW"),
  distance = "euclidean",
  ...
)
```

**Arguments**

<i>x</i>	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
labels	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. Currently, only the silhouette width is supported at the node-level.
distance	The distance metric to use (default euclidean).
...	Optional arguments. See details.

**Value**

A data.frame of metrics for each node/element of *x*.



---

```
getEmbeddingGlobalMetrics
      getEmbeddingGlobalMetrics
```

---

**Description**

Computes dataset-level, embedding-based metrics.

**Usage**

```
getEmbeddingGlobalMetrics(
  x,
  labels,
  metrics = c("meanSW", "meanClassSW", "pnSW", "minClassSW", "cdbw", "cohesion",
    "compactness", "sep", "dbcv"),
  distance = "euclidean",
  ...
)
```

**Arguments**

x	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
labels	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute.
distance	The distance metric to use (default euclidean).
...	Optional arguments. See details.

**Value**

A data.frame (with 1 row) of metrics.

---

```
getEmbeddingMetrics    Compute embedding-based metrics
```

---

**Description**

Computes embedding-based metrics for the specified level.

**Usage**

```
getEmbeddingMetrics(
  x,
  labels,
  metrics = c("meanSW", "minSW", "pnSW", "dbcv"),
  distance = "euclidean",
  level = "class",
  ...
)
```

**Arguments**

x	A data.frame or matrix (with features as columns and items as rows) from which the metrics will be computed.
labels	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. See details.
distance	The distance metric to use (default euclidean).
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
...	Optional arguments. See details.

**Details**

The allowed values for metrics depend on the value of level:

- If level = "element", the allowed metrics are: "SW".
- If level = "class", the allowed metrics are: "meanSW", "minSW", "pnSW", "dbcv".
- If level = "dataset", the allowed metrics are: "meanSW", "meanClassSW", "pnSW", "minClassSW", "cdbw", "cohesion", "compactness", "sep", "dbcv".

The function(s) that the optional arguments ... passed to depend on the value of level:

- If level = "element", optional arguments are passed to `stats::dist()`.
- If level = "class", optional arguments are passed to `dbcv()`.
- If level = "dataset", optional arguments are passed to `dbcv()` or `CDbw()`.

**Value**

A data.frame of metrics.

**Examples**

```
d1 <- mockData()
getEmbeddingMetrics(d1[,seq_len(2)], labels=d1$class,
metrics=c("meanSW", "minSW", "pnSW", "dbcv"), level="class")
```

---

getFuzzyLabel                      *Get fuzzy representation of labels*

---

### Description

Get fuzzy representation of labels according to the spatial neighborhood label composition.

### Usage

```
getFuzzyLabel(labels, location, k = 6, alpha = 0.5, ...)
```

### Arguments

labels	An anomic vector of cluster labels
location	A matrix or data.frame of coordinates
k	The wished number of nearest neighbors
alpha	The parameter to control to what extend the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
...	Passed to <a href="#">findSpatialKNN()</a> .

### Value

A matrix of fuzzy memberships.

### Examples

```
data(sp_toys)
data <- sp_toys
getFuzzyLabel(data$label, data[,c("x", "y")], k=6)
```

---

getFuzzyPartitionElementMetrics  
*getFuzzyPartitionElementMetrics*

---

### Description

Computes a selection of external fuzzy clustering evaluation metrics at the element level.

**Usage**

```

getFuzzyPartitionElementMetrics(
  hardTrue = NULL,
  fuzzyTrue = NULL,
  hardPred = NULL,
  fuzzyPred = NULL,
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  metrics = c("fuzzySPC"),
  useNegatives = TRUE,
  verbose = TRUE,
  usePairs = TRUE
)

```

**Arguments**

<code>hardTrue</code>	A vector of true cluster labels
<code>fuzzyTrue</code>	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns). Must have the same number of rows as the length of <code>hardTrue</code> .
<code>hardPred</code>	A vector of predicted cluster labels
<code>fuzzyPred</code>	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
<code>fuzzy_true</code>	Logical; whether the truth is fuzzy.
<code>fuzzy_pred</code>	Logical; whether the prediction is fuzzy.
<code>metrics</code>	The metrics to compute. Currently only "fuzzySPC" is included at the element level.
<code>useNegatives</code>	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
<code>verbose</code>	Logical; whether to print expected memory usage for large datasets.
<code>usePairs</code>	Logical; whether to compute over pairs instead of elements. Only useful when <code>fuzzy_true=TRUE</code> and <code>fuzzy_pred=FALSE</code> .

**Value**

A dataframe of metric values.

---

getFuzzyPartitionMetrics

*Compute external metrics for fuzzy clusterings*


---

### Description

Computes a selection of external fuzzy clustering evaluation metrics.

### Usage

```
getFuzzyPartitionMetrics(
  hardTrue = NULL,
  fuzzyTrue = NULL,
  hardPred = NULL,
  fuzzyPred = NULL,
  metrics = c("fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC"),
  level = "class",
  nperms = NULL,
  verbose = TRUE,
  returnElementPairAccuracy = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  useNegatives = TRUE,
  usePairs = NULL,
  ...
)
```

### Arguments

hardTrue	An atomic vector coercible to a factor or integer vector containing the true hard labels.
fuzzyTrue	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
hardPred	An atomic vector coercible to a factor or integer vector containing the predicted hard labels.
fuzzyPred	A object coercible to a numeric matrix with membership probability of elements (rows) in clusters (columns).
metrics	The metrics to compute. See details.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
nperms	The number of permutations (for correction for chance). If NULL (default), a first set of 10 permutations will be run to estimate whether the variation across permutations is above 0.0025, in which case more (max 1000) permutations will be run.
verbose	Logical; whether to print info and warnings, including the standard error of the mean across permutations (giving an idea of the precision of the adjusted metrics).

returnElementPairAccuracy	Logical. If TRUE, returns the per-element pair accuracy instead of the various partition-level and dataset-level metrics. Default FALSE.
BPPARAM	BiocParallel params for multithreading (default none)
useNegatives	Logical; whether to include negative pairs in the concordance score (tends to result in a larger overall concordance and lower dynamic range of the score). Default TRUE.
usePairs	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
...	Optional arguments for <code>fuzzyPartitionMetrics</code> : <code>tnorm</code> . Only useful when <code>fuzzy_true=TRUE</code> and <code>fuzzy_pred=TRUE</code> .

## Details

The allowed values for metrics depend on the value of level:

- If level = "element", the allowed metrics are: "fuzzySPC".
- If level = "class", the allowed metrics are: "fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC".
- If level = "dataset", the allowed metrics are: "fuzzyRI", "fuzzyARI", "fuzzyWH", "fuzzyAWH", "fuzzyWC", "fuzzyAWC".

## Value

A dataframe of metric results.

## Examples

```
# generate fuzzy partitions:
m1 <- matrix(c(0.95, 0.025, 0.025,
              0.98, 0.01, 0.01,
              0.96, 0.02, 0.02,
              0.95, 0.04, 0.01,
              0.95, 0.01, 0.04,
              0.99, 0.005, 0.005,
              0.025, 0.95, 0.025,
              0.97, 0.02, 0.01,
              0.025, 0.025, 0.95),
            ncol = 3, byrow=TRUE)
m2 <- matrix(c(0.95, 0.025, 0.025,
              0.98, 0.01, 0.01,
              0.96, 0.02, 0.02,
              0.025, 0.95, 0.025,
              0.02, 0.96, 0.02,
              0.01, 0.98, 0.01,
              0.05, 0.05, 0.95,
              0.02, 0.02, 0.96,
              0.01, 0.01, 0.98),
            ncol = 3, byrow=TRUE)
colnames(m1) <- colnames(m2) <- LETTERS[seq_len(3)]
getFuzzyPartitionMetrics(fuzzyTrue=m1, fuzzyPred=m2, level="class")
```

```

# generate a fuzzy truth:
fuzzyTrue <- matrix(c(
  0.95, 0.025, 0.025,
  0.98, 0.01, 0.01,
  0.96, 0.02, 0.02,
  0.95, 0.04, 0.01,
  0.95, 0.01, 0.04,
  0.99, 0.005, 0.005,
  0.025, 0.95, 0.025,
  0.97, 0.02, 0.01,
  0.025, 0.025, 0.95),
  ncol = 3, byrow=TRUE)
# a hard truth:
hardTrue <- apply(fuzzyTrue,1,FUN=which.max)
# some predicted labels:
hardPred <- c(1,1,1,1,1,1,2,2,2)
getFuzzyPartitionMetrics(hardPred=hardPred, hardTrue=hardTrue,
  fuzzyTrue=fuzzyTrue, nperms=3, level="class")

```

---

```
getGraphClassMetrics  getGraphClassMetrics
```

---

### Description

Computes a selection of supervised graph evaluation metrics using ground truth class labels. The metrics are reported (as average) per class.

### Usage

```

getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

## S4 method for signature 'list'
getGraphClassMetrics(x, labels, metrics, directed = NULL, k = NULL, ...)

## S4 method for signature 'data.frame'
getGraphClassMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,

```

```

    shared = FALSE,
    ...
)

## S4 method for signature 'matrix'
getGraphClassMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)

## S4 method for signature 'igraph'
getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

## S4 method for signature 'dist'
getGraphClassMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  ...
)

```

### Arguments

x	Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
labels	Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of x.
metrics	The metrics to compute. See details.
directed	Logical; whether to compute the metrics in a directed fashion. If left to NULL, conventional choices will be made per metric (adhesion, cohesion, PWC AMSP undirected, others directed).
...	Optional arguments for <a href="#">emb2knn()</a> or <a href="#">emb2snn()</a> .
k	The number of nearest neighbors to compute and/or use. Can be omitted if x is a graph or list of nearest neighbors.



shared Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if x is not an embedding or dist object.

### Value

A data.frame of metrics for each class.

---

```
getGraphElementMetrics
      getGraphElementMetrics
```

---

### Description

Computes a selection of supervised graph evaluation metrics using ground truth class labels. The metrics are reported (as average) per node/element.

### Usage

```
getGraphElementMetrics(x, labels, directed = NULL, ...)
```

```
## S4 method for signature 'list'
```

```
getGraphElementMetrics(x, labels, metrics, directed = NULL, k = NULL, ...)
```

```
## S4 method for signature 'data.frame'
```

```
getGraphElementMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)
```

```
## S4 method for signature 'matrix'
```

```
getGraphElementMetrics(
  x,
  labels,
  metrics,
  directed = NULL,
  k,
  shared = FALSE,
  ...
)
```

```
## S4 method for signature 'igraph'
```

```
getGraphElementMetrics(x, labels, directed = NULL, ...)
```

```
## S4 method for signature 'dist'
getGraphElementMetrics(x, labels, directed = NULL, ...)
```

### Arguments

x	Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
labels	Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of x.
directed	Logical; whether to compute the metrics in a directed fashion. If left to NULL, conventional choices will be made per metric (adhesion, cohesion, PWC AMSP undirected, others directed).
...	Optional arguments for <a href="#">emb2knn()</a> or <a href="#">emb2snn()</a> .
metrics	The metrics to compute. See details.
k	The number of nearest neighbors to compute and/or use. Can be omitted if x is a graph or list of nearest neighbors.
shared	Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if x is not an embedding or dist object.

### Value

A data.frame of metrics for each node/element of x.

---

getGraphMetrics	<i>Compute graph-based metrics</i>
-----------------	------------------------------------

---

### Description

Computes a selection of graph evaluation metrics using class labels.

### Usage

```
getGraphMetrics(
  x,
  labels,
  metrics = c("SI", "NP", "AMSP", "PWC", "NCE"),
  directed = NULL,
  k = 10,
  shared = FALSE,
  level = "class",
  ...
)
```

**Arguments**

x	Either an igraph object, a list of nearest neighbors (see details below), or a data.frame or matrix (with features as columns and items as rows) from which nearest neighbors will be computed.
labels	Either a factor or a character vector indicating the true class label of each element (i.e. row or vertex) of x.
metrics	The metrics to compute. See details.
directed	Logical; whether to compute the metrics in a directed fashion. If left to NULL, conventional choices will be made per metric (adhesion, cohesion, PWC AMSP undirected, others directed).
k	The number of nearest neighbors to compute and/or use. Can be omitted if x is a graph or list of nearest neighbors.
shared	Logical; whether to use a shared nearest neighbor network instead of a nearest neighbor network. Ignored if x is not an embedding or dist object.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
...	Optional arguments for <code>emb2knn()</code> or <code>emb2snn()</code> .

**Details**

The allowed values for `metrics` depend on the value of `level`:

- If `level = "element"`, the allowed metrics are: "SI", "ISI", "NP", "NCE" (see below for details).
- If `level = "class"`, the allowed metrics are:
  - "SI": Simpson's Index.
  - "ISI": Inverse Simpson's Index
  - "NP": Neighborhood Purity
  - "AMSP": Adjusted Mean Shortest Path
  - "PWC": Proportion of Weakly Connected
  - "NCE": Neighborhood Class Enrichment
  - "adhesion": adhesion of a graph, is the minimum number of nodes that must be removed to split a graph.
  - "cohesion": cohesion of a graph, is the minimum number of edges that must be removed to split a graph.
- If `level = "dataset"`, the allowed metrics are: "SI", "ISI", "NP", "AMSP", "PWC", "NCE", "adhesion", "cohesion".

**Value**

A data.frame of metrics.

**Examples**

```
d1 <- mockData()
getGraphMetrics(d1[,seq_len(2)], labels=d1$class, level="class")
```

---

`getNeighboringPairConcordance`

*Per-element local concordance between a clustering and a ground truth*

---

### Description

Per-element local concordance between a clustering and a ground truth

### Usage

```
getNeighboringPairConcordance(  
  true,  
  pred,  
  location,  
  k = 20L,  
  useNegatives = FALSE,  
  distWeights = TRUE,  
  BNPARAM = NULL  
)
```

### Arguments

<code>true</code>	A vector of true class labels
<code>pred</code>	A vector of predicted clusters
<code>location</code>	A matrix or data.frame with spatial dimensions as columns. Alternatively, a nearest neighbor object as produced by <code>findKNN</code> .
<code>k</code>	Approximate number of nearest neighbors to consider
<code>useNegatives</code>	Logical; whether to include the concordance of negative pairs in the score (default FALSE).
<code>distWeights</code>	Logical; whether to weight concordance by distance (default TRUE).
<code>BNPARAM</code>	A <code>BiocNeighbors</code> parameter object to compute kNNs. Ignored unless the input is a matrix or data.frame. If omitted, the Annoy approximation will be used if there are more than 500 elements.

### Value

A vector of concordance scores

### Examples

```
data(sp_toys)  
data <- sp_toys  
getNeighboringPairConcordance(data$label, data$p1, data[,c("x", "y")], k=6)
```

---

getPairConcordance      *Per-element pair concordance score*

---

**Description**

Per-element pair concordance between a clustering and a ground truth

**Usage**

```
getPairConcordance(  
  true,  
  pred,  
  usePairs = TRUE,  
  useNegatives = FALSE,  
  adjust = FALSE  
)
```

**Arguments**

true	A vector of true class labels
pred	A vector of predicted clusters
usePairs	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
useNegatives	Logical; whether to include the consistency of negative pairs in the score (default FALSE).
adjust	Logical; whether to adjust for chance. Only implemented for useNegatives=FALSE (doesn't make sense on a element-level otherwise).

**Value**

A vector of concordance scores

---

getPartitionClassMetrics  
*getPartitionClassMetrics*

---

**Description**

Computes a selection of external evaluation metrics for partition. The metrics are reported per class.

**Usage**

```
getPartitionClassMetrics(
  true,
  pred,
  metrics = c("WC", "WH", "AWC", "AWH", "FM")
)
```

**Arguments**

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. If omitted, main metrics will be computed.

**Value**

A dataframe of metrics.

---

```
getPartitionElementMetrics
  getPartitionElementMetrics
```

---

**Description**

Computes a selection of external evaluation metrics for partition. The metrics are reported per element.

**Usage**

```
getPartitionElementMetrics(
  true,
  pred,
  metrics = c("SPC"),
  usePairs = TRUE,
  useNegatives = TRUE
)
```

**Arguments**

true	A vector of true class labels
pred	A vector of predicted clusters
metrics	The metrics to compute.
usePairs	Logical; whether to compute over pairs instead of elements Recommended and TRUE by default.
useNegatives	Logical; whether to include the consistency of negative pairs in the score (default FALSE).

**Value**

A dataframe of metrics.

---

```
getPartitionGlobalMetrics
      getPartitionGlobalMetrics
```

---

**Description**

Computes a selection of external evaluation metrics for partition. The metrics are reported per dataset.

**Usage**

```
getPartitionGlobalMetrics(
  true,
  pred,
  metrics = c("RI", "WC", "WH", "ARI", "NCR", "AWC", "AWH", "MI", "AMI", "VI", "EH",
             "EC", "VM", "FM"),
  ...
)
```

**Arguments**

<code>true</code>	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>pred</code>	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>metrics</code>	The metrics to compute. If omitted, main metrics will be computed. See below for more details.
<code>...</code>	Optional arguments for MI, VI, or VM. See <a href="#">clevr::mutual_info()</a> , <a href="#">clevr::variation_info()</a> and <a href="#">clevr::v_measure()</a> for more details.

**Value**

A dataframe of metric results. Possible metrics are:

RI	Rand Index
WC	Wallace Completeness
WH	Wallace Homogeneity
ARI	Adjusted Rand Index
AWC	Adjusted Wallace Completeness
AWH	Adjusted Wallace Homogeneity
NCR	Normalized class size Rand index

MI	Mutual Information
AMI	Adjusted Mutual Information
VI	Variation of Information
EH	(Entropy-based) Homogeneity
EC	(Entropy-based) Completeness
VM	V-measure
FM	F-measure/weighted average F1 score
VDM	Van Dongen Measure
MHM	Meila-Heckerman Measure
MMM	Maximum-Match Measure
Mirkin	Mirkin Metric
Accuracy	Set Matching Accuracy

---

getPartitionMetrics    *Compute partition-based metrics*

---

### Description

Computes a selection of external evaluation metrics for partition.

### Usage

```
getPartitionMetrics(
  true,
  pred,
  metrics = c("WC", "WH", "AWC", "AWH", "FM"),
  level = "class",
  ...
)
```

### Arguments

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
metrics	The metrics to compute. If omitted, main metrics will be computed. See details.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
...	Optional arguments for MI, VI, or VM. See <a href="#">clevr::mutual_info()</a> , <a href="#">clevr::variation_info()</a> and <a href="#">clevr::v_measure()</a> for more details.



## Details

The allowed values for metrics depend on the value of level:

- If level = "element", the allowed metrics are:
  - "SPC": Spot-wise Pair Concordance.
  - "ASPC": Adjusted Spot-wise Pair Concordance.
- If level = "class", the allowed metrics are: "WC", "WH", "AWC", "AWH", "FM" (see below for details).
- If level = "dataset", the allowed metrics are:
  - "RI": Rand Index
  - "WC": Wallace Completeness
  - "WH": Wallace Homogeneity
  - "ARI": Adjusted Rand Index
  - "AWC": Adjusted Wallace Completeness
  - "AWH": Adjusted Wallace Homogeneity
  - "NCR": Normalized class size Rand index
  - "MI": Mutual Information
  - "AMI": Adjusted Mutual Information
  - "VI": Variation of Information
  - "EH": (Entropy-based) Homogeneity
  - "EC": (Entropy-based) Completeness
  - "VM": V-measure
  - "FM": F-measure/weighted average F1 score
  - "VDM": Van Dongen Measure
  - "MHM": Meila-Heckerman Measure
  - "MMM": Maximum-Match Measure
  - "Mirkin": Mirkin Metric
  - "Accuracy": Set Matching Accuracy

## Value

A data.frame of metrics.

## Examples

```
true <- rep(LETTERS[seq_len(3)], each=10)
pred <- c(rep("A", 8), rep("B", 9), rep("C", 3), rep("D", 10))
getPartitionMetrics(true, pred, level="class")
getPartitionMetrics(true, pred, level="dataset")
```

---

```
getSpatialClassExternalMetrics
```

*Compute class-level external evaluation metrics for spatially-resolved data*

---

### Description

Computes a selection of external clustering evaluation metrics for spatial data at the class/cluster level.

### Usage

```
getSpatialClassExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)
```

### Arguments

<code>true</code>	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>pred</code>	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>location</code>	A matrix or data.frame of coordinates
<code>k</code>	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics.
<code>alpha</code>	The parameter to control to what extent the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
<code>metrics</code>	a vector of metric names to compute.
<code>fuzzy_true</code>	Logical; whether to compute fuzzy class memberships for true.
<code>fuzzy_pred</code>	Logical; whether to compute fuzzy class memberships for pred.
<code>...</code>	Optional params for <a href="#">fuzzyPartitionMetrics</a> or <a href="#">findSpatialKNN</a> .

### Value

A data.frame of metrics.

---

```
getSpatialClassInternalMetrics
```

*Compute class-level internal evaluation metrics for spatially-resolved data*

---

### Description

Computes a selection of internal clustering evaluation metrics for spatial data for each class.

### Usage

```
getSpatialClassInternalMetrics(  
  labels,  
  location,  
  k = 6,  
  metrics = c("CHAOS", "PAS", "ELSA"),  
  ...  
)
```

### Arguments

labels	A vector containing the labels to be evaluated.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
metrics	Possible metrics: "CHAOS", "PAS" and "ELSA".
...	Optional params for <a href="#">PAS()</a> .

### Value

A dataframe of metric values.

---

```
getSpatialElementExternalMetrics
```

*getSpatialElementExternalMetrics*

---

### Description

Computes a selection of external clustering evaluation metrics for spatial data at the element level.

**Usage**

```
getSpatialElementExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("SpatialSPC", "SpatialNPC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)
```

**Arguments**

true	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
pred	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
location	A matrix or data.frame of coordinates
k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.
alpha	The parameter to control to what extent the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
metrics	a vector of metric names to compute.
fuzzy_true	Logical; whether to compute fuzzy class memberships for true.
fuzzy_pred	Logical; whether to compute fuzzy class memberships for pred.
...	Optional params for <a href="#">getFuzzyPartitionElementMetrics()</a> or <a href="#">findSpatialKNN()</a> .

**Value**

A data.frame of metrics.

---

```
getSpatialElementInternalMetrics
```

*Compute spot-level internal evaluation metrics for spatially-resolved data*

---

**Description**

Computes a selection of internal clustering evaluation metrics for spatial data at each spot level.

**Usage**

```
getSpatialElementInternalMetrics(
  labels,
  location,
  k = 6,
  metrics = c("PAS", "ELSA"),
  ...
)
```

**Arguments**

labels	A vector containing the labels to be evaluated.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
metrics	Possible metrics: "PAS" and "ELSA".
...	Optional params for <a href="#">PAS()</a> .

**Value**

A dataframe containing the metric values for all samples in the dataset. If PAS is calculated, the value is a Boolean about the abnormality of a spot. If ELSA is calculated, Ea, Ec and ELSA for all spots will be returned.

---

```
getSpatialExternalMetrics
```

*Calculate Spatial External Metrics*

---

**Description**

A generic function to calculate spatial external metrics. It can be applied to raw components (true, pred, location) or directly to a SpatialExperiment object.

**Usage**

```
getSpatialExternalMetrics(
  object = NULL,
  true,
  pred,
  location = NULL,
  k = 6,
  alpha = 0.5,
  level = "class",
  metrics = c("SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC"),
)
```

```

    fuzzy_true = TRUE,
    fuzzy_pred = FALSE,
    ...
)

## S4 method for signature 'missing'
getSpatialExternalMetrics(
  object = NULL,
  true,
  pred,
  location = NULL,
  k = 6,
  alpha = 0.5,
  level = "class",
  metrics = c("SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)

## S4 method for signature 'SpatialExperiment'
getSpatialExternalMetrics(
  object = NULL,
  true,
  pred,
  location = NULL,
  k = 6,
  alpha = 0.5,
  level = "class",
  metrics = c("SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)

```

### Arguments

object	The main input. Can be a <code>SpatialExperiment</code> object or missing (when using <code>true</code> , <code>pred</code> , and <code>location</code> directly).
true	When <code>object</code> is missing: a vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list. When <code>object</code> is a <code>SpatialExperiment</code> object: the column name in <code>colData(object)</code> containing the true labels.
pred	When <code>object</code> is missing: a vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list. When <code>object</code> is a <code>SpatialExperiment</code> object: the column name in <code>colData(object)</code> containing the predicted labels.
location	A matrix or data.frame of coordinates

k	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.
alpha	The parameter to control to what extent the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
level	The level to calculate the metrics. Options include "element", "class" and "dataset".
metrics	The metrics to compute. See details.
fuzzy_true	Logical; whether to compute fuzzy class memberships for true.
fuzzy_pred	Logical; whether to compute fuzzy class memberships for pred.
...	Additional arguments passed to specific methods.

### Details

The allowed values for metrics depend on the value of level:

- If level = "element", the allowed metrics are: "SpatialSPC", "SpatialNPC".
- If level = "class", the allowed metrics are: "SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC".
- If level = "dataset", the allowed metrics are: "SpatialRI", "SpatialARI", "SpatialWH", "SpatialAWH", "SpatialWC", "SpatialAWC", "SpatialAccuracy".

### Value

A data.frame of metrics based on the specified input.

### Examples

```
# Example with individual components
data(sp_toys)
data <- sp_toys
getSpatialExternalMetrics(true=data$label, pred=data$p1,
location=data[,c("x", "y")], k=6, level="class")

# Example with SpatialExperiment object
se_object <- SpatialExperiment::SpatialExperiment(assays=matrix(NA,
nrow = nrow(data[,c("x", "y")]),
ncol = ncol(data[,c("x", "y")]),
spatialCoords=as.matrix(data[,c("x", "y")]))
SummarizedExperiment::colData(se_object) <-
cbind(SummarizedExperiment::colData(se_object),
data.frame(true=data$label, pred=data$p1))
getSpatialExternalMetrics(object=se_object, true="true", pred="pred", k=6,
level="class")
```

---

```
getSpatialGlobalExternalMetrics
```

*Compute dataset-level external evaluation metrics for spatially-resolved data*

---

### Description

Computes a selection of external clustering evaluation metrics for spatial data at the dataset level. Options include a series of fuzzy pair-counting metrics and set matching-based accuracy.

### Usage

```
getSpatialGlobalExternalMetrics(
  true,
  pred,
  location,
  k = 6,
  alpha = 0.5,
  metrics = c("SpatialRI", "SpatialARI", "SpatialWH", "SpatialAWH", "SpatialWC",
    "SpatialAWC", "SpatialAccuracy"),
  fuzzy_true = TRUE,
  fuzzy_pred = FALSE,
  ...
)
```

### Arguments

<code>true</code>	A vector containing the labels of the true classes. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>pred</code>	A vector containing the labels of the predicted clusters. Must be a vector of characters, integers, numerics, or a factor, but not a list.
<code>location</code>	A matrix or data.frame of coordinates
<code>k</code>	The number of neighbors used when calculating the fuzzy class memberships for fuzzy metrics, or when calculating the weighted accuracy.
<code>alpha</code>	The parameter to control to what extent the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
<code>metrics</code>	a vector of metric names to compute.
<code>fuzzy_true</code>	Logical; whether to compute fuzzy class memberships for true.
<code>fuzzy_pred</code>	Logical; whether to compute fuzzy class memberships for pred.
<code>...</code>	Optional params for <a href="#">fuzzyPartitionMetrics</a> or <a href="#">findSpatialKNN</a> .



**Value**

A data.frame of metrics.

---

```
getSpatialGlobalInternalMetrics
```

*Compute dataset-level internal evaluation metrics for spatially-resolved data*

---

**Description**

Computes a selection of internal clustering evaluation metrics for spatial data at the dataset level. MPC, PC and PE are internal metrics for fuzzy clustering, and their implementations in package fclust are used.

**Usage**

```
getSpatialGlobalInternalMetrics(
  labels,
  location,
  k = 6,
  metrics = c("PAS", "ELSA", "CHAOS"),
  ...
)
```

**Arguments**

labels	A vector containing the labels to be evaluated.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	The size of the spatial neighborhood to look at for each spot. This is used for calculating PAS and ELSA scores.
metrics	The metrics to compute. See below for more details.
...	Optional arguments for <a href="#">PAS()</a> .

**Value**

A named vector containing metric values. Possible metrics are:

PAS	Proportion of abnormal spots (PAS score).
ELSA	Entropy-based Local indicator of Spatial Association (ELSA score).
CHAOS	Spatial Chaos Score.
MPC	Modified partition coefficient
PC	Partition coefficient
PE	Partition entropy

## References

Yuan, Zhiyuan, et al., 2024; 10.1038/s41592-024-02215-8

Naimi, Babak, et al., 2019; 10.1016/j.spasta.2018.10.001

Wang, et al., 2022; 10.1016/j.ins.2022.11.010

---

getSpatialInternalMetrics

*Compute internal metrics for spatial data*

---

## Description

A generic function to compute a selection of internal clustering evaluation metrics for spatial data. It can be applied to raw components (labels, location) or directly to a SpatialExperiment object.

## Usage

```
getSpatialInternalMetrics(  
  object = NULL,  
  labels,  
  location = NULL,  
  k = 6,  
  level = "class",  
  metrics = c("CHAOS", "PAS", "ELSA"),  
  ...  
)  
  
## S4 method for signature 'missing'  
getSpatialInternalMetrics(  
  object = NULL,  
  labels,  
  location = NULL,  
  k = 6,  
  level = "class",  
  metrics = c("CHAOS", "PAS", "ELSA"),  
  ...  
)  
  
## S4 method for signature 'SpatialExperiment'  
getSpatialInternalMetrics(  
  object = NULL,  
  labels,  
  location = NULL,  
  k = 6,  
  level = "class",  
  metrics = c("CHAOS", "PAS", "ELSA"),  
  ...  
)
```



```

      spatialCoords=as.matrix(data[,c("x", "y")]))
SummarizedExperiment::colData(se_object) <-
cbind(SummarizedExperiment::colData(se_object),
      data.frame(label=data$label))
getSpatialInternalMetrics(object=se_object, labels="label", k=6,
                          level="class")

```

---

knnComposition

*Compute neighborhood composition*


---

### Description

For a given dataset with locations and labels, compute the label composition of the neighborhood for each sample.

### Usage

```
knnComposition(location, k = 6, labels, alpha = 0.5, ...)
```

### Arguments

location	A numeric data matrix containing location information, where rows are points and columns are location dimensions.
k	The number of nearest neighbors to look at.
labels	A vector containing the label for the dataset.
alpha	The parameter to control to what extent the spot itself contribute to the class composition calculation. "equal" means it is weighted the same as other neighbors. A numeric value between 0 and 1 means the weight of the frequency contribution for the spot itself, and the frequency contribution for its knn is then 1-alpha. By default 0.5.
...	Optional arguments for <a href="#">findSpatialKNN()</a> .

### Value

A numerical matrix indicating the composition, where rows correspond to samples and columns correspond to the classes in label.

### Examples

```

data(sp_toys)
data <- sp_toys
knnComposition(data[,c("x", "y")], k=6, data$label)

```

---

matchSets	<i>Match two partitions using Hungarian algorithm</i>
-----------	---

---

**Description**

Match sets from a partitions to a reference partition using the Hungarian algorithm to optimize F1 scores.

**Usage**

```
matchSets(pred, true, forceMatch = TRUE, returnIndices = is.integer(true))
```

**Arguments**

pred	An integer or factor of cluster labels
true	An integer or factor of reference labels
forceMatch	Logical; whether to enforce a match for every set of pred
returnIndices	Logical; whether to return indices rather than levels

**Value**

A vector of matching sets (i.e. level) from true for every set (i.e. level) of pred.

---

metric_info	<i>Metrics Information</i>
-------------	----------------------------

---

**Description**

A dataframe storing the information of all metrics. The code to generate the dataset is at `system.file('inst/scripts/', 'metric_info.R', package='poem')`.

**Usage**

```
metric_info
```

**Format**

```
metric_info:
A data frame.
```

---

`mockData`*Generate mock multidimensional data*

---

**Description**

Generates mock multidimensional data of a given number of classes of points, for testing.

**Usage**

```
mockData(  
  Ns = c(25, 15),  
  classDiff = 2,  
  Sds = 1,  
  ndims = 2,  
  spread = c(1, 2),  
  rndFn = rnorm  
)
```

**Arguments**

<code>Ns</code>	A vector of more than one positive integers specifying the number of elements of each class.
<code>classDiff</code>	The distances between the classes. If there are more than 2 classes, this can be a <code>dist</code> object or a symmetric matrix of <code>length(Ns)-1</code> columns/rows where the lower triangle indicates the desired distances between classes.
<code>Sds</code>	The standard deviation. Can either be a fixed value, a value per class, or a matrix of values for each class (rows) and dimension (column).
<code>ndims</code>	The number of dimensions to generate (default 2).
<code>spread</code>	The spread of the points. Can either be a fixed value, a value per class, or a matrix of values for each class (rows) and dimension (col).
<code>rndFn</code>	The random function, by default <code>rnorm</code> , but should also work for <code>rlnorm</code> and similar.

**Value**

A `data.frame` with coordinates and a `class` column.

**Examples**

```
d <- mockData()
```

---

nnWeightedAccuracy	<i>nnWeightedAccuracy</i>
--------------------	---------------------------

---

**Description**

Computes an accuracy score which weighs elements/spots that are misclassified by the proportion of their (spatial) neighborhood that is not of the element/spot's predicted class. This reduces the weight of misclassifications happening at the boundary between domains.

**Usage**

```
nnWeightedAccuracy(true, pred, location, k = 5, ...)
```

**Arguments**

true	True class labels (vector coercible to factor)
pred	Predicted labels (vector coercible to factor)
location	The spatial coordinates to compute the nearest neighbors.
k	Number of nearest neighbors
...	Optional params passed to <a href="#">findSpatialKNN()</a> .

**Value**

A scalar representing the weighted accuracy.

---

noisy_moon	<i>The noisy moon dataset</i>
------------	-------------------------------

---

**Description**

A simple toy dataset consists of two interleaving half circles. The code to generate the dataset is at `system.file('inst/scripts/', 'noisy_moon.R', package='poem')`.

**Usage**

```
noisy_moon
```

**Format**

**noisy\_moon:**

A data frame with 100 rows and 5 columns:

**x, y** Coordinates of each observations.

**label** Ground truth labels. Either 1 or 2.

**kmeans\_label** Predicted clustering labels using kmeans with 2 centers.

**hdbscan\_label** Predicted clustering labels using hdbscan with minPts = 5.

---

PAS	<i>Calculate PAS score</i>
-----	----------------------------

---

**Description**

PAS score measures the clustering performance by calculating the randomness of the spots that located outside of the spatial region where it was clustered to. Lower PAS score indicates better spatial domain clustering performance.

**Usage**

```
PAS(labels, location, k = 10, ...)
```

**Arguments**

labels	Cluster labels.
location	A numerical matrix containing the location information, with rows as samples and columns as location dimensions.
k	Number of nearest neighbors.
...	Optional params for <code>findSpatialKNN()</code> .

**Value**

A numeric value for PAS score, and a boolean vector about the abnormal spots.

**Examples**

```
data(sp_toys)
data <- sp_toys
PAS(data$label, data[,c("x", "y")], k=6)
PAS(data$p1, data[,c("x", "y")], k=6)
PAS(data$p2, data[,c("x", "y")], k=6)
```

---

setMatchingAccuracy	<i>The non-spatially-weighted counterpart of nnWeightedAccuracy</i>
---------------------	---

---

**Description**

The non-spatially-weighted counterpart of `nnWeightedAccuracy`

**Usage**

```
setMatchingAccuracy(true, pred)
```



**Arguments**

**true** True class labels (vector coercible to factor)  
**pred** Predicted labels (vector coercible to factor)

**Value**

A scalar representing the weighted accuracy.

---

sp_toys	<i>Toy examples of spatial data</i>
---------	-------------------------------------

---

**Description**

Toy examples of spatial data. The code to generate the dataset is at `system.file('inst/scripts/', 'sp_toys.R', package='poem')`.

**Usage**

```
sp_toys
```

**Format**

**sp\_toys:**  
 A data frame with 240 rows and 11 columns, representing a 16 x 15 array of spots:  
**x, y** Coordinates of each spots.  
**row, col** The row and column index of each spots.  
**label** Ground truth labels. Either 1 or 2.  
**p1-p6** Hypothetical predicted spatial clustering labels.

---

toyExamples	<i>Toy embedding examples</i>
-------------	-------------------------------

---

**Description**

Toy example 2D embeddings of elements of different classes, with varying mixing and spread. Graphs 1-3 all have 20 elements of each of 4 classes, but that are mixed in different fashion in the embedding space. Graphs 4-7 all have 100 elements of class1 and 60 of class2, and the class1 elements vary in their spread. The code to generate the dataset is at `system.file('inst/scripts/', 'graph_example.R', package='poem')`.

**Usage**

```
toyExamples
```

**Format**

`toyExamples:`

A data frame.

**graph** The name of the embedding to which the element belongs.

**x, y** Coordinates in the 2D embedding.

**class** The class to which the element belongs.

# Index

## \* datasets

metric\_info, 53  
noisy\_moon, 55  
sp\_toys, 57  
toyExamples, 57

## \* internal

.check\_duplicated\_samples, 3  
.compute\_cluster\_core\_distance, 4  
.compute\_mutual\_reach\_dists, 4  
.compute\_pair\_to\_pair\_dists, 5  
.convert\_singleton\_clusters\_to\_noise,  
5  
.fn\_density\_separation, 6  
.fn\_density\_sparseness, 6  
.get\_internal\_objects, 7  
.get\_submatrix, 8  
FMeasure, 15  
fuzzyHardMetrics2, 18  
getEmbeddingClassMetrics, 23  
getEmbeddingElementMetrics, 24  
getEmbeddingGlobalMetrics, 25  
getFuzzyPartitionElementMetrics,  
27  
getGraphClassMetrics, 31  
getGraphElementMetrics, 33  
getPartitionClassMetrics, 37  
getPartitionElementMetrics, 38  
getPartitionGlobalMetrics, 39  
getSpatialClassExternalMetrics, 42  
getSpatialClassInternalMetrics, 43  
getSpatialElementExternalMetrics,  
43  
getSpatialElementInternalMetrics,  
44  
getSpatialGlobalExternalMetrics,  
48  
getSpatialGlobalInternalMetrics,  
49  
nnWeightedAccuracy, 55

setMatchingAccuracy, 56  
.check\_duplicated\_samples, 3  
.compute\_cluster\_core\_distance, 4  
.compute\_mutual\_reach\_dists, 4  
.compute\_pair\_to\_pair\_dists, 5  
.convert\_singleton\_clusters\_to\_noise,  
5  
.fn\_density\_separation, 6  
.fn\_density\_sparseness, 6  
.get\_internal\_objects, 7  
.get\_submatrix, 8

bluster::neighborsToSNNGraph(), 14

CDbw, 8

CDbw(), 26

CHAOS, 10

clevr::mutual\_info(), 39, 40

clevr::v\_measure(), 39, 40

clevr::variation\_info(), 39, 40

dbcv, 10

dbcv(), 26

ELSA, 12

emb2knn, 13

emb2knn(), 32, 34, 35

emb2snn, 13

emb2snn(), 32, 34, 35

findKNN, 10, 15, 36

findSpatialKNN, 14, 42, 48

findSpatialKNN(), 27, 44, 52, 55, 56

FMeasure, 15

fuzzyHardMetrics, 16, 18

fuzzyHardMetrics2, 18

fuzzyHardSpotConcordance, 19

fuzzyPartitionMetrics, 16, 21, 30, 42, 48

fuzzySpotConcordance, 22

getEmbeddingClassMetrics, 23

- getEmbeddingElementMetrics, 24
- getEmbeddingGlobalMetrics, 25
- getEmbeddingMetrics, 25
- getFuzzyLabel, 27
- getFuzzyPartitionElementMetrics, 27
- getFuzzyPartitionElementMetrics(), 44
- getFuzzyPartitionMetrics, 29
- getGraphClassMetrics, 31
- getGraphClassMetrics, data.frame-method  
(getGraphClassMetrics), 31
- getGraphClassMetrics, dist-method  
(getGraphClassMetrics), 31
- getGraphClassMetrics, igraph-method  
(getGraphClassMetrics), 31
- getGraphClassMetrics, list-method  
(getGraphClassMetrics), 31
- getGraphClassMetrics, matrix-method  
(getGraphClassMetrics), 31
- getGraphElementMetrics, 33
- getGraphElementMetrics, data.frame-method  
(getGraphElementMetrics), 33
- getGraphElementMetrics, dist-method  
(getGraphElementMetrics), 33
- getGraphElementMetrics, igraph-method  
(getGraphElementMetrics), 33
- getGraphElementMetrics, list-method  
(getGraphElementMetrics), 33
- getGraphElementMetrics, matrix-method  
(getGraphElementMetrics), 33
- getGraphMetrics, 34
- getNeighboringPairConcordance, 36
- getPairConcordance, 37
- getPartitionClassMetrics, 37
- getPartitionElementMetrics, 38
- getPartitionGlobalMetrics, 39
- getPartitionMetrics, 40
- getSpatialClassExternalMetrics, 42
- getSpatialClassInternalMetrics, 43
- getSpatialElementExternalMetrics, 43
- getSpatialElementInternalMetrics, 44
- getSpatialExternalMetrics, 45
- getSpatialExternalMetrics, missing-method  
(getSpatialExternalMetrics), 45
- getSpatialExternalMetrics, SpatialExperiment-method  
(getSpatialExternalMetrics), 45
- getSpatialGlobalExternalMetrics, 48
- getSpatialGlobalInternalMetrics, 49
- getSpatialInternalMetrics, 50
- getSpatialInternalMetrics, missing-method  
(getSpatialInternalMetrics), 50
- getSpatialInternalMetrics, SpatialExperiment-method  
(getSpatialInternalMetrics), 50
- knnComposition, 52
- matchSets, 53
- metric\_info, 53
- mockData, 54
- nnWeightedAccuracy, 55
- noisy\_moon, 55
- PAS, 56
- PAS(), 43, 45, 49, 51
- poem::fuzzyHardMetrics(), 19
- poem::FuzzyPartitionMetrics(), 17
- setMatchingAccuracy, 56
- sp\_toys, 57
- stats::dist(), 26
- toyExamples, 57