

BSgenome.Dmelanogaster.UCSC.dm3

October 16, 2018

BSgenome.Dmelanogaster.UCSC.dm3

Full genome sequences for Drosophila melanogaster (UCSC version dm3)

Description

Full genome sequences for *Drosophila melanogaster* (Fly) as provided by UCSC (dm3, Apr. 2006) and stored in Biostrings objects.

Note

This BSgenome data package was made from the following source data files:

chromFa.tar.gz from <http://hgdownload.cse.ucsc.edu/goldenPath/dm3/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Author(s)

The Bioconductor Dev Team

See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNAString](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Examples

```

BSgenome.Drosophila.melanogaster.UCSC.dm3
genome <- BSgenome.Drosophila.melanogaster.UCSC.dm3
seqlengths(genome)
genome$chr2L # same as genome[["chr2L"]]

## -----
## Upstream sequences
## -----
## Starting with BioC 3.0, the upstream1000, upstream2000, and
## upstream5000 sequences for dm3 are not included in the BSgenome data
## package anymore. However they can easily be extracted from the full
## genome sequences with something like:

library(TxDb.Drosophila.melanogaster.UCSC.dm3.ensGene)
txdb <- TxDb.Drosophila.melanogaster.UCSC.dm3.ensGene
gn <- sort(genes(txdb))
up1000 <- flank(gn, width=1000)
up1000seqs <- getSeq(genome, up1000)

## IMPORTANT: Make sure you use a TxDb package (or TranscriptDb object),
## that contains a gene model based on the exact same reference genome
## as the BSgenome object you pass to getSeq(). Note that you can make
## your own custom TranscriptDb object from various annotation resources.
## See the makeTranscriptDbFromUCSC(), makeTranscriptDbFromBiomart(),
## and makeTranscriptDbFromGFF() functions in the GenomicFeatures
## package.

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")

```

Index

*Topic **data**

BSgenome.Dmelanogaster.UCSC.dm3, [1](#)

*Topic **package**

BSgenome.Dmelanogaster.UCSC.dm3, [1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Dmelanogaster.UCSC.dm3, [1](#)

BSgenome.Dmelanogaster.UCSC.dm3-package
(BSgenome.Dmelanogaster.UCSC.dm3),
[1](#)

BSgenomeForge, [1](#)

Dmelanogaster

(BSgenome.Dmelanogaster.UCSC.dm3),
[1](#)

DNAString, [1](#)