

Methylation status calling with METHimpute

Aaron Taudt*

*aaron.taudt@gmail.com

January 4, 2019

Contents

1	Introduction	2
2	Methylation status calling on individual cytosines	2
2.1	Separate-context model.	2
2.2	Interacting-context model	6
3	Methylation status calling on binned data	10
4	Description of columns in the output	13
5	Plots and enrichment analysis	13
6	Export results	15
7	Session Info	15

1 Introduction

Methimpute implements a powerful HMM-based binomial test for methylation status calling. Besides improved accuracy over the classical binomial test, the HMM allows imputation of the methylation status of **all cytosines** in the genome. It achieves this by borrowing information from neighboring covered cytosines. The confidence in the methylation status call is reported as well. The HMM can also be used to impute the methylation status for binned data instead of individual cytosines. Furthermore, *methimpute* outputs context-specific conversion rates, which might be used to optimize the experimental procedure.

For the exact workings of *methimpute* we refer the interested reader to our publication at <https://doi.org/10.1186/s12864-018-4641-x>.

2 Methylation status calling on individual cytosines

The following examples explain the necessary steps for methylation status calling (and imputation). To keep the calculation time short, it uses only the first 200.000 bp of the Arabidopsis genome. The example consists of three steps: 1) Data import, 2) estimating the distance correlation and 3) methylation status calling. At the end of this example you will see that positions without counts are assigned a methylation status, but the confidence (column "posteriorMax") is generally quite low for those cytosines, whereas it is high for well-covered cytosines (≥ 0.99).

2.1 Separate-context model

The separate-context model runs a separate HMM for each context. This assumes that only within-context correlations are important, and between-context correlations do not need to be considered.

```
library(methimpute)

# ===== Step 1: Importing the data ===== #

# We load an example file in BSseeker format that comes with the package
file <- system.file("extdata", "arabidopsis.bsseeker.txt.gz", package="methimpute")
bsseeker.data <- importBSseeker(file)
print(bsseeker.data)

## GRanges object with 110927 ranges and 2 metadata columns:
##           seqnames      ranges strand | context  counts
##           <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1]    chr1         34      - |    CHG      0:4
##      [2]    chr1         80      - |    CHH      2:9
##      [3]    chr1         84      + |    CHH      1:1
##      [4]    chr1         85      + |    CHH      1:1
##      [5]    chr1         86      + |    CHH      1:1
##      ...      ...      ...      ... |    ...      ...
## [110923]    chr1    533552      - |    CG      2:2
## [110924]    chr1    533554      - |    CG      2:2
```

Methylation status calling with METHimpute

```
## [110925] chr1 533595 + | CHG 0:1
## [110926] chr1 533601 + | CHG 0:2
## [110927] chr1 533614 + | CG 0:2
## -----
## seqinfo: 1 sequence from an unspecified genome; no seqlengths

# Because most methylation extractor programs report only covered cytosines,
# we need to inflate the data to include all cytosines (including non-covered sites)
fasta.file <- system.file("extdata","arabidopsis_sequence.fa.gz", package="methimpute")
cytosine.positions <- extractCytosinesFromFASTA(fasta.file,
                                                contexts = c('CG','CHG','CHH'))
methylome <- inflateMethylome(bsseeker.data, cytosine.positions)
print(methylome)

## GRanges object with 199978 ranges and 2 metadata columns:
##      seqnames      ranges strand | context counts
##      <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1] chr1      1      + | CHH      0:0
##      [2] chr1      2      + | CHH      0:0
##      [3] chr1      3      + | CHH      0:0
##      [4] chr1      8      + | CHH      0:0
##      [5] chr1      9      + | CHH      0:0
##      ...      ...      ...      ...      ...
## [199974] chr1 533554 - | CG 2:2
## [199975] chr1 533557 + | CHH 0:0
## [199976] chr1 533560 + | CG 0:0
## [199977] chr1 533561 - | CG 0:0
## [199978] chr1 533565 - | CHH 0:0
## -----
## seqinfo: 1 sequence from an unspecified genome


# ===== Step 2: Obtain correlation parameters ===== #

# The correlation of methylation levels between neighboring cytosines is an important
# parameter for the methylation status calling, so we need to get it first. Keep in mind
# that we only use the first 200.000 bp here, that's why the plot looks a bit meagre.
distcor <- distanceCorrelation(methylome, separate.contexts = TRUE)
fit <- estimateTransDist(distcor)
print(fit)

## $transDist
##      CG-CG      CHG-CHG      CHH-CHH
## 1.866779e+02 1.869434e+09 2.374003e+01
##
## $plot

## Warning: Removed 23 rows containing missing values (geom_path).
```

Methylation status calling with METHimpute



```
# ===== Step 3: Methylation status calling (and imputation) ===== #

model <- callMethylationSeparate(data = methylome, transDist = fit$transDist,
                                verbosity = 0)

# The confidence in the methylation status call is given in the column "posteriorMax".
# For further analysis one could split the results into high-confidence
# (posteriorMax >= 0.98) and low-confidence calls (posteriorMax < 0.98) for instance.
print(model)

## GRanges object with 199978 ranges and 9 metadata columns:
##      seqnames      ranges strand | context  counts  distance
##      <Rle> <IRanges> <Rle> | <factor> <matrix> <numeric>
##      [1]    chr1         1    + |    CHH      0:0      Inf
##      [2]    chr1         2    + |    CHH      0:0        0
##      [3]    chr1         3    + |    CHH      0:0        0
##      [4]    chr1         8    + |    CHH      0:0        4
##      [5]    chr1         9    + |    CHH      0:0        0
##      ...      ...      ...    ... .    ...      ...      ...
## [199974]   chr1    533554    - |    CG        2:2        0
## [199975]   chr1    533557    + |    CHH      0:0        8
## [199976]   chr1    533560    + |    CG        0:0        5
## [199977]   chr1    533561    - |    CG        0:0        0
## [199978]   chr1    533565    - |    CHH      0:0        7
##      transitionContext      posteriorMax      posteriorMeth
##      <factor>      <numeric>      <numeric>
##      [1]      <NA> 0.500403392500598 0.500403392500598
##      [2]    CHH-CHH 0.630124466026651 0.369875533974147
##      [3]    CHH-CHH 0.726585843137985 0.273414156862813
##      [4]    CHH-CHH 0.751636531740801 0.248363468259997
##      [5]    CHH-CHH 0.816371230118716 0.183628769882082
```

Methylation status calling with METHimpute


```
##      ...      ...      ...      ...
## [199974]      CG-CG 0.999975488842536 0.999975488842536
## [199975]      CHH-CHH 0.77422277474309 0.22577722525691
## [199976]      CG-CG 0.905791249227652 0.905791249227652
## [199977]      CG-CG 0.83049955129406 0.83049955129406
## [199978]      CHH-CHH 0.74804177720675 0.25195822279325
##      posteriorUnmeth      status      rc.meth.lvl
##      <numeric>      <factor>      <numeric>
##      [1] 0.499596607500199 Methylated 0.142145049642914
##      [2] 0.630124466026651 Unmethylated 0.105094723888745
##      [3] 0.726585843137985 Unmethylated 0.0777141670864102
##      [4] 0.751636531740801 Unmethylated 0.0706035304485425
##      [5] 0.816371230118716 Unmethylated 0.0522285897303235
##      ...      ...      ...      ...
## [199974] 2.45111574637448e-05 Methylated 0.851514345575296
## [199975] 0.77422277474309 Unmethylated 0.0641924265640977
## [199976] 0.0942087507723487 Methylated 0.772216179664385
## [199977] 0.169500448705941 Methylated 0.708824538144899
## [199978] 0.74804177720675 Unmethylated 0.0716239013330945
## -----
## seqinfo: 1 sequence from an unspecified genome

# Bisulfite conversion rates can be obtained with
1 - model$params$emissionParams$Unmethylated


##      prob
## CG 0.9904123
## CHG 0.9907659
## CHH 0.9998944
```

You can also check several properties of the fitted Hidden Markov Model, such as convergence or transition probabilities, and check how well the fitted distributions describe the data.

```
plotConvergence(model)
```




```
plotTransitionProbs(model)
```



Methylation status calling with METHimpute

```
plotHistogram(model, total.counts = 10)
```



2.2 Interacting-context model

The interacting-context model runs a single HMM for all contexts. This takes into account the within-context and between-context correlations and should be more accurate than the separate-context model if sufficient data is available. However, we have observed that in low coverage settings too much information from well covered contexts is diffusing into the low covered contexts (e.g. CHH and CHG will look like CG with very low coverage). In this case, please use the separate-context model in section 2.1.

```
library(methimpute)

# ===== Step 1: Importing the data ===== #

# We load an example file in BSseeker format that comes with the package
file <- system.file("extdata", "arabidopsis_bsseeker.txt.gz", package="methimpute")
bsseeker.data <- importBSseeker(file)
print(bsseeker.data)

## GRanges object with 110927 ranges and 2 metadata columns:
##           seqnames      ranges strand | context  counts
##           <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1]   chr1         34      - |    CHG     0:4
##      [2]   chr1         80      - |    CHH     2:9
##      [3]   chr1         84      + |    CHH     1:1
##      [4]   chr1         85      + |    CHH     1:1
##      [5]   chr1         86      + |    CHH     1:1
##      ...     ...         ...     .    ...     ...
## [110923]   chr1    533552      - |    CG      2:2
## [110924]   chr1    533554      - |    CG      2:2
## [110925]   chr1    533595      + |    CHG      0:1
## [110926]   chr1    533601      + |    CHG      0:2
## [110927]   chr1    533614      + |    CG      0:2
##      -----
##      seqinfo: 1 sequence from an unspecified genome; no seqlengths

# Because most methylation extractor programs report only covered cytosines,
# we need to inflate the data to include all cytosines (including non-covered sites)
fasta.file <- system.file("extdata", "arabidopsis_sequence.fa.gz", package="methimpute")
cytosine.positions <- extractCytosinesFromFASTA(fasta.file,
                                                contexts = c('CG', 'CHG', 'CHH'))
methyloome <- inflateMethyloome(bsseeker.data, cytosine.positions)
```

Methylation status calling with METHimpute

```
print(methylome)

## GRanges object with 199978 ranges and 2 metadata columns:
##           seqnames      ranges strand | context  counts
##           <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1]    chr1         1      + |    CHH      0:0
##      [2]    chr1         2      + |    CHH      0:0
##      [3]    chr1         3      + |    CHH      0:0
##      [4]    chr1         8      + |    CHH      0:0
##      [5]    chr1         9      + |    CHH      0:0
##      ...      ...      ...      .    ...      ...
## [199974]    chr1    533554      - |    CG      2:2
## [199975]    chr1    533557      + |    CHH      0:0
## [199976]    chr1    533560      + |    CG      0:0
## [199977]    chr1    533561      - |    CG      0:0
## [199978]    chr1    533565      - |    CHH      0:0
## -----
## seqinfo: 1 sequence from an unspecified genome


# ===== Step 2: Obtain correlation parameters ===== #

# The correlation of methylation levels between neighboring cytosines is an important
# parameter for the methylation status calling, so we need to get it first. Keep in mind
# that we only use the first 200,000 bp here, that's why the plot looks a bit meagre.
distcor <- distanceCorrelation(methylome)
fit <- estimateTransDist(distcor)
print(fit)

## $transDist
##      CG-CG      CG-CHG      CG-CHH      CHG-CHG      CHG-CHH      CHH-CHH
## 4.163161e+08 3.764952e+06 8.663764e+01 4.124081e+00 8.989007e+07 4.409969e+01
##
## $plot

## Warning: Removed 24 rows containing missing values (geom_path).
```

Methylation status calling with METHimpute



```
# ===== Step 3: Methylation status calling (and imputation) ===== #
```

```
model <- callMethylation(data = methylome, transDist = fit$transDist)
```

```
## Iteration      log(P)      dlog(P)      Time in sec
##      0          -inf          -            0
##      1    -40631.538364      inf            0
##      2    -26304.340570    14327.197794      0
##      3    -24210.680366    2093.660204      0
##      4    -23635.136829     575.543537      1
##      5    -23374.140150     260.996679      1
##      6    -23224.427402     149.712749      1
##      7    -23134.096529      90.330873      1
##      8    -23079.925890      54.170638      1
##      9    -23047.280470      32.645421      1
##     10    -23027.416339      19.864131      1
##     11    -23015.215444      12.200895      1
##     12    -23007.665702       7.549743      1
##     13    -23002.970956       4.694745      2
##     14    -23000.044292       2.926664      2
##     15    -22998.218552       1.825740      2
##     16    -22997.079038       1.139514      2
##     17    -22996.365767       0.713271      2
```

```
## HMM: Convergence reached!
```

```
# The confidence in the methylation status call is given in the column "posteriorMax".
# For further analysis one could split the results into high-confidence
# (posteriorMax >= 0.98) and low-confidence calls (posteriorMax < 0.98) for instance.
print(model)
```

```
## GRanges object with 199978 ranges and 9 metadata columns:
```

Methylation status calling with METHimpute

```
##          seqnames    ranges strand | context  counts  distance
##          <Rle> <IRanges> <Rle> | <factor> <matrix> <numeric>
##      [1]    chr1         1      + |    CHH      0:0      Inf
##      [2]    chr1         2      + |    CHH      0:0         0
##      [3]    chr1         3      + |    CHH      0:0         0
##      [4]    chr1         8      + |    CHH      0:0         4
##      [5]    chr1         9      + |    CHH      0:0         0
##      ...      ...      ...      ... |    ...      ...      ...
## [199974]    chr1    533554      - |    CG        2:2         0
## [199975]    chr1    533557      + |    CHH      0:0         2
## [199976]    chr1    533560      + |    CG        0:0         2
## [199977]    chr1    533561      - |    CG        0:0         0
## [199978]    chr1    533565      - |    CHH      0:0         3
##          transitionContext      posteriorMax      posteriorMeth
##          <factor>              <numeric>              <numeric>
##      [1]          <NA> 0.660644776579006 0.339355223421633
##      [2]      CHH-CHH 0.706837606307422 0.293162393693218
##      [3]      CHH-CHH 0.747153931606099 0.252846068394541
##      [4]      CHH-CHH 0.762497751475107 0.237502248525533
##      [5]      CHH-CHH 0.796351667673073 0.203648332327567
##      ...      ...      ...      ...
## [199974]      CG-CG 0.999992331296328 0.999992331296328
## [199975]      CG-CHH 0.502982261503237 0.497017738496763
## [199976]      CHH-CG 0.529427694969351 0.470572305030649
## [199977]      CG-CG 0.559538772790009 0.440461227209991
## [199978]      CG-CHH 0.768933290456711 0.231066709543289
##          posteriorUnmeth      status      rc.meth.lvl
##          <numeric>      <factor>      <numeric>
##      [1] 0.660644776579006 Unmethylated 0.11618207339763
##      [2] 0.706837606307422 Unmethylated 0.100477543895639
##      [3] 0.747153931606099 Unmethylated 0.08677089453496
##      [4] 0.762497751475107 Unmethylated 0.0815543387789519
##      [5] 0.796351667673073 Unmethylated 0.070044764050261
##      ...      ...      ...
## [199974] 7.66870367162539e-06 Methylated 0.82388257609264
## [199975] 0.502982261503237 Unmethylated 0.16978380409724
## [199976] 0.529427694969351 Unmethylated 0.39068490235593
## [199977] 0.559538772790009 Unmethylated 0.366046527873533
## [199978] 0.768933290456711 Unmethylated 0.0793663993865807
## -----
## seqinfo: 1 sequence from an unspecified genome

# Bisulfite conversion rates can be obtained with
1 - model$params$emissionParams$Unmethylated

##          prob
## CG 0.9943607
## CHG 0.9979215
## CHH 0.9991911
```

3 Methylation status calling on binned data

The following examples explain the necessary steps for methylation status calling (and imputation) on binned data, such as commonly used 100bp bins. To keep the calculation time short, it uses only the first 200.000 bp of the Arabidopsis genome. The example consists of four steps: 1) Data import, 2) binning and 3) methylation status calling.

```
library(methimpute)

# ===== Step 1: Importing the data ===== #

# We load an example file in BSseeker format that comes with the package
file <- system.file("extdata", "arabidopsis_bsseeker.txt.gz", package="methimpute")
bsseeker.data <- importBSseeker(file)
print(bsseeker.data)

## GRanges object with 110927 ranges and 2 metadata columns:
##           seqnames      ranges strand | context  counts
##           <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1]    chr1         34      - |    CHG      0:4
##      [2]    chr1         80      - |    CHH      2:9
##      [3]    chr1         84      + |    CHH      1:1
##      [4]    chr1         85      + |    CHH      1:1
##      [5]    chr1         86      + |    CHH      1:1
##      ...      ...      ...      ... |    ...      ...
## [110923]    chr1    533552      - |    CG      2:2
## [110924]    chr1    533554      - |    CG      2:2
## [110925]    chr1    533595      + |    CHG      0:1
## [110926]    chr1    533601      + |    CHG      0:2
## [110927]    chr1    533614      + |    CG      0:2
##      -----
## seqinfo: 1 sequence from an unspecified genome; no seqlengths

# Because most methylation extractor programs report only covered cytosines,
# we need to inflate the data to include all cytosines (including non-covered sites)
fasta.file <- system.file("extdata", "arabidopsis_sequence.fa.gz", package="methimpute")
cytosine.positions <- extractCytosinesFromFASTA(fasta.file,
                                                contexts = c('CG', 'CHG', 'CHH'))

methyloome <- inflateMethyloome(bsseeker.data, cytosine.positions)
print(methyloome)

## GRanges object with 199978 ranges and 2 metadata columns:
##           seqnames      ranges strand | context  counts
##           <Rle> <IRanges> <Rle> | <factor> <matrix>
##      [1]    chr1          1      + |    CHH      0:0
##      [2]    chr1          2      + |    CHH      0:0
##      [3]    chr1          3      + |    CHH      0:0
##      [4]    chr1          8      + |    CHH      0:0
##      [5]    chr1          9      + |    CHH      0:0
##      ...      ...      ...      ... |    ...      ...
## [199974]    chr1    533554      - |    CG      2:2
## [199975]    chr1    533557      + |    CHH      0:0
## [199976]    chr1    533560      + |    CG      0:0
## [199977]    chr1    533561      - |    CG      0:0
## [199978]    chr1    533565      - |    CHH      0:0
```

Methylation status calling with METHimpute

```
## -----
## seqinfo: 1 sequence from an unspecified genome

# ===== Step 2: Binning into 100bp bins ===== #
binnedMethylome <- binMethylome(methylome, binsize = 100, contexts = c('total','CG'))
print(binnedMethylome$CG)

## GRanges object with 5335 ranges and 3 metadata columns:
##      seqnames      ranges strand | cytosines context counts
##      <Rle>      <IRanges> <Rle> | <integer> <factor> <matrix>
##      [1]      chr1        1-100   * |         0      CG    7:19
##      [2]      chr1       101-200   * |         6      CG   41:62
##      [3]      chr1       201-300   * |         0      CG    3:58
##      [4]      chr1       301-400   * |         2      CG    4:43
##      [5]      chr1       401-500   * |         1      CG    0:19
##      ...      ...      ...      ... | ...      ...      ...
## [5331]      chr1 533001-533100   * |         0      CG    0:55
## [5332]      chr1 533101-533200   * |        14      CG   3:171
## [5333]      chr1 533201-533300   * |        10      CG    0:16
## [5334]      chr1 533301-533400   * |         2      CG    0:35
## [5335]      chr1 533401-533500   * |         8      CG    1:44
## -----
## seqinfo: 1 sequence from an unspecified genome

# ===== Step 3: Methylation status calling (and imputation) ===== #

binnedModel <- callMethylation(data = binnedMethylome$CG)

## Iteration      log(P)      dlog(P)      Time in sec
##      0          -inf          -            0
##      1    -27231.884280          inf            0
##      2    -16567.652577    10664.231703            0
##      3    -14617.459829    1950.192748            0
##      4    -13264.059065    1353.400764            0
##      5    -12272.683299     991.375766            0
##      6    -11836.442261     436.241038            0
##      7    -11645.945339     190.496922            0
##      8    -11556.833035      89.112304            0
##      9    -11524.535678     32.297356            0
##     10    -11514.865975      9.669703            0
##     11    -11512.066277      2.799698            0
##     12    -11511.303950      0.762327            0
## HMM: Convergence reached!

print(binnedModel)


## GRanges object with 5335 ranges and 10 metadata columns:
##      seqnames      ranges strand | cytosines context counts distance
##      <Rle>      <IRanges> <Rle> | <integer> <factor> <matrix> <numeric>
##      [1]      chr1        1-100   * |         0      CG    7:19      Inf
##      [2]      chr1       101-200   * |         6      CG   41:62        0
##      [3]      chr1       201-300   * |         0      CG    3:58        0
##      [4]      chr1       301-400   * |         2      CG    4:43        0
##      [5]      chr1       401-500   * |         1      CG    0:19        0
##      ...      ...      ...      ... | ...      ...      ...      ...
## [5331]      chr1 533001-533100   * |         0      CG    0:55        0
## [5332]      chr1 533101-533200   * |        14      CG   3:171        0
## [5333]      chr1 533201-533300   * |        10      CG    0:16        0
```

Methylation status calling with METHimpute

```
## [5334] chr1 533301-533400 * | 2 CG 0:35 0
## [5335] chr1 533401-533500 * | 8 CG 1:44 0
## transitionContext posteriorMax posteriorMeth
## <factor> <numeric> <numeric>
## [1] <NA> 1.000000000000004 1.000000000000004
## [2] CG-CG 1.000000000000004 1.000000000000004
## [3] CG-CG 0.64221455778955 0.357785442210489
## [4] CG-CG 0.974229886049142 0.974229886049142
## [5] CG-CG 0.964947193718799 0.0350528062812398
## ... ...
## [5331] CG-CG 0.99999959766252 4.02337484841841e-08
## [5332] CG-CG 0.999999999999999 1.36231328639882e-15
## [5333] CG-CG 0.999017508882559 0.000982491117440949
## [5334] CG-CG 0.99999277818462 7.22181537982054e-06
## [5335] CG-CG 0.999908468202932 9.15317970682571e-05
## posteriorUnmeth status rc.meth.lvl
## <numeric> <factor> <numeric>
## [1] 3.27850556847052e-109 Methylated 0.231438411060918
## [2] 6.63409639736331e-70 Methylated 0.231438411060918
## [3] 0.64221455778955 Unmethylated 0.0854671890961148
## [4] 0.0257701139508971 Methylated 0.22558103056719
## [5] 0.964947193718799 Unmethylated 0.0121121449553186
## ... ...
## [5331] 0.99999959766252 Unmethylated 0.00414487758160785
## [5332] 0.999999999999999 Unmethylated 0.00414486843673693
## [5333] 0.999017508882559 Unmethylated 0.00436818232341656
## [5334] 0.99999277818462 Unmethylated 0.00414650990873848
## [5335] 0.999908468202932 Unmethylated 0.00416567302315502
## -----
## seqinfo: 1 sequence from an unspecified genome
```


You can also check several properties of the fitted Hidden Markov Model, such as convergence or transition probabilities, and check how well the fitted distributions describe the data. This last point is important because the binomial distributions that the HMM uses were originally meant to describe individual cytosines and not bins. However, we have observed that they still capture the bimodal distributions of methylation levels in binned data quite well. Note that the histogram for our example looks quite sparse due to the very low number of bins that were used.

```
plotConvergence(binnedModel)
```




```
plotTransitionProbs(binnedModel)
```

Methylation status calling with METHimpute



```
plotHistogram(binnedModel, total.counts = 150)
```



4 Description of columns in the output

- **context** The sequence context of the cytosine.
- **counts** Counts for methylated and total number of reads at each position.
- **distance** The distance in base-pairs from the previous to the current cytosine.
- **transitionContext** Transition context in the form "previous-current".
- **posteriorMax** Maximum posterior value of the methylation status call, can be interpreted as the confidence in the call.
- **posteriorMeth** Posterior value of the "methylated" component.
- **posteriorUnmeth** Posterior value of the "unmethylated" component.
- **status** Methylation status.
- **rc.meth.lvl** Recalibrated methylation level, calculated from the posteriors and the fitted parameters (see ?methimputeBinomialHMM for details).

5 Plots and enrichment analysis


This package also offers plotting functions for a simple enrichment analysis. Let's say we are interested in the methylation level around genes and transposable elements. We would also like to see how the imputation works on cytosines with missing data compared to covered cytosines.

```
# Define categories to distinguish missing from covered cytosines
model$data$category <- factor('covered', levels=c('missing', 'covered'))
model$data$category[model$data$counts[, 'total'] >= 1] <- 'covered'
model$data$category[model$data$counts[, 'total'] == 0] <- 'missing'
```


Methylation status calling with METHimpute

```
# Note that the plots look a bit ugly because our toy data has only 200.000 datapoints.
data(arabidopsis_genes)
seqlengths(model$data) <- seqlengths(arabidopsis_genes)[seqlevels(model$data)] # this
# line should only be necessary for our toy example
plotEnrichment(model$data, annotation=arabidopsis_genes, range = 2000,
               category.column = 'category')

## $meth.lvl
## Warning: Removed 180 rows containing missing values (geom_path).
```




```
##
## $src.meth.lvl
```




```
data(arabidopsis_TEs)
plotEnrichment(model$data, annotation=arabidopsis_TEs, range = 2000,
               category.column = 'category')

## $meth.lvl
## Warning: Removed 180 rows containing missing values (geom_path).
```



Methylation status calling with METHimpute

```
##  
## $rc.meth.lvl
```



6 Export results

You can export the results as TSV file with the following columns:

- chromosome, position, strand, context, counts.methylated, counts.total, posteriorMax, posteriorMeth, posteriorUnmeth, status, rc.meth.lvl

```
exportMethylome(model, filename = tempfile())
```

Please see section 4 for a description of the columns.

7 Session Info

```
toLatex(sessionInfo())
```

- R version 3.5.2 (2018-12-20), x86_64-w64-mingw32
- Locale: LC_COLLATE=C, LC_CTYPE=English_United States.1252, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows Server 2012 R2 x64 (build 9600)
- Matrix products: default
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, stats4, utils
- Other packages: BiocGenerics 0.28.0, GenomInfoDb 1.18.1, GenomicRanges 1.34.0, IRanges 2.16.0, S4Vectors 0.20.1, ggplot2 3.1.0, methimpute 1.4.1
- Loaded via a namespace (and not attached): BiocManager 1.30.4, BiocStyle 2.10.0, Biostrings 2.50.2, GenomInfoDbData 1.2.0, R.methodsS3 1.7.1, R.oo 1.22.0, R.utils 2.7.0, R6 2.3.0, RCurl 1.95-4.11, Rcpp 1.0.0, XVector 0.22.0, assertthat 0.2.0, bindr 0.1.1, bindrcpp 0.2.2, bitops 1.0-6, colorspace 1.3-2, compiler 3.5.2, crayon 1.3.4, data.table 1.11.8, digest 0.6.18, dplyr 0.7.8, evaluate 0.12, glue 1.3.0, grid 3.5.2, gtable 0.2.0, highr 0.7, htmltools 0.3.6, knitr 1.21, labeling 0.3, lazyeval 0.2.1, magrittr 1.5, minpack.lm 1.2-1, munsell 0.5.0, pillar 1.3.1, pkgconfig 2.0.2, plyr 1.8.4, purrr 0.2.5, reshape2 1.4.3, rlang 0.3.0.1, rmarkdown 1.11, scales 1.0.0, stringi 1.2.4, stringr 1.3.1, tibble 2.0.0, tidyr 0.2.5, tools 3.5.2, withr 2.1.2, xfun 0.4, yaml 2.2.0, zlibbioc 1.28.0