

Package ‘AlpsNMR’

May 17, 2022

Type Package

Title Automated spectraL Processing System for NMR

Version 3.7.0

Encoding UTF-8

Description Reads Bruker NMR data directories both zipped and unzipped.

It provides automated and efficient signal processing for untargeted NMR metabolomics.

It is able to interpolate the samples, detect outliers, exclude regions, normalize, detect peaks, align the spectra, integrate peaks, manage metadata and visualize the spectra.

After spectra processing, it can apply multivariate analysis on extracted data.

Efficient plotting with 1-D data is also available.

Basic reading of 1D ACD/Labs exported JDX samples is also available.

License MIT + file LICENSE

LazyData FALSE

Depends R (>= 4.1), dplyr (>= 0.7.5), future (>= 1.10.0), magrittr (>= 1.5)

Imports utils, graphics, stats, grDevices, signal (>= 0.7-6), rlang (>= 0.3.0.1), stringr (>= 1.3.1), tibble(>= 1.3.4), tidyr (>= 1.0.0), readxl (>= 1.1.0), purrr (>= 0.2.5), glue (>= 1.2.0), reshape2 (>= 1.4.3), mixOmics (>= 6.3.2), matrixStats (>= 0.54.0), fs (>= 1.2.6), rmarkdown (>= 1.10), speaq (>= 2.4.0), htmltools (>= 0.3.6), pcaPP (>= 1.9-73), ggplot2 (>= 3.1.0), baseline (>= 1.2-1), vctrs (>= 0.3.0), BiocParallel

Suggests DT (>= 0.5), testthat (>= 2.0.0), plotly (>= 4.7.1), ChemoSpec, knitr, zip (>= 2.0.4), GGally (>= 1.4.0), ggrepel (>= 0.8.0), writexl (>= 1.0), curl, progressr, SummarizedExperiment, S4Vectors

biocViews Software, Preprocessing, Visualization, Classification, Cheminformatics, Metabolomics, DataImport

RoxygenNote 7.1.2

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/AlpsNMR>

git_branch master

git_last_commit e268ec2

git_last_commit_date 2022-04-26

Date/Publication 2022-05-17

Author Ivan Montoliu Roura [aut],
 Sergio Oller Moreno [aut, cre]
 (<<https://orcid.org/0000-0002-8994-1549>>),
 Francisco Madrid Gambin [aut] (<<https://orcid.org/0000-0001-9333-0014>>),
 Luis Fernandez [aut] (<<https://orcid.org/0000-0001-9790-6287>>),
 Héctor Gracia Cabrera [aut],
 Santiago Marco Colás [aut] (<<https://orcid.org/0000-0003-2663-2965>>),
 Nestlé Institute of Health Sciences [cph],
 Institute for Bioengineering of Catalonia [cph]

Maintainer Sergio Oller Moreno <sergioller@gmail.com>

R topics documented:

AlpsNMR-package	4
AUC_model	6
bp_kfold_VIP_analysis	6
bp_VIP_analysis	8
computes_peak_width_ppm	10
confusion_matrix	11
download_MTBLS242	12
files_to_rDolphin	12
file_lister	14
filter.nmr_dataset_family	15
format.nmr_dataset	16
format.nmr_dataset_1D	17
format.nmr_dataset_peak_table	18
get_integration_with_metadata	19
hmdb	19
HMDB_blood	20
HMDB_cell	20
HMDB_urine	20
is.nmr_dataset	21
is.nmr_dataset_1D	21
is.nmr_dataset_peak_table	22
load_and_save_functions	23
models_stability_plot_bootstrap	24
models_stability_plot_plsda	26
model_VIP	27
MUVR_model_plot	28
new_nmr_dataset	28

new_nmr_dataset_1D	29
new_nmr_dataset_peak_table	31
nmr_align	32
nmr_align_find_ref	33
nmr_baseline_removal	33
nmr_baseline_threshold	34
nmr_batman	35
nmr_batman_options	37
nmr_data	39
nmr_dataset	40
nmr_dataset_1D	40
nmr_dataset_family	41
nmr_dataset_peak_table	41
nmr_dataset_peak_table_to_SummarizedExperiment	42
nmr_data_1r_to_SummarizedExperiment	42
nmr_data_analysis	43
nmr_data_analysis_method	45
nmr_detect_peaks	46
nmr_detect_peaks_plot	48
nmr_detect_peaks_tune_snr	49
nmr_exclude_region	50
nmr_export_data_1r	51
nmr_identify_regions_blood	52
nmr_identify_regions_cell	53
nmr_identify_regions_urine	54
nmr_integrate_peak_positions	55
nmr_integrate_regions	56
nmr_interpolate_1D	57
nmr_meta_add	59
nmr_meta_export	61
nmr_meta_get	62
nmr_meta_get_column	63
nmr_normalize	64
nmr_pca_build_model	65
nmr_pca_outliers	67
nmr_pca_outliers_filter	68
nmr_pca_outliers_plot	69
nmr_pca_outliers_robust	70
nmr_pca_plots	71
nmr_ppm_resolution	72
nmr_read_bruker_fid	74
nmr_read_samples	74
nmr_zip_bruker_samples	76
Parameters_blood	77
Parameters_cell	77
Parameters_urine	77
Peak_detection	78
permutation_test_model	79

permutation_test_plot	81
Pipelines	82
plot.nmr_dataset_1D	86
plot_bootstrap_multimodel	88
plot_interactive	89
plot_plsda_multimodel	90
plot_plsda_samples	91
plot_vip_scores	93
plot_webgl	94
plsda_auroc_vip_compare	95
plsda_auroc_vip_method	97
ppm_resolution	98
ppm_VIP_vector	98
print.nmr_dataset	99
print.nmr_dataset_1D	100
print.nmr_dataset_peak_table	101
p_value_perm	102
random_subsampling	102
rdCV_PLS_RF	103
rdCV_PLS_RF_ML	104
read_bruker_sample	105
regions_from_peak_table	106
ROI_blood	107
ROI_cell	107
ROI_urine	107
save_files_to_rDolphin	108
save_profiling_output	109
SummarizedExperiment_to_nmr_dataset_peak_table	110
SummarizedExperiment_to_nmr_data_1r	111
to_ChemoSpec	111
validate_nmr_dataset	112
validate_nmr_dataset_family	113
validate_nmr_dataset_peak_table	114
[.nmr_dataset	115
[.nmr_dataset_1D	116
[.nmr_dataset_peak_table	117

Index**118**

AlpsNMR-package

*AlpsNMR: Automated spectral Processing System for NMR***Description**

AlpsNMR allows you to import NMR spectra into R and provides automated and efficient signal processing for untargeted NMR metabolomics.

Details

The following functions can be combined with the pipe. They create or modify the `nmr_dataset` object.

- `nmr_read_samples_dir()` or `nmr_read_samples()`
- `nmr_interpolate_1D()`
- `nmr_exclude_region()`
- `nmr_normalize()`
- `plot()`

There are also functions to extract the metadata and submit the samples to irods, see the example below.

The `nmr_dataset` object is essentially a list, so it is easy to access its components for further analysis.

Author(s)

Maintainer: Sergio Oller Moreno <sergioller@gmail.com> ([ORCID](#))

Authors:

- Ivan Montoliu Roura <Ivan.MontoliuRoura@rd.nestle.com>
- Francisco Madrid Gambin <fmadrid@ibecbarcelona.eu> ([ORCID](#))
- Luis Fernandez <lfernandez@ibecbarcelona.eu> ([ORCID](#))
- Héctor Gracia Cabrera <hgracia@ibecbarcelona.eu>
- Santiago Marco Colás <smarco@ibecbarcelona.eu> ([ORCID](#))

Other contributors:

- Nestlé Institute of Health Sciences [copyright holder]
- Institute for Bioengineering of Catalonia [copyright holder]

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
my_nmr_dataset <- dataset %>%
  nmr_interpolate_1D(axis = c(0.4, 10)) %>%
  nmr_exclude_region(exclude = list(water = c(4.6, 5))) %>%
  nmr_normalize(method = "pqn") %>%
  plot
```

AUC_model	<i>Deprecated function Extracts AUC value</i>
-----------	---

Description

The function extracts the AUC value from the middle MUVR model

Usage

```
AUC_model(MVObj)
```

Arguments

MVObj a MUVR model

Value

the AUC value of the middle model

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,
use bp_kfold_VIP_analysis method instead")
```

bp_kfold_VIP_analysis *K-fold bootstrap and permutation over PLS-VIP*

Description

Bootstrap and permutation over PLS-VIP on AlpsNMR can be performed on both [nmr_dataset_1D](#) full spectra as well as [nmr_dataset_peak_table](#) peak tables.

Usage

```
bp_kfold_VIP_analysis(dataset, y_column, k = 4, ncomp = 3, nbootstrap = 300)
```

Arguments

dataset	An nmr_dataset_family object
y_column	A string with the name of the y column (present in the metadata of the dataset)
k	Number of folds, recommended between 4 to 10
ncomp	number of components for the bootstrap models
nbootstrap	number of bootstrap dataset

Details

Use of the bootstrap and permutation methods for a more robust variable importance in the projection metric for partial least squares regression, in a k-fold cross validation

Value

A list with the following elements:

- `important_vips`: A list with the important vips selected
- `relevant_vips`: List of vips with some relevance
- `wilcoxon_vips`: List of vips that pass a wilcoxon test
- `vip_means`: Means of the vips scores
- `vip_score_plot`: plot of the vips scores
- `kfold_results`: results of the k [bp_VIP_analysis](#)
- `kfold_index`: list of index of partitions of the folds

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 64 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)
rownames(peak_matrix) <- paste0("Sample", 1:num_samples)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)
```

```
## We will use bootstrap and permutation method for VIPs selection
## in a a k-fold cross validation
bp_results <- bp_kfold_VIP_analysis(peak_table, # Data to be analyzed
                                   y_column = "Condition", # Label
                                   k = 3,
                                   nbootstrap = 10)

message("Selected VIPs are: ", bp_results$important_vips)
```

bp_VIP_analysis *Bootstrap and permutation over PLS-VIP*

Description

Bootstrap and permutation over PLS-VIP on AlpsNMR can be performed on both [nmr_dataset_1D](#) full spectra as well as [nmr_dataset_peak_table](#) peak tables.

Usage

```
bp_VIP_analysis(dataset, train_index, y_column, ncomp, nbootstrap = 300)
```

Arguments

dataset	An nmr_dataset_family object
train_index	set of index used to generate the bootstrap datasets
y_column	A string with the name of the y column (present in the metadata of the dataset)
ncomp	number of components used in the plsda models
nbootstrap	number of bootstrap dataset

Details

Use of the bootstrap and permutation methods for a more robust variable importance in the projection metric for partial least squares regression

Value

A list with the following elements:

- `important_vips`: A list with the important vips selected
- `relevant_vips`: List of vips with some relevance
- `pls_vip`: Pls-VIPs of every bootstrap
- `pls_vip_perm`: Pls-VIPs of every bootstrap with permuted variables
- `pls_vip_means`: Pls-VIPs normalized differences means
- `pls_vip_score_diff`: Differences of `pls_vip` and `pls_vip_perm`

- pls_models: pls models of the different bootstraps
- pls_perm_models: pls permuted models of the different bootstraps
- classif_rate: classification rate of the bootstrap models
- general_model: pls model trained with all train data
- general_CR: classification rate of the general_model
- vips_model: pls model trained with vips selection over all train data
- vips_CR: classification rate of the vips_model
- error: error expected in a t distribution
- lower_bound: lower bound of the confidence interval
- upper_bound: upper bound of the confidence interval

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use a double cross validation, splitting the samples with random
## subsampling both in the external and internal validation.
## The classification model will be a PLS-DA, exploring at maximum 3 latent
## variables.
```

```
## The best model will be selected based on the area under the ROC curve
methodology <- plsda_auroc_vip_method(ncomp = 3)
model <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 1, test_size = 0.25),
  internal_val = list(iterations = 3, test_size = 0.25),
  data_analysis_method = methodology
)
## Area under ROC for each outer cross-validation iteration:
model$outer_cv_results_digested$auroc

## The number of components for the bootstrap models is selected
ncomps <- model$outer_cv_results$`1`$model$ncomp
train_index <- model$train_test_partitions$outer$`1`$outer_train

# Bootstrap and permutation for VIP selection
bp_VIPS <- bp_VIP_analysis(peak_table, # Data to be analyzed
  train_index,
  y_column = "Condition",
  ncomp = ncomps,
  nbootstrap = 10)
```

computes_peak_width_ppm

Peak width estimation for integration

Description

Estimates the peak width (ppm width) to perform peak integration using `nmr_integrate_peak_positions`. for this purpose, the full width at half maximum of a peak from alanine doublet is considered.

Usage

```
computes_peak_width_ppm(nmr_dataset)
```

Arguments

`nmr_dataset` An [nmr_dataset_ID](#).

Value

Numerical. A peak width (ppm) that may be set in `nmr_integrate_peak_positions`

See Also

Other peak integration functions: [Pipelines](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

confusion_matrix

Deprecated function Confusion matrix of the MUVR model

Description

After creating a model with the `rdCV_PLS_RF` function, you can run `confusion_matrix` on the model to make a confusion matrix from MUVR. This gives information about the model performance (e.g. classification rate).

Usage

```
confusion_matrix(MVObj, model = "mid")
```

Arguments

`MVObj` a MUVR model

`model` What type of model to plot ('min', 'mid' or 'max'). Defaults to 'mid'.

Value

A confusion matrix of the model comparing actual vs predicted class

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

download_MTBLS242 *Download MTBLS242*

Description

Downloads part of the MTBLS242 dataset (few hundred megabytes)

Usage

```
download_MTBLS242(dest_dir = "MTBLS242")
```

Arguments

dest_dir Directory where the dataset should be saved

Details

NMR dataset from Gralka et al., 2015. DOI: 10.3945/ajcn.115.110536.

Value

A data frame with the downloaded samples

Examples

```
## Not run:  
download_MTBLS242("./MTBLS242")  
  
## End(Not run)
```

files_to_rDolphin *Files to rDolphin*

Description

The rDolphin family functions are introduced to perform automatic targeted metabolite profiling. Therefore, ensure that you interpolated from -0.1 ppm in order to consider the TSP/DSS signal at 0.0 ppm. The function generates a list with the files required by to_rDolphin function. Then, it is required to save them with the save_files_to_rDolphin. to_rDolphin function will read the generated "parameters.csv" file. function.

Usage

```
files_to_rDolphin(nmr_dataset, biological_origin)
```

Arguments

`nmr_dataset` An `nmr_dataset` object
`biological_origin` String specify the type of sample (blood, urine, cell)

Value

a list containing:

- `meta_rDolphin`: metadata in rDolphin format,
- `NMR_spectra`: spectra matrix
- `ROI`: ROI template
- `Parameters`: parameters file

See Also

Other import/export functions: [Pipelines](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
## Not run:  
# Set the directory in which rDolphin files will be saved  
output_dir_10_rDolphin <- file.path(your_path, "10-rDolphin")  
fs::dir_create(output_dir_10_rDolphin)  
  
# Generate the files (for plasma/serum)  
files_rDolphin = files_to_rDolphin(nmr_dataset_0_10_ppm, blood)  
  
# Save the files  
save_files_to_rDolphin(files_rDolphin, output_dir_10_rDolphin)  
  
# Build the rDolphin object. Do not forget to set the directory  
setwd(output_dir_10_rDolphin)  
rDolphin_object = to_rDolphin("Parameters.csv")  
  
# Visualize your spectra  
rDolphin_plot(rDolphin_object)
```

```

# Run the main profiling function (it takes a while)
targeted_profiling = Automatic_targeted_profiling(rDolphin_object)

# Save results
save_profiling_output(targeted_profiling, output_dir_10_rDolphin)

save_profiling_plots(output_dir_10_rDolphin, targeted_profiling$final_output,
targeted_profiling$reproducibility_data)

#Additionally, you can run some stats
intensities = targeted_profiling$final_output$intensity
group = as.factor(rDolphin_object$Metadata$type)
model_PLS <- rdCV_PLS_RF(X = intensities, Y = group)

## End(Not run)

```

file_lister

NMR file lister

Description

The function lists samples from the chosen folder required to import and create a [nmr_dataset_1D](#) object. The function is based on the `fs::dir_ls()` function.

Usage

```
file_lister(dataset_path_nmr, glob)
```

Arguments

dataset_path_nmr	A character vector of the path where samples are.
glob	A wildcard or globbing pattern common for the samples to be read, for example ending with *0 (spectra acquired by a NOESY sequence often end by 0: 10, 20, 30...) or *s (for example, samples from the tutorial in this package) passed on to <code>grep()</code> to filter paths.

Value

lists of samples from the chosen folder

See Also

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#),

```
nmr_pca_outliers_filter(), nmr_pca_outliers_plot(), nmr_pca_outliers_robust(), nmr_pca_outliers(),  
nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(),  
rdCV_PLS_RF_ML(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()
```

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
lists_of_samples <- file_lister(dir_to_demo_dataset, "*0")
```

```
filter.nmr_dataset_family
```

Keep samples based on metadata column criteria

Description

Keep samples based on metadata column criteria

Usage

```
## S3 method for class 'nmr_dataset_family'  
filter(.data, ...)
```

Arguments

```
.data      An nmr\_dataset\_family object  
...        conditions, as in dplyr
```

Value

The same object, with the matching rows

See Also

Other subsetting functions: [\[.nmr_dataset_1D\(\)](#), [\[.nmr_dataset_peak_table\(\)](#), [\[.nmr_dataset\(\)](#), [nmr_pca_outliers_filter\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))  
  
## example 1  
sample_10 <- filter(dataset_1D, NMRExperiment == "10")  
  
## example 2  
#test_samples <- dataset_1D %>% filter(nmr_peak_table$metadata$external$Group == "placebo")
```

format.nmr_dataset *Format for nmr_dataset*

Description

Format for nmr_dataset

Usage

```
## S3 method for class 'nmr_dataset'  
format(x, ...)
```

Arguments

x an [nmr_dataset](#) object
... for future use

Value

Format for nmr_dataset

See Also

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset_peak_table\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_1D\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset_family\(\)](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Other nmr_dataset functions: [\[.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
format(dataset)
```

format.nmr_dataset_1D *format for nmr_dataset_1D*

Description

format for nmr_dataset_1D

Usage

```
## S3 method for class 'nmr_dataset_1D'  
format(x, ...)
```

Arguments

x an `nmr_dataset_1D` object
... for future use

Value

format for nmr_dataset_1D

See Also

Other class helper functions: `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`, `validate_nmr_dataset()`

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_list()`, `files_to_rDolphin()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))  
format(dataset_1D)
```

```
format.nmr_dataset_peak_table
```

Format for nmr_dataset_peak_table

Description

Format for nmr_dataset_peak_table

Usage

```
## S3 method for class 'nmr_dataset_peak_table'
format(x, ...)
```

Arguments

x an [nmr_dataset_peak_table](#) object
 ... for future use

Value

Format for nmr_dataset_peak_table

See Also

Other [nmr_dataset_peak_table](#) functions: [\[.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_peak_table\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset_peak_table\(\)](#)

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset_peak_table\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_1D\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset_fam](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
new <- new_nmr_dataset_peak_table(peak_table, metadata)
format(new)
```

`get_integration_with_metadata`*Get integrals with metadata from integrate peak positions*

Description

Get integrals with metadata from integrate peak positions

Usage

```
get_integration_with_metadata(integration_object)
```

Arguments

`integration_object`
A `nmr_dataset` object

Value

Get integrals with metadata from integrate peak positions
integration dataframe

See Also

Other peak integration functions: `Pipelines`, `computes_peak_width_ppm()`, `nmr_identify_regions_blood()`, `nmr_identify_regions_cell()`, `nmr_identify_regions_urine()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

`hmdb`*The Human Metabolome DataBase multiplet table*

Description

The Human Metabolome DataBase multiplet table

References

<https://hmdb.ca/>

HMDB_blood	<i>The Human Metabolome DataBase multiplet table: blood metabolites normally found in NMR-based metabolomics</i>
------------	--

Description

The Human Metabolome DataBase multiplet table: blood metabolites normally found in NMR-based metabolomics

References

<https://hmdb.ca/>

HMDB_cell	<i>The Human Metabolome DataBase multiplet table: cell metabolites normally found in NMR-based metabolomics</i>
-----------	---

Description

The Human Metabolome DataBase multiplet table: cell metabolites normally found in NMR-based metabolomics

References

<https://hmdb.ca/>

HMDB_urine	<i>The Human Metabolome DataBase multiplet table: urine metabolites normally found in NMR-based metabolomics</i>
------------	--

Description

The Human Metabolome DataBase multiplet table: urine metabolites normally found in NMR-based metabolomics

References

<https://hmdb.ca/>

is.nmr_dataset *Object is of [nmr_dataset](#) class*

Description

Object is of [nmr_dataset](#) class

Usage

```
is.nmr_dataset(x)
```

Arguments

x An object

Value

TRUE if the object is an [nmr_dataset](#), FALSE otherwise

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
is(dataset)
```

is.nmr_dataset_1D *Object is of [nmr_dataset_1D](#) class*

Description

Object is of [nmr_dataset_1D](#) class

Usage

```
is.nmr_dataset_1D(x)
```

Arguments

x an [nmr_dataset_1D](#) object

Value

TRUE if the object is an [nmr_dataset_1D](#), FALSE otherwise

See Also

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`, `validate_nmr_dataset()`

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
result <- is(dataset_1D)
```

```
is.nmr_dataset_peak_table
```

Object is of `nmr_dataset_peak_table` class

Description

Object is of `nmr_dataset_peak_table` class

Usage

```
is.nmr_dataset_peak_table(x)
```

Arguments

x an `nmr_dataset_peak_table` object

Value

TRUE if the object is an `nmr_dataset_peak_table`, FALSE otherwise

See Also

Other `nmr_dataset_peak_table` functions: `[.nmr_dataset_peak_table()`, `format.nmr_dataset_peak_table()`, `load_and_save_functions`, `new_nmr_dataset_peak_table()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `print.nmr_dataset_peak_table()`, `validate_nmr_dataset_peak_table()`

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`, `validate_nmr_dataset()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
new <- new_nmr_dataset_peak_table(peak_table, metadata)
is(new)
```

load_and_save_functions

nmr_dataset_load

Description

`nmr_dataset_load`

`nmr_dataset_save`

Usage

```
nmr_dataset_load(file_name)
```

```
nmr_dataset_save(nmr_dataset, file_name, ...)
```

Arguments

<code>file_name</code>	The file name to load or save to
<code>nmr_dataset</code>	An object from the nmr_dataset_family
<code>...</code>	Additional arguments passed to saveRDS .

Value

Functions to load and save nmr_dataset objects

load nmr dataset

save nmr dataset

See Also

Other nmr_dataset functions: [.nmr_dataset(), format.nmr_dataset(), new_nmr_dataset(), nmr_interpolate_1D(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), nmr_ppm_resolution(), nmr_read_samples(), print.nmr_dataset(), validate_nmr_dataset()]

Other nmr_dataset_1D functions: [.nmr_dataset_1D(), computes_peak_width_ppm(), file_list(), files_to_rDolphin(), format.nmr_dataset_1D(), get_integration_with_metadata(), is.nmr_dataset_1D(), new_nmr_dataset_1D(), nmr_align_find_ref(), nmr_align(), nmr_baseline_removal(), nmr_baseline_threshold(), nmr_detect_peaks_plot(), nmr_detect_peaks_tune_snr(), nmr_detect_peaks(), nmr_exclude_region(), nmr_integrate_peak_positions(), nmr_integrate_regions(), nmr_interpolate_1D(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), nmr_normalize(), nmr_pca_build_model(), nmr_pca_outliers_filter(), nmr_pca_outliers_plot(), nmr_pca_outliers_robust(), nmr_pca_outliers(), nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(), rdCV_PLS_RF_ML(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()]

Other nmr_dataset_peak_table functions: [.nmr_dataset_peak_table(), format.nmr_dataset_peak_table(), is.nmr_dataset_peak_table(), new_nmr_dataset_peak_table(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), print.nmr_dataset_peak_table(), validate_nmr_dataset_peak_table()]

Other import/export functions: Pipelines, files_to_rDolphin(), nmr_data(), nmr_meta_export(), nmr_read_bruker_fid(), nmr_read_samples(), nmr_zip_bruker_samples(), save_files_to_rDolphin(), save_profiling_output(), to_ChemoSpec()

Examples

```
# dataset <- nmr_dataset_load("test")
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
# nmr_dataset_save(dataset, "test")
```

models_stability_plot_bootstrap

Models stability plot

Description

Plot stability among models of the external cross validation

Usage

```
models_stability_plot_bootstrap(bp_results)
```


Arguments

bp_results bp_kfold_VIP_analysis results

Value

A plot of models stability

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 64 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use bootstrap and permutation method for VIPs selection
## in a k-fold cross validation
#bp_results <- bp_kfold_VIP_analysis(peak_table, # Data to be analyzed
#                                y_column = "Condition", # Label
#                                k = 3,
#                                nbootstrap = 10)

#message("Selected VIPs are: ", bp_results$important_vips)

#models_stability_plot_bootstrap(bp_results)
```

```
models_stability_plot_plsda
      Models stability plot
```

Description

Plot stability among models of the external cross validation

Usage

```
models_stability_plot_plsda(model)
```

Arguments

```
model          A nmr_data_analysis_model
```

Value

A plot of models stability

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
```

```
    peak_table = peak_matrix,  
    metadata = list(external = metadata)  
  )  
  
  methodology <- plsda_auroc_vip_method(ncomp = 3)  
  model <- nmr_data_analysis(  
    peak_table,  
    y_column = "Condition",  
    identity_column = NULL,  
    external_val = list(iterations = 3, test_size = 0.25),  
    internal_val = list(iterations = 3, test_size = 0.25),  
    data_analysis_method = methodology  
  )  
  
  #models_stability_plot_plsda(model)
```

model_VIP

Deprecated function Model VIP values

Description

Once, the MVObj is created and validated, this function extracts autoselected ranked variables from the model (MUVR object). See rdCV_PLS_RF function.

Usage

```
model_VIP(MVObj)
```

Arguments

MVObj a MUVR model

Value

a data frame with the order, name and average rank of selected variables

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

MUVR_model_plot	<i>Deprecated function Model plot</i>
-----------------	---------------------------------------

Description

Plot the model (a MUVR object) obtained from rdCV_PLS_RF function. For more information about the multivariate modelling with minimally biased variable selection (MUVR) from the MUVR package, see Shi et al., 2018 (DOI: 10.1093/bioinformatics/bty710).

Usage

```
MUVR_model_plot(MVObj, model = "mid", factCols, sampLabels, ylim = NULL)
```

Arguments

MVObj	a MUVR model
model	What type of model to plot ('min', 'mid' or 'max'). Defaults to 'mid'.
factCols	An optional vector with colors for the factor levels (in the same order as the levels).
sampLabels	Sample labels (optional; implemented for classification)
ylim	Optional for imposing y-limits for regression and classification analysis

Value

A plot with the model performance

Examples

```
message("MUVR is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

new_nmr_dataset	<i>Create an nmr_dataset object</i>
-----------------	-------------------------------------

Description

Create an nmr_dataset object

Usage

```
new_nmr_dataset(metadata, data_fields, axis)
```

Arguments

metadata	A named list of data frames
data_fields	A named list. Check the examples
axis	A list. Check the examples

Value

Create an nmr_dataset object
 Create an nmr_dataset object

See Also

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`, `validate_nmr_dataset()`

Other nmr_dataset functions: `[.nmr_dataset()`, `format.nmr_dataset()`, `load_and_save_functions`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_ppm_resolution()`, `nmr_read_samples()`, `print.nmr_dataset()`, `validate_nmr_dataset()`

Examples

```
#
metadata_1D <- list(external = data.frame(NMRExperiment = c("10", "20")))
# Sample 10 and Sample 20 can have different lengths (due to different setups)
data_fields_1D <- list(data_1r = list(runif(16), runif(32)))
# Each sample has its own axis list, with one element (because this example is 1D)
axis_1D <- list(list(1:16), list(1:32))
my_1D_data <- new_nmr_dataset(metadata_1D, data_fields_1D, axis_1D)

# Example for 2D samples
metadata_2D <- list(external = data.frame(NMRExperiment = c("11", "21")))
data_fields_2D <- list(data_2rr = list(matrix(runif(16*3), nrow=16, ncol=3),
      runif(32*3), nrow=32, ncol=3))
# Each sample has its own axis list, with one element (because this example is 1D)
axis_2D <- list(list(1:16, 1:3), list(1:32, 1:3))
my_2D_data <- new_nmr_dataset(metadata_2D, data_fields_2D, axis_2D)
```

`new_nmr_dataset_1D` *Creates a new 1D nmr_dataset object from scratch*

Description

Creates a new 1D nmr_dataset object from scratch

`new_nmr_dataset_peak_table`*Creates a new nmr_dataset_peak_table object from scratch*

Description

Creates a new `nmr_dataset_peak_table` object from scratch

Usage

```
new_nmr_dataset_peak_table(peak_table, metadata)
```

Arguments

`peak_table` A numeric matrix with one NMR spectrum on each row
`metadata` A list of data frames with at least the `NMRExperiment` column

Value

Creates a new `nmr_dataset_peak_table` object from scratch

See Also

Other `nmr_dataset_peak_table` functions: [\[.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [load_and_save_functions](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset_peak_table](#)

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_1D\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset_family\(\)](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
new <- new_nmr_dataset_peak_table(peak_table, metadata)
```

nmr_align

*Align NMR spectra***Description**

This function is based on [speaq::dohCluster](#).

Usage

```
nmr_align(
  nmr_dataset,
  peak_data,
  NMRExp_ref = NULL,
  maxShift_ppm = 0.0015,
  acceptLostPeak = FALSE
)
```

Arguments

nmr_dataset	An nmr_dataset_1D
peak_data	The detected peak data given by nmr_detect_peaks .
NMRExp_ref	NMRExperiment of the reference to use for alignment
maxShift_ppm	The maximum shift allowed, in ppm
acceptLostPeak	This is an option for users, TRUE is the default value. If the users believe that all the peaks in the peak list are true positive, change it to FALSE.

Value

An [nmr_dataset_1D](#), with the spectra aligned

See Also

Other alignment functions: [Pipelines](#), [nmr_align_find_ref\(\)](#)

Other peak alignment functions: [nmr_align_find_ref\(\)](#)

Other [nmr_dataset_1D](#) functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_list\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

nmr_align_find_ref *Find alignment reference*

Description

Find alignment reference

Usage

```
nmr_align_find_ref(nmr_dataset, peak_data)
```

Arguments

nmr_dataset An [nmr_dataset_1D](#)
 peak_data The detected peak data given by [nmr_detect_peaks](#).

Value

The NMRExperiment of the reference sample

See Also

Other alignment functions: [Pipelines](#), [nmr_align\(\)](#)

Other peak alignment functions: [nmr_align\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

nmr_baseline_removal *Baseline Removal NMR*

Description

Removes the baseline on an [nmr_dataset_1D](#) object, using [baseline::baseline.als](#).

Usage

```
nmr_baseline_removal(nmr_dataset, lambda = 6, p = 0.05, maxit = 20)
```

Arguments

nmr_dataset	An nmr_dataset_1D .
lambda	2nd derivative constraint
p	Weighting of positive residuals
maxit	Maximum number of iterations

Value

The same [nmr_dataset_1D](#) object after baseline removal.

See Also

[baseline::baseline.als](#)

Other [nmr_dataset_1D](#) functions: [[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_threshold](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)]

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
dataset_no_base_line <- nmr_baseline_removal(dataset_1D, lambda = 6, p = 0.01)
```

nmr_baseline_threshold

Threshold estimation for peak detection

Description

Estimates the threshold value for peak detection on an [nmr_dataset_1D](#) object. This is performed computing the mean and the standard deviation of each spectrum beyond 9.5 ppm. The threshold is then averaged of means and adding 3 times the mean of the standard deviations

Usage

```
nmr_baseline_threshold(nmr_dataset, range_without_peaks = c(9.5, 10))
```

Arguments

nmr_dataset An [nmr_dataset_1D](#).
 range_without_peaks
 A vector with two doubles describing a range without peaks suitable for baseline detection

Value

Numerical. A threshold value in intensity below that no peak is detected.

See Also

Other peak detection functions: [Pipelines](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_ur](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)\]](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
bl_threshold <- nmr_baseline_threshold(dataset_1D)
```

nmr_batman

Batman helpers

Description

Batman helpers

Usage

```
nmr_batman_write_options(  
  bopts,  
  batman_dir = "BatmanInput",  
  filename = "batmanOptions.txt"  
)
```

```
nmr_batman_export_dataset(  
  nmr_dataset,  
  batman_dir = "BatmanInput",  
  filename = "NMRdata.txt"  
)  
  
nmr_batman_multi_data_user_hmdb(  
  batman_dir = "BatmanInput",  
  filename = "multi_data_user.csv"  
)  
  
nmr_batman_multi_data_user(  
  multiplet_table,  
  batman_dir = "BatmanInput",  
  filename = "multi_data_user.csv"  
)  
  
nmr_batman_metabolites_list(  
  metabolite_names,  
  batman_dir = "BatmanInput",  
  filename = "metabolitesList.csv"  
)
```

Arguments

bopts	Batman options
batman_dir	Batman input directorye
filename	Filename to use, inside batman_dir
nmr_dataset	An nmr_dataset_1D object
multiplet_table	A data frame, like the hmdb dataset
metabolite_names	A character vector of the metabolite names to consider

Value

These are helper functions to make Batman tests easier

See Also

Other batman functions: [nmr_batman_options\(\)](#)

Examples

```
bopts <- nmr_batman_options()  
# nmr_batman_write_options(bopts)
```

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
#nmr_batman_export_dataset(dataset_1D)

message("Use of multi_data_user_hmdb")
#multi_data_user_hmdb <- nmr_batman_multi_data_user_hmdb()
hmdb <- NULL
#utils::data("hmdb", package = "AlpsNMR", envir = environment())
#hmdb <- nmr_batman_multi_data_user(hmdb)

metabolite_names <- c("alanine", "glucose")
#metabolite_names <- nmr_batman_metabolites_list(metabolite_names)
```

nmr_batman_options *Batman Options helper*

Description

Batman Options helper

Usage

```
nmr_batman_options(
  ppmRange = matrix(c(3, 3.1, 3.6, 3.7, 3.9, 4, 4, 4.1, 6.95, 7.05, 7.6, 7.7, 7.8,
    7.9), ncol = 2, byrow = TRUE),
  specNo = "1",
  paraProc = 4L,
  negThresh = -0.5,
  scaleFac = 1e+06,
  downSamp = 1,
  hiresFlag = 1,
  randSeed = 100025L,
  nItBurnin = 200L,
  nItPostBurnin = 5000L,
  multFile = 2L,
  thinning = 50L,
  cfeFlag = 0,
  nItRerun = 5000L,
  startTemp = 1000,
  specFreq = 600,
  a = 1e-05,
  b = 1e-09,
  muMean = 1.1,
  muVar = 0.2,
  muVar_prop = 0.002,
  nuMVar = 0.0025,
```

```

    nuMVarProp = 0.1,
    tauMean = -0.05,
    tauPrec = 2,
    rdelta = 0.02,
    csFlag = 0
)

```

Arguments

ppmRange	Range of ppm to process
specNo	Index of spectra to process
paraProc	Number of cores to use
negThresh	Truncation threshold for negative intensities
scaleFac	Divide each spectrum by this number
downSamp	Decimate each spectrum by this factor
hiresFlag	Keep High Resolution deconvolved spectra
randSeed	A random seed
nItBurnin	Number of burn-in iterations
nItPostBurnin	Number of iterations after burn-in
multFile	Multiplet file (integer)
thinning	Save MCMC state every thinning iterations
cfeFlag	Same concentration for all spectra (fixed effect)
nItRerun	Number of iterations for a batman rerun
startTemp	Start temperature
specFreq	NMR Spectrometer frequency
a	Shape parameter for the gamma distribution (used for lambda, the precision)
b	Rate distribution parameter for the gamma distribution (used for lambda, the precision)
muMean	Peak width mean in ln(Hz)
muVar	Peak width variance in ln(Hz)
muVar_prop	Peak width proposed variance in ln(Hz)
nuMVar	Peak width metabolite variance in ln(Hz)
nuMVarProp	Peak width metabolite proposed variance in ln(Hz)
tauMean	mean of the prior on tau
tauPrec	inverse of variance of prior on tau
rdelta	Truncation of the prior on peak shift (ppm)
csFlag	Specify chemical shift for each multiplet in each spectrum? (chemShiftperSpectra.csv file)

Value

A batman_options object with the Batman Options

See Also

Other batman functions: [nmr_batman](#)

Examples

```
bopts <- nmr_batman_options()
```

nmr_data	<i>Set/Return the full spectra matrix</i>
----------	---

Description

Set/Return the full spectra matrix

Usage

```
nmr_data(nmr_dataset, ...)  
  
nmr_data(nmr_dataset) <- value  
  
## S3 replacement method for class 'nmr_dataset_1D'  
nmr_data(nmr_dataset) <- value
```

Arguments

nmr_dataset	An object from the nmr_dataset_family to get the raw data from
...	Unused and left for future compatibility
value	A matrix

Value

a matrix
The given nmr_dataset

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))  
dataset_data <- nmr_data(dataset_1D)
```

nmr_dataset	<i>nmr_dataset (S3 class)</i>
-------------	-------------------------------

Description

An `nmr_dataset` represents a set of NMR samples. It is defined as an S3 class, and it can be treated as a regular list.

Details

It currently has the following elements:

- `metadata`: A list of data frames. Each data frame contains metadata of a given area (acquisition parameters, preprocessing parameters, general sample information...)
- `axis`: A list with length equal to the dimensionality of the data. For 1D spectra it is a list with a numeric vector
- `data_*`: Data arrays with the actual spectra. The first index represents the sample, the rest of the indices match the length of each `axis`. Typically `data_1r` is a matrix with one sample on each row and the chemical shifts in the columns.
- `num_samples`: The number of samples in the dataset

See Also

[Functions to save and load these objects](#)

Other AlpsNMR dataset objects: [nmr_dataset_1D](#), [nmr_dataset_family](#)

nmr_dataset_1D	<i>nmr_dataset_1D (S3 class)</i>
----------------	----------------------------------

Description

An `nmr_dataset_1D` represents a set of 1D interpolated NMR samples. It is defined as an S3 class, and it can be treated as a regular list.

Details

It currently has the following elements:

- `metadata`: A list of data frames. Each data frame contains metadata of a given area (acquisition parameters, preprocessing parameters, general sample information...)
- `axis`: A numeric vector with the chemical shift axis in ppm.
- `data_1r`: A matrix with one sample on each row and the chemical shifts in the columns.

See Also

Other AlpsNMR dataset objects: [nmr_dataset_family](#), [nmr_dataset](#)

nmr_dataset_family *nmr_dataset like objects (S3 classes)*

Description

The AlpsNMR package defines and uses several objects to manage NMR Data.

Details

These objects share some structure and functions, so it makes sense to have an abstract class to ensure that the shared structures are compatible

See Also

[Functions to save and load these objects](#)

Other AlpsNMR dataset objects: [nmr_dataset_1D](#), [nmr_dataset](#)

nmr_dataset_peak_table
nmr_dataset_peak_table (S3 class)

Description

An `nmr_dataset_peak_table` represents a peak table with metadata. It is defined as an S3 class, and it can be treated as a regular list.

Details

- `metadata`: A list of data frames. Each data frame contains metadata. Usually the list only has one data frame named "external".
- `peak_table`: A matrix with one sample on each row and the peaks in the columns

nmr_dataset_peak_table_to_SummarizedExperiment
Export nmr_dataset_peak_table to SummarizedExperiment

Description

Export nmr_dataset_peak_table to SummarizedExperiment

Usage

```
nmr_dataset_peak_table_to_SummarizedExperiment(nmr_peak_table)
```

Arguments

nmr_peak_table An [nmr_dataset_peak_table](#) object

Value

SummarizedExperiment object (unmodified)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
nmr_peak_table <- new_nmr_dataset_peak_table(peak_table, metadata)
se <- nmr_dataset_peak_table_to_SummarizedExperiment(nmr_peak_table)
```

nmr_data_1r_to_SummarizedExperiment
Export 1D NMR data to SummarizedExperiment

Description

Export 1D NMR data to SummarizedExperiment

Usage

```
nmr_data_1r_to_SummarizedExperiment(nmr_dataset)
```

Arguments

nmr_dataset An [nmr_dataset_1D](#) object

Value

SummarizedExperiment An SummarizedExperiment object (unmodified)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
se <- nmr_data_1r_to_SummarizedExperiment(dataset_1D)
```

nmr_data_analysis *Data analysis*

Description

Data analysis on AlpsNMR can be performed on both [nmr_dataset_1D](#) full spectra as well as [nmr_dataset_peak_table](#) peak tables.

Usage

```
nmr_data_analysis(
  dataset,
  y_column,
  identity_column,
  external_val,
  internal_val,
  data_analysis_method
)
```

Arguments

dataset An [nmr_dataset_family](#) object

y_column A string with the name of the y column (present in the metadata of the dataset)

identity_column NULL or a string with the name of the identity column (present in the metadata of the dataset).

external_val, internal_val A list with two elements: iterations and test_size. See [random_subsampling](#) for further details

data_analysis_method An [nmr_data_analysis_method](#) object

Details

The workflow consists of a double cross validation strategy using random subsampling for splitting into train and test sets. The classification model and the metric to choose the best model can be customized (see `new_nmr_data_analysis_method()`), but for now only a PLSDA classification model with a best area under ROC curve metric is implemented (see the examples here and `plsda_auroc_vip_method`)

Value

A list with the following elements:

- `train_test_partitions`: A list with the indices used in train and test on each of the cross-validation iterations
- `inner_cv_results`: The output returned by `train_evaluate_model` on each inner cross-validation
- `inner_cv_results_digested`: The output returned by `choose_best_inner`.
- `outer_cv_results`: The output returned by `train_evaluate_model` on each outer cross-validation
- `outer_cv_results_digested`: The output returned by `train_evaluate_model_digest_outer`.

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
```

```

    peak_table = peak_matrix,
    metadata = list(external = metadata)
  )

  ## We will use a double cross validation, splitting the samples with random
  ## subsampling both in the external and internal validation.
  ## The classification model will be a PLSDA, exploring at maximum 3 latent
  ## variables.
  ## The best model will be selected based on the area under the ROC curve
  methodology <- plsda_auroc_vip_method(ncomp = 3)
  model <- nmr_data_analysis(
    peak_table,
    y_column = "Condition",
    identity_column = NULL,
    external_val = list(iterations = 3, test_size = 0.25),
    internal_val = list(iterations = 3, test_size = 0.25),
    data_analysis_method = methodology
  )
  ## Area under ROC for each outer cross-validation iteration:
  model$outer_cv_results_digested$auroc
  ## Rank Product of the Variable Importance in the Projection
  ## (Lower means more important)
  sort(model$outer_cv_results_digested$vip_rankproducts)

```

```
nmr_data_analysis_method
```

Create method for NMR data analysis

Description

Create method for NMR data analysis

Usage

```

new_nmr_data_analysis_method(
  train_evaluate_model,
  train_evaluate_model_params_inner,
  choose_best_inner,
  train_evaluate_model_params_outer,
  train_evaluate_model_digest_outer
)

```

Arguments

`train_evaluate_model`

A function. The `train_evaluate_model` must have the following signature:

```
function(x_train, y_train, identity_train, x_test, y_test, identity_test, ...)
```

The `x_train` and `y_train` (and their test counterparts) are self-explanatory.

The `identity_` arguments are expected to be factors. They can be used for instance with a callback that uses [mixOmics::plsda](#) in a multilevel approach for longitudinal studies. In those studies the identity would be an identifier of the subject.

The `...` arguments are free to be defined for each `train_evaluate_model`.

`train_evaluate_model_params_inner`, `train_evaluate_model_params_outer`

A list with additional arguments to pass to `train_evaluate_model` either in the inner cv loop or in the outer cv loop.

`choose_best_inner`

A function with a single argument:

```
function(inner_cv_results)
```

The argument is a list of `train_evaluate_model` outputs. The return value of must be a list with at least an element named `train_evaluate_model_args`. `train_evaluate_model_args` must be a named list.

- Each element must be named as one of the `train_evaluate_model` arguments.
- Each element must be a vector as long as the number of outer cross-validations.
- The values of each vector must be the values that the `train_evaluate_model` argument must take on each outer cross-validation iteration. Additional list elements can be returned and will be given back to the user.

`train_evaluate_model_digest_outer`

A function with a single argument:

```
function(outer_cv_results)
```

The argument is a list of `train_evaluate_model` outputs in outer cross-validation. The return value is returned by `nmr_data_analysis`

Value

An object encapsulating the method dependent functions that can be used with [nmr_data_analysis](#)

Examples

```
help(new_nmr_data_analysis_method)
```

nmr_detect_peaks

Peak detection for NMR

Description

The function detects peaks on an [nmr_dataset_1D](#) object, using [speaq::detectSpecPeaks](#). `detectSpecPeaks` divides the whole spectra into smaller segments and uses [MassSpecWavelet::peakDetectionCWT](#) for peak detection.

Usage

```
nmr_detect_peaks(
  nmr_dataset,
  nDivRange_ppm = 0.1,
  scales = seq(1, 16, 2),
  baselineThresh = NULL,
  SNR.Th = 3
)
```

Arguments

nmr_dataset	An nmr_dataset_1D .
nDivRange_ppm	Segment size, in ppms, to divide the spectra and search for peaks.
scales	The parameter of peakDetectionCWT function of MassSpecWavelet package, look it up in the original function.
baselineThresh	It will remove all peaks under an intensity set by baselineThresh. If you set it to 'NULL', nmr_detect_peaks will automatically compute an approximate value considering baseline between 9.5 and 10.0 ppm (automatically calculation using baselineThresh = NULL will not work if spectra were not interpolated up to 10.0 ppm)
SNR.Th	The parameter of peakDetectionCWT function of MassSpecWavelet package, look it up in the original function. If you set -1, the function will itself recompute this value.

Value

A data frame with the NMRExperiment, the sample index, the position in ppm and index and the peak intensity

See Also

[nmr_align](#) for peak alignment with the detected peak table

Peak_detection

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

nmr_detect_peaks_plot *Plot peak detection results*

Description

Plot peak detection results

Usage

```
nmr_detect_peaks_plot(nmr_dataset, peak_data, NMRExperiment, ...)
```

Arguments

nmr_dataset	An nmr_dataset_1D .
peak_data	The peak table returned by nmr_detect_peaks
NMRExperiment	a single NMR experiment to plot
...	Arguments passed to plot.nmr_dataset_1D (chemshift_range, ...)

Value

Plot peak detection results

See Also

Peak_detection [nmr_detect_peaks](#)

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_ur](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_ur](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other [nmr_dataset_1D](#) functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

nmr_detect_peaks_tune_snr

Diagnose SNR threshold in peak detection

Description

Diagnose SNR threshold in peak detection

Usage

```
nmr_detect_peaks_tune_snr(
  ds,
  NMRExperiment = NULL,
  SNR_thresholds = seq(from = 2, to = 6, by = 0.1),
  ...
)
```

Arguments

ds	An nmr_dataset_ID dataset
NMRExperiment	A string with the single NMRExperiment used explore the SNR thresholds. If not given, use the first one.
SNR_thresholds	A numeric vector with the SNR thresholds to explore
...	Arguments passed on to nmr_detect_peaks
nmr_dataset	An nmr_dataset_ID .
nDivRange_ppm	Segment size, in ppms, to divide the spectra and search for peaks.
baselineThresh	It will remove all peaks under an intensity set by baselineThresh. If you set it to 'NULL', nmr_detect_peaks will automatically compute an approximate value considering baseline between 9.5 and 10.0 ppm (automatically calculation using baselineThresh = NULL will not work if spectra were not interpolated up to 10.0 ppm)
scales	The parameter of peakDetectionCWT function of MassSpecWavelet package, look it up in the original function.
SNR.Th	The parameter of peakDetectionCWT function of MassSpecWavelet package, look it up in the original function. If you set -1, the function will itself re-compute this value.

Value

A list with the following elements:

- peaks_detected: A data frame with the columns from the [nmr_detect_peaks](#) output and an additional column SNR_threshold with the threshold used on each row.
- num_peaks_per_region: A summary of the peaks_detected table, with the number of peaks detected on each chemical shift region

- `plot_num_peaks_per_region`: A visual representation of `num_peaks_per_region`
- `plot_spectrum_and_detections`: A visual representation of the spectrum and the peaks detected with each SNR threshold. Use `plotly::ggplotly` or `plot_interactive` on this to zoom and explore the results.

See Also

`nmr_detect_peaks`

Other peak detection functions: `Pipelines`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks()`, `nmr_identify_regions_blood()`, `nmr_identify_regions_cell()`, `nmr_identify_regions_ur`, `nmr_integrate_regions()`, `regions_from_peak_table()`

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_listner()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

<code>nmr_exclude_region</code>	<i>Exclude region from samples</i>
---------------------------------	------------------------------------

Description

Excludes a given region (for instance to remove the water peak)

Usage

```
nmr_exclude_region(samples, exclude = list(water = c(4.7, 5)))
```

```
## S3 method for class 'nmr_dataset_1D'
nmr_exclude_region(samples, exclude = list(water = c(4.7, 5)))
```

Arguments

<code>samples</code>	An object
<code>exclude</code>	A list with regions to be removed Typically: <code>exclude = list(water = c(4.7, 5.0))</code>

Value

The same object, with the regions excluded

See Also

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Examples

```
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
exclude_regions <- list(water = c(5.1, 4.5))
nmr_dataset <- nmr_exclude_region(nmr_dataset, exclude = exclude_regions)

nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
exclude_regions <- list(water = c(5.1, 4.5))
nmr_dataset <- nmr_exclude_region(nmr_dataset, exclude = exclude_regions)
```

`nmr_export_data_1r` *Export 1D NMR data to a CSV file*

Description

Export 1D NMR data to a CSV file

Usage

```
nmr_export_data_1r(nmr_dataset, filename)
```

Arguments

<code>nmr_dataset</code>	An nmr_dataset_1D object
<code>filename</code>	The csv filename

Value

The `nmr_dataset` object (unmodified)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
#nmr_export_data_1r(dataset_1D, "exported_nmr_dataset")
```

`nmr_identify_regions_blood`*NMR peak identification (plasma/serum samples)*

Description

Identify given regions and return a data frame with plausible assignments in human plasma/serum samples.

Usage

```
nmr_identify_regions_blood(  
  ppm_to_assign,  
  num_proposed_compounds = 3,  
  verbose = FALSE  
)
```

Arguments

`ppm_to_assign` A vector with the ppm regions to assign

`num_proposed_compounds` set the number of proposed metabolites sorted by the number times reported in the HMDB: HMDB_blood.

`verbose` Logical value. Set it to TRUE to print additional information

Value

a data frame with plausible assignments.

See Also

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other peak integration functions: [Pipelines](#), [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#)

Examples

```
# We identify regions from from the corresponding ppm stored in a vector.  
ppm_to_assign <- c(4.060960203, 3.048970634, 2.405935596,  
3.24146865, 0.990616851, 1.002075066, 0.955325548)  
identification <- nmr_identify_regions_blood (ppm_to_assign)
```

`nmr_identify_regions_cell`*NMR peak identification (cell samples)*

Description

Identify given regions and return a data frame with plausible assignments in cell samples.

Usage

```
nmr_identify_regions_cell(  
  ppm_to_assign,  
  num_proposed_compounds = 3,  
  verbose = FALSE  
)
```

Arguments

`ppm_to_assign` A vector with the ppm regions to assign

`num_proposed_compounds`
set the number of proposed metabolites in HMDB_cell.

`verbose` Logical value. Set it to TRUE to print additional information

Value

a data frame with plausible assignments.

See Also

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other peak integration functions: [Pipelines](#), [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#)

Examples

```
# We identify regions from from the corresponding ppm stored in a vector.  
ppm_to_assign <- c(4.060960203, 3.048970634, 2.405935596,  
3.24146865, 0.990616851, 1.002075066, 0.955325548)  
identification <- nmr_identify_regions_cell (ppm_to_assign, num_proposed_compounds = 3)
```

`nmr_identify_regions_urine`*NMR peak identification (urine samples)*

Description

Identify given regions and return a data frame with plausible assignments in human urine samples. The data frame contains the column "Bouatra_2013" showing if the proposed metabolite was reported in this publication as regular urinary metabolite.

Usage

```
nmr_identify_regions_urine(  
  ppm_to_assign,  
  num_proposed_compounds = 5,  
  verbose = FALSE  
)
```

Arguments

`ppm_to_assign` A vector with the ppm regions to assign

`num_proposed_compounds` set the number of proposed metabolites sorted by the number times reported in the HMDB: HMDB_urine.

`verbose` Logical value. Set it to TRUE to print additional information

Value

a data frame with plausible assignments.

See Also

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other peak integration functions: [Pipelines](#), [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#)

Examples

```
# We identify regions from from the corresponding ppm stored in a vector.  
ppm_to_assign <- c(4.060960203, 3.048970634, 2.405935596,  
3.24146865, 0.990616851, 1.002075066, 0.955325548)  
identification <- nmr_identify_regions_urine (ppm_to_assign, num_proposed_compounds = 5)
```

```
nmr_integrate_peak_positions
      Integrate peak positions
```

Description

The function allows the integration of a given ppm vector with a specific width.

Usage

```
nmr_integrate_peak_positions(
  samples,
  peak_pos_ppm,
  peak_width_ppm = 0.006,
  ...
)
```

Arguments

<code>samples</code>	A nmr_dataset object
<code>peak_pos_ppm</code>	The peak positions, in ppm
<code>peak_width_ppm</code>	The peak widths (or a single peak width for all peaks)
<code>...</code>	Arguments passed on to nmr_integrate_regions
<code>regions</code>	A named list. Each element of the list is a region, given as a named numeric vector of length two with the range to integrate. The name of the region will be the name of the column

Value

Integrate peak positions

See Also

Other peak integration functions: [Pipelines](#), [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

nmr_integrate_regions *Integrate regions*

Description

Integrate given regions and return a data frame with them

Usage

```
nmr_integrate_regions(samples, regions, ...)
```

```
## S3 method for class 'nmr_dataset_1D'  
nmr_integrate_regions(  
  samples,  
  regions,  
  fix_baseline = TRUE,  
  excluded_regions_as_zero = FALSE,  
  set_negative_areas_to_zero = FALSE,  
  ...  
)
```

Arguments

<code>samples</code>	A nmr_dataset object
<code>regions</code>	A named list. Each element of the list is a region, given as a named numeric vector of length two with the range to integrate. The name of the region will be the name of the column
<code>...</code>	Keep for compatibility
<code>fix_baseline</code>	A logical. If TRUE it removes the baseline. See details below
<code>excluded_regions_as_zero</code>	A logical. It determines the behaviour of the integration when integrating regions that have been excluded. If TRUE, it will treat those regions as zero. If FALSE (the default) it will return NA values. If <code>fix_baseline</code> is TRUE, then the region boundaries are used to estimate a baseline. The baseline is estimated "connecting the boundaries with a straight line". Only when the spectrum is above the baseline the area is integrated (negative contributions due to the baseline estimation are ignored).
<code>set_negative_areas_to_zero</code>	A logical. Ignored if <code>fix_baseline</code> is FALSE. When set to TRUE negative areas are set to zero.

Value

An [nmr_dataset_peak_table](#) object

See Also

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [regions_from_peak_table\(\)](#)

Other peak integration functions: [Pipelines](#), [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_peak_positions\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)\]](#), [computes_peak_width_ppm\(\)](#), [file_listener\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
#Creating a dataset
dataset <- new_nmr_dataset_1D(ppm_axis = 1:10,
                             data_1r = matrix(sample(0:99,replace = TRUE), nrow = 10),
                             metadata = list(external = data.frame(NMRExperiment = c("10",
                                                                           "20", "30", "40", "50", "60", "70", "80", "90", "100"))))

# Integrating selected regions
peak_table_integration = nmr_integrate_regions(
  samples = dataset,
  regions = list(ppm = c(2,5)),
  fix_baseline = TRUE)

#Creating a dataset
dataset <- new_nmr_dataset_1D(ppm_axis = 1:10,
                             data_1r = matrix(sample(0:99,replace = TRUE), nrow = 10),
                             metadata = list(external = data.frame(NMRExperiment = c("10",
                                                                           "20", "30", "40", "50", "60", "70", "80", "90", "100"))))

# Integrating selected regions
peak_table_integration = nmr_integrate_regions(
  samples = dataset,
  regions = list(ppm = c(2,5)),
  fix_baseline = TRUE)
```

Description

Interpolate a set of 1D NMR Spectra

Usage

```
nmr_interpolate_1D(samples, axis = c(min = 0.2, max = 10, by = 8e-04))

## S3 method for class 'nmr_dataset'
nmr_interpolate_1D(samples, axis = c(min = 0.2, max = 10, by = 8e-04))
```

Arguments

<code>samples</code>	An NMR dataset
<code>axis</code>	The ppm axis range and optionally the ppm step

Value

Interpolate a set of 1D NMR Spectra

See Also

Other `nmr_dataset` functions: [\[.nmr_dataset\(\)\]](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)\]](#), [computes_peak_width_ppm\(\)](#), [file_listter\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
```

nmr_meta_add	<i>Add metadata to an nmr_dataset object</i>
--------------	--

Description

This is useful to add metadata to datasets that can be later used for plotting spectra or further analysis (PCA...).

Usage

```
nmr_meta_add(nmr_data, metadata, by = "NMRExperiment")
```

```
nmr_meta_add_tidy_excel(nmr_data, excel_file)
```

Arguments

nmr_data	an nmr_dataset_family object
metadata	A data frame with metadata to add
by	A column name of both the <code>nmr_data\$metadata\$external</code> and the <code>metadata</code> data.frame. If you want to merge two columns with different headers you can use a named character vector <code>c("NMRExperiment" = "ExperimentNMR")</code> where the left side is the column name of the <code>nmr_data\$metadata\$external</code> and the right side is the column name of the <code>metadata</code> data frame.
excel_file	Path to a tidy Excel file name. The Excel can consist of multiple sheets, that are added sequentially. The first column of the first sheet MUST be named as one of the metadata already present in the dataset, typically will be "NMRExperiment". The rest of the columns of the first sheet can be named at will. Similarly, the first column of the second sheet must be named as one of the metadata already present in the dataset, typically "NMRExperiment" or any of the columns of the first sheet. The rest of the columns of the second sheet can be named at will. See the package vignette for an example.

Value

The `nmr_dataset_family` object with the added metadata

See Also

Other metadata functions: [Pipelines](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#)

Other `nmr_dataset` functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#),

```
nmr_exclude_region(), nmr_integrate_peak_positions(), nmr_integrate_regions(), nmr_interpolate_1D(),
nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), nmr_normalize(), nmr_pca_build_model(),
nmr_pca_outliers_filter(), nmr_pca_outliers_plot(), nmr_pca_outliers_robust(), nmr_pca_outliers(),
nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(),
rdCV_PLS_RF_ML(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()
```

```
Other nmr_dataset_peak_table functions: [.nmr_dataset_peak_table(), format.nmr_dataset_peak_table(),
is.nmr_dataset_peak_table(), load_and_save_functions, new_nmr_dataset_peak_table(),
nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), print.nmr_dataset_peak_table(),
validate_nmr_dataset_peak_table()
```

Examples

```
# Load a demo dataset with four samples:
dataset <- system.file("dataset-demo", package = "AlpsNMR")
nmr_dataset <- nmr_read_samples_dir(dataset)

# At first we just have the NMRExperiment column
nmr_meta_get(nmr_dataset, groups = "external")
# Get a table with NMRExperiment -> SubjectID
dummy_metadata <- system.file("dataset-demo", "dummy_metadata.xlsx", package = "AlpsNMR")
NMRExp_SubjID <- readxl::read_excel(dummy_metadata, sheet = 1)

NMRExp_SubjID
# We can link the SubjectID column of the first excel into the dataset
nmr_dataset <- nmr_meta_add(nmr_dataset, NMRExp_SubjID, by = "NMRExperiment")
nmr_meta_get(nmr_dataset, groups = "external")
# The second excel can use the SubjectID:
SubjID_Age <- readxl::read_excel(dummy_metadata, sheet = 2)
SubjID_Age
# Add the metadata by its SubjectID:
nmr_dataset <- nmr_meta_add(nmr_dataset, SubjID_Age, by = "SubjectID")
# The final loaded metadata:
nmr_meta_get(nmr_dataset, groups = "external")

# Read a tidy excel file:

dataset <- system.file("dataset-demo", package = "AlpsNMR")
nmr_dataset <- nmr_read_samples_dir(dataset)

# At first we just have the NMRExperiment column
nmr_meta_get(nmr_dataset, groups = "external")
# Get a table with NMRExperiment -> SubjectID
dummy_metadata <- system.file("dataset-demo", "dummy_metadata.xlsx", package = "AlpsNMR")

nmr_dataset <- nmr_meta_add_tidy_excel(nmr_dataset, dummy_metadata)
# Updated Metadata:
nmr_meta_get(nmr_dataset, groups = "external")
```

nmr_meta_export	<i>Export Metadata to an Excel file</i>
-----------------	---

Description

Export Metadata to an Excel file

Usage

```
nmr_meta_export(
  nmr_dataset,
  xlsx_file,
  groups = c("info", "orig", "title", "external")
)
```

Arguments

nmr_dataset	An nmr_dataset_family object
xlsx_file	"The .xlsx excel file"
groups	A character vector. Use "external" for the external metadata or the default for a more generic solution

Value

The Excel file name

See Also

Other metadata functions: [Pipelines](#), [nmr_meta_add\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#)

Other nmr_dataset functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Other nmr_dataset_peak_table functions: [\[.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_peak_table\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset_peak_table\(\)](#)

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
#nmr_meta_export(dataset, "metadata.xlsx")
```

nmr_meta_get	<i>Get metadata</i>
--------------	---------------------

Description

Get metadata

Usage

```
nmr_meta_get(samples, columns = NULL, groups = NULL)
```

Arguments

samples	a nmr_dataset_family object
columns	Columns to get. By default gets all the columns.
groups	Groups to get. Groups are predefined of columns. Typically "external" for metadata added with nmr_meta_add . Both groups and columns can't be given simultaneously.

Value

a data frame with the injection metadata

See Also

Other metadata functions: [Pipelines](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#)

Other [nmr_dataset](#) functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other [nmr_dataset_1D](#) functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#),

nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(), rdCV_PLS_RF_ML(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()

Other nmr_dataset_peak_table functions: [.nmr_dataset_peak_table(), format.nmr_dataset_peak_table(), is.nmr_dataset_peak_table(), load_and_save_functions, new_nmr_dataset_peak_table(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get_column(), print.nmr_dataset_peak_table(), validate_nmr_dataset_peak_table()

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
metadata <- nmr_meta_get(dataset)
```

nmr_meta_get_column *Get a single metadata column*

Description

Get a single metadata column

Usage

```
nmr_meta_get_column(samples, column = "NMRExperiment")
```

Arguments

samples	a nmr_dataset_family object
column	A column to get

Value

A vector with the column

See Also

Other metadata functions: [Pipelines](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get\(\)](#)

Other nmr_dataset functions: [\[.nmr_dataset\(\)\]](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)\]](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#),

nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(), rdCV_PLS_RF_ML(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()

Other nmr_dataset_peak_table functions: [.nmr_dataset_peak_table(), format.nmr_dataset_peak_table(), is.nmr_dataset_peak_table(), load_and_save_functions, new_nmr_dataset_peak_table(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get(), print.nmr_dataset_peak_table(), validate_nmr_dataset_peak_table()

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
metadata_column <- nmr_meta_get_column(dataset)
```

nmr_normalize	<i>Normalize nmr_dataset_1D samples</i>
---------------	---

Description

The nmr_normalize function is used to normalize all the samples according to a given criteria.

Usage

```
nmr_normalize(
  samples,
  method = c("area", "max", "value", "region", "pqn", "none"),
  ...
)

nmr_normalize_extra_info(samples)
```

Arguments

samples	A nmr_dataset_1D object
method	The criteria to be used for normalization - area: Normalize to the total area - max: Normalize to the maximum intensity - value: Normalize each sample to a user defined value - region: Integrate a region and normalize each sample to that region - pqn: Use Probabalistic Quotient Normalization for normalization - none: Do not normalize at all
...	Method dependent arguments: - method == "value": - value: A numeric vector with the normalization values to use - method == "region": - ppm_range: A chemical shift region to integrate - ...: Other arguments passed on to nmr_integrate_regions

Details

The nmr_normalize_extra_info function is used to extract additional information after the normalization. Typically, we want to know what was the actual normalization factor applied to each sample. The extra information includes a plot, representing the dispersion of the normalization factor for each sample.

Value

The `nmr_dataset_1D` object, with the samples normalized. Further information for diagnostic of the normalization process is also saved and can be extracted by calling `nmr_normalize_extra_info()` afterwards.

See Also

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Examples

```
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_dataset <- nmr_normalize(nmr_dataset, method = "area")
norm_dataset <- nmr_normalize(nmr_dataset)
norm_dataset$plot
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_dataset <- nmr_normalize(nmr_dataset, method = "area")
norm_extra_info <- nmr_normalize_extra_info(nmr_dataset)
norm_extra_info$plot
```

`nmr_pca_build_model` *Build a PCA on for an nmr_dataset*

Description

This function builds a PCA model with all the NMR spectra. Regions with zero values (excluded regions) or near-zero variance regions are automatically excluded from the analysis.

Usage

```
nmr_pca_build_model(
  nmr_dataset,
  ncomp = NULL,
  center = TRUE,
  scale = FALSE,
  ...
)

## S3 method for class 'nmr_dataset_1D'
```

```
nmr_pca_build_model(
  nmr_dataset,
  ncomp = NULL,
  center = TRUE,
  scale = FALSE,
  ...
)
```

Arguments

<code>nmr_dataset</code>	a nmr_dataset_1D object
<code>ncomp</code>	Integer, if data is complete <code>ncomp</code> decides the number of components and associated eigenvalues to display from the <code>pcasvd</code> algorithm and if the data has missing values, <code>ncomp</code> gives the number of components to keep to perform the reconstitution of the data using the NIPALS algorithm. If <code>NULL</code> , function sets <code>ncomp = min(nrow(X), ncol(X))</code>
<code>center</code>	(Default= <code>TRUE</code>) Logical, whether the variables should be shifted to be zero centered. Only set to <code>FALSE</code> if data have already been centered. Alternatively, a vector of length equal the number of columns of <code>X</code> can be supplied. The value is passed to <code>scale</code> . If the data contain missing values, columns should be centered for reliable results.
<code>scale</code>	(Default= <code>FALSE</code>) Logical indicating whether the variables should be scaled to have unit variance before the analysis takes place. The default is <code>FALSE</code> for consistency with <code>prcomp</code> function, but in general scaling is advisable. Alternatively, a vector of length equal the number of columns of <code>X</code> can be supplied. The value is passed to <code>scale</code> .
<code>...</code>	Additional arguments passed on to mixOmics::pca

Value

A PCA model as given by [mixOmics::pca](#) with two additional attributes:

- `nmr_data_axis` containing the full ppm axis
- `nmr_included` with the data points included in the model These attributes are used internally by `AlpsNMR` to create loading plots

See Also

Other PCA related functions: [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_pca_plots](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
model <- nmr_pca_build_model(dataset_1D)
```

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
model <- nmr_pca_build_model(dataset_1D)
```

nmr_pca_outliers	<i>Compute PCA residuals and score distance for each sample</i>
------------------	---

Description

Compute PCA residuals and score distance for each sample

Usage

```
nmr_pca_outliers(  
  nmr_dataset,  
  pca_model,  
  ncomp = NULL,  
  quantile_critical = 0.975  
)
```

Arguments

nmr_dataset	An nmr_dataset_1D object
pca_model	A pca model returned by nmr_pca_build_model
ncomp	Number of components to use. Use NULL for 90% of the variance
quantile_critical	critical quantile

Value

A list with:

- outlier_info: A data frame with the NMRExperiment, the Q residuals and T scores
- ncomp: Number of components used to compute Q and T
- Tscore_critical, QResidual_critical: Critical values, given a quantile, for both Q and T.

See Also

Other PCA related functions: [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_plots](#)

Other outlier detection functions: [Pipelines](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#)

Other [nmr_dataset_1D](#) functions: [\[.nmr_dataset_1D\(\)\]](#), [computes_peak_width_ppm\(\)](#), [file_listener\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
model <- nmr_pca_build_model(dataset_1D)
outliers_info <- nmr_pca_outliers(dataset_1D, model)
```

`nmr_pca_outliers_filter`

Exclude outliers

Description

Exclude outliers

Usage

```
nmr_pca_outliers_filter(nmr_dataset, pca_outliers)
```

Arguments

`nmr_dataset` An [nmr_dataset_1D](#) object

`pca_outliers` The output from [nmr_pca_outliers\(\)](#)

Value

An [nmr_dataset_1D](#) without the detected outliers

See Also

Other PCA related functions: `nmr_pca_build_model()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_pca_plots`

Other outlier detection functions: `Pipelines`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Other subsetting functions: `[.nmr_dataset_1D()`, `[.nmr_dataset_peak_table()`, `[.nmr_dataset()`, `filter.nmr_dataset_family()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
model <- nmr_pca_build_model(dataset_1D)
outliers_info <- nmr_pca_outliers(dataset_1D, model)
dataset_whitout_outliers <- nmr_pca_outliers_filter(dataset_1D, outliers_info)
```

`nmr_pca_outliers_plot` *Plot for outlier detection diagnostic*

Description

Plot for outlier detection diagnostic

Usage

```
nmr_pca_outliers_plot(nmr_dataset, pca_outliers, ...)
```

Arguments

<code>nmr_dataset</code>	An <code>nmr_dataset_1D</code> object
<code>pca_outliers</code>	The output from <code>nmr_pca_outliers()</code>
<code>...</code>	Additional parameters passed on to <code>ggplot2::aes_string()</code>

Value

A plot for the outlier detection

See Also

Other PCA related functions: [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_pca_plots](#)

Other outlier detection functions: [Pipelines](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
#dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
#dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
#dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
#model <- nmr_pca_build_model(dataset_1D)
#outliers_info <- nmr_pca_outliers(dataset_1D, model)
#nmr_pca_outliers_plot(dataset_1D, outliers_info)
```

nmr_pca_outliers_robust

Outlier detection through robust PCA

Description

Outlier detection through robust PCA

Usage

```
nmr_pca_outliers_robust(nmr_dataset, ncomp = 5)
```

Arguments

nmr_dataset An nmr_dataset_1D object

ncomp Number of rPCA components to use

We have observed that the statistical test used as a threshold for outlier detection usually flags as outliers too many samples, due possibly to a lack of gaussianity. As a workaround, a heuristic method has been implemented: We know that in the Q residuals vs T scores plot from [nmr_pca_outliers_plot\(\)](#) outliers

are on the right or on the top of the plot, and quite separated from non-outlier samples.

To determine the critical value, both for Q and T, we find the biggest gap between samples in the plot and use as critical value the center of the gap.

This approach seems to work well when there are outliers, but it fails when there isn't any outlier. For that case, the gap would be placed anywhere and that is not desirable as many samples would be incorrectly flagged. The second assumption that we use is that no more than 10% the samples may pass our critical value. If more than 10% pass the critical value, then we assume that our heuristics are not reasonable and we don't set any critical limit.

Value

A list similar to [nmr_pca_outliers](#)

See Also

Other PCA related functions: [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_pca_plots](#)

Other outlier detection functions: [Pipelines](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_list\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
outliers_info <- nmr_pca_outliers_robust(dataset_1D)
```

nmr_pca_plots

Plotting functions for PCA

Description

Plotting functions for PCA

Usage

```
nmr_pca_plot_variance(pca_model)

nmr_pca_scoreplot(nmr_dataset, pca_model, comp = seq_len(2), ...)

nmr_pca_loadingplot(pca_model, comp)
```

Arguments

<code>pca_model</code>	A PCA model trained with nmr_pca_build_model
<code>nmr_dataset</code>	an nmr_dataset_1D object
<code>comp</code>	Components to represent
<code>...</code>	Additional aesthetics passed on to ggplot2::aes (use bare unquoted names)

Value

Plot of PCA

See Also

Other PCA related functions: [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
model <- nmr_pca_build_model(dataset_1D)
nmr_pca_plot_variance(model)
nmr_pca_scoreplot(dataset_1D, model)
nmr_pca_loadingplot(model, 1)
```

<code>nmr_ppm_resolution</code>	<i>PPM resolution of the spectra</i>
---------------------------------	--------------------------------------

Description

The function gets the ppm resolution of the dataset using the median of the difference of data points.

Usage

```
nmr_ppm_resolution(nmr_dataset)

## S3 method for class 'nmr_dataset'
nmr_ppm_resolution(nmr_dataset)

## S3 method for class 'nmr_dataset_1D'
nmr_ppm_resolution(nmr_dataset)
```

Arguments

`nmr_dataset` An object containing NMR samples

Value

Numeric (the ppm resolution, measured in ppms)

See Also

Other `nmr_dataset` functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_read_samples\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listter\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_ppm_resolution(nmr_dataset)
message("the ppm resolution of this dataset is ", nmr_ppm_resolution(nmr_dataset), " ppm")

nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_ppm_resolution(nmr_dataset)
message("the ppm resolution of this dataset is ", nmr_ppm_resolution(nmr_dataset), " ppm")

nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_ppm_resolution(nmr_dataset)
message("the ppm resolution of this dataset is ", nmr_ppm_resolution(nmr_dataset), " ppm")
```

nmr_read Bruker FID *Read Free Induction Decay file*

Description

Reads an FID file. This is a very simple function.

Usage

```
nmr_read Bruker FID(sample_name, endian = "little")
```

Arguments

sample_name	A single sample name
endian	Endianness of the fid file ("little" by default, use "big" if <code>acqus\$BYTORDA == 1</code>)

Value

A numeric vector with the free induction decay values

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip Bruker samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Examples

```
fid <- nmr_read Bruker FID("sample.fid")
```

nmr_read_samples *Read NMR samples*

Description

These functions load samples from files and return a [nmr_dataset](#).

Usage

```

nmr_read_samples_dir(
  samples_dir,
  format = "bruker",
  pulse_sequence = NULL,
  metadata_only = FALSE,
  ...
)

nmr_read_samples(
  sample_names,
  format = "bruker",
  pulse_sequence = NULL,
  metadata_only = FALSE,
  ...
)

```

Arguments

<code>samples_dir</code>	A directory that contains multiple samples
<code>format</code>	Either "bruker" or "jdx"
<code>pulse_sequence</code>	If it is set to a pulse sequence ("NOESY", "JRES", "CPMG"...) it will only load the samples that match that pulse sequence.
<code>metadata_only</code>	A logical, to load only metadata (default: FALSE)
<code>...</code>	Arguments passed to read_bruker_sample() for data loading
<code>sample_names</code>	A character vector with file or directory names.

Value

a [nmr_dataset](#) object

See Also

Other `nmr_dataset` functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset\(\)](#)

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Examples

```

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
zip_files <- fs::dir_ls(dir_to_demo_dataset, glob = "*.zip")

```

```
dataset <- nmr_read_samples(sample_names = zip_files)
```

```
nmr_zip_bruker_samples
```

Create one zip file for each brucker sample path

Description

Create one zip file for each brucker sample path

Usage

```
nmr_zip_bruker_samples(path, workdir, overwrite = FALSE, ...)
```

Arguments

path	Character vector with sample directories
workdir	Directory to store zip files
overwrite	Should existing zip files be overwritten?
...	Passed to utils::zip

Value

A character vector of the same length as path, with the zip file names

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Examples

```
outpaths <- nmr_zip_bruker_samples(".", getwd())
```

Parameters_blood *to rDolphin*

Description

Parameters for blood (plasma/serum) samples profiling

Details

The template Parameters_blood contains the chosen normalization approach (by default, PQN), the Spectrometer Frequency (by default, 600.04MHz), alignment (by default, TSP 0.00 ppm), bucket resolution (by default, 0.00023)

References

github.com/danielcanueto/rDolphin

Parameters_cell *Parameters for cell samples profiling*

Description

The template Parameters_cell contains the chosen normalization approach (by default, PQN), the Spectrometer Frequency (by default, 600.04MHz), alignment (by default, TSP 0.00 ppm), bucket resolution (by default, 0.00023)

References

github.com/danielcanueto/rDolphin

Parameters_urine *Parameters for urine samples profiling*

Description

The template Parameters_urine contains the chosen normalization approach (by default, PQN), the Spectrometer Frequency (by default, 600.04MHz), alignment (by default, TSP 0.00 ppm), bucket resolution (by default, 0.00023)

References

github.com/danielcanueto/rDolphin

Peak_detection	<i>Peak detection for NMR</i>
----------------	-------------------------------

Description

Peak detection for NMR

Examples

```

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
nmr_dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(nmr_dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))

sample_10 <- filter(dataset_1D, NMRExperiment == "10")

# 1. Peak detection in the dataset.
peak_data <- nmr_detect_peaks(dataset_1D,
                             nDivRange_ppm = 0.1, # Size of detection segments
                             scales = seq(1, 16, 2),
                             baselineThresh = 0, # Minimum peak intensity
                             SNR.Th = 4) # Signal to noise ratio

#nmr_detect_peaks_plot(sample_10, peak_data, "NMRExp_ref")

peaks_detected <- nmr_detect_peaks_tune_snr(
  sample_10,
  SNR_thresholds = seq(from = 2, to = 3, by = 0.5),
  nDivRange_ppm = 0.03,
  scales = seq(1, 16, 2),
  baselineThresh = 0
)

# 2. Find the reference spectrum to align with.
NMRExp_ref <- nmr_align_find_ref(dataset_1D, peak_data)

# 3. Spectra alignment using the ref spectrum and a maximum alignment shift
nmr_dataset <- nmr_align(dataset_1D, # the dataset
                        peak_data, # detected peaks
                        NMRExp_ref = NMRExp_ref, # ref spectrum
                        maxShift_ppm = 0.0015, # max alignment shift
                        acceptLostPeak = FALSE) # lost peaks

# 4. PEAK INTEGRATION (please, consider previous normalization step).
# First we take the peak table from the reference spectrum
peak_data_ref <- filter(peak_data, NMRExperiment == NMRExp_ref)

# Then we integrate spectra considering the peaks from the ref spectrum
nmr_peak_table <- nmr_integrate_peak_positions(
  samples = nmr_dataset,

```

```

peak_pos_ppm = peak_data_ref$ppm,
peak_width_ppm = NULL)

validate_nmr_dataset_peak_table(nmr_peak_table)

#If you wanted the final peak table before machine learning you can run
nmr_peak_table_completed <- get_integration_with_metadata(nmr_peak_table)

```

permutation_test_model

Permutation test

Description

Make permutations with data and default settings from an `nmr_data_analysis_method`

Usage

```

permutation_test_model(
  dataset,
  y_column,
  identity_column,
  external_val,
  internal_val,
  data_analysis_method,
  nPerm = 50
)

```

Arguments

<code>dataset</code>	An nmr_dataset_family object
<code>y_column</code>	A string with the name of the y column (present in the metadata of the dataset)
<code>identity_column</code>	NULL or a string with the name of the identity column (present in the metadata of the dataset).
<code>external_val</code>	A list with two elements: <code>iterations</code> and <code>test_size</code> . See random_subsampling for further details
<code>internal_val</code>	A list with two elements: <code>iterations</code> and <code>test_size</code> . See random_subsampling for further details
<code>data_analysis_method</code>	An nmr_data_analysis_method object
<code>nPerm</code>	number of permutations

Value

A permutation matrix with permuted values

Examples

```

# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

methodology <- plsda_auroc_vip_method(ncomp = 3)
model <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 3, test_size = 0.25),
  internal_val = list(iterations = 3, test_size = 0.25),
  data_analysis_method = methodology
)

p = permutation_test_model(peak_table,
                           y_column = "Condition",
                           identity_column = NULL,
                           external_val = list(iterations = 3, test_size = 0.25),
                           internal_val = list(iterations = 3, test_size = 0.25),
                           data_analysis_method = methodology,
                           nPerm = 10)

```

permutation_test_plot *Permutation test plot*

Description

Plot permutation test using actual model and permuted models

Usage

```
permutation_test_plot(  
  nmr_data_analysis_model,  
  permMatrix,  
  xlab = "AUCs",  
  xlim,  
  ylim = NULL,  
  breaks = "Sturges",  
  main = "Permutation test"  
)
```

Arguments

nmr_data_analysis_model	A nmr_data_analysis_model
permMatrix	A permutation fitness outcome from permutation_test_model
xlab	optional xlabel
xlim	optional x-range
ylim	optional y-range
breaks	optional custom histogram breaks (defaults to 'sturges')
main	optional plot title (or TRUE for autname)

Value

A plot with the comparison between the actual model versus the permuted models

Examples

```
# Data analysis for a table of integrated peaks  
  
## Generate an artificial nmr_dataset_peak_table:  
### Generate artificial metadata:  
num_samples <- 32 # use an even number in this example  
num_peaks <- 20  
metadata <- data.frame(  
  NMRExperiment = as.character(1:num_samples),  
  Condition = rep(c("A", "B"), times = num_samples/2),  
  stringsAsFactors = FALSE
```

```

)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)

colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

methodology <- plsda_auc_vip_method(ncomp = 3)
model <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 3, test_size = 0.25),
  internal_val = list(iterations = 3, test_size = 0.25),
  data_analysis_method = methodology
)

p = permutation_test_model(peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 3, test_size = 0.25),
  internal_val = list(iterations = 3, test_size = 0.25),
  data_analysis_method = methodology,
  nPerm = 10)

permutation_test_plot(model, p)

```

Pipelines

Pipelines

Description

Uses [nmr_pca_outliers_robust](#) to perform the detection of outliers

Normalize the full spectra to the internal calibrant region, then exclude that region and finally perform PQN normalization.

Usage

```

pipe_load_samples(samples_dir, glob = "*0", output_dir = NULL)

pipe_add_metadata(nmr_dataset_rds, excel_file, output_dir)

pipe_interpolate_1D(nmr_dataset_rds, axis, output_dir)

pipe_exclude_regions(nmr_dataset_rds, exclude, output_dir)

pipe_outlier_detection(nmr_dataset_rds, output_dir)

pipe_filter_samples(nmr_dataset_rds, conditions, output_dir)

pipe_peakdet_align(
  nmr_dataset_rds,
  nDivRange_ppm = 0.1,
  scales = seq(1, 16, 2),
  baselineThresh = 0.01,
  SNR.Th = -1,
  maxShift_ppm = 0.0015,
  acceptLostPeak = FALSE,
  output_dir = NULL
)

pipe_peak_integration(
  nmr_dataset_rds,
  peak_det_align_dir,
  peak_width_ppm,
  output_dir
)

pipe_normalization(
  nmr_dataset_rds,
  internal_calibrant = NULL,
  output_dir = NULL
)

```

Arguments

<code>samples_dir</code>	The directory where the samples are
<code>glob</code>	A wildcard aka globbing pattern (e.g. *.csv) passed on to <code>grep()</code> to filter paths.
<code>output_dir</code>	The output directory for this pipe element
<code>nmr_dataset_rds</code>	The <code>nmr_dataset.rds</code> file name coming from previous nodes
<code>excel_file</code>	An excel file name. See details for the requirements The excel file can have one or more sheets. The excel sheets need to be as simple as possible: One header column on the first row and values below.

Each of the sheets contain metadata that has to be integrated. The merge (technically a left join) is done using the first column of each sheet as key.

In practical terms this means that the first sheet of the excel file MUST start with an "NMRExperiment" column, and as many additional columns to add (e.g. FluidXBarcode, SampleCollectionDate, TimePoint and SubjectID).

The second sheet can have as the first column any of the already added columns, for instance the "SubjectID", and any additional columns (e.g. Gender, Age).

The first column on each sheet, named the key column, MUST have unique values. For instance, a sheet starting with "SubjectID" MUST specify each subject ID only once (without repetitions).

axis	The ppm axis range and optionally the ppm step
exclude	A list with regions to be removed Typically: <code>exclude = list(water = c(4.7, 5.0))</code>
conditions	A character vector with conditions to filter metadata. The conditions parameter should be a character vector of valid R logical conditions. Some examples: <ul style="list-style-type: none"> • <code>conditions <- 'Gender == "Female"'</code> • <code>conditions <- 'Cohort == "Chuv"'</code> • <code>conditions <- 'TimePoint %in% c("T0", "T31")'</code> • <code>conditions <- c(Cohort == "Chuv", 'TimePoint %in% c("T0", "T31")')</code> Only samples fulfilling all the given conditions are kept in further analysis.
nDivRange_ppm	Segment size, in ppms, to divide the spectra and search for peaks.
scales	The parameter of <code>peakDetectionCWT</code> function of <code>MassSpecWavelet</code> package, look it up in the original function.
baselineThresh	It will remove all peaks under an intensity set by <code>baselineThresh</code> . If you set it to 'NULL', <code>nmr_detect_peaks</code> will automatically compute an approximate value considering baseline between 9.5 and 10.0 ppm (automatically calculation using <code>baselineThresh = NULL</code> will not work if spectra were not interpolated up to 10.0 ppm)
SNR.Th	The parameter of <code>peakDetectionCWT</code> function of <code>MassSpecWavelet</code> package, look it up in the original function. If you set -1, the function will itself recompute this value.
maxShift_ppm	The maximum shift allowed, in ppm
acceptLostPeak	This is an option for users, TRUE is the default value. If the users believe that all the peaks in the peak list are true positive, change it to FALSE.
peak_det_align_dir	Output directory from pipe_peakdet_align
peak_width_ppm	A peak width in ppm
internal_calibrant	A ppm range where the internal calibrant is, or NULL.

Details

If there is no internal calibrant, only the PQN normalization is done.

Value

This function saves the result to the output directory

This function saves the result to the output directory

This function saves the result to the output directory

This function saves the result to the output directory

This function saves the result to the output directory

Pipeline: Filter samples according to metadata conditions

Pipeline: Peak detection and Alignment

Pipeline: Peak integration

Pipe: Full spectra normalization

See Also

Other import/export functions: [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Other metadata functions: [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#)

Other outlier detection functions: [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#)

Other peak detection functions: [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#), [regions_from_peak_table\(\)](#)

Other alignment functions: [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#)

Other peak integration functions: [computes_peak_width_ppm\(\)](#), [get_integration_with_metadata\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_cell\(\)](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#)

Examples

```
## Example of pipeline usage
## There are differet ways of load the dataset
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
#excel_file <- system.file("dataset-demo",
#                           "dummy_metadata.xlsx",
#                           package = "AlpsNMR")
#output_dir <- tempdir()

## Load samples with pipes
#pipe_load_samples(dir_to_demo_dataset,
#                  glob = "*.zip",
#                  output_dir = "../pipe_output")

## Another way to load it
#nmr_dataset <- nmr_read_samples_dir(dir_to_demo_dataset)

## Saving the dataset in a .rds file
```

```
#nmr_dataset_rds <- tempfile(fileext = ".rds")
#nmr_dataset_save(nmr_dataset, nmr_dataset_rds)

## Interpolation
#pipe_interpolate_1D(nmr_dataset_rds,
#                    # axis = c(min = -0.5, max = 10, by = 2.3E-4),
#                    # output_dir)

## Get the new path, based in output_dir
#nmr_dataset_rds <- paste(output_dir, "\\", "nmr_dataset.rds", sep = "", collapse = NULL)

## Adding metadata to samples
#pipe_add_metadata(nmr_dataset_rds = nmr_dataset_rds, output_dir = output_dir,
#                 # excel_file = excel_file)

## Filtering samples
#conditions <- 'SubjectID == "Ana"'
#pipe_filter_samples(nmr_dataset_rds, conditions, output_dir)

## Outlier detection
#pipe_outlier_detection(nmr_dataset_rds, output_dir)

## Exclude regions
#exclude_regions <- list(water = c(5.1, 4.5))
#pipe_exclude_regions(nmr_dataset_rds, exclude_regions, output_dir)

## peak aling
#pipe_peakdet_align(nmr_dataset_rds, output_dir = output_dir)

## peak integration
#pipe_peak_integration(nmr_dataset_rds,
#                     # peak_det_align_dir = output_dir,
#                     # peak_width_ppm = 0.006, output_dir)

## Normalization
#pipe_normalization(nmr_dataset_rds, output_dir = output_dir)
```

plot.nmr_dataset_1D *Plot an nmr_dataset_1D*

Description

Plot an nmr_dataset_1D

Usage

```
## S3 method for class 'nmr_dataset_1D'
plot(
  x,
```

```

  NMRExperiment = NULL,
  chemshift_range = NULL,
  interactive = FALSE,
  quantile_plot = NULL,
  quantile_colors = NULL,
  ...
)

```

Arguments

x a [nmr_dataset_1D](#) object

NMRExperiment A character vector with the NMRExperiments to include. Use "all" to include all experiments.

chemshift_range range of the chemical shifts to be included. Can be of length 3 to include the resolution in the third element (e.g. `c(0.2, 0.8, 0.005)`)

interactive if TRUE return an interactive plotly plot, otherwise return a ggplot one.

quantile_plot If TRUE plot the 10\ If two numbers between 0 and 1 are given then a custom percentile can be plotted

quantile_colors A vector with the colors for each of the quantiles

... arguments passed to [ggplot2::aes_string](#).

Value

The plot

See Also

Other plotting functions: [plot_interactive\(\)](#)

Other `nmr_dataset_1D` functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
#dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
#dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
#plot(dataset_1D)

```

`plot_bootstrap_multimodel`*Bootstrap plot predictions*

Description

Bootstrap plot predictions

Usage

```
plot_bootstrap_multimodel(bp_results, dataset, y_column, plot = TRUE)
```

Arguments

<code>bp_results</code>	bp_kfold_VIP_analysis results
<code>dataset</code>	An nmr_dataset_family object
<code>y_column</code>	A string with the name of the y column (present in the metadata of the dataset)
<code>plot</code>	A boolean that indicate if results are plotted or not

Value

A plot of the results or a ggplot object

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 64 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70
```



```
peak_matrix[metadata$Condition == "A", "Peak6"] <-  
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60  
  
### The nmr_dataset_peak_table  
peak_table <- new_nmr_dataset_peak_table(  
  peak_table = peak_matrix,  
  metadata = list(external = metadata)  
)  
  
## We will use bootstrap and permutation method for VIPs selection  
## in a a k-fold cross validation  
#bp_results <- bp_kfold_VIP_analysis(peak_table, # Data to be analyzed  
#                                     y_column = "Condition", # Label  
#                                     k = 3,  
#                                     nbootstrap = 10)  
  
#message("Selected VIPs are: ", bp_results$important_vips)  
  
#plot_bootstrap_multimodel(bp_results, peak_table, "Condition")
```

plot_interactive

Plots in WebGL

Description

Plots in WebGL

Usage

```
plot_interactive(plt, html_filename, overwrite = NULL)
```

Arguments

plt	A plot created with plotly or ggplot2
html_filename	The file name where the plot will be saved
overwrite	Overwrite the lib/ directory (use NULL to prompt the user)

Value

The html_filename

See Also

Other plotting functions: [plot.nmr_dataset_1D\(\)](#)

Examples

```

dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
# plot <- plot(dataset_1D)
# html_plot_interactive <- plot_interactive(plot, "html_plot_interactive.html")

```

plot_plsda_multimodel *Multi PLDSA model plot predictions*

Description

Multi PLDSA model plot predictions

Usage

```
plot_plsda_multimodel(model, plot = TRUE)
```

Arguments

model	A nmr_data_analysis_model
plot	A boolean that indicate if results are plotted or not

Value

A plot of the results or a ggplot object

Examples

```

#' # Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

```

```
## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use a double cross validation, splitting the samples with random
## subsampling both in the external and internal validation.
## The classification model will be a PLSDA, exploring at maximum 3 latent
## variables.
## The best model will be selected based on the area under the ROC curve
methodology <- plsda_auroc_vip_method(ncomp = 1)
model <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 2, test_size = 0.25),
  internal_val = list(iterations = 2, test_size = 0.25),
  data_analysis_method = methodology
)

#plot_plsda_multimodel(model)
```

plot_plsda_samples *Plot PLSDA predictions*

Description

Plot PLSDA predictions

Usage

```
plot_plsda_samples(model, newdata = NULL, plot = TRUE)
```

Arguments

model	A plsda model
newdata	newdata to predict, if not included model\$X_test will be used
plot	A boolean that indicate if results are plotted or not

Value

A plot of the samples or a ggplot object

Examples

```
#' # Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use a double cross validation, splitting the samples with random
## subsampling both in the external and internal validation.
## The classification model will be a PLSDA, exploring at maximum 3 latent
## variables.
## The best model will be selected based on the area under the ROC curve
methodology <- plsda_auroc_vip_method(ncomp = 1)
model <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 1, test_size = 0.25),
  internal_val = list(iterations = 1, test_size = 0.25),
  data_analysis_method = methodology
)
```

```
#plot_plsda_samples(model$outer_cv_results[[1]]$model)
```

```
plot_vip_scores      Plot vip scores of bootstrap
```

Description

Plot vip scores of bootstrap

Usage

```
plot_vip_scores(vip_means, error, nbootstrap, plot = TRUE)
```

Arguments

vip_means	vips means values of bootstraps
error	error tolerated, calculated in the bootstrap
nbootstrap	number of bootstraps realized
plot	A boolean that indicate if results are plotted or not

Value

A plot of the results or a ggplot object

Examples

```
# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 64 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70
```

```

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use bootstrap and permutation method for VIPs selection
## in a k-fold cross validation
#bp_results <- bp_kfold_VIP_analysis(peak_table, # Data to be analyzed
#                                y_column = "Condition", # Label
#                                k = 3,
#                                nbootstrap = 10)

#message("Selected VIPs are: ", bp_results$important_vips)

#plot_vip_scores(bp_results$fold_results[[1]]$vip_means,
#               bp_results$fold_results[[1]]$error[1],
#               nbootstrap = 10)

```

plot_webgl

Plot a dataset into a HTML file

Description

Uses WebGL for performance

Usage

```
plot_webgl(nmr_dataset, html_filename, ...)
```

Arguments

nmr_dataset	An nmr_dataset_1D
html_filename	The output HTML filename to be created
...	Arguments passed on to plot.nmr_dataset_1D
	x a nmr_dataset_1D object
	chemshift_range range of the chemical shifts to be included. Can be of length 3 to include the resolution in the third element (e.g. c(0.2, 0.8, 0.005))
	NMRExperiment A character vector with the NMRExperiments to include. Use "all" to include all experiments.
	quantile_plot If TRUE plot the 10\ If two numbers between 0 and 1 are given then a custom percentile can be plotted

quantile_colors A vector with the colors for each of the quantiles
 interactive if TRUE return an interactive plotly plot, otherwise return a ggplot
 one.

Value

the html filename created

See Also

Other `nmr_dataset_1D` functions: [`.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`]

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
#dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
#dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
#html_plot <- plot_webgl(dataset_1D, "html_plot.html")
```

plsda_auroc_vip_compare

Compare PLSDA auroc VIP results

Description

Compare PLSDA auroc VIP results

Usage

```
plsda_auroc_vip_compare(...)
```

Arguments

... Results of `nmr_data_analysis` to be combined. Give each result a name.

Value

A plot of the AUC for each method

Examples

```

# Data analysis for a table of integrated peaks

## Generate an artificial nmr_dataset_peak_table:
### Generate artificial metadata:
num_samples <- 32 # use an even number in this example
num_peaks <- 20
metadata <- data.frame(
  NMRExperiment = as.character(1:num_samples),
  Condition = rep(c("A", "B"), times = num_samples/2),
  stringsAsFactors = FALSE
)

### The matrix with peaks
peak_means <- runif(n = num_peaks, min = 300, max = 600)
peak_sd <- runif(n = num_peaks, min = 30, max = 60)
peak_matrix <- mapply(function(mu, sd) rnorm(num_samples, mu, sd),
                      mu = peak_means, sd = peak_sd)
colnames(peak_matrix) <- paste0("Peak", 1:num_peaks)

## Artificial differences depending on the condition:
peak_matrix[metadata$Condition == "A", "Peak2"] <-
  peak_matrix[metadata$Condition == "A", "Peak2"] + 70

peak_matrix[metadata$Condition == "A", "Peak6"] <-
  peak_matrix[metadata$Condition == "A", "Peak6"] - 60

### The nmr_dataset_peak_table
peak_table <- new_nmr_dataset_peak_table(
  peak_table = peak_matrix,
  metadata = list(external = metadata)
)

## We will use a double cross validation, splitting the samples with random
## subsampling both in the external and internal validation.
## The classification model will be a PLSDA, exploring at maximum 3 latent
## variables.
## The best model will be selected based on the area under the ROC curve
methodology <- plsda_auroc_vip_method(ncomp = 1)
model1 <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",
  identity_column = NULL,
  external_val = list(iterations = 1, test_size = 0.25),
  internal_val = list(iterations = 1, test_size = 0.25),
  data_analysis_method = methodology
)

methodology2 <- plsda_auroc_vip_method(ncomp = 2)
model2 <- nmr_data_analysis(
  peak_table,
  y_column = "Condition",

```



```
identity_column = NULL,  
external_val = list(iterations = 1, test_size = 0.25),  
internal_val = list(iterations = 1, test_size = 0.25),  
data_analysis_method = methodology2  
)  
  
plsda_auroc_vip_compare(model1 = model1, model2 = model2)
```

plsda_auroc_vip_method

Method for nmr_data_analysis (PLSDA model with AUROC and VIP outputs)

Description

Method for nmr_data_analysis (PLSDA model with AUROC and VIP outputs)

Usage

```
plsda_auroc_vip_method(ncomp, auc_increment_threshold = 0.05)
```

Arguments

ncomp Max. number of latent variables to explore in the PLSDA analysis

auc_increment_threshold
Choose the number of latent variables when the AUC does not increment more than this threshold.

Value

Returns an object to be used with [nmr_data_analysis](#) to perform a (optionally multilevel) PLS-DA model, using the area under the ROC curve as figure of merit to determine the optimum number of latent variables.

Examples

```
method <- plsda_auroc_vip_method(3)
```

ppm_resolution *Unlisted PPM resolution*

Description

A wrapper to unlist the output from the function `nmr_ppm_resolution(nmr_dataset)` when no interpolation has been applied.

Usage

```
ppm_resolution(nmr_dataset)
```

Arguments

`nmr_dataset` An object containing NMR samples

Value

A number (the ppm resolution, measured in ppms)

Numeric (the ppm resolution, measured in ppms)

Examples

```
nmr_dataset <- nmr_dataset_load(system.file("extdata", "nmr_dataset.rds", package = "AlpsNMR"))
nmr_ppm_resolution(nmr_dataset)
```

ppm_VIP_vector *Feature selection and validation in multivariate analysis*

Description

Numeric VIPs vector

Usage

```
ppm_VIP_vector(VIPs)
```

Arguments

`VIPs` a dataframe from the `model_VIP(MVObj)` function. It requires a "ppms" variable

Details

The function extracts the VIPs vector (numeric) from the `model_VIP(MVObj)` function. It is not necessary if you have the ppm values in a numeric vector. This is needed in case that an automated pipeline is applied, connecting the output from `model_VIP(MVObj)` to `nmr_identify_regions` family functions.

Value

a numeric ppm vector ready to be identified with `nmr_identify_regions_blood`, `nmr_identify_cell` or `nmr_identify_regions_urine`

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

```
print.nmr_dataset      Print for nmr_dataset
```

Description

Print for `nmr_dataset`

Usage

```
## S3 method for class 'nmr_dataset'  
print(x, ...)
```

Arguments

<code>x</code>	an <code>nmr_dataset</code> object
<code>...</code>	for future use

Value

Print for `nmr_dataset`

See Also

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset_peak_table\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_1D\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset_family\(\)](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Other `nmr_dataset` functions: [\[.nmr_dataset\(\)](#), [format.nmr_dataset\(\)](#), [load_and_save_functions](#), [new_nmr_dataset\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_ppm_resolution\(\)](#), [nmr_read_samples\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
print(dataset)
```

```
print.nmr_dataset_1D  print for nmr_dataset_1D
```

Description

print for nmr_dataset_1D

Usage

```
## S3 method for class 'nmr_dataset_1D'
print(x, ...)
```

Arguments

x an [nmr_dataset_1D](#) object
 ... for future use

Value

print for nmr_dataset_1D

See Also

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset_peak_table\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset_family\(\)](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
print(dataset_1D)
```

```
print.nmr_dataset_peak_table
      print for nmr_dataset_peak_table
```

Description

print for nmr_dataset_peak_table

Usage

```
## S3 method for class 'nmr_dataset_peak_table'
print(x, ...)
```

Arguments

x an [nmr_dataset_peak_table](#) object
... for future use

Value

print for nmr_dataset_peak_table

See Also

Other [nmr_dataset_peak_table](#) functions: [\[.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_peak_table\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [validate_nmr_dataset_peak_table\(\)](#)

Other class helper functions: [format.nmr_dataset_1D\(\)](#), [format.nmr_dataset_peak_table\(\)](#), [format.nmr_dataset\(\)](#), [is.nmr_dataset_1D\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [new_nmr_dataset_1D\(\)](#), [new_nmr_dataset_peak_table\(\)](#), [new_nmr_dataset\(\)](#), [print.nmr_dataset_1D\(\)](#), [print.nmr_dataset\(\)](#), [validate_nmr_dataset_family\(\)](#), [validate_nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
new <- new_nmr_dataset_peak_table(peak_table, metadata)
new
```

p_value_perm *Deprecated function p-Value from permutation test*

Description

The function calculates the cumulative (1-tailed) probability of 'actual' belonging to 'h0' (permutation_object from the permutation_test_model function).

Usage

```
p_value_perm(model_actual, permutation_object)
```

Arguments

model_actual The actual model performance (e.g. misclassifications or Q2)
permutation_object Null hypothesis distribution from permutation test from permutation_test_model function

Value

The p-value indicating if there is significant differences between the model performance and the null hypothesis distribution from permutation test test

Examples

```
message("MUVr is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

random_subsampling *Random subsampling*

Description

Random subsampling

Usage

```
random_subsampling(  
  sample_idx,  
  iterations = 10L,  
  test_size = 0.25,  
  keep_together = NULL,  
  balance_in_train = NULL  
)
```

Arguments

<code>sample_idx</code>	Typically a numeric vector with sample index to be separated. A character vector with sample IDs could also be used
<code>iterations</code>	An integer, the number of iterations in the random subsampling
<code>test_size</code>	A number between 0 and 1. The samples to be included in the test set on each iteration.
<code>keep_together</code>	Either NULL or a factor with the same length as <code>sample_idx</code> . <code>keep_together</code> can be used to ensure that groups of samples are kept in together in all iterations (either on training or on test, but never split). A typical use case for this is when you have sample replicates and you want to keep all replicates together to prevent overoptimistic results (having one sample on the train subset and its replicate on the test subset would make the prediction easier to guess). Another use case for this is when you have a longitudinal study and you want to keep some subjects in the same train or test group, because you want to use some information in a longitudinal way (e.g. a multilevel plsda model).
<code>balance_in_train</code>	Either NULL or a factor with the same length as <code>sample_idx</code> . <code>balance_in_train</code> can be used to force that on each iteration, the train partition contains the same number of samples of the given factor levels. For instance, if we have a dataset with 40 samples of class "A" and 20 samples of class "B", using a <code>test_size = 0.25</code> , we can force to always have 16 samples of class "A" and 16 samples of class "B" in the training subset. This is beneficial to those algorithms that require that the training groups are balanced.

Value

A list of length equal to `iterations`. Each element of the list is a list with two entries (training and test) containing the `sample_idx` values that will belong to each subset.

Examples

```
random_subsampling(1:100, iterations = 4, test_size = 0.25)

subject_id <- c("Alice", "Bob", "Charlie", "Eve")
random_subsampling(1:4, iterations = 2, test_size = 0.25, keep_together = subject_id)
```

`rdCV_PLS_RF`*Deprecated function*

Description

Deprecated function

Usage

```
rdCV_PLS_RF(nmr_peak_table)
```

Arguments

`nmr_peak_table` an AlpsNMR integration object (2 classes)

Value

a MUVR model containing selection parameters, validation and fitness

References

Shi,L. et al. (2018) Variable selection and validation in multivariate modelling. *Bioinformatics*.

See Also

`nmr_data_analysis` Feature selection and validation in multivariate analysis

Statistical analysis and feature selection in a repeated double cross-validation frame based on the partial least squares (PLS) or random forest (RF) analyses using an algorithm for multivariate modelling with minimally biased variable selection (MUVR) from the MUVR package. If your work with a `nmr_peak_table` object from AlpsNMR, first you need to extract the X data from the main `nmr_dataset` object (e.g. your peak table) with the `nmr_data` function, otherwise you would try to set a list on the X. You also need to set the class from this object, or just set it from another Y vector.

Other `nmr_dataset_1D` functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_lister()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`, `validate_nmr_dataset()`

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,
use bp_kfold_VIP_analysis method instead")
```

rdCV_PLS_RF_ML

Deprecated function Feature selection and validation in MULTI-LEVEL analysis

Description

Statistical analysis and feature selection in a repeated double cross-validation frame based on the partial least squares (PLS) or random forest (RF) analyses using an algorithm for multivariate modelling with minimally biased variable selection (MUVR) from the MUVR package. The function `rdCV_PLS_RF_ML` allows the multilevel comparison, especially useful in crossover or longitudinal studies (2 timepoints) considering the same individual (it requires 2 samples of the same observation).

Usage

```
rdCV_PLS_RF_ML(nmr_peak_table)
```

Arguments

nmr_peak_table an AlpsNMR integration object (2 classes)

Value

a MUVR model containing selection parameters, validation and fitness

References

Shi,L. et al. (2018) Variable selection and validation in multivariate modelling. *Bioinformatics*.

See Also

Other nmr_dataset_1D functions: [.nmr_dataset_1D(), computes_peak_width_ppm(), file_listner(), files_to_rDolphin(), format.nmr_dataset_1D(), get_integration_with_metadata(), is.nmr_dataset_1D(), load_and_save_functions, new_nmr_dataset_1D(), nmr_align_find_ref(), nmr_align(), nmr_baseline_removal(), nmr_baseline_threshold(), nmr_detect_peaks_plot(), nmr_detect_peaks_tune_snr(), nmr_detect_peaks(), nmr_exclude_region(), nmr_integrate_peak_positions(), nmr_integrate_regions(), nmr_interpolate_1D(), nmr_meta_add(), nmr_meta_export(), nmr_meta_get_column(), nmr_meta_get(), nmr_normalize(), nmr_pca_build_model(), nmr_pca_outliers_filter(), nmr_pca_outliers_plot(), nmr_pca_outliers_robust(), nmr_pca_outliers(), nmr_ppm_resolution(), plot.nmr_dataset_1D(), plot_webgl(), print.nmr_dataset_1D(), rdCV_PLS_RF(), save_files_to_rDolphin(), to_ChemoSpec(), validate_nmr_dataset()

Examples

```
message("Deprecated. MUVR is not compatible with Bioconductor,  
use bp_kfold_VIP_analysis method instead")
```

read_bruker_sample *Read a Bruker sample directory*

Description

Read a Bruker sample directory

Usage

```
read_bruker_sample(  
  sample_path,  
  pdata_file = NULL,  
  pdata_path = "pdata/1",  
  all_components = FALSE  
)
```

Arguments

sample_path	A character path of the sample directory
pdata_file	File name of the binary NMR data to load. Usually "1r". If it is null it is autodetected and all files are loaded.
pdata_path	Path from sample_path to the preprocessed data
all_components	If FALSE load only the real component. Otherwise load all of them

Value

a list with all the bruker sample information

regions_from_peak_table

Build list of regions for peak integration

Description

Build list of regions for peak integration

Usage

```
regions_from_peak_table(peak_pos_ppm, peak_width_ppm)
```

Arguments

peak_pos_ppm	The peak positions, in ppm
peak_width_ppm	The peak widths (or a single peak width for all peaks)

Value

A list of regions suitable for [nmr_integrate_regions](#)

See Also

Other peak detection functions: [Pipelines](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_identify_regions_blood\(\)](#), [nmr_identify_regions_ce](#), [nmr_identify_regions_urine\(\)](#), [nmr_integrate_regions\(\)](#)

ROI_blood

ROIs for blood (plasma/serum) samples

Description

The template ROI_blood contains the targeted list of metabolites to be quantified (blood samples)

References

github.com/danielcanueto/rDolphin

ROI_cell

ROIs for cell samples

Description

The template ROI_cell contains the targeted list of metabolites to be quantified (cell samples)

References

github.com/danielcanueto/rDolphin

ROI_urine

ROIs for urine samples

Description

The template ROI_urine contains the targeted list of metabolites to be quantified (urine samples)

References

github.com/danielcanueto/rDolphin

save_files_to_rDolphin

Save files to rDolphin

Description

The function saves the CSV files required by to_rDolphin and Automatic_targeted_profiling functions for metabolite profiling.

Usage

```
save_files_to_rDolphin(files_rDolphin, output_directory)
```

Arguments

files_rDolphin a list containing 4 elements from files_to_rDolphin

- meta_rDolphin: metadata in rDolphin format,
- NMR_spectra: spectra matrix
- ROI: ROI template
- Parameters_blood: parameters file

output_directory

a directory in which the CSV files are saved

Value

CSV files containing:

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_profiling_output\(\)](#), [to_ChemoSpec\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_listner\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Other to_rDolphin_blood functions: [save_profiling_output\(\)](#)

Examples

```
## Not run:
dataset <- system.file("dataset-demo", package = "AlpsNMR")
excel_file <- system.file("dataset-demo", "dummy_metadata.xlsx", package = "AlpsNMR")
nmr_dataset <- nmr_read_samples_dir(dataset)
files_rDolphin = files_to_rDolphin_blood(nmr_dataset)
output_directory = "."
save_files_to_rDolphin(files_rDolphin, output_directory)

## End(Not run)
```

save_profiling_output *Save rDolphin output*

Description

The function saves the output from Automatic_targeted_profiling function in CSV format.

Usage

```
save_profiling_output(targeted_profiling, output_directory)
```

Arguments

targeted_profiling
A list from Automatic_targeted_profiling function

output_directory
a directory in which the CSV files are saved

Value

rDolphin output from Automatic_targeted_profiling function:

- metabolites_intensity
- metabolites_quantification
- ROI_profiles_used
- chemical_shift
- fitting_error
- half_bandwidth
- signal_area_ratio

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#)

Other to_rDolphin_blood functions: [save_files_to_rDolphin\(\)](#)

Examples

```
## Not run:
rDolphin_object = to_rDolphin(parameters)
targeted_profiling = Automatic_targeted_profiling(rDolphin)
save_profiling_output(targeted_profiling, output_directory)

## End(Not run)
```

SummarizedExperiment_to_nmr_dataset_peak_table

Import SummarizedExperiment as mr_dataset_peak_table

Description

Import SummarizedExperiment as mr_dataset_peak_table

Usage

```
SummarizedExperiment_to_nmr_dataset_peak_table(se)
```

Arguments

se An SummarizedExperiment object

Value

nmr_dataset_peak_table An [nmr_dataset_peak_table](#) object (unmodified)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")
metadata <- readxl::read_excel(meta, sheet = 1)
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")
metadata <- list(external = dataset_1D[["metadata"]][["external"]])
peak_table <- nmr_data(dataset_1D)
nmr_peak_table <- new_nmr_dataset_peak_table(peak_table, metadata)
se <- nmr_dataset_peak_table_to_SummarizedExperiment(nmr_peak_table)
nmr_peak_table <- SummarizedExperiment_to_nmr_dataset_peak_table(se)
```

SummarizedExperiment_to_nmr_data_1r
Import SummarizedExperiment as 1D NMR data

Description

Import SummarizedExperiment as 1D NMR data

Usage

```
SummarizedExperiment_to_nmr_data_1r(se)
```

Arguments

se An SummarizedExperiment object

Value

nmr_dataset An [nmr_dataset_1D](#) object (unmodified)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
se <- nmr_data_1r_to_SummarizedExperiment(dataset_1D)
dataset_1D <- SummarizedExperiment_to_nmr_data_1r(se)
```

to_ChemoSpec *Convert to ChemoSpec Spectra class*

Description

Convert to ChemoSpec Spectra class

Usage

```
to_ChemoSpec(nmr_dataset, desc = "A nmr_dataset", group = NULL)
```

Arguments

nmr_dataset An [nmr_dataset_1D](#) object
desc a description for the dataset
group A string with the column name from the metadata that has grouping information

Value

A Spectra object from the ChemoSpec package

See Also

Other import/export functions: [Pipelines](#), [files_to_rDolphin\(\)](#), [load_and_save_functions](#), [nmr_data\(\)](#), [nmr_meta_export\(\)](#), [nmr_read_bruker_fid\(\)](#), [nmr_read_samples\(\)](#), [nmr_zip_bruker_samples\(\)](#), [save_files_to_rDolphin\(\)](#), [save_profiling_output\(\)](#)

Other nmr_dataset_1D functions: [\[.nmr_dataset_1D\(\)](#), [computes_peak_width_ppm\(\)](#), [file_list\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold\(\)](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
chemo_spectra <- to_ChemoSpec(dataset_1D)
```

validate_nmr_dataset *Validate nmr_dataset objects*

Description

Validate nmr_dataset objects

Validate 1D nmr datasets

Usage

```
validate_nmr_dataset(samples)
```

```
validate_nmr_dataset_1D(nmr_dataset_1D)
```

Arguments

samples An nmr_dataset object

nmr_dataset_1D An [nmr_dataset_1D](#) object

Value

Validate nmr_dataset objects

The `nmr_dataset_1D` unchanged

This function is useful for its side-effects. Stopping in case of error

See Also

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`

Other nmr_dataset functions: `[.nmr_dataset()`, `format.nmr_dataset()`, `load_and_save_functions`, `new_nmr_dataset()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_ppm_resolution()`, `nmr_read_samples()`, `print.nmr_dataset()`

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset_peak_table()`

Other nmr_dataset_1D functions: `[.nmr_dataset_1D()`, `computes_peak_width_ppm()`, `file_listner()`, `files_to_rDolphin()`, `format.nmr_dataset_1D()`, `get_integration_with_metadata()`, `is.nmr_dataset_1D()`, `load_and_save_functions`, `new_nmr_dataset_1D()`, `nmr_align_find_ref()`, `nmr_align()`, `nmr_baseline_removal()`, `nmr_baseline_threshold()`, `nmr_detect_peaks_plot()`, `nmr_detect_peaks_tune_snr()`, `nmr_detect_peaks()`, `nmr_exclude_region()`, `nmr_integrate_peak_positions()`, `nmr_integrate_regions()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_normalize()`, `nmr_pca_build_model()`, `nmr_pca_outliers_filter()`, `nmr_pca_outliers_plot()`, `nmr_pca_outliers_robust()`, `nmr_pca_outliers()`, `nmr_ppm_resolution()`, `plot.nmr_dataset_1D()`, `plot_webgl()`, `print.nmr_dataset_1D()`, `rdCV_PLS_RF_ML()`, `rdCV_PLS_RF()`, `save_files_to_rDolphin()`, `to_ChemoSpec()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
validate_nmr_dataset(dataset)
```

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
dataset_1D_validated <- validate_nmr_dataset_1D(dataset_1D)
```

validate_nmr_dataset_family

Validate nmr_dataset_family objects

Description

Validate `nmr_dataset_family` objects

Usage

```
validate_nmr_dataset_family(nmr_dataset_family)
```

Arguments

`nmr_dataset_family`
An `nmr_dataset_family` object

Value

The `nmr_dataset_family` unchanged

This function is useful for its side-effects: Stopping in case of error

See Also

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_peak_table()`, `validate_nmr_dataset()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
validate_nmr_dataset_family(dataset_1D)
```

`validate_nmr_dataset_peak_table`

Validate nmr_dataset_peak_table objects

Description

Validate `nmr_dataset_peak_table` objects

Usage

```
validate_nmr_dataset_peak_table(nmr_dataset_peak_table)
```

Arguments

`nmr_dataset_peak_table`
An `nmr_dataset_peak_table` object

Value

The `nmr_dataset_peak_table` unchanged

See Also

Other `nmr_dataset_peak_table` functions: `[.nmr_dataset_peak_table()`, `format.nmr_dataset_peak_table()`, `is.nmr_dataset_peak_table()`, `load_and_save_functions`, `new_nmr_dataset_peak_table()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `print.nmr_dataset_peak_table()`

Other class helper functions: `format.nmr_dataset_1D()`, `format.nmr_dataset_peak_table()`, `format.nmr_dataset()`, `is.nmr_dataset_1D()`, `is.nmr_dataset_peak_table()`, `new_nmr_dataset_1D()`, `new_nmr_dataset_peak_table()`, `new_nmr_dataset()`, `print.nmr_dataset_1D()`, `print.nmr_dataset_peak_table()`, `print.nmr_dataset()`, `validate_nmr_dataset_family()`, `validate_nmr_dataset()`

[.nmr_dataset

*Extract parts of an nmr_dataset***Description**

Extract parts of an `nmr_dataset`

Usage

```
## S3 method for class 'nmr_dataset'
x[i]
```

Arguments

`x` an `nmr_dataset` object
`i` indices of the samples to keep

Value

an `nmr_dataset` with the extracted samples

See Also

Other subsetting functions: `[.nmr_dataset_1D()`, `[.nmr_dataset_peak_table()`, `filter.nmr_dataset_family()`, `nmr_pca_outliers_filter()`

Other `nmr_dataset` functions: `format.nmr_dataset()`, `load_and_save_functions`, `new_nmr_dataset()`, `nmr_interpolate_1D()`, `nmr_meta_add()`, `nmr_meta_export()`, `nmr_meta_get_column()`, `nmr_meta_get()`, `nmr_ppm_resolution()`, `nmr_read_samples()`, `print.nmr_dataset()`, `validate_nmr_dataset()`

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset2 <- dataset[1:3] # get the first 3 samples
```

[.nmr_dataset_1D *Extract parts of an nmr_dataset_1D*

Description

Extract parts of an nmr_dataset_1D

Usage

```
## S3 method for class 'nmr_dataset_1D'
x[i]
```

Arguments

x an [nmr_dataset_1D](#) object
i indices of the samples to keep

Value

an nmr_dataset_1D with the extracted samples

See Also

Other subsetting functions: [\[.nmr_dataset_peak_table\(\)](#), [\[.nmr_dataset\(\)](#), [filter.nmr_dataset_family\(\)](#), [nmr_pca_outliers_filter\(\)](#)

Other nmr_dataset_1D functions: [computes_peak_width_ppm\(\)](#), [file_lister\(\)](#), [files_to_rDolphin\(\)](#), [format.nmr_dataset_1D\(\)](#), [get_integration_with_metadata\(\)](#), [is.nmr_dataset_1D\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_1D\(\)](#), [nmr_align_find_ref\(\)](#), [nmr_align\(\)](#), [nmr_baseline_removal\(\)](#), [nmr_baseline_threshold](#), [nmr_detect_peaks_plot\(\)](#), [nmr_detect_peaks_tune_snr\(\)](#), [nmr_detect_peaks\(\)](#), [nmr_exclude_region\(\)](#), [nmr_integrate_peak_positions\(\)](#), [nmr_integrate_regions\(\)](#), [nmr_interpolate_1D\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [nmr_normalize\(\)](#), [nmr_pca_build_model\(\)](#), [nmr_pca_outliers_filter\(\)](#), [nmr_pca_outliers_plot\(\)](#), [nmr_pca_outliers_robust\(\)](#), [nmr_pca_outliers\(\)](#), [nmr_ppm_resolution\(\)](#), [plot.nmr_dataset_1D\(\)](#), [plot_webgl\(\)](#), [print.nmr_dataset_1D\(\)](#), [rdCV_PLS_RF_ML\(\)](#), [rdCV_PLS_RF\(\)](#), [save_files_to_rDolphin\(\)](#), [to_ChemoSpec\(\)](#), [validate_nmr_dataset\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))
dataset_1D[0]
```

`[.nmr_dataset_peak_table`*Extract parts of an nmr_dataset_peak_table*

Description

Extract parts of an `nmr_dataset_peak_table`

Usage

```
## S3 method for class 'nmr_dataset_peak_table'  
x[i]
```

Arguments

`x` an `nmr_dataset_peak_table` object
`i` indices of the samples to keep

Value

an `nmr_dataset_peak_table` with the extracted samples

See Also

Other subsetting functions: [\[.nmr_dataset_1D\(\)](#), [\[.nmr_dataset\(\)](#), [filter.nmr_dataset_family\(\)](#), [nmr_pca_outliers_filter\(\)](#)

Other `nmr_dataset_peak_table` functions: [format.nmr_dataset_peak_table\(\)](#), [is.nmr_dataset_peak_table\(\)](#), [load_and_save_functions](#), [new_nmr_dataset_peak_table\(\)](#), [nmr_meta_add\(\)](#), [nmr_meta_export\(\)](#), [nmr_meta_get_column\(\)](#), [nmr_meta_get\(\)](#), [print.nmr_dataset_peak_table\(\)](#), [validate_nmr_dataset_peak_table\(\)](#)

Examples

```
dir_to_demo_dataset <- system.file("dataset-demo", package = "AlpsNMR")  
dataset <- nmr_read_samples_dir(dir_to_demo_dataset)  
dataset_1D <- nmr_interpolate_1D(dataset, axis = c(min = -0.5, max = 10, by = 2.3E-4))  
meta <- file.path(dir_to_demo_dataset, "dummy_metadata.xlsx")  
metadata <- readxl::read_excel(meta, sheet = 1)  
dataset_1D <- nmr_meta_add(dataset_1D, metadata = metadata, by = "NMRExperiment")  
metadata <- list(external = dataset_1D[["metadata"]][["external"]])  
peak_table <- nmr_data(dataset_1D)  
new <- new_nmr_dataset_peak_table(peak_table, metadata)  
new[0]
```

Index

- * **AlpsNMR dataset objects**
 - [nmr_dataset](#), 40
 - [nmr_dataset_1D](#), 40
 - [nmr_dataset_family](#), 41
- * **PCA related functions**
 - [nmr_pca_build_model](#), 65
 - [nmr_pca_outliers](#), 67
 - [nmr_pca_outliers_filter](#), 68
 - [nmr_pca_outliers_plot](#), 69
 - [nmr_pca_outliers_robust](#), 70
 - [nmr_pca_plots](#), 71
- * **alignment functions**
 - [nmr_align](#), 32
 - [nmr_align_find_ref](#), 33
 - [Pipelines](#), 82
- * **baseline removal functions**
 - [nmr_baseline_removal](#), 33
- * **batman functions**
 - [nmr_batman](#), 35
 - [nmr_batman_options](#), 37
- * **class helper functions**
 - [format.nmr_dataset](#), 16
 - [format.nmr_dataset_1D](#), 17
 - [format.nmr_dataset_peak_table](#), 18
 - [is.nmr_dataset_1D](#), 21
 - [is.nmr_dataset_peak_table](#), 22
 - [new_nmr_dataset](#), 28
 - [new_nmr_dataset_1D](#), 29
 - [new_nmr_dataset_peak_table](#), 31
 - [print.nmr_dataset](#), 99
 - [print.nmr_dataset_1D](#), 100
 - [print.nmr_dataset_peak_table](#), 101
 - [validate_nmr_dataset](#), 112
 - [validate_nmr_dataset_family](#), 113
 - [validate_nmr_dataset_peak_table](#), 114
- * **data**
 - [hmdb](#), 19
 - [HMDB_blood](#), 20
 - [HMDB_cell](#), 20
 - [HMDB_urine](#), 20
 - [Parameters_blood](#), 77
 - [Parameters_cell](#), 77
 - [Parameters_urine](#), 77
 - [ROI_blood](#), 107
 - [ROI_cell](#), 107
 - [ROI_urine](#), 107
- * **import/export functions**
 - [files_to_rDolphin](#), 12
 - [load_and_save_functions](#), 23
 - [nmr_data](#), 39
 - [nmr_meta_export](#), 61
 - [nmr_read_bruker_fid](#), 74
 - [nmr_read_samples](#), 74
 - [nmr_zip_bruker_samples](#), 76
 - [Pipelines](#), 82
 - [save_files_to_rDolphin](#), 108
 - [save_profiling_output](#), 109
 - [to_ChemoSpec](#), 111
- * **metadata functions**
 - [nmr_meta_add](#), 59
 - [nmr_meta_export](#), 61
 - [nmr_meta_get](#), 62
 - [nmr_meta_get_column](#), 63
 - [Pipelines](#), 82
- * **nmr_dataset functions**
 - [\[.nmr_dataset](#), 115
 - [format.nmr_dataset](#), 16
 - [load_and_save_functions](#), 23
 - [new_nmr_dataset](#), 28
 - [nmr_interpolate_1D](#), 57
 - [nmr_meta_add](#), 59
 - [nmr_meta_export](#), 61
 - [nmr_meta_get](#), 62
 - [nmr_meta_get_column](#), 63
 - [nmr_ppm_resolution](#), 72
 - [nmr_read_samples](#), 74
 - [print.nmr_dataset](#), 99

- validate_nmr_dataset, 112
- * **nmr_dataset manipulation functions**
 - is.nmr_dataset, 21
- * **nmr_dataset_1D functions**
 - [.nmr_dataset_1D, 116
 - computes_peak_width_ppm, 10
 - file_list, 14
 - files_to_rDolphin, 12
 - format.nmr_dataset_1D, 17
 - get_integration_with_metadata, 19
 - is.nmr_dataset_1D, 21
 - load_and_save_functions, 23
 - new_nmr_dataset_1D, 29
 - nmr_align, 32
 - nmr_align_find_ref, 33
 - nmr_baseline_removal, 33
 - nmr_baseline_threshold, 34
 - nmr_detect_peaks, 46
 - nmr_detect_peaks_plot, 48
 - nmr_detect_peaks_tune_snr, 49
 - nmr_exclude_region, 50
 - nmr_integrate_peak_positions, 55
 - nmr_integrate_regions, 56
 - nmr_interpolate_1D, 57
 - nmr_meta_add, 59
 - nmr_meta_export, 61
 - nmr_meta_get, 62
 - nmr_meta_get_column, 63
 - nmr_normalize, 64
 - nmr_pca_build_model, 65
 - nmr_pca_outliers, 67
 - nmr_pca_outliers_filter, 68
 - nmr_pca_outliers_plot, 69
 - nmr_pca_outliers_robust, 70
 - nmr_ppm_resolution, 72
 - plot.nmr_dataset_1D, 86
 - plot_webgl, 94
 - print.nmr_dataset_1D, 100
 - rdCV_PLS_RF, 103
 - rdCV_PLS_RF_ML, 104
 - save_files_to_rDolphin, 108
 - to_ChemoSpec, 111
 - validate_nmr_dataset, 112
- * **nmr_dataset_family functions**
 - validate_nmr_dataset_family, 113
- * **nmr_dataset_family manipulation functions**
 - filter.nmr_dataset_family, 15
- * **nmr_dataset_peak_table functions**
 - [.nmr_dataset_peak_table, 117
 - format.nmr_dataset_peak_table, 18
 - is.nmr_dataset_peak_table, 22
 - load_and_save_functions, 23
 - new_nmr_dataset_peak_table, 31
 - nmr_meta_add, 59
 - nmr_meta_export, 61
 - nmr_meta_get, 62
 - nmr_meta_get_column, 63
 - print.nmr_dataset_peak_table, 101
 - validate_nmr_dataset_peak_table, 114
- * **outlier detection functions**
 - nmr_pca_outliers, 67
 - nmr_pca_outliers_filter, 68
 - nmr_pca_outliers_plot, 69
 - nmr_pca_outliers_robust, 70
 - Pipelines, 82
- * **peak alignment functions**
 - nmr_align, 32
 - nmr_align_find_ref, 33
- * **peak detection functions**
 - nmr_baseline_threshold, 34
 - nmr_detect_peaks, 46
 - nmr_detect_peaks_plot, 48
 - nmr_detect_peaks_tune_snr, 49
 - nmr_identify_regions_blood, 52
 - nmr_identify_regions_cell, 53
 - nmr_identify_regions_urine, 54
 - nmr_integrate_regions, 56
 - Pipelines, 82
 - regions_from_peak_table, 106
- * **peak integration functions**
 - computes_peak_width_ppm, 10
 - get_integration_with_metadata, 19
 - nmr_identify_regions_blood, 52
 - nmr_identify_regions_cell, 53
 - nmr_identify_regions_urine, 54
 - nmr_integrate_peak_positions, 55
 - nmr_integrate_regions, 56
 - Pipelines, 82
- * **pipeline functions**
 - Pipelines, 82
- * **plotting functions**
 - plot.nmr_dataset_1D, 86
 - plot_interactive, 89
- * **plotting nmr datasets**

- plot_webgl, 94
- * **subsetting functions**
 - [.nmr_dataset, 115
 - [.nmr_dataset_1D, 116
 - [.nmr_dataset_peak_table, 117
 - filter.nmr_dataset_family, 15
 - nmr_pca_outliers_filter, 68
- * **to_rDolphin functions**
 - files_to_rDolphin, 12
- * **to_rDolphin_blood functions**
 - save_files_to_rDolphin, 108
 - save_profiling_output, 109
- [.nmr_dataset, 15, 16, 24, 29, 58, 59, 61–63, 69, 73, 75, 99, 113, 115, 116, 117
- [.nmr_dataset_1D, 11, 13–15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 100, 104, 105, 108, 112, 113, 115, 116, 117
- [.nmr_dataset_peak_table, 15, 18, 23, 24, 31, 60, 61, 63, 64, 69, 101, 115, 116, 117

- AlpsNMR (AlpsNMR-package), 4
- AlpsNMR-package, 4
- AUC_model, 6

- baseline::baseline.als, 33, 34
- bp_kfold_VIP_analysis, 6
- bp_VIP_analysis, 7, 8

- computes_peak_width_ppm, 10, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116
- confusion_matrix, 11

- download_MTBLS242, 12
- dplyr, 15

- file_listner, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 100, 104, 105, 108, 112, 113, 116
- files_to_rDolphin, 11, 12, 14, 17, 19, 22, 24, 30, 32–35, 39, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73–76, 85, 87, 95, 100, 104, 105, 108, 109, 112, 113, 116

- filter.nmr_dataset_family, 15, 69, 115–117
- format.nmr_dataset, 16, 17, 18, 22–24, 29–31, 58, 59, 61–63, 73, 75, 99–101, 113–115
- format.nmr_dataset_1D, 11, 13, 14, 16, 17, 18, 19, 22–24, 29–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 99–101, 104, 105, 108, 112–116
- format.nmr_dataset_peak_table, 16, 17, 18, 22–24, 29–31, 60, 61, 63, 64, 99–101, 113–115, 117
- fs::dir_ls(), 14
- Functions to save and load these objects, 40, 41

- get_integration_with_metadata, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116
- ggplot2::aes, 72
- ggplot2::aes_string, 87
- ggplot2::aes_string(), 69
- grep(), 83

- hmdb, 19, 36
- HMDB_blood, 20
- HMDB_cell, 20
- HMDB_urine, 20

- is.nmr_dataset, 21
- is.nmr_dataset_1D, 11, 13, 14, 16–19, 21, 23, 24, 29–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 99–101, 104, 105, 108, 112–116
- is.nmr_dataset_peak_table, 16–18, 22, 22, 24, 29–31, 60, 61, 63, 64, 99–101, 113–115, 117

- load_and_save_functions, 11, 13, 14, 16–19, 22, 23, 23, 29–35, 39, 47, 48, 50, 51, 55, 57–66, 68–71, 73–76, 85, 87, 95, 99–101, 104, 105, 108, 109, 112, 113, 115–117

- MassSpecWavelet::peakDetectionCWT, 46
- mixOmics::pca, 66
- mixOmics::plsda, 46

- model_VIP, 27
- models_stability_plot_bootstrap, 24
- models_stability_plot_plsda, 26
- MUVR_model_plot, 28
- new_nmr_data_analysis_method
(nmr_data_analysis_method), 45
- new_nmr_data_analysis_method(), 44
- new_nmr_dataset, 16–18, 22–24, 28, 30, 31, 58, 59, 61–63, 73, 75, 99–101, 113–115
- new_nmr_dataset_1D, 11, 13, 14, 16–19, 22–24, 29, 29, 31–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 99–101, 104, 105, 108, 112–116
- new_nmr_dataset_peak_table, 16–18, 22–24, 29, 30, 31, 60, 61, 63, 64, 99–101, 113–115, 117
- nmr_align, 11, 13, 14, 17, 19, 22, 24, 30, 32, 33–35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116
- nmr_align_find_ref, 11, 13, 14, 17, 19, 22, 24, 30, 32, 33, 34, 35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116
- nmr_baseline_removal, 11, 13, 14, 17, 19, 22, 24, 30, 32, 33, 33, 35, 47, 48, 50, 51, 55, 57–59, 61–63, 65, 66, 68–71, 73, 87, 95, 100, 104, 105, 108, 112, 113, 116
- nmr_baseline_threshold, 11, 13, 14, 17, 19, 22, 24, 30, 32–34, 34, 47, 48, 50–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104–106, 108, 112, 113, 116
- nmr_batman, 35, 39
- nmr_batman_export_dataset (nmr_batman), 35
- nmr_batman_metabolites_list
(nmr_batman), 35
- nmr_batman_multi_data_user
(nmr_batman), 35
- nmr_batman_multi_data_user_hmdb
(nmr_batman), 35
- nmr_batman_options, 36, 37
- nmr_batman_write_options (nmr_batman), 35
- nmr_data, 13, 24, 39, 62, 74–76, 85, 108, 109, 112
- nmr_data<- (nmr_data), 39
- nmr_data_1r_to_SummarizedExperiment, 42
- nmr_data_analysis, 43, 46, 95, 97
- nmr_data_analysis_method, 43, 45, 79
- nmr_dataset, 5, 13, 16, 19, 21, 40, 40, 41, 55, 56, 74, 75, 99, 115
- nmr_dataset_1D, 6, 8, 10, 14, 17, 21, 32–36, 40, 40, 41, 43, 46–49, 51, 64–69, 72, 87, 94, 100, 111–113, 116
- nmr_dataset_family, 6, 8, 15, 23, 39, 40, 41, 43, 59, 61–63, 79, 88, 114
- nmr_dataset_load
(load_and_save_functions), 23
- nmr_dataset_peak_table, 6, 8, 18, 22, 41, 42, 43, 56, 101, 110, 114, 115, 117
- nmr_dataset_peak_table_to_SummarizedExperiment, 42
- nmr_dataset_save
(load_and_save_functions), 23
- nmr_detect_peaks, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 46, 48–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104–106, 108, 112, 113, 116
- nmr_detect_peaks_plot, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104–106, 108, 112, 113, 116
- nmr_detect_peaks_tune_snr, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 49, 51–55, 57–59, 61–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104–106, 108, 112, 113, 116
- nmr_exclude_region, 11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 50, 55, 57, 58, 60–63, 65, 66, 68–71, 73, 87, 95, 100, 104, 105, 108, 112, 113, 116
- nmr_exclude_region(), 5
- nmr_export_data_1r, 51
- nmr_identify_regions_blood, 11, 19, 35, 47, 48, 50, 52, 53–55, 57, 85, 106
- nmr_identify_regions_cell, 11, 19, 35, 47, 48, 50, 52, 53, 54, 55, 57, 85, 106

- nmr_identify_regions_urine, *11, 19, 35, 47, 48, 50, 52, 53, 54, 55, 57, 85, 106*
 nmr_integrate_peak_positions, *11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50–54, 55, 57, 58, 60–63, 65, 66, 68–71, 73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_integrate_regions, *11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50–55, 56, 58, 60–66, 68–71, 73, 85, 87, 95, 100, 104–106, 108, 112, 113, 116*
 nmr_interpolate_1D, *11, 13, 14, 16, 17, 19, 22, 24, 29, 30, 32–35, 47, 48, 50, 51, 55, 57, 57, 59–63, 65, 66, 68–71, 73, 75, 87, 95, 99, 100, 104, 105, 108, 112, 113, 115, 116*
 nmr_interpolate_1D(), *5*
 nmr_meta_add, *11, 13, 14, 16–19, 22–24, 29–35, 47, 48, 50, 51, 55, 57, 58, 59, 61–66, 68–71, 73, 75, 85, 87, 95, 99–101, 104, 105, 108, 112, 113, 115–117*
 nmr_meta_add_tidy_excel (nmr_meta_add), *59*
 nmr_meta_export, *11, 13, 14, 16–19, 22–24, 29–35, 39, 47, 48, 50, 51, 55, 57–60, 61, 62–66, 68–71, 73–76, 85, 87, 95, 99–101, 104, 105, 108, 109, 112, 113, 115–117*
 nmr_meta_get, *11, 13, 14, 16–19, 22–24, 29–35, 47, 48, 50, 51, 55, 57–61, 62, 63–66, 68–71, 73, 75, 85, 87, 95, 99–101, 104, 105, 108, 112, 113, 115–117*
 nmr_meta_get_column, *11, 13, 14, 16–19, 22–24, 29–35, 47, 48, 50, 51, 55, 57–63, 63, 65, 66, 68–71, 73, 75, 85, 87, 95, 99–101, 104, 105, 108, 112, 113, 115–117*
 nmr_normalize, *11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 64, 66, 68–71, 73, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_normalize(), *5*
 nmr_normalize_extra_info (nmr_normalize), *64*
 nmr_pca_build_model, *11, 13, 14, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 65, 65, 67–73, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_pca_loadingplot (nmr_pca_plots), *71*
 nmr_pca_outliers, *11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 65, 66, 67, 69–73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_pca_outliers(), *68, 69*
 nmr_pca_outliers_filter, *11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 65, 66, 68, 68, 70–73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 115–117*
 nmr_pca_outliers_plot, *11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 65, 66, 68, 69, 69, 71–73, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_pca_outliers_plot(), *70*
 nmr_pca_outliers_robust, *11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60–63, 65, 66, 68–70, 70, 72, 73, 82, 85, 87, 95, 100, 104, 105, 108, 112, 113, 116*
 nmr_pca_plot_variance (nmr_pca_plots), *71*
 nmr_pca_plots, *66, 68–71, 71*
 nmr_pca_scoreplot (nmr_pca_plots), *71*
 nmr_ppm_resolution, *11, 13, 15–17, 19, 22, 24, 29, 30, 32–35, 47, 48, 50, 51, 55, 57–66, 68–71, 72, 75, 87, 95, 99, 100, 104, 105, 108, 112, 113, 115, 116*
 nmr_read_bruker_fid, *13, 24, 39, 62, 74, 75, 76, 85, 108, 109, 112*
 nmr_read_samples, *13, 16, 24, 29, 39, 58, 59, 61–63, 73, 74, 74, 76, 85, 99, 108, 109, 112, 113, 115*
 nmr_read_samples(), *5*
 nmr_read_samples_dir (nmr_read_samples), *74*
 nmr_read_samples_dir(), *5*
 nmr_zip_bruker_samples, *13, 24, 39, 62, 74, 75, 76, 85, 108, 109, 112*
 p_value_perm, *102*
 Parameters_blood, *77*
 Parameters_cell, *77*
 Parameters_urine, *77*

- Peak_detection, 78
- permutation_test_model, 79
- permutation_test_plot, 81
- pipe_add_metadata (Pipelines), 82
- pipe_exclude_regions (Pipelines), 82
- pipe_filter_samples (Pipelines), 82
- pipe_interpolate_1D (Pipelines), 82
- pipe_load_samples (Pipelines), 82
- Pipe_normalization (Pipelines), 82
- pipe_normalization (Pipelines), 82
- pipe_outlier_detection (Pipelines), 82
- pipe_pakdet_align (Pipelines), 82
- pipe_peak_integration (Pipelines), 82
- pipe_peakdet_align, 84
- pipe_peakdet_align (Pipelines), 82
- Pipelines, 11, 13, 19, 24, 32, 33, 35, 39, 47, 48, 50, 52–55, 57, 59, 61–63, 68–71, 74–76, 82, 106, 108, 109, 112
- plot(), 5
- plot.nmr_dataset_1D, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60, 61, 63–66, 68–71, 73, 86, 89, 94, 95, 100, 104, 105, 108, 112, 113, 116
- plot_bootstrap_multimodel, 88
- plot_interactive, 50, 87, 89
- plot_plsda_multimodel, 90
- plot_plsda_samples, 91
- plot_vip_scores, 93
- plot_webgl, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60, 61, 63–66, 68–71, 73, 87, 94, 100, 104, 105, 108, 112, 113, 116
- plotly::ggplotly, 50
- plsda_auroc_vip_compare, 95
- plsda_auroc_vip_method, 44, 97
- ppm_resolution, 98
- ppm_VIP_vector, 98
- print.nmr_dataset, 16–18, 22–24, 29–31, 58, 59, 61–63, 73, 75, 99, 100, 101, 113–115
- print.nmr_dataset_1D, 11, 13, 15–19, 22–24, 29–35, 47, 48, 50, 51, 55, 57, 58, 60, 61, 63–66, 68–71, 73, 87, 95, 99, 100, 101, 104, 105, 108, 112–116
- print.nmr_dataset_peak_table, 16–18, 22–24, 29–31, 60, 61, 63, 64, 99, 100, 101, 113–115, 117
- random_subsampling, 43, 79, 102
- rdCV_PLS_RF, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60, 61, 63–66, 68–71, 73, 87, 95, 100, 103, 105, 108, 112, 113, 116
- rdCV_PLS_RF_ML, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 47, 48, 50, 51, 55, 57, 58, 60, 61, 63–66, 68–71, 73, 87, 95, 100, 104, 104, 108, 112, 113, 116
- read_bruker_sample, 105
- read_bruker_sample(), 75
- regions_from_peak_table, 35, 47, 48, 50, 52–54, 57, 85, 106
- ROI_blood, 107
- ROI_cell, 107
- ROI_urine, 107
- save_files_to_rDolphin, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 39, 47, 48, 50, 51, 55, 57, 58, 60–66, 68–71, 73–76, 85, 87, 95, 100, 104, 105, 108, 109, 112, 113, 116
- save_profiling_output, 13, 24, 39, 62, 74–76, 85, 108, 109, 112
- saveRDS, 23
- scale, 66
- speaq::detectSpecPeaks, 46
- speaq::dohCluster, 32
- SummarizedExperiment_to_nmr_data_1r, 111
- SummarizedExperiment_to_nmr_dataset_peak_table, 110
- to_ChemoSpec, 11, 13, 15, 17, 19, 22, 24, 30, 32–35, 39, 47, 48, 50, 51, 55, 57, 58, 60–66, 68–71, 73–76, 85, 87, 95, 100, 104, 105, 108, 109, 111, 113, 116
- utils::zip, 76
- validate_nmr_dataset, 11, 13, 15–19, 22–24, 29–35, 47, 48, 50, 51, 55, 57–66, 68–71, 73, 75, 87, 95, 99–101, 104, 105, 108, 112, 112, 114–116
- validate_nmr_dataset_1D (validate_nmr_dataset), 112
- validate_nmr_dataset_family, 16–18, 22, 23, 29–31, 99–101, 113, 113, 115

`validate_nmr_dataset_peak_table`, [16–18](#),
[22–24](#), [29–31](#), [60](#), [61](#), [63](#), [64](#),
[99–101](#), [113](#), [114](#), [114](#), [117](#)