

Package ‘Doscheda’

May 14, 2025

Type Package

Title A DownStream Chemo-Proteomics Analysis Pipeline

Version 1.30.0

Author Bruno Contrino, Piero Ricchiuto

Maintainer Bruno Contrino <br1contrino@yahoo.co.uk>

Description Doscheda focuses on quantitative chemoproteomics used to determine protein interaction profiles of small molecules from whole cell or tissue lysates using Mass Spectrometry data. The package provides a shiny application to run the pipeline, several visualisations and a downloadable report of an experiment.

License GPL-3

Depends R (>= 3.4)

Imports methods, drc, stats, httr, jsonlite, reshape2, vsn, affy, limma, stringr, ggplot2, graphics, grDevices, calibrate, corrgram, gridExtra, DT, shiny, shinydashboard, readxl, prodlim, matrixStats

biocViews Proteomics, Normalization, Preprocessing, MassSpectrometry, QualityControl, DataImport, Regression

Suggests BiocStyle, knitr, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/Doscheda>

git_branch RELEASE_3_21

git_last_commit c8edeec

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-05-14

Contents

boxplot,ChemoProtSet-method	2
ChemoProtSet-class	3
corrPlot	3
densityPlot	4
doscheda	5
doschedaApp	5
doschedaData	5
fitModel	6
getDatasets	7
getFinal	8
getInput	8
getNorm	9
getParameters	10
makeReport	10
meanSdPlot	11
pcaPlot	12
plot.ChemoProtSet	13
processedExample	13
removePeptides	14
replicatePlot	15
runDoscheda	16
runNormalisation	18
setData	18
setParameters	20
volcanoPlot	22
Index	23

boxplot,ChemoProtSet-method

Default boxplot for objects of class ChemoProtSet

Description

Description

Usage

```
## S4 method for signature 'ChemoProtSet'
boxplot(x, ...)
```

Arguments

x	object of class 'ChemoProtSet'
...	other plotting options

Value

boxplot for objects of class ChemoProtSet

ChemoProtSet-class *An S4 class to run the doscheda pipeline*

Description

An S4 class to run the doscheda pipeline

Slots

input A data.frame containing the input data

normData A data.frame containin a processed and standardised version of the input data

finalData A data.frame containing the final data produced by the pipeline

parameters A list containing all the parameters required to make the pipeline run successfully

datasets A list containing other potentially useful datasets

corrPlot *Plot showing correlation between all channels across replicates*

Description

Plot of the correlation between all the channels in the data.

Usage

```
corrPlot(x, ...)
```

```
## S4 method for signature 'ChemoProtSet'
corrPlot(x, ...)
```

Arguments

x object of class 'ChemoProtSet'

... corrplot options

Value

correlation plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample
ex <- runNormalisation(ex)
ex <- fitModel(ex)
corrPlot(ex)
```

densityPlot *Density plot for objects of class ChemoProtSet*

Description

Description

Usage

```
densityPlot(x, rankProteins = FALSE, ...)

## S4 method for signature 'ChemoProtSet'
densityPlot(x, rankProteins = FALSE, ...)
```

Arguments

x	object of class 'ChemoProtSet'
rankProteins	plot a the set of ranked proteins or plot the density of the channels
...	other plot options

Value

density plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample
ex <- runNormalisation(ex)
ex <- fitModel(ex)
densityPlot(ex)
```

doscheda	<i>Doscheda: A package for Down Stream Chemo-Proteomics Data Analysis</i>
----------	---

Description

The Doscheda package provides three categories of important functions: foo, bar and baz.

Foo functions

The foo functions ...

doschedaApp	<i>Run shiny application for DOSCHEDA</i>
-------------	---

Description

Run a version of the pipeline with some extra features and a simple user experience. The application is documented in detail at [here](#)

Usage

```
doschedaApp()
```

Value

Launches shiny application

doschedaData	<i>Peptide Intensity data set for Doscheda</i>
--------------	--

Description

A fabricated data set to run the Doscheda pipeline from peptide intensity.

Usage

```
data(doschedaData)
```

Format

An object of class `data.frame` with 21140 rows and 15 columns.

Examples

```
data(doschedaData)
head(doschedaData)
```

fitModel

Method to fit a model to an object of class 'ChemoProtSet'

Description

Method to fit a model to an object of class 'ChemoProtSet'

Usage

```
fitModel(x)
```

```
## S4 method for signature 'ChemoProtSet'
fitModel(x)
```

Arguments

x object of class 'ChemoProtSet'

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
'Abundance..F2..131..Sample..REP_2')
ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
modelTypeStr = 'linear',PDBool = FALSE,removePepsBool = FALSE,
incPDofPDBool = FALSE,incGeneFileBool = FALSE,organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
ex<- setData(x = ex, dataFrame = doschedaData, dataChannels = channelNames,
accessionChannel = 'Master.Protein.Accessions',
sequenceChannel = 'Sequence', qualityChannel = 'Quality.PEP' )
ex <- removePeptides(ex,removePeps = FALSE)
ex <- runNormalisation(ex)
ex <- fitModel(ex)
ex
ex <- processedExample
ex <- runNormalisation(ex)
```

```
ex <- fitModel(ex)
ex
```

getDatasets *Accessor function for the datasets slot.*

Description

Accessor function for the datasets slot of a ChemoProtSet object.

Usage

```
getDatasets(x)

## S4 method for signature 'ChemoProtSet'
getDatasets(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getDatasets(ex)
```

getFinal	<i>Accessor function for the finalData slot.</i>
----------	--

Description

Accessor function for the finalData slot of a ChemoProtSet object.

Usage

```
getFinal(x)  
  
## S4 method for signature 'ChemoProtSet'  
getFinal(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')  
getParameters(ex)
```

getInput	<i>Accessor function for the Input</i>
----------	--

Description

Accessor function for the Input slot of a ChemoProtSet object.

Usage

```
getInput(x)  
  
## S4 method for signature 'ChemoProtSet'  
getInput(x)
```


Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getInput(ex)
```

getNorm

Accessor function for the normData

Description

Accessor function for the normData slot of a ChemoProtSet object.

Usage

```
getNorm(x)
```

```
## S4 method for signature 'ChemoProtSet'
getNorm(x)
```

Arguments

x object of class ChemoProtSet

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- new('ChemoProtSet')
getNorm(ex)
```


Value

html report of processed 'ChemoProtSet' object

Examples

```
## Not run:  
ex<- new('ChemoProtSet')  
makeReport(ex)  
  
## End(Not run)
```

meanSdPlot

MeanSd plot for objects of class ChemoProtSet

Description

Shows the ranked means with a running median calculated with a window size of 10

Usage

```
meanSdPlot(x, ...)  
  
## S4 method for signature 'ChemoProtSet'  
meanSdPlot(x, ...)
```

Arguments

x object of class 'ChemoProtSet'
... other plot options

Value

meanSd plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
meanSdPlot(ex)
```

pcaPlot

PCA of the main data sets contained in a object of class ChemoProtSet

Description

Plot of Principal Component Analysis for the first two principal components of the experimental data.

Usage

```
pcaPlot(x, ...)  
  
## S4 method for signature 'ChemoProtSet'  
pcaPlot(x, ...)
```

Arguments

x	object of class 'ChemoProtSet'
...	other plot options

Value

PCA plot for objects of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
pcaPlot(ex)  
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
pcaPlot(ex)
```

plot.ChemoProtSet *Default plot for objects of class ChemoProtSet*

Description

Description

Usage

```
## S3 method for class 'ChemoProtSet'  
plot(x, sigmoidCoef = "rb50", ...)
```

Arguments

x	object of class 'ChemoProtSet'
sigmoidCoef	the sigmoidal coefficient, one of ('difference', 'slope', 'rb50'). Obsolete if modelType is 'linear'
...	other plotting options

Value

plot for objects of class ChemoProtSet

processedExample *Processed Peptide Intensity data set for Doscheda*

Description

A processed fabricated data set to run the Doscheda pipeline from peptide intensity.

Usage

```
data(processedExample)
```

Format

An object of class ChemoProtSet of length 1.

Examples

```
data(processedExample)  
str(processedExample)
```

removePeptides	<i>Method to remove peptides from input data of an object of class 'ChemoProtSet'</i>
----------------	---

Description

Method to remove peptides from input data of an object of class 'ChemoProtSet'

Usage

```
removePeptides(x, changePearson = NA, removePeps = TRUE)
```

```
## S4 method for signature 'ChemoProtSet'
removePeptides(x, changePearson = NA,
  removePeps = TRUE)
```

Arguments

x	object of class 'ChemoProtSet'
changePearson	option to change the pearson threshold cut-off parameter
removePeps	boolean value indicating whether peptide removal should take place

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
## Not run:
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,
  dataTypeStr = 'intensity', modelTypeStr = 'linear',
  PDBool = FALSE,removePepsBool = FALSE,incPDofPDBool = FALSE,
  incGeneFileBool = FALSE,organismStr = 'H.sapiens',
  pearsonThrshVal = 0.4)

ex<- setData(x = ex, dataFrame = doschedaData,
```

```
dataChannels = channelNames,  
accessionChannel = 'Master.Protein.Accessions',  
sequenceChannel = 'Sequence',  
qualityChannel = 'Quality.PEP' )  
ex <- removePeptides(ex,removePeps = FALSE)  
ex  
  
## End(Not run)
```

replicatePlot

Plot replicates between concentrations

Description

Plot of Fold Change between replicate i and replicate j at a given concentration

Usage

```
replicatePlot(x, conc, repIndex1, repIndex2, ...)
```

```
## S4 method for signature 'ChemoProtSet'  
replicatePlot(x, conc, repIndex1, repIndex2, ...)
```

Arguments

x	object of class 'ChemoProtSet'
conc	concentration of channel
repIndex1	index of replicate on x axis
repIndex2	index of replicate on y axis
...	options

Value

Replicate plot for objects of class ChemoProtSet

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
replicatePlot(ex,0,1,2)
```

runDoscheda	<i>Wrapper Function to run the entire Doscheda pipeline</i>
-------------	---

Description

A wrapper for the whole Doscheda pipeline, if users want to avoid using the separate steps.

Usage

```
runDoscheda(dataFrame, dataChannels, accessionChannel, chansVal, repsVal,
  dataTypeStr, modelTypeStr, PDBool = TRUE, removePepsBool = NA,
  incPDofPDBool = FALSE, PDofPDname = NA, incGeneFileBool = FALSE,
  organismStr = "h.sapiens", sigmoidConc = NA, pearsonThrshVal = 0.4,
  uniquePeps = NA, sequenceChannel = NA, qualityChannel = NA,
  pdofpdChannel = NA, incGeneID = FALSE, geneIDFile = NA,
  normType = "loess")
```

Arguments

dataFrame	data.frame of the input data set
dataChannels	column names of dataFrame that correspond to data channels. These should be ordered in the format: rep1_concentration_0, ..., rep1_concentration_n, rep2_concentration_0, ...
accessionChannel	string that is the same as the column name for the protein accessions in dataFrame
chansVal	number of channels / concentrations in experiment
repsVal	number of replicates in experiment
dataTypeStr	string describing the data type of input data set. This can be 'LFC' for log fold-changes, 'FC' for fold-changes and 'intensity' for peptide intensities
modelTypeStr	string describing the type of model applied. This can be 'linear' for a linear model or 'sigmoid' for a sigmoidal model
PDBool	boolean value indicating if the input data is from Proteome Discoverer 2.1 or not
removePepsBool	boolean value indicating if peptide removal will take place. Only valid if input data is peptide intensities
incPDofPDBool	boolean value indicating if the input data contains a pull-down of pull-down column
PDofPDname	string with the same name as column containing pull-down of pull-down data. NA if this is not applicable
incGeneFileBool	boolean value indicating if the data requires a protein accession to gene ID conversion file

organismStr	string giving the name of organism. the options are: 'H.sapiens', 'D. melanogaster', 'C. elegans', 'R. norvegicus', 'M. musculus'. This is only needed if PDbool is FALSE
sigmoidConc	vector of numerical values for concentrations of channels in the case of a sigmoidal fit
pearsonThrshVal	numerical value between -1 and 1 which determines the cut-off used to discard peptides during peptide removal
uniquePeps	string that is the same as the column name for the number of unique peptides in dataframe
sequenceChannel	string that is the same as the column name for the peptide sequences in dataframe
qualityChannel	string that is the same as the column name for the peptide quality score in dataframe
pdofpdChannel	string that is the same as the column name for the pull-down of pull-down data in dataframe
incGeneID	boolean value indicating if a protein accession to gene ID file is supplied
geneIDFile	data.frame containing a protein accession to gene ID conversion file
normType	string indicating the type of normalisation that should take place ('loess', 'median', 'none')

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
```

```
ex <- runDoscheda(dataFrame = doschedaData, dataChannels = channelNames,
  chansVal = 6, repsVal = 2, dataTypeStr = 'intensity',
  modelTypeStr = 'linear', PDBool = FALSE, removePepsBool = FALSE,
  accessionChannel = 'Master.Protein.Accessions',
  sequenceChannel = 'Sequence', qualityChannel = 'Quality.PEP',
  incPDofPDBool = FALSE, incGeneFileBool = FALSE,
  organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
```

runNormalisation	<i>Method to remove peptides from input data of an object of class 'ChemoProtSet'</i>
------------------	---

Description

Method to remove peptides from input data of an object of class 'ChemoProtSet'

Usage

```
runNormalisation(x, normalise = "loess")  
  
## S4 method for signature 'ChemoProtSet'  
runNormalisation(x, normalise = "loess")
```

Arguments

x	object of class 'ChemoProtSet'
normalise	string indicating the type of normalisation that should take place ('loess', 'median', 'none')

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex
```

setData	<i>Method for attaching and standardising data for objects of class 'ChemoProtSet'</i>
---------	--

Description

This method will subset the original data set into the required columns, standardising column names in the process.

Usage

```
setData(x, dataFrame, dataChannels, accessionChannel, uniquePeps = NA,
        sequenceChannel = NA, qualityChannel = NA, pdofpdChannel = NA,
        incGeneID = FALSE, geneIDFile = NA)
```

```
## S4 method for signature 'ChemoProtSet'
setData(x, dataFrame, dataChannels, accessionChannel,
        uniquePeps = NA, sequenceChannel = NA, qualityChannel = NA,
        pdofpdChannel = NA, incGeneID = FALSE, geneIDFile = NA)
```

Arguments

x	object of class 'ChemoProtSet'
dataFrame	data.frame of the input data set
dataChannels	column names of dataFrame that correspond to data channels. These should be ordered in the format: rep1_concentration_0, ..., rep1_concentration_n, rep2_concentration_0, ...
accessionChannel	string that is the same as the column name for the protein accessions in dataFrame
uniquePeps	string that is the same as the column name for the number of unique peptides in dataFrame
sequenceChannel	string that is the same as the column name for the peptide sequences in dataFrame
qualityChannel	string that is the same as the column name for the peptide quality score in dataFrame
pdofpdChannel	string that is the same as the column name for the pull-down of pull-down data in dataFrame
incGeneID	boolean value indicating if a protein accession to gene ID file is supplied
geneIDFile	data.frame containing a protein accession to gene ID conversion file

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')
```

```

ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
modelTypeStr = 'linear',PDBool = FALSE,removePepsBool = FALSE,
incPDofPDBool = FALSE,incGeneFileBool = FALSE,organismStr = 'H.sapiens', pearsonThrshVal = 0.4)
ex<- setData(x = ex, dataFrame = doschedaData, dataChannels = channelNames,
accessionChannel = 'Master.Protein.Accessions',
sequenceChannel = 'Sequence',qualityChannel = 'Quality.PEP')

ex

```

setParameters

Method to set parameters for a ChemoProtSet

Description

Give the ChemoProtSet object the correct parameters for a given experiment in order to successfully run the pipeline

Usage

```

setParameters(x, chansVal, repsVal, dataTypeStr, modelTypeStr, PDBool = TRUE,
removePepsBool = NA, incPDofPDBool = FALSE, PDofPDname = NA,
incGeneFileBool = FALSE, organismStr = "h.sapiens", sigmoidConc = NA,
pearsonThrshVal = 0.4)

```

```

## S4 method for signature 'ChemoProtSet'
setParameters(x, chansVal, repsVal, dataTypeStr,
modelTypeStr, PDBool = TRUE, removePepsBool = NA, incPDofPDBool = FALSE,
PDofPDname = NA, incGeneFileBool = FALSE, organismStr = "h.sapiens",
sigmoidConc = NA, pearsonThrshVal = 0.4)

```

Arguments

x	object of class 'ChemoProtSet'
chansVal	number of channels / concentrations in experiment
repsVal	number of replicates in experiment
dataTypeStr	string describing the data type of input data set. This can be 'LFC' for log fold-changes, 'FC' for fold-changes and 'intensity' for peptide intensities
modelTypeStr	string describing the type of model applied. This can be 'linear' for a linear model or 'sigmoid' for a sigmoidal model
PDBool	boolean value indicating if the input data is from Proteome Discoverer 2.1 or not
removePepsBool	boolean value indicating if peptide removal will take place. Only valid if input data is peptide intensities

incPDofPDBool	boolean value indicating if the input data contains a pull-down of pull-down column
PDofPDname	string with the same name as column containing pull-down of pull-down data. NA if this is not applicable
incGeneFileBool	boolean value indicating if the data requires a protein accession to gene ID conversion file
organismStr	string giving the name of organism. the options are: 'H.sapiens', 'D. melanogaster', 'C. elegans', 'R. norvegicus', 'M. musculus'. This is only needed if PDbool is FALSE
sigmoidConc	vector of numerical values for concentrations of channels in the case of a sigmoidal fit
pearsonThrshVal	numerical value between -1 and 1 which determines the cut-off used to discard peptides during peptide removal

Value

object of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
channelNames <- c('Abundance..F1..126..Control..REP_1',
  'Abundance..F1..127..Sample..REP_1', 'Abundance..F1..128..Sample..REP_1',
  'Abundance..F1..129..Sample..REP_1', 'Abundance..F1..130..Sample..REP_1',
  'Abundance..F1..131..Sample..REP_1', 'Abundance..F2..126..Control..REP_2',
  'Abundance..F2..127..Sample..REP_2', 'Abundance..F2..128..Sample..REP_2',
  'Abundance..F2..129..Sample..REP_2', 'Abundance..F2..130..Sample..REP_2',
  'Abundance..F2..131..Sample..REP_2')

ex <- new('ChemoProtSet')
ex<- setParameters(x = ex,chansVal = 6, repsVal = 2,dataTypeStr = 'intensity',
  modelTypeStr = 'linear',PDBool = FALSE, removePepsBool = FALSE,
  incPDofPDBool = FALSE, incGeneFileBool = FALSE,
  organismStr = 'H.sapiens', pearsonThrshVal = 0.4)

ex
```

`volcanoPlot`*Volcano plot for objects of class ChemoProtSet*

Description

Volcano plots designed to be run on objects of class 'ChemoProtSet' when a linear model has been applied.

Usage

```
volcanoPlot(x, coefficient = "slope", avExprs = 0.2, pVal = 0.05, ...)
```

```
## S4 method for signature 'ChemoProtSet'  
volcanoPlot(x, coefficient = "slope",  
  avExprs = 0.2, pVal = 0.05, ...)
```

Arguments

<code>x</code>	object of class 'ChemoProtSet'
<code>coefficient</code>	coefficient of linear model to be plotted ('slope','intercept','quadratic')
<code>avExprs</code>	average expression cutoff
<code>pVal</code>	p-value cut-off
<code>...</code>	other plotting options

Value

volcano plot for objects of class ChemoProtSet

See Also

[DoschedaSet](#)

Examples

```
ex <- processedExample  
ex <- runNormalisation(ex)  
ex <- fitModel(ex)  
volcanoPlot(ex)
```

Index

- * **datasets**
 - doschedaData, 5
 - processedExample, 13
- boxplot, ChemoProtSet-method, 2
- ChemoProtSet-class, 3
- corrPlot, 3
- corrPlot, ANY, ANY-method (corrPlot), 3
- corrPlot, ChemoProtSet-method (corrPlot), 3
- densityPlot, 4
- densityPlot, ANY, ANY-method (densityPlot), 4
- densityPlot, ChemoProtSet-method (densityPlot), 4
- doscheda, 5
- doscheda-package (doscheda), 5
- doschedaApp, 5
- doschedaData, 5
- DoschedaSet, 6–10, 12, 14, 17–19, 21, 22
- DoschedaSet (ChemoProtSet-class), 3
- fitModel, 6
- fitModel, ANY, ANY-method (fitModel), 6
- fitModel, ChemoProtSet-method (fitModel), 6
- getDatasets, 7
- getDatasets, ANY, ANY-method (getDatasets), 7
- getDatasets, ChemoProtSet-method (getDatasets), 7
- getFinal, 8
- getFinal, ANY, ANY-method (getFinal), 8
- getFinal, ChemoProtSet-method (getFinal), 8
- getInput, 8
- getInput, ANY, ANY-method (getInput), 8
- getInput, ChemoProtSet-method (getInput), 8
- getNorm, 9
- getNorm, ANY, ANY-method (getNorm), 9
- getNorm, ChemoProtSet-method (getNorm), 9
- getParameters, 10
- getParameters, ANY, ANY-method (getParameters), 10
- getParameters, ChemoProtSet-method (getParameters), 10
- makeReport, 10
- meanSdPlot, 11
- meanSdPlot, ANY, ANY-method (meanSdPlot), 11
- meanSdPlot, ChemoProtSet-method (meanSdPlot), 11
- pcaPlot, 12
- pcaPlot, ANY, ANY-method (pcaPlot), 12
- pcaPlot, ChemoProtSet-method (pcaPlot), 12
- plot.ChemoProtSet, 13
- processedExample, 13
- removePeptides, 14
- removePeptides, ANY, ANY-method (removePeptides), 14
- removePeptides, ChemoProtSet-method (removePeptides), 14
- replicatePlot, 15
- replicatePlot, ANY, ANY-method (replicatePlot), 15
- replicatePlot, ChemoProtSet-method (replicatePlot), 15
- runDoscheda, 16
- runNormalisation, 18
- runNormalisation, ANY, ANY-method (runNormalisation), 18

runNormalisation,ChemoProtSet-method
(runNormalisation), [18](#)

setData, [18](#)

setData,ANY,ANY-method (setData), [18](#)

setData,ChemoProtSet-method (setData),
[18](#)

setParameters, [20](#)

setParameters,ANY,ANY-method
(setParameters), [20](#)

setParameters,ChemoProtSet-method
(setParameters), [20](#)

volcanoPlot, [22](#)

volcanoPlot,ANY,ANY-method
(volcanoPlot), [22](#)

volcanoPlot,ChemoProtSet-method
(volcanoPlot), [22](#)