

Package ‘PIPETS’

April 27, 2024

Title Poisson Identification of PEaks from Term-Seq data

Version 0.99.12

Description PIPETS provides statistically robust analysis for 3'-seq/term-seq data. It utilizes a sliding window approach to apply a Poisson Distribution test to identify genomic positions with termination read coverage that is significantly higher than the surrounding signal. PIPETS then condenses proximal signal and produces strand specific results that contain all significant termination peaks.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.0

Depends R (>= 4.4.0)

Imports dplyr, utils, stats, GenomicRanges, BiocGenerics, methods

Suggests BiocStyle, knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

BugReports <https://github.com/qfurumo/PIPETS/issues>

URL <https://github.com/qfurumo/PIPETS>

biocViews Sequencing, Transcription, GeneRegulation, PeakDetection, Genetics, Transcriptomics, Coverage

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/PIPETS>

git_branch devel

git_last_commit 99dedcd

git_last_commit_date 2024-02-06

Repository Bioconductor 3.19

Date/Publication 2024-04-26

Author Quinlan Furumo [aut, cre] (<<https://orcid.org/0000-0003-4486-302X>>)

Maintainer Quinlan Furumo <furumo@bc.edu>

Contents

PIPETS_FullRun	2
--------------------------	---

Index	5
--------------	----------

PIPETS_FullRun	<i>Analyze 3'-seq Data with PIPETS Poisson Identification of PEaks from Term-Seq data. This is the full run method that begins with input Bed file and returns the strand split results</i>
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

PIPETS_FullRun

Usage

```
PIPETS_FullRun(
  inputData,
  readLength,
  OutputFileID,
  OutputFileDir,
  slidingWindowSize = 25,
  slidingWindowMovementDistance = 25,
  threshAdjust = 0.75,
  pValue = 5e-04,
  topEndPercentage = 0.01,
  adjacentPeakDistance = 2,
  peakCondensingDistance = 20,
  inputDataFormat = "bedFile"
)
```

Arguments

inputData	Either input Bed file or GRanges object. Either must have at least chromosome, start, stop, and strand information
readLength	The user must input the expected length of each “proper” read from the 3'-seq protocol. PIPETS gives a +/- 2 range for detecting reads to be used in the input BED files based on distributions of read coverage in parameter testing.
OutputFileID	User defined header for the output files of PIPETS. Will be the prefix for output bed and csv files.
OutputFileDir	User defined output file directory where all files generated by PIPETS will be placed
slidingWindowSize	This parameter establishes the distance up and down stream of each position that a sliding window will be created around. The default value is 25, and this will result in a sliding window of total size 51 (25 upstream + position (1) + 25 downstream).

slidingWindowMovementDistance	This parameter sets the distance that the sliding window will be moved. By default, it is set to move by half of the sliding window size in order to ensure that almost every position in the data is tested twice.
threshAdjust	This parameter is used to establish a global cutoff threshold informed by the data. PIPETS sorts the genomic positions of each strand from highest to lowest, and starts with the highest read coverage position and subtracts that value from the total read coverage for that strand. By default, this continues until 75% of the total read coverage has been accounted for. Increasing the percentage (e.x. 0.9) will lower the strictness of the cutoff, thus increasing the total number of significant results.
pValue	Choose the minimum pValue that the Poisson distribution test must pass in order to be considered significant
topEndPercentage	This parameter is used along with threshAdjust to trim off the influence exerted by high read coverage outliers. By default, it removes the top 0.01 percent of the highest read coverage positions from the calculation of the global threshold (e.x. if there are 200 positions that make up 75% of the total reads, then this parameter will take the top 2 read coverage positions and remove them from the calculation of the global threshold). This parameter can be tuned to account for datasets with outliers that would otherwise severely skew the global threshold.
adjacentPeakDistance	During the peak condensing step, this parameter is used to define “adjacent” for significant genomic positions. This is used to identify initial peak structures in the data. By default this value is set to 2 to ensure that single instances of loss of signal are not sufficient to prevent otherwise contiguous peak signatures from being combined.
peakCondensingDistance	Following the initial peak condensing step, this parameter is used to identify peak structures in the data that are close enough to be considered part of the same termination signal. In testing, we have not identified cases in which two distinct termination signals so proximal that the default parameters incorrectly combine the signals together.
inputDataFormat	PIPETS currently supports "bedFile" (default) and "GRanges" as input formats

Value

PIPETS outputs strand specific results files as well as strand specific bed files to the directory that the R project is in.

Examples

```
## When run, the user will be prompted to provide a string for file names
## During the run, PIPETS will output the minimum read coverage cutoff for each strand
## After completion, the output files will be created in the R project directory

## For run with default strictness of analysis
```

```
PIPETS_FullRun(inputData = "PIPETS_TestData.bed", readLength = 58,  
OutputFileDir = "~/Desktop/", OutputFileID = "Antibiotic1")  
  
## For a more strict run (can be run for files with high total read depth)  
PIPETS_FullRun(inputData = "PIPETS_TestData.bed", readLength = 58, threshAdjust = 0.6,  
OutputFileDir = "~/Desktop/", OutputFileID = "Antibiotic1_Strict")  
  
## For a less strict run (for data with low total read depth)  
PIPETS_FullRun(inputData = "PIPETS_TestData.bed", readLength = 58, threshAdjust = 0.9,  
OutputFileDir = "~/Desktop/", OutputFileID = "Antibiotic1_Lax")
```

Index

PIPETS_FullRun, [2](#)