

# Package ‘alabaster.mae’

December 6, 2024

**Title** Load and Save MultiAssayExperiments

**Version** 1.7.0

**Date** 2024-10-28

**License** MIT + file LICENSE

**Description** Save MultiAssayExperiments into file artifacts, and load them back into memory.  
This is a more portable alternative to serialization of such objects into RDS files.  
Each artifact is associated with metadata for further interpretation;  
downstream applications can enrich this metadata with context-specific properties.

**Depends** MultiAssayExperiment, alabaster.base

**Imports** methods, alabaster.se, S4Vectors, jsonlite, rhdf5

**Suggests** testthat, knitr, SummarizedExperiment, BiocParallel,  
BiocStyle, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 7.3.2

**biocViews** DataImport, DataRepresentation

**git\_url** <https://git.bioconductor.org/packages/alabaster.mae>

**git\_branch** devel

**git\_last\_commit** f6e4c7b

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2024-12-06

**Author** Aaron Lun [aut, cre]

**Maintainer** Aaron Lun <[infinite.monkeys.with.keyboards@gmail.com](mailto:infinite.monkeys.with.keyboards@gmail.com)>

## Contents

readMultiAssayExperiment . . . . .	2
saveObject,MultiAssayExperiment-method . . . . .	3
<b>Index</b>	<b>4</b>

readMultiAssayExperiment

*Read a MultiAssayExperiment from disk*

---

### Description

Read a [MultiAssayExperiment](#) from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

### Usage

```
readMultiAssayExperiment(path, metadata, ...)
```

### Arguments

path	String containing a path to a directory, itself created using the <a href="#">stageObject</a> method for <a href="#">MultiAssayExperiment</a> objects.
metadata	Named list of metadata for this object, see <a href="#">readObjectFile</a> for details.
...	Further arguments passed to internal <a href="#">altReadObject</a> calls.

### Value

A [MultiAssayExperiment](#) object.

### Author(s)

Aaron Lun

### Examples

```
library(SummarizedExperiment)

# Mocking up an MAE
mat <- matrix(rnorm(1000), ncol=10)
colnames(mat) <- letters[1:10]
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))
se <- SummarizedExperiment(list(counts=mat))

library(MultiAssayExperiment)
mae <- MultiAssayExperiment(list(gene=se))

# Staging it:
tmp <- tempfile()
dir.create(tmp)
info <- stageObject(mae, tmp, "dataset")

# Loading it back in:
loadMultiAssayExperiment(info, tmp)
```

---

saveObject,MultiAssayExperiment-method  
*Save a MultiAssayExperiment*

---

## Description

Save a [MultiAssayExperiment](#) to its on-disk representation.

## Usage

```
## S4 method for signature 'MultiAssayExperiment'  
saveObject(x, path, ...)
```

## Arguments

x	A <a href="#">MultiAssayExperiment</a> object or one of its subclasses.
path	String containing the path to a directory in which to save x.
...	Additional named arguments to pass to specific methods.

## Value

The contents of x are saved into a path, and NULL is invisibly returned.

## Author(s)

Aaron Lun

## Examples

```
# Mocking up an MAE  
mat <- matrix(rnorm(1000), ncol=10)  
colnames(mat) <- letters[1:10]  
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))  
  
library(SummarizedExperiment)  
se <- SummarizedExperiment(list(counts=mat))  
  
library(MultiAssayExperiment)  
mae <- MultiAssayExperiment(list(gene=se))  
  
# Saving it:  
tmp <- tempfile()  
saveObject(mae, tmp)
```

# Index

altReadObject, [2](#)

loadMultiAssayExperiment  
    (readMultiAssayExperiment), [2](#)

MultiAssayExperiment, [2](#), [3](#)

readMultiAssayExperiment, [2](#)

readObject, [2](#)

readObjectFile, [2](#)

saveObject, MultiAssayExperiment-method,  
    [3](#)

stageObject, [2](#)

stageObject, MultiAssayExperiment-method  
    (saveObject, MultiAssayExperiment-method),  
    [3](#)