

Package ‘pgxRpi’

April 27, 2024

Title R wrapper for Progenetix

Version 0.99.15

Description The package is an R wrapper for Progenetix REST API built upon the Beacon v2 protocol. Its purpose is to provide a seamless way for retrieving genomic data from Progenetix database—an open resource dedicated to curated oncogenomic profiles. Empowered by this package, users can effortlessly access and visualize data from Progenetix.

biocViews CopyNumberVariation, GenomicVariation, DataImport, Software

License Artistic-2.0

Encoding UTF-8

LazyData FALSE

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports utils, methods, grDevices, graphics, circlize, httr, dplyr, attempt, lubridate, survival, survminer, ggplot2, plyr, GenomicRanges, SummarizedExperiment, S4Vectors

Depends R (>= 4.2)

Suggests BiocStyle, rmarkdown, knitr, testthat

BugReports <https://github.com/progenetix/pgxRpi/issues>

URL <https://github.com/progenetix/pgxRpi>

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/pgxRpi>

git_branch devel

git_last_commit 1d64cbf

git_last_commit_date 2024-04-18

Repository Bioconductor 3.19

Date/Publication 2024-04-26

Author Hangjia Zhao [aut, cre] (<<https://orcid.org/0000-0001-8376-5751>>),
Michael Baudis [aut] (<<https://orcid.org/0000-0002-9903-4248>>)

Maintainer Hangjia Zhao <hangjia.zhao@uzh.ch>

Contents

hg19_bins	2
hg19_cytoband	3
hg38_bins	3
hg38_cytoband	4
pgxCount	4
pgxFilter	5
pgxFreqplot	6
pgxLoader	7
pgxSegprocess	9

Index	11
--------------	-----------

hg19_bins	<i>A dataframe containing location information for 1MB-size bins within the hg19 genome. This dataset is generated based on the accessed cytoband data and used for CNV frequency calculation from local pgxseg files.</i>
-----------	--

Description

A dataframe containing location information for 1MB-size bins within the hg19 genome. This dataset is generated based on the accessed cytoband data and used for CNV frequency calculation from local pgxseg files.

Usage

```
hg19_bins
```

Format

An object of class `data.frame` with 3114 rows and 6 columns.

Value

genomic bin locations of hg19 genome

hg19_cytoband	<i>A dataframe containing cytoband annotation details extracted from the hg19 genome. It is used for CNV frequency visualization.</i>
---------------	---

Description

A dataframe containing cytoband annotation details extracted from the hg19 genome. It is used for CNV frequency visualization.

Usage

```
hg19_cytoband
```

Format

An object of class `data.frame` with 862 rows and 5 columns.

Value

cytoband of hg19 genome

Source

<http://hgdownload.cse.ucsc.edu/goldenpath/hg19/database/cytoBand.txt.gz>

hg38_bins	<i>A dataframe containing location information for 1MB-size bins within the hg38 genome. This dataset is generated based on the accessed cytoband data and used for CNV frequency calculation from local pxxseg files.</i>
-----------	--

Description

A dataframe containing location information for 1MB-size bins within the hg38 genome. This dataset is generated based on the accessed cytoband data and used for CNV frequency calculation from local pxxseg files.

Usage

```
hg38_bins
```

Format

An object of class `data.frame` with 3106 rows and 6 columns.

Value

genomic bin locations of hg38 genome

hg38_cytoband	<i>A dataframe containing cytoband annotation details extracted from the hg38 genome. It is used for CNV frequency visualization.</i>
---------------	---

Description

A dataframe containing cytoband annotation details extracted from the hg38 genome. It is used for CNV frequency visualization.

Usage

```
hg38_cytoband
```

Format

An object of class `data.frame` with 862 rows and 5 columns.

Value

cytoband of hg38 genome

Source

<http://hgdownload.cse.ucsc.edu/goldenpath/hg38/database/cytoBand.txt.gz>

pgxCount	<i>Count samples in one collation of a given filter</i>
----------	---

Description

This function returns the number of samples for every filter in Progenetix database.

Usage

```
pgxCount(
  filters = NULL,
  domain = "http://progenetix.org",
  dataset = "progenetix"
)
```

Arguments

filters	A single or a comma-concatenated list of identifiers such as <code>c("NCIT:C7376","icdom-98353")</code>
domain	A string specifying the domain of database. Default is <code>"http://progenetix.org"</code> .
dataset	A string specifying the dataset to query. Default is <code>"progenetix"</code> . Other available options are <code>"cancercllines"</code> .

Value

Count of samples in the given filter

Examples

```
pgxCount(filters = "NCIT:C3512")
```

pgxFilter

Query available filters

Description

This function retrieves available filters in the Progenetix database.

Usage

```
pgxFilter(  
  prefix = NULL,  
  return_all_prefix = FALSE,  
  domain = "http://progenetix.org",  
  dataset = "progenetix"  
)
```

Arguments

prefix	A string specifying the prefix of filters, such as 'NCIT' and 'PMID'. Default is NULL, which means that all available filters will be returned. When specified, it returns all filters with the specified prefix.
return_all_prefix	A logical value determining whether to return all valid prefixes of filters used in Progenetix. If TRUE, the prefix parameter will be ignored. Default is FALSE.
domain	A string specifying the domain of the Progenetix database. Default is "http://progenetix.org".
dataset	A string specifying the dataset to query. Default is "progenetix". Other available options are "cancercllines".

Value

filter terms used in Progenetix.

Examples

```
pgxFilter(prefix = "NCIT")
```

pgxFreqplot

Plot CNV frequency data

Description

This function plots the frequency of deletions and duplications

Usage

```
pgxFreqplot(  
  data,  
  chrom = NULL,  
  layout = c(1, 1),  
  filters = NULL,  
  circos = FALSE,  
  highlight = NULL,  
  assembly = "hg38"  
)
```

Arguments

<code>data</code>	The frequency object returned by <code>pgxLoader</code> function.
<code>chrom</code>	A vector with chromosomes to be plotted. If <code>NULL</code> , return the plot by genome. If specified the frequencies are plotted with one panel for each chromosome. Default is <code>NULL</code> .
<code>layout</code>	Number of columns and rows in plot. Only used in plot by chromosome. Default is <code>c(1,1)</code> .
<code>filters</code>	Index or string value to indicate which filter to be plotted, such as 1 (the first filters in data slot of object) or 'NCIT:C4038' (specific filter name). The length of filters is limited to one if the parameter <code>circos</code> is <code>False</code> . Default is 1.
<code>circos</code>	A logical value to indicate if return a circos plot. If <code>TRUE</code> , it can return a circos plot with multiple filters for display and comparison. Default is <code>FALSE</code> .
<code>highlight</code>	Indices of genomic bins to be highlighted with red color.
<code>assembly</code>	A string specifying which genome assembly version should be applied to CNV frequency plotting. Allowed options are "hg19", "hg38". Default is "hg38" (genome version used in Progenetix).

Value

The binned CNV frequency plot

Examples

```
## load necessary data (this step can be skipped in real implementation)
data("hg38_cytoband")
## get frequency data
freq <- pgxLoader(type="frequency", output='pgxfreq', filters="NCIT:C3512")
## visualize
pgxFreqplot(freq)
```

pgxLoader

*Load data from Progenetix database***Description**

This function loads various data from Progenetix database.

Usage

```
pgxLoader(
  type = NULL,
  output = NULL,
  filters = NULL,
  codematches = FALSE,
  filterLogic = "AND",
  limit = 0,
  skip = NULL,
  biosample_id = NULL,
  individual_id = NULL,
  save_file = FALSE,
  filename = NULL,
  domain = "http://progenetix.org",
  dataset = "progenetix"
)
```

Arguments

type	A string specifying output data type. Available options are "biosample", "individual", "variant" or "frequency". The first two options return corresponding metadata, "variant" returns CNV variant data, and "frequency" returns precomputed CNV frequency based on data in Progenetix.
output	A string specifying output data format. When the parameter type is "variant", available options are NULL, "pgxseg", "seg", "coverage", or "pgxmatrix"; When the parameter type is "frequency", available options are "pgxfreq" or "pgxmatrix".
filters	Identifiers for cancer type, literature, cohorts, and age such as c("NCIT:C7376", "pgx:icdom-98353", "PMID:22824167", "pgx:cohort-TCGAcancers", "age:>=P50Y").

codematches	A logical value determining whether to exclude samples from child concepts of specified filters that belong to cancer type/tissue encoding system (NCIT, icdom/t, Uberon). If TRUE, retrieved samples only keep samples exactly encoded by specified filters. Do not use this parameter when filters include cancer-irrelevant filters such as PMID and cohort identifiers. Default is FALSE.
filterLogic	A string specifying logic for combining multiple filters when query metadata (the parameter type = "biosample" or "individual"). Available options are "AND" and "OR". Default is "AND". An exception is filters associated with age that always use AND logic when combined with any other filter, even if filterLogic = "OR", which affects other filters. Note that when type = "frequency", the combining logic is "OR", which is not changed by this parameter.
limit	Integer to specify the number of returned biosample/individual/variant profiles for each filter. Default is 0 (return all).
skip	Integer to specify the number of skipped biosample/individual/variant profiles for each filter. E.g. if skip = 2, limit=500, the first 2*500 =1000 profiles are skipped and the next 500 profiles are returned. Default is NULL (no skip).
biosample_id	Identifiers used in Progenetix database for identifying biosamples.
individual_id	Identifiers used in Progenetix database for identifying individuals.
save_file	A logical value determining whether to save the segment variant data as file instead of direct return. Only used when the parameter type is "variant" and output is "pgxseg" or "seg". Default is FALSE.
filename	A string specifying the path and name of the file to be saved. Only used if the parameter save_file is TRUE. Default is "variants.seg/pgxseg" in current work directory.
domain	A string specifying the domain of database. Default is "http://progenetix.org".
dataset	A string specifying the dataset to query. Default is "progenetix". Other available options are "cancercellines".

Value

Data from Progenetix database

Examples

```
## query metadata
biosamples <- pgxLoader(type="biosample", filters = "NCIT:C3512")
## query segment variants
seg <- pgxLoader(type="variant", output = "pgxseg", biosample_id = "pgxbs-kftvgx4y")
## query CNV frequency
freq <- pgxLoader(type="frequency", output = 'pgxfreq', filters="NCIT:C3512")
```

pgxSegprocess

Extract, analyse and visualize "pgxseg" files

Description

This function extracts segments, CNV frequency, and metadata from local "pgxseg" files and supports survival data visualization

Usage

```
pgxSegprocess(
  file,
  group_id = "group_id",
  show_KM_plot = FALSE,
  return_metadata = FALSE,
  return_seg = FALSE,
  return_frequency = FALSE,
  assembly = "hg38",
  ...
)
```

Arguments

file	A string specifying the path and name of the "pgxseg" file where the data is to be read.
group_id	A string specifying which id is used for grouping in KM plot or CNV frequency calculation. Default is "group_id".
show_KM_plot	A logical value determining whether to return the Kaplan-Meier plot based on metadata. Default is FALSE.
return_metadata	A logical value determining whether to return metadata. Default is FALSE.
return_seg	A logical value determining whether to return segment data. Default is FALSE.
return_frequency	A logical value determining whether to return CNV frequency data. The frequency calculation is based on segments in segment data and specified group id in metadata. Default is FALSE.
assembly	A string specifying which genome assembly version should be applied to CNV frequency calculation and plotting. Allowed options are "hg19", "hg38". Default is "hg38".
...	Other parameters relevant to KM plot. These include <code>pval</code> , <code>pval.coord</code> , <code>pval.method</code> , <code>conf.int</code> , <code>linetype</code> , and <code>palette</code> (see <code>ggsurvplot</code> from <code>survminer</code>)

Value

Segments data, CNV frequency object, meta data or KM plots from local "pgxseg" files

Examples

```
file_path <- system.file("extdata", "example.pgxseg", package = 'pgxRpi')  
info <- pgxSegprocess(file=file_path, show_KM_plot = TRUE, return_seg = TRUE, return_metadata = TRUE)
```

Index

* datasets

hg19_bins, [2](#)

hg19_cytoband, [3](#)

hg38_bins, [3](#)

hg38_cytoband, [4](#)

hg19_bins, [2](#)

hg19_cytoband, [3](#)

hg38_bins, [3](#)

hg38_cytoband, [4](#)

pgxCount, [4](#)

pgxFilter, [5](#)

pgxFreqplot, [6](#)

pgxLoader, [7](#)

pgxSegprocess, [9](#)