

DMRcate for bisulfite sequencing

Peters TJ

April 24, 2024

Summary

Worked example to find DMRs from whole genome bisulfite sequencing data.

```
if (!require("BiocManager"))
  install.packages("BiocManager")
BiocManager::install("DMRcate")
```

Load DMRcate into the workspace:

```
library(DMRcate)
```

Bisulfite sequencing assays are fundamentally different to arrays, because methylation is represented as a pair of methylated and unmethylated reads per sample, instead of a single beta value. Although we could simply take the logit-transformed fraction of methylated reads per CpG, this removes the effect of varying read depth across the genome. For example, a sampling depth of 30 methylated reads and 10 unmethylated reads is a much more precise estimate of the methylation level of a given CpG site than 3 methylated and 1 unmethylated. Hence, we take advantage of the fact that the overall effect can be expressed as an interaction between the coefficient of interest and a two-level factor representing methylated and unmethylated reads [1].

The example shown here will be performed on a BSseq object containing bisulfite sequencing of regulatory T cells from various tissues as part of the `tissueTreg` package[2], imported using ExperimentHub. First, we will import the data:

```
library(ExperimentHub)
eh <- ExperimentHub()
bis_1072 <- eh[["EH1072"]]
bis_1072

## An object of type 'BSseq' with
## 21867550 methylation loci
```

```

## 15 samples
## has been smoothed with
## BSmooth (ns = 70, h = 1000, maxGap = 100000000)
## All assays are in-memory

colnames(bis_1072)

## [1] "Fat-Treg-R1"      "Fat-Treg-R2"      "Fat-Treg-R3"      "Liver-Treg-R1"
## [5] "Liver-Treg-R2"    "Liver-Treg-R3"    "Skin-Treg-R1"     "Skin-Treg-R2"
## [9] "Skin-Treg-R3"     "Lymph-N-Tcon-R1"  "Lymph-N-Tcon-R2"  "Lymph-N-Tcon-R3"
## [13] "Lymph-N-Treg-R1" "Lymph-N-Treg-R2" "Lymph-N-Treg-R3"

```

The data contains 15 samples: 3 (unmatched) replicates of mouse Tregs from fat, liver, skin and lymph node, plus a group of 3 CD4+ conventional lymph node T cells (Tcon). We will annotate the BSmooth object to reflect this phenotypic information:

```

bsseq::pData(bis_1072) <- data.frame(replicate=gsub(".*-", "", colnames(bis_1072)),
                                     tissue=substr(colnames(bis_1072), 1,
                                                    nchar(colnames(bis_1072))-3),
                                     row.names=colnames(bis_1072))
colData(bis_1072)$tissue <- gsub("-", "_", colData(bis_1072)$tissue)
as.data.frame(colData(bis_1072))

##           replicate      tissue
## Fat-Treg-R1          R1  Fat_Treg
## Fat-Treg-R2          R2  Fat_Treg
## Fat-Treg-R3          R3  Fat_Treg
## Liver-Treg-R1         R1 Liver_Treg
## Liver-Treg-R2         R2 Liver_Treg
## Liver-Treg-R3         R3 Liver_Treg
## Skin-Treg-R1          R1  Skin_Treg
## Skin-Treg-R2          R2  Skin_Treg
## Skin-Treg-R3          R3  Skin_Treg
## Lymph-N-Tcon-R1       R1 Lymph_N_Tcon
## Lymph-N-Tcon-R2       R2 Lymph_N_Tcon
## Lymph-N-Tcon-R3       R3 Lymph_N_Tcon
## Lymph-N-Treg-R1       R1 Lymph_N_Treg
## Lymph-N-Treg-R2       R2 Lymph_N_Treg
## Lymph-N-Treg-R3       R3 Lymph_N_Treg

```

For standardisation purposes (and for DMR.plot to recognise the genome) we will change the chromosome naming convention to UCSC:

```
bis_1072 <- renameSeqlevels(bis_1072, mapSeqlevels(seqlevels(bis_1072), "UCSC"))
```

For demonstration purposes, we will retain CpGs on chromosome 19 only:

```
bis_1072 <- bis_1072[seqnames(bis_1072)=="chr19",]
bis_1072

## An object of type 'BSseq' with
## 558056 methylation loci
## 15 samples
## has been smoothed with
## BSmooth (ns = 70, h = 1000, maxGap = 100000000)
## All assays are in-memory
```

Now we can prepare the model to be fit for `sequencing.annotate()`. The arguments are equivalent to `cpg.annotate()` but for a couple of exceptions:

- There is an extra argument `all.cov` giving an option whether to retain only CpGs where *all* samples have non-zero coverage, or whether to retain CpGs with only partial sample representation.
- The design matrix should be constructed to reflect the 2-factor structure of methylated and unmethylated reads. Fortunately, `edgeR::modelMatrixMeth()` can take a regular design matrix and transform it into the appropriate structure ready for model fitting.

```
tissue <- factor(pData(bis_1072)$tissue)
tissue <- relevel(tissue, "Liver_Treg")

#Regular matrix design
design <- model.matrix(~tissue)
colnames(design) <- gsub("tissue", "", colnames(design))
colnames(design)[1] <- "Intercept"
rownames(design) <- colnames(bis_1072)
design

##              Intercept Fat_Treg Lymph_N_Tcon Lymph_N_Treg Skin_Treg
## Fat-Treg-R1           1         1           0             0           0
## Fat-Treg-R2           1         1           0             0           0
## Fat-Treg-R3           1         1           0             0           0
## Liver-Treg-R1         1         0           0             0           0
## Liver-Treg-R2         1         0           0             0           0
## Liver-Treg-R3         1         0           0             0           0
## Skin-Treg-R1          1         0           0             0           1
## Skin-Treg-R2          1         0           0             0           1
## Skin-Treg-R3          1         0           0             0           1
```

```

## Lymph-N-Tcon-R1      1      0      1      0      0
## Lymph-N-Tcon-R2      1      0      1      0      0
## Lymph-N-Tcon-R3      1      0      1      0      0
## Lymph-N-Treg-R1      1      0      0      1      0
## Lymph-N-Treg-R2      1      0      0      1      0
## Lymph-N-Treg-R3      1      0      0      1      0
## attr("assign")
## [1] 0 1 1 1 1
## attr("contrasts")
## attr("contrasts")$tissue
## [1] "contr.treatment"

#Methylation matrix design
methdesign <- edgeR::modelMatrixMeth(design)
methdesign

##      Sample1 Sample2 Sample3 Sample4 Sample5 Sample6 Sample7 Sample8 Sample9
## 1          1      0      0      0      0      0      0      0      0
## 2          1      0      0      0      0      0      0      0      0
## 3          0      1      0      0      0      0      0      0      0
## 4          0      1      0      0      0      0      0      0      0
## 5          0      0      1      0      0      0      0      0      0
## 6          0      0      1      0      0      0      0      0      0
## 7          0      0      0      1      0      0      0      0      0
## 8          0      0      0      1      0      0      0      0      0
## 9          0      0      0      0      1      0      0      0      0
## 10         0      0      0      0      1      0      0      0      0
## 11         0      0      0      0      0      1      0      0      0
## 12         0      0      0      0      0      1      0      0      0
## 13         0      0      0      0      0      0      1      0      0
## 14         0      0      0      0      0      0      1      0      0
## 15         0      0      0      0      0      0      0      1      0
## 16         0      0      0      0      0      0      0      1      0
## 17         0      0      0      0      0      0      0      0      1
## 18         0      0      0      0      0      0      0      0      1
## 19         0      0      0      0      0      0      0      0      0
## 20         0      0      0      0      0      0      0      0      0
## 21         0      0      0      0      0      0      0      0      0
## 22         0      0      0      0      0      0      0      0      0
## 23         0      0      0      0      0      0      0      0      0
## 24         0      0      0      0      0      0      0      0      0
## 25         0      0      0      0      0      0      0      0      0
## 26         0      0      0      0      0      0      0      0      0
## 27         0      0      0      0      0      0      0      0      0
## 28         0      0      0      0      0      0      0      0      0
## 29         0      0      0      0      0      0      0      0      0

```

##	30	0	0	0	0	0	0	0	0	0	0
##		Sample10	Sample11	Sample12	Sample13	Sample14	Sample15	Intercept	Fat_Treg		
##	1	0	0	0	0	0	0		1	1	
##	2	0	0	0	0	0	0		0	0	
##	3	0	0	0	0	0	0		1	1	
##	4	0	0	0	0	0	0		0	0	
##	5	0	0	0	0	0	0		1	1	
##	6	0	0	0	0	0	0		0	0	
##	7	0	0	0	0	0	0		1	0	
##	8	0	0	0	0	0	0		0	0	
##	9	0	0	0	0	0	0		1	0	
##	10	0	0	0	0	0	0		0	0	
##	11	0	0	0	0	0	0		1	0	
##	12	0	0	0	0	0	0		0	0	
##	13	0	0	0	0	0	0		1	0	
##	14	0	0	0	0	0	0		0	0	
##	15	0	0	0	0	0	0		1	0	
##	16	0	0	0	0	0	0		0	0	
##	17	0	0	0	0	0	0		1	0	
##	18	0	0	0	0	0	0		0	0	
##	19	1	0	0	0	0	0		1	0	
##	20	1	0	0	0	0	0		0	0	
##	21	0	1	0	0	0	0		1	0	
##	22	0	1	0	0	0	0		0	0	
##	23	0	0	1	0	0	0		1	0	
##	24	0	0	1	0	0	0		0	0	
##	25	0	0	0	1	0	0		1	0	
##	26	0	0	0	1	0	0		0	0	
##	27	0	0	0	0	1	0		1	0	
##	28	0	0	0	0	1	0		0	0	
##	29	0	0	0	0	0	1		1	0	
##	30	0	0	0	0	0	1		0	0	
##		Lymph_N_Tcon	Lymph_N_Treg	Skin_Treg							
##	1	0	0	0							
##	2	0	0	0							
##	3	0	0	0							
##	4	0	0	0							
##	5	0	0	0							
##	6	0	0	0							
##	7	0	0	0							
##	8	0	0	0							
##	9	0	0	0							
##	10	0	0	0							
##	11	0	0	0							
##	12	0	0	0							

```
## 13      0      0      1
## 14      0      0      0
## 15      0      0      1
## 16      0      0      0
## 17      0      0      1
## 18      0      0      0
## 19      1      0      0
## 20      0      0      0
## 21      1      0      0
## 22      0      0      0
## 23      1      0      0
## 24      0      0      0
## 25      0      1      0
## 26      0      0      0
## 27      0      1      0
## 28      0      0      0
## 29      0      1      0
## 30      0      0      0
```

Just like for `cpg.annotate()`, we can specify a contrast matrix to find our comparisons of interest.

```
cont.mat <- limma::makeContrasts(treg_vs_tcon=Lymph_N_Treg-Lymph_N_Tcon,
                                fat_vs_ln=Fat_Treg-Lymph_N_Treg,
                                skin_vs_ln=Skin_Treg-Lymph_N_Treg,
                                fat_vs_skin=Fat_Treg-Skin_Treg,
                                levels=methdesign)

cont.mat

##           Contrasts
## Levels   treg_vs_tcon fat_vs_ln skin_vs_ln fat_vs_skin
## Sample1           0         0         0         0
## Sample2           0         0         0         0
## Sample3           0         0         0         0
## Sample4           0         0         0         0
## Sample5           0         0         0         0
## Sample6           0         0         0         0
## Sample7           0         0         0         0
## Sample8           0         0         0         0
## Sample9           0         0         0         0
## Sample10          0         0         0         0
## Sample11          0         0         0         0
## Sample12          0         0         0         0
## Sample13          0         0         0         0
## Sample14          0         0         0         0
## Sample15          0         0         0         0
```

```
## Intercept          0      0      0      0
## Fat_Treg           0      1      0      1
## Lymph_N_Tcon      -1      0      0      0
## Lymph_N_Treg       1     -1     -1      0
## Skin_Treg          0      0      1     -1
```

Say we want to find DMRs between the regulatory and conventional T cells from the lymph node. First we would fit the model, where `sequencing.annotate()` transforms counts into log2CPMs (via `limma::voom()`) and uses `limma` under the hood to generate per-CpG *t*-statistics, indexing the FDR at 0.05:

```
seq_annot <- sequencing.annotate(bis_1072, methdesign, all.cov = TRUE,
                                contrasts = TRUE, cont.matrix = cont.mat,
                                coef = "treg_vs_tcon", fdr=0.05)

## Filtering out all CpGs where at least one sample has zero coverage...
## Processing BSseq object...
## Transforming counts...
## Fitting model...
## Your contrast returned 157 individually significant CpGs. We recommend
## the default setting of pcutoff in dmrcate().

seq_annot

## CpGannotated object describing 506908 CpG sites, with independent
## CpG threshold indexed at fdr=0.05 and 157 significant CpG sites.
```

And then, just like before, we can call DMRs with `dmrcate()`:

```
dmrcate.res <- dmrcate(seq_annot, C=2, min.cpgs = 5)

## Fitting chr19...
## Demarcating regions...
## Done!

dmrcate.res

## DMResults object with 9 DMRs.
## Use extractRanges() to produce a GRanges object of these.

treg_vs_tcon.ranges <- extractRanges(dmrcate.res, genome="mm10")

## see ?DMRcatedata and browseVignettes('DMRcatedata') for documentation
## loading from cache

treg_vs_tcon.ranges
```

```

## GRanges object with 9 ranges and 8 metadata columns:
##      seqnames      ranges strand | no.cpgs min_smoothed_fdr Stouffer
##      <Rle>        <IRanges> <Rle> | <integer>      <numeric> <numeric>
## [1] chr19 29270611-29272005 * | 16 4.32351e-94 1.000000
## [2] chr19 26683453-26684174 * | 12 1.77927e-57 1.000000
## [3] chr19 32276886-32278089 * | 13 1.74620e-56 1.000000
## [4] chr19 29374953-29375393 * | 12 1.48257e-54 1.000000
## [5] chr19 36378257-36379597 * | 27 1.53747e-76 1.000000
## [6] chr19 46653280-46654180 * | 19 3.94008e-59 1.000000
## [7] chr19 57092365-57092646 * | 10 3.80468e-36 0.139494
## [8] chr19 40808208-40809554 * | 26 3.43873e-63 1.000000
## [9] chr19 41874401-41874895 * | 22 2.75829e-39 1.000000
##      HMFDR      Fisher      maxdiff      meandiff      overlapping.genes
##      <numeric> <numeric> <numeric> <numeric> <character>
## [1] 0.0151786 2.14645e-08 -6.40482 -4.22353      Jak2
## [2] 0.0078774 1.28163e-04 -6.40328 -3.53692      Smarca2
## [3] 0.0446759 1.50767e-04 5.81470 3.93201      Sgms1
## [4] 0.0282265 2.41191e-03 -6.10902 -3.02083      Cd274, Gm36043
## [5] 0.0482585 7.25026e-03 -6.09625 -3.03550      Pcgf5
## [6] 0.0512002 4.52566e-02 5.18388 2.93152      Wbp11
## [7] 0.0711193 6.39021e-02 -4.67645 -3.36472      Ablim1
## [8] 0.1802571 3.05279e-01 -4.83855 -3.07494      Cc2d2b
## [9] 0.1858534 6.90217e-01 4.57011 2.56520      Rrp12
## -----
## seqinfo: 1 sequence from an unspecified genome; no seqlengths

```


Looks like the top DMR is associated with the *Jak2* locus and hypomethylated in the Treg cells (since `meandiff < 0`). We can plot it like so:

```

cols <- as.character(plyr::mapvalues(tissue, unique(tissue),
                                     c("darkorange", "maroon", "blue",
                                       "black", "magenta")))
names(cols) <- tissue

DMR.plot(treg_vs_tcon.ranges, dmr = 1,
         CpGs=bis_1072[,tissue %in% c("Lymph_N_Tcon", "Lymph_N_Treg")],
         phen.col = cols[tissue %in% c("Lymph_N_Tcon", "Lymph_N_Treg")],
         genome="mm10")

```

Now, let's find DMRs between fat and skin Tregs.

```
seq_annot <- sequencing.annotate(bis_1072, methdesign, all.cov = TRUE,
                                contrasts = TRUE, cont.matrix = cont.mat,
                                coef = "fat_vs_skin", fdr=0.05)

## Filtering out all CpGs where at least one sample has zero coverage...
## Processing BSseq object...
## Transforming counts...
## Fitting model...
## Your contrast returned 5 individually significant CpGs; a small
but real effect. Consider increasing the 'fdr' parameter using changeFDR(),
but be warned there is an increased risk of Type I errors.
```

Because this comparison is a bit more subtle, there are very few significantly differential CpGs at this threshold. So we can use `changeFDR()` to relax the


FDR to 0.25, taking into account that there is an increased risk of false positives.

```
seq_annot <- changeFDR(seq_annot, 0.25)
## Threshold is now set at FDR=0.25, resulting in 63 significantly differential CpGs.
```

```
dmrcate.res <- dmrcate(seq_annot, C=2, min.cpgs = 5)
## Fitting chr19...
## Demarcating regions...
## Done!
fat_vs_skin.ranges <- extractRanges(dmrcate.res, genome="mm10")
## see ?DMRcatedata and browseVignettes('DMRcatedata') for documentation
## loading from cache
```

Now let's plot the top DMR with not only fat and skin, but with all samples:

```
cols
##      Fat_Treg      Fat_Treg      Fat_Treg      Liver_Treg      Liver_Treg      Liver_Treg
## "darkorange" "darkorange" "darkorange"      "maroon"      "maroon"      "maroon"
##      Skin_Treg      Skin_Treg      Skin_Treg      Lymph_N_Tcon      Lymph_N_Tcon      Lymph_N_Tcon
##      "blue"      "blue"      "blue"      "black"      "black"      "black"
##      Lymph_N_Treg      Lymph_N_Treg      Lymph_N_Treg
##      "magenta"      "magenta"      "magenta"
DMR.plot(fat_vs_skin.ranges, dmr = 1, CpGs=bis_1072, phen.col = cols, genome="mm10")
```



Here we can see the methylation of skin cells over this region near the *Gent1* promoter is hypomethylated not only relative to fat, but to the other tissues as well.

```

sessionInfo()

## R version 4.4.0 beta (2024-04-15 r86425)
## Platform: x86_64-pc-linux-gnu
## Running under: Ubuntu 22.04.4 LTS
##
## Matrix products: default
## BLAS: /home/biocbuild/bbs-3.19-bioc/R/lib/libRblas.so
## LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.10.0
##
## locale:
## [1] LC_CTYPE=en_US.UTF-8 LC_NUMERIC=C

```

```

## [3] LC_TIME=en_GB          LC_COLLATE=C
## [5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
## [7] LC_PAPER=en_US.UTF-8    LC_NAME=C
## [9] LC_ADDRESS=C            LC_TELEPHONE=C
## [11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C
##
## time zone: America/New_York
## tzcode source: system (glibc)
##
## attached base packages:
## [1] parallel stats4 stats graphics grDevices utils datasets
## [8] methods base
##
## other attached packages:
## [1] bsseq_1.39.0
## [2] tissueTreg_1.23.0
## [3] DMRcatedata_2.21.3
## [4] IlluminaHumanMethylationEPICanno.ilm10b4.hg19_0.6.0
## [5] IlluminaHumanMethylationEPICmanifest_0.3.0
## [6] FlowSorted.Blood.EPIC_2.7.0
## [7] minfi_1.49.1
## [8] bumpHunter_1.45.1
## [9] locfit_1.5-9.9
## [10] iterators_1.0.14
## [11] foreach_1.5.2
## [12] Biostrings_2.71.6
## [13] XVector_0.43.1
## [14] SummarizedExperiment_1.33.3
## [15] Biobase_2.63.1
## [16] MatrixGenerics_1.15.1
## [17] matrixStats_1.3.0
## [18] GenomicRanges_1.55.4
## [19] GenomeInfoDb_1.39.14
## [20] IRanges_2.37.1
## [21] S4Vectors_0.41.7
## [22] ExperimentHub_2.11.3
## [23] AnnotationHub_3.11.5
## [24] BiocFileCache_2.11.2
## [25] dbplyr_2.5.0
## [26] BiocGenerics_0.49.1
## [27] DMRcate_2.99.6
##
## loaded via a namespace (and not attached):
## [1] splines_4.4.0
## [2] BiocIO_1.13.0

```

```
## [3] bitops_1.0-7
## [4] filelock_1.0.3
## [5] cellranger_1.1.0
## [6] tibble_3.2.1
## [7] R.oo_1.26.0
## [8] preprocessCore_1.65.0
## [9] XML_3.99-0.16.1
## [10] rpart_4.1.23
## [11] lifecycle_1.0.4
## [12] httr2_1.0.1
## [13] edgeR_4.1.26
## [14] base64_2.0.1
## [15] MASS_7.3-60.2
## [16] lattice_0.22-6
## [17] ensemblDb_2.27.1
## [18] socr_1.3.5
## [19] backports_1.4.1
## [20] magrittr_2.0.3
## [21] limma_3.59.10
## [22] Hmisc_5.1-2
## [23] rmarkdown_2.26
## [24] yaml_2.3.8
## [25] doRNG_1.8.6
## [26] askpass_1.2.0
## [27] Gviz_1.47.1
## [28] DBI_1.2.2
## [29] RColorBrewer_1.1-3
## [30] abind_1.4-5
## [31] zlibbioc_1.49.3
## [32] quadprog_1.5-8
## [33] purrr_1.0.2
## [34] R.utils_2.12.3
## [35] AnnotationFilter_1.27.0
## [36] biovizBase_1.51.0
## [37] RCurl_1.98-1.14
## [38] nnet_7.3-19
## [39] VariantAnnotation_1.49.7
## [40] rappdirs_0.3.3
## [41] GenomeInfoDbData_1.2.12
## [42] genefilter_1.85.1
## [43] annotate_1.81.2
## [44] permute_0.9-7
## [45] DelayedMatrixStats_1.25.4
## [46] codetools_0.2-20
## [47] DelayedArray_0.29.9
```

```
## [48] xml2_1.3.6
## [49] tidyselect_1.2.1
## [50] UCSC.utils_0.99.7
## [51] beanplot_1.3.1
## [52] base64enc_0.1-3
## [53] illuminaio_0.45.0
## [54] GenomicAlignments_1.39.5
## [55] jsonlite_1.8.8
## [56] multtest_2.59.0
## [57] Formula_1.2-5
## [58] survival_3.6-4
## [59] missMethyl_1.37.0
## [60] tools_4.4.0
## [61] progress_1.2.3
## [62] Rcpp_1.0.12
## [63] glue_1.7.0
## [64] gridExtra_2.3
## [65] SparseArray_1.3.5
## [66] xfun_0.43
## [67] dplyr_1.1.4
## [68] HDF5Array_1.31.6
## [69] withr_3.0.0
## [70] IlluminaHumanMethylation450kanno.ilmn12.hg19_0.6.1
## [71] BiocManager_1.30.22
## [72] fastmap_1.1.1
## [73] latticeExtra_0.6-30
## [74] rhdf5filters_1.15.5
## [75] fansi_1.0.6
## [76] openssl_2.1.2
## [77] digest_0.6.35
## [78] mime_0.12
## [79] R6_2.5.1
## [80] colorspace_2.1-0
## [81] gtools_3.9.5
## [82] jpeg_0.1-10
## [83] dichromat_2.0-0.1
## [84] biomaRt_2.59.1
## [85] RSQLite_2.3.6
## [86] R.methodsS3_1.8.2
## [87] tidyr_1.3.1
## [88] utf8_1.2.4
## [89] generics_0.1.3
## [90] data.table_1.15.4
## [91] rtracklayer_1.63.2
## [92] prettyunits_1.2.0
```

```
## [93] httr_1.4.7
## [94] htmlwidgets_1.6.4
## [95] S4Arrays_1.3.7
## [96] pkgconfig_2.0.3
## [97] gtable_0.3.5
## [98] blob_1.2.4
## [99] siggenes_1.77.0
## [100] htmltools_0.5.8.1
## [101] ProtGenerics_1.35.4
## [102] scales_1.3.0
## [103] png_0.1-8
## [104] knitr_1.46
## [105] rstudioapi_0.16.0
## [106] tzdb_0.4.0
## [107] rjson_0.2.21
## [108] nlme_3.1-164
## [109] checkmate_2.3.1
## [110] curl_5.2.1
## [111] org.Hs.eg.db_3.19.1
## [112] cachem_1.0.8
## [113] rhdf5_2.47.7
## [114] stringr_1.5.1
## [115] BiocVersion_3.19.1
## [116] foreign_0.8-86
## [117] AnnotationDbi_1.65.2
## [118] restfulr_0.0.15
## [119] GEOquery_2.71.0
## [120] pillar_1.9.0
## [121] grid_4.4.0
## [122] reshape_0.8.9
## [123] vctrs_0.6.5
## [124] xtable_1.8-4
## [125] cluster_2.1.6
## [126] htmlTable_2.4.2
## [127] evaluate_0.23
## [128] readr_2.1.5
## [129] GenomicFeatures_1.55.4
## [130] cli_3.6.2
## [131] compiler_4.4.0
## [132] Rsamtools_2.19.4
## [133] rngtools_1.5.2
## [134] rlang_1.1.3
## [135] crayon_1.5.2
## [136] nor1mix_1.3-3
## [137] mclust_6.1
```

```
## [138] interp_1.1-6
## [139] plyr_1.8.9
## [140] stringi_1.8.3
## [141] deldir_2.0-4
## [142] BiocParallel_1.37.1
## [143] munsell_0.5.1
## [144] lazyeval_0.2.2
## [145] Matrix_1.7-0
## [146] BSgenome_1.71.4
## [147] hms_1.1.3
## [148] sparseMatrixStats_1.15.1
## [149] bit64_4.0.5
## [150] ggplot2_3.5.1
## [151] Rhdf5lib_1.25.3
## [152] KEGGREST_1.43.0
## [153] statmod_1.5.0
## [154] highr_0.10
## [155] memoise_2.0.1
## [156] bit_4.0.5
## [157] readxl_1.4.3
```

References

- [1] Chen Y, Pal B, Visvader JE, Smyth GK. Differential methylation analysis of reduced representation bisulfite sequencing experiments using edgeR. *F1000Research*. 2017 **6**, 2055.
- [2] Delacher M, Imbusch CD, Weichenhan D, Breiling A, Hotz-Wagenblatt A, Trager U, ... Feuerer M. (2017). Genome-wide DNA-methylation landscape defines specialization of regulatory T cells in tissues. *Nature Immunology*. 2017 **18**(10), 1160-1172.