

Package ‘esetVis’

March 17, 2025

Type Package

Title Visualizations of expressionSet Bioconductor object

Version 1.32.0

Date 2023-12-15

Author Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Maintainer Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Description Utility functions for visualization of expressionSet (or SummarizedExperiment) Bioconductor object, including spectral map, tsne and linear discriminant analysis. Static plot via the ggplot2 package or interactive via the ggvis or rbokeh packages are available.

Imports mpm, hexbin, Rtsne, MLP, grid, Biobase, MASS, stats, utils, grDevices, methods

Suggests ggplot2, ggvis, plotly, ggrepel, knitr, rmarkdown, ALL, hgu95av2.db, AnnotationDbi, pander, SummarizedExperiment, GO.db

biocViews Visualization, DataRepresentation, DimensionReduction, PrincipalComponent, Pathways

VignetteBuilder knitr

License GPL-3

NeedsCompilation no

RoxygenNote 7.2.3

git_url <https://git.bioconductor.org/packages/esetVis>

git_branch RELEASE_3_20

git_last_commit e3637dd

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-03-17

Contents

| | |
|---|---|
| characterORexpressionOrCall-class | 2 |
| esetLda | 2 |
| esetPlot-class | 7 |

| | |
|--|----|
| eSetPlotInteractive-class | 10 |
| eSetPlotWrapper | 10 |
| eSetSpectralMap | 15 |
| eSetTsne | 21 |
| formatManualScale | 24 |
| formatOutput | 25 |
| getAxesLimits | 25 |
| getCoordGeneSets | 26 |
| getDataPlotSamplesWithAnnotation | 27 |
| getGeneSetsForPlot | 27 |
| getMethodsInputObjectEsetVis | 29 |
| getTopElements | 29 |
| ggPlotEset | 30 |
| ggplotEsetPlot-class | 31 |
| ggvisEsetPlot-class | 32 |
| ggvisPlotEset | 32 |
| plotEset | 33 |
| plotlyEsetPlot-class | 33 |
| plotlyPlotEset | 34 |
| plotTopElements | 34 |
| setFixElement | 35 |
| setManualScale | 36 |
| simpleCap | 36 |
| varToFm | 37 |

Index 38

characterORexpressionORcall-class
S4 Class Union with character/expression/call

Description

This is used for the definition of the title/axes labels for the ggplot2 version

eSetLda *plot a biplot of a linear discriminant analysis of an eSet object*

Description

eSetLda reduces the dimension of the data contained in the [eSet](#) via a linear discriminant analysis on the specified grouping variable with the lda function and plot the subsequent biplot, possibly with sample annotation and gene annotation contained in the eSet.

Usage

```

esetLda(
  eset,
  ldaVar,
  psids = 1:nrow(eset),
  dim = c(1, 2),
  colorVar = character(),
  color = if (length(colorVar) == 0) "black" else character(),
  shapeVar = character(),
  shape = if (length(shapeVar) == 0) 15 else numeric(),
  sizeVar = character(),
  size = if (length(sizeVar) == 0) {
    ifelse(typePlot[1] == "interactive" &&
      packageInteractivity[1] == "plotly", 20, 2.5)
  } else {
    numeric()
  },
  sizeRange = numeric(),
  alphaVar = character(),
  alpha = if (length(alphaVar) == 0) 1 else numeric(),
  alphaRange = numeric(),
  title = "",
  symmetryAxes = c("combine", "separate", "none"),
  packageTextLabel = c("ggrepel", "ggplot2"),
  cloudGenes = TRUE,
  cloudGenesColor = "black",
  cloudGenesNBins = sqrt(length(psids)),
  cloudGenesIncludeLegend = FALSE,
  cloudGenesTitleLegend = "nGenes",
  topGenes = 10,
  topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGenesVar = character(),
  topGenesJust = c(0.5, 0.5),
  topGenesColor = "black",
  topSamples = 10,
  topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topSamplesVar = character(),
  topSamplesJust = c(0.5, 0.5),
  topSamplesColor = "black",
  geneSets = list(),
  geneSetsVar = character(),
  geneSetsMaxNChar = numeric(),
  topGeneSets = 10,
  topGeneSetsCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGeneSetsJust = c(0.5, 0.5),
  topGeneSetsColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),

```

```

packageInteractivity = c("plotly", "ggvis"),
figInteractiveSize = c(600, 400),
ggvisAdjustLegend = TRUE,
interactiveTooltip = TRUE,
interactiveTooltipExtraVars = character(),
returnAnalysis = FALSE,
returnEsetPlot = FALSE
)

```

Arguments

| | |
|------------------|---|
| eset | expressionSet (or SummarizedExperiment) object with data |
| ldaVar | name of variable (in varLabels of the eset) used for grouping for lda |
| psids | featureNames of genes to include in the plot, all by default |
| dim | dimensions of the analysis to represent, first two dimensions by default |
| colorVar | name of variable (in varLabels of the eset) used for coloring, empty by default |
| color | character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise |
| shapeVar | name of variable (in varLabels of the eset) used for the shape, empty by default |
| shape | character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise |
| sizeVar | name of variable (in varLabels of the eset) used for the size, empty by default |
| size | character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise |
| sizeRange | size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer' |
| alphaVar | name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case). |
| alpha | character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis. |
| alphaRange | transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot. |
| title | plot title, "" by default |
| symmetryAxes | set symmetry for axes, either: <ul style="list-style-type: none"> 'combine' (by default): both axes are symmetric and with the same limits 'separate': each axis is symmetric and has its own limits 'none': axes by default (plot limits) |
| packageTextLabel | package used to label the outlying genes/samples/gene sets, either ggrepel (by default, only used if package ggrepel is available), or ggplot2 |

| | |
|-------------------------|---|
| cloudGenes | logical, if TRUE (by default), include the cloud of genes in the plot |
| cloudGenesColor | if cloudGenes is TRUE, color for the cloud of genes, black by default |
| cloudGenesNBins | number of bins to used for the clouds of genes, by default the square root of the number of genes |
| cloudGenesIncludeLegend | logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends) |
| cloudGenesTitleLegend | string with title for the legend for the cloud of genes 'nGenes' by default |
| topGenes | numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot. |
| topGenesCex | cex for gene annotation (used when topGenes > 0) |
| topGenesVar | variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when topGenes > 0) |
| topGenesJust | text justification for the genes (used when topGenes > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topGenesColor | text color for the genes (used when topGenes > 0), black by default |
| topSamples | numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot. |
| topSamplesCex | cex for sample annotation (used when topSamples > 0) |
| topSamplesVar | variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0) |
| topSamplesJust | text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topSamplesColor | text color for the samples (used when topSamples > 0), black by default |
| geneSets | list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets. |
| geneSetsVar | variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| geneSetsMaxNChar | maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters) |

| | |
|--|--|
| <code>topGeneSets</code> | numeric indicating which percentile (if ≤ 1) or number (if > 1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected. If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when <code>topGeneSets > 0</code> and the parameter <code>geneSets</code> is specified. |
| <code>topGeneSetsCex</code> | <code>cex</code> for gene sets annotation. Only used when <code>topGeneSets > 0</code> and the parameter <code>geneSets</code> is specified. |
| <code>topGeneSetsJust</code> | text justification for the gene sets by default: <code>c(0.5, 0.5)</code> so centered. Only used when <code>topGeneSets > 0</code> , the parameter <code>geneSets</code> is specified and if <code>packageTextLabel</code> is <code>ggplot2</code> . |
| <code>topGeneSetsColor</code> | color for the gene sets (used when <code>topGeneSets > 0</code> and <code>geneSets</code> is specified), black by default. Only used when <code>topGeneSets > 0</code> and the parameter <code>geneSets</code> is specified. |
| <code>includeLegend</code> | logical if TRUE (by default) include a legend, otherwise not |
| <code>includeLineOrigin</code> | if TRUE (by default) include vertical line at $x = 0$ and horizontal line at $y = 0$ |
| <code>typePlot</code> | type of the plot returned, either 'static' (static) or 'interactive' (potentially interactive) |
| <code>packageInteractivity</code> | if <code>typePlot</code> is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'. |
| <code>figInteractiveSize</code> | vector containing the size of the interactive plot, as [width, height] by default: <code>c(600, 400)</code> . This is passed to the width and height parameters of: <ul style="list-style-type: none"> • for plotly plots: the <code>ggplotly</code> function • for ggvis plots: the <code>ggvis::set_options</code> function |
| <code>ggvisAdjustLegend</code> | logical, if TRUE (by default) adjust the legends in <code>ggvis</code> to avoid overlapping legends when multiple legends |
| <code>interactiveTooltip</code> | logical, if TRUE, add hover functionality showing sample annotation (variables used in the plot) in the plot |
| <code>interactiveTooltipExtraVars</code> | name of extra variable(s) (in <code>varLabels</code> of the <code>eset</code>) to add in <code>plotlyEsetPlot</code> to label the samples, empty by default |
| <code>returnAnalysis</code> | logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the <code>topElements</code> element if any, otherwise only the plot object |
| <code>returnEsetPlot</code> | logical, if TRUE return also the <code>esetPlot</code> object |

Value

if `returnAnalysis` is TRUE, return a list:

- `analysis`: output of the spectral map analysis, whose parameters can be given as input to the `esetPlotWrapper` function
 - `dataPlotSamples`: coordinates of the samples

- dataPlotGenes: coordinates of the genes
- esetUsed: expressionSet used in the plot
- topElements: list with top outlying elements if any, possibly genes, samples and gene sets
- plot: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

Fisher, R. A. (1936). The Use of Multiple Measurements in Taxonomic Problems. *Annals of Eugenics*, 7 (2), 179–188

See Also

the function used internally: [lda](#)

Examples

```
# load data
library(ALL)
data(ALL)

# specify several variables in ldaVar (this might take a few minutes to run...)

# sample subsetting: currently cannot deal with missing values
samplesToRemove <- which(apply(pData(ALL)[, c("sex", "BT")], 1, anyNA))

# extract random features, because analysis is quite time consuming
retainedFeatures <- sample(featureNames(ALL), size = floor(nrow(ALL)/5))

# create the plot
esetLda(eset = ALL[retainedFeatures, -samplesToRemove],
        ldaVar = "BT", colorVar = "BT", shapeVar = "sex", sizeVar = "age",
        title = "Linear discriminant analysis on the ALL dataset")
```

esetPlot-class

An S4 class to represent esetPlot object expressionSet with visualization data from dimension-reduction methods

Description

Constructor of the [esetPlot](#) class

Usage

```
## S4 method for signature 'esetPlot'
initialize(Object, ...)
```

Arguments

.Object [esetPlot](#) object
 ... additional class arguments

Value

S4 object of class `esetPlot`

Slots

`dataPlotSamples` data.frame with columns 'X', 'Y' with coordinates for the samples and with rownames which should correspond and be in the same order as the `sampleNames` of `esetUsed`

`dataPlotGenes` data.frame with two columns 'X' and 'Y' with coordinates for the genes

`eset` expressionSet (or SummarizedExperiment) object with data

`colorVar` name of variable (in `varLabels` of the `eset`) used for coloring, empty by default

`color` character or factor with specified color(s) for the points, replicated if needed. This is used only if `colorVar` is empty. By default: 'black' if `colorVar` is not specified and default `ggplot` palette otherwise

`shapeVar` name of variable (in `varLabels` of the `eset`) used for the shape, empty by default

`shape` character or factor with specified shape(s) (`pch`) for the points, replicated if needed. This is used only if `shapeVar` is empty. By default: '15' (filled square) if `shapeVar` is not specified and default `ggplot` shape(s) otherwise

`sizeVar` name of variable (in `varLabels` of the `eset`) used for the size, empty by default

`size` size character or factor with specified size(s) (`cex`) for the points, replicated if needed. This is used only if `sizeVar` is empty. By default: '2.5' if `sizeVar` is not specified and default `ggplot` size(s) otherwise

`sizeRange`, `size` (`cex`) range used in the plot, possible only if the `sizeVar` is 'numeric' or 'integer'

`alphaVar` name of variable (in `varLabels` of the `eset`) used for the transparency, empty by default.

`alpha` alpha character or factor with specified transparency(s) for the points, replicated if needed. This is used only if `shapeVar` is empty. By default: '1' if `alphaVar` is not specified and default `ggplot` alpha otherwise.

`alphaRange` transparency (alpha) range used in the plot, possible only if the `alphaVar` is 'numeric' or 'integer'

`symmetryAxes` set symmetry for axes, either:

- 'combine' (by default): both axes are symmetric and with the same limits
- 'separate': each axis is symmetric and has its own limits
- 'none': axes by default (plot limits)

`cloudGenes` logical, if TRUE (by default), include the cloud of genes in the spectral map

`cloudGenesColor` if `cloudGenes` is TRUE, color for the cloud of genes, black by default

`cloudGenesNBins` number of bins to used for the clouds of genes, by default the square root of the number of genes

`cloudGenesIncludeLegend` logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends)

`cloudGenesTitleLegend` string with title for the legend for the cloud of genes 'nGenes' by default

`packageTextLabel` package used to label the outlying genes/samples/gene sets, either `ggrepel` (by default, only used if package `ggrepel` is available), or `ggplot2`

- `topGenes` numeric indicating which percentile (if <1) or number (if ≥ 1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected. If no genes should be annotated, set this parameter to 0. Currently only available for static plot.
- `topGenesCex` cex for gene annotation (used when `topGenes > 0`)
- `topGenesVar` variable of the `featureData` used to label the genes, by default: empty, the `featureNames` are used for labelling (used when `topGenes > 0`)
- `topGenesJust` text justification for the genes (used when `topGenes > 0` and if `packageTextLabel` is `ggplot2`), by default: `c(0.5, 0.5)` so centered
- `topGenesColor` text color for the genes (used when `topGenes > 0`), black by default
- `topSamples` numeric indicating which percentile (if <1) or number (if ≥ 1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected. If no samples should be annotated, set this parameter to 0. Currently available for static plot.
- `topSamplesCex` cex for sample annotation (used when `topSamples > 0`)
- `topSamplesVar` variable of the `phenoData` used to label the samples, by default: empty, the `sampleNames` are used for labelling (used when `topSamples > 0`)
- `topSamplesJust` text justification for the samples (used when `topSamples > 0` and if `packageTextLabel` is `ggplot2`), by default: `c(0.5, 0.5)` so centered
- `topSamplesColor` text color for the samples (used when `topSamples > 0`), black by default
- `geneSets` list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the `getGeneSetsForPlot` function or any custom list of pathways. The genes identifiers should correspond to the variable `geneSetsVar` contained in the `phenoData`, if not specified the `featureNames` are used. If several gene sets have the same name, they will be combine to extract the top gene sets.
- `geneSetsVar` variable of the `featureData` used to match the genes contained in `geneSets`, most probably `ENTREZID`, if not specified the `featureNames` of the `eSet` are used. Only used when `topGeneSets > 0` and the parameter `geneSets` is specified.
- `geneSetsMaxNChar` maximum number of characters for pathway names, by default keep entire names. Only used when `topGeneSets > 0` and the parameter `geneSets` is specified.
- `topGeneSets` numeric indicating which percentile (if ≤ 1) or number (if > 1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected. If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when `topGeneSets > 0` and the parameter `geneSets` is specified.
- `topGeneSetsCex` cex for gene sets annotation. Only used when `topGeneSets > 0` and the parameter `geneSets` is specified.
- `topGeneSetsJust` text justification for the gene sets by default: `c(0.5, 0.5)` so centered. Only used when `topGeneSets > 0`, the parameter `geneSets` is specified and if `packageTextLabel` is `ggplot2`.
- `topGeneSetsColor` color for the gene sets (used when `topGeneSets > 0` and `geneSets` is specified), black by default. Only used when `topGeneSets > 0` and the parameter `geneSets` is specified.
- `includeLegend` logical if `TRUE` (by default) include a legend, otherwise not
- `includeLineOrigin` if `TRUE` (by default) include vertical line at $x = 0$ and horizontal line at $y = 0$

eSetPlotInteractive-class
a S4 class to represent interactive plots

Description

a S4 class to represent interactive plots

Value

S4 object of class eSetPlotInteractive

Slots

`includeTooltip` logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot
`tooltipVars` name of extra phenotypic variable(s) to add in `plotlyESetPlot` to label the samples
`sizePlot` vector containing the size of the interactive plot, as [width, height], by default: `c(600, 400)`.
`title` string plot title, " by default
`xlab` string label for the x axis
`ylab` string label for the y axis

Author(s)

Laure Cougnaud

eSetPlotWrapper *wrapper for biplot of features/samples contained in a eSet object*

Description

Wrapper function used for all plots of the visualizations contained in the package.

Usage

```
eSetPlotWrapper(
  dataPlotSamples,
  dataPlotGenes = data.frame(),
  eSetUsed,
  xlab = "",
  ylab = "",
  colorVar = character(0),
  color = if (length(colorVar) == 0) "black" else character(0),
  shapeVar = character(0),
  shape = if (length(shapeVar) == 0) 15 else numeric(0),
  sizeVar = character(0),
  size = if (length(sizeVar) == 0) {
```

```

        ifelse(typePlot[1] == "interactive" &&
              packageInteractivity[1] == "plotly", 20, 2.5)
    } else {
        numeric()
    },
    sizeRange = numeric(0),
    alphaVar = character(0),
    alpha = if (length(alphaVar) == 0) 1 else numeric(0),
    alphaRange = numeric(0),
    title = "",
    symmetryAxes = c("combine", "separate", "none"),
    cloudGenes = TRUE,
    cloudGenesColor = "black",
    cloudGenesNBins = if (nrow(dataPlotGenes) > 0) sqrt(nrow(dataPlotGenes)) else numeric(),
    cloudGenesIncludeLegend = FALSE,
    cloudGenesTitleLegend = "nGenes",
    packageTextLabel = c("ggrepel", "ggplot2"),
    topGenes = 10,
    topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
                        "plotly", 10, 2.5),
    topGenesVar = character(0),
    topGenesJust = c(0.5, 0.5),
    topGenesColor = "black",
    topSamples = 10,
    topSamplesCex = 2.5,
    topSamplesVar = character(0),
    topSamplesJust = c(0.5, 0.5),
    topSamplesColor = "black",
    geneSets = list(),
    geneSetsVar = character(0),
    geneSetsMaxNChar = numeric(0),
    topGeneSets = 10,
    topGeneSetsCex = 2.5,
    topGeneSetsJust = c(0.5, 0.5),
    topGeneSetsColor = "black",
    includeLegend = TRUE,
    includeLineOrigin = TRUE,
    typePlot = c("static", "interactive"),
    figInteractiveSize = c(600, 400),
    ggvisAdjustLegend = TRUE,
    interactiveTooltip = TRUE,
    interactiveTooltipExtraVars = character(0),
    packageInteractivity = c("plotly", "ggvis"),
    returnTopElements = FALSE,
    returnEsetPlot = FALSE
)

```

Arguments

`dataPlotSamples`

data.frame with columns 'X', 'Y' with coordinates for the samples and with rownames which should correspond and be in the same order as the sample-Names of `esetUsed`

| | |
|-------------------------|---|
| dataPlotGenes | data.frame with two columns 'X' and 'Y' with coordinates for the genes |
| esetUsed | expressionSet (or SummarizedExperiment) object with data |
| xlab | label for the x axis |
| ylab | label for the y axis |
| colorVar | name of variable (in varLabels of the eset) used for coloring, empty by default |
| color | character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise |
| shapeVar | name of variable (in varLabels of the eset) used for the shape, empty by default |
| shape | character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise |
| sizeVar | name of variable (in varLabels of the eset) used for the size, empty by default |
| size | character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise |
| sizeRange | size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer' |
| alphaVar | name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case). |
| alpha | character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis. |
| alphaRange | transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot. |
| title | plot title, "" by default |
| symmetryAxes | set symmetry for axes, either: <ul style="list-style-type: none"> • 'combine' (by default): both axes are symmetric and with the same limits • 'separate': each axis is symmetric and has its own limits • 'none': axes by default (plot limits) |
| cloudGenes | logical, if TRUE (by default), include the cloud of genes in the plot |
| cloudGenesColor | if cloudGenes is TRUE, color for the cloud of genes, black by default |
| cloudGenesNBins | number of bins to used for the clouds of genes, by default the square root of the number of genes |
| cloudGenesIncludeLegend | logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends) |
| cloudGenesTitleLegend | string with title for the legend for the cloud of genes 'nGenes' by default |
| packageTextLabel | package used to label the outlying genes/samples/gene sets, either ggrepel (by default, only used if package ggrepel is available), or ggplot2 |

| | |
|------------------|---|
| topGenes | numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot. |
| topGenesCex | cex for gene annotation (used when topGenes > 0) |
| topGenesVar | variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when topGenes > 0) |
| topGenesJust | text justification for the genes (used when topGenes > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topGenesColor | text color for the genes (used when topGenes > 0), black by default |
| topSamples | numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot. |
| topSamplesCex | cex for sample annotation (used when topSamples > 0) |
| topSamplesVar | variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0) |
| topSamplesJust | text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topSamplesColor | text color for the samples (used when topSamples > 0), black by default |
| geneSets | list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets. |
| geneSetsVar | variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| geneSetsMaxNChar | maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters) |
| topGeneSets | numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| topGeneSetsCex | cex for gene sets annotation Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| topGeneSetsJust | text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when topGeneSets > 0, the parameter geneSets is specified and if packageTextLabel is ggplot2. |

| | |
|--|---|
| <code>topGeneSetsColor</code> | color for the gene sets (used when <code>topGeneSets > 0</code> and <code>geneSets</code> is specified), black by default Only used when <code>topGeneSets > 0</code> and the parameter <code>geneSets</code> is specified. |
| <code>includeLegend</code> | logical if TRUE (by default) include a legend, otherwise not |
| <code>includeLineOrigin</code> | if TRUE (by default) include vertical line at <code>x = 0</code> and horizontal line at <code>y = 0</code> |
| <code>typePlot</code> | type of the plot returned, either 'static' (static) or 'interactive' (potentially interactive) |
| <code>figInteractiveSize</code> | vector containing the size of the interactive plot, as [width, height] by default: <code>c(600, 400)</code> . This is passed to the <code>width</code> and <code>height</code> parameters of: <ul style="list-style-type: none"> • for plotly plots: the <code>ggplotly</code> function • for ggvis plots: the <code>ggvis::set_options</code> function |
| <code>ggvisAdjustLegend</code> | logical, if TRUE (by default) adjust the legends in ggvis to avoid overlapping legends when multiple legends |
| <code>interactiveTooltip</code> | logical, if TRUE, add hover functionality showing sample annotation (variables used in the plot) in the plot |
| <code>interactiveTooltipExtraVars</code> | name of extra variable(s) (in <code>varLabels</code> of the <code>eset</code>) to add in <code>plotlyEsetPlot</code> to label the samples, empty by default |
| <code>packageInteractivity</code> | if <code>typePlot</code> is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'. |
| <code>returnTopElements</code> | logical, if TRUE return also the top elements |
| <code>returnEsetPlot</code> | logical, if TRUE return also the <code>esetPlot</code> object |

Value

if `typePlot` is:

- `static`:
 - if `returnTopElements` is TRUE, and top elements can be displayed, a list with:
 - * 'topElements': the top elements labelled in the plot
 - * 'plot': the ggplot object
 - otherwise, the ggplot object only
- `interactive`: a ggvis or plotly object, depending on the `packageInteractivity` parameter

Author(s)

Laure Cougnaud

Examples

```

library(ALL)
data(ALL)

## run one spectral map analysis

# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white", "dodgerblue2", "darkblue"))(5)[-1],
  "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])

# run the analysis
# with 'returnAnalysis' set to TRUE to have all objects required for the esetPlotWrapper
outputEsetSPM <- esetSpectralMap(eset = ALL,
  title = "Acute lymphoblastic leukemia dataset \n Spectral map complete",
  colorVar = "BT", color = colorPalette,
  shapeVar = "sex", shape = 15:16,
  sizeVar = "age", sizeRange = c(2, 6),
  symmetryAxes = "separate",
  topGenes = 10, topGenesJust = c(1, 0), topGenesCex = 2, topGenesColor = "darkgrey",
  topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
  topSamplesJust = c(1, 0), topSamplesCex = 3, returnAnalysis = TRUE)

# plot the biplot
print(outputEsetSPM$plot)

## re-call the plot function, to change some visualizations parameters
esetPlotWrapper(
  dataPlotSamples = outputEsetSPM$analysis$dataPlotSamples,
  dataPlotGenes = outputEsetSPM$analysis$dataPlotGenes,
  esetUsed = outputEsetSPM$analysis$esetUsed,
  title = paste("Acute lymphoblastic leukemia dataset \n Spectral map"),
  colorVar = "BT", color = colorPalette,
  shapeVar = "relapse",
  sizeVar = "age", sizeRange = c(2, 6),
  topSamplesVar = "cod", topGenesVar = "SYMBOL"
)

```

esetSpectralMap

plot a spectral map biplot of an [eSet](#).

Description

esetSpectralMap reduces the dimension of the data contained in the [eSet](#) with the [mpm](#) function and plot the subsequent biplot of the specified dimensions, possibly with gene and sample annotation contained in the [eSet](#). A spectral map with the default parameters is equivalent to a principal component analysis on the log-transformed, double centered and global normalized data (from documentation of the [mpm](#) function).

Usage

```

esetSpectralMap(
  eset,

```

```

psids = 1:nrow(eset),
dim = c(1, 2),
colorVar = character(),
color = if (length(colorVar) == 0) "black" else character(),
shapeVar = character(),
shape = if (length(shapeVar) == 0) 15 else numeric(),
sizeVar = character(),
size = if (length(sizeVar) == 0) {
  ifelse(typePlot[1] == "interactive" &&
    packageInteractivity[1] == "plotly", 20, 2.5)
} else {
  numeric()
},
sizeRange = numeric(),
alphaVar = character(),
alpha = if (length(alphaVar) == 0) 1 else numeric(),
alphaRange = numeric(),
title = "",
mpm.args = list(closure = "none", center = "double", normal = "global", row.weight =
  "mean", col.weight = "constant", logtrans = FALSE),
plot.mpm.args = list(scale = "uvc"),
symmetryAxes = c("combine", "separate", "none"),
packageTextLabel = c("ggrepel", "ggplot2"),
cloudGenes = TRUE,
cloudGenesColor = "black",
cloudGenesNBins = sqrt(length(psids)),
cloudGenesIncludeLegend = FALSE,
cloudGenesTitleLegend = "nGenes",
topGenes = 10,
topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
  "plotly", 10, 2.5),
topGenesVar = character(),
topGenesJust = c(0.5, 0.5),
topGenesColor = "black",
topSamples = 10,
topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
  "plotly", 10, 2.5),
topSamplesVar = character(),
topSamplesJust = c(0.5, 0.5),
topSamplesColor = "black",
geneSets = list(),
geneSetsVar = character(),
geneSetsMaxNChar = numeric(),
topGeneSets = 10,
topGeneSetsCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
  "plotly", 10, 2.5),
topGeneSetsJust = c(0.5, 0.5),
topGeneSetsColor = "black",
includeLegend = TRUE,
includeLineOrigin = TRUE,
typePlot = c("static", "interactive"),
packageInteractivity = c("plotly", "ggvis"),

```



```

figInteractiveSize = c(600, 400),
ggvisAdjustLegend = TRUE,
interactiveTooltip = TRUE,
interactiveTooltipExtraVars = character(),
returnAnalysis = FALSE,
returnEsetPlot = FALSE
)

```

Arguments

| | |
|---------------|--|
| eset | expressionSet (or SummarizedExperiment) object with data |
| psids | featureNames of genes to include in the plot, all by default |
| dim | dimensions of the analysis to represent, first two dimensions by default |
| colorVar | name of variable (in varLabels of the eset) used for coloring, empty by default |
| color | character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise |
| shapeVar | name of variable (in varLabels of the eset) used for the shape, empty by default |
| shape | character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise |
| sizeVar | name of variable (in varLabels of the eset) used for the size, empty by default |
| size | character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise |
| sizeRange | size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer' |
| alphaVar | name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case). |
| alpha | character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis. |
| alphaRange | transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot. |
| title | plot title, "" by default |
| mpm.args | list with input parameters for the <code>mpm</code> function. The default value is: <code>list(closure = 'none', center = 'double', normal = 'global', 'row.weight' = 'mean', col.weight = 'constant', logtrans = FALSE)</code> . This assumes that the data are already in a log scale. |
| plot.mpm.args | list with input parameters for the <code>plot.mpm</code> function. The default value is: <code>list(scale = "uvc")</code> . |
| symmetryAxes | set symmetry for axes, either: <ul style="list-style-type: none"> • 'combine' (by default): both axes are symmetric and with the same limits • 'separate': each axis is symmetric and has its own limits |

- 'none': axes by default (plot limits)

| | |
|-------------------------|---|
| packageTextLabel | package used to label the outlying genes/samples/gene sets, either ggrepel (by default, only used if package ggrepel is available), or ggplot2 |
| cloudGenes | logical, if TRUE (by default), include the cloud of genes in the plot |
| cloudGenesColor | if cloudGenes is TRUE, color for the cloud of genes, black by default |
| cloudGenesNBins | number of bins to used for the clouds of genes, by default the square root of the number of genes |
| cloudGenesIncludeLegend | logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends) |
| cloudGenesTitleLegend | string with title for the legend for the cloud of genes 'nGenes' by default |
| topGenes | numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot. |
| topGenesCex | cex for gene annotation (used when topGenes > 0) |
| topGenesVar | variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when topGenes > 0) |
| topGenesJust | text justification for the genes (used when topGenes > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topGenesColor | text color for the genes (used when topGenes > 0), black by default |
| topSamples | numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot. |
| topSamplesCex | cex for sample annotation (used when topSamples > 0) |
| topSamplesVar | variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0) |
| topSamplesJust | text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered |
| topSamplesColor | text color for the samples (used when topSamples > 0), black by default |
| geneSets | list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets. |
| geneSetsVar | variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| geneSetsMaxNChar | maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. |

If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters)

| | |
|-----------------------------|---|
| topGeneSets | numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| topGeneSetsCex | cex for gene sets annotation Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| topGeneSetsJust | text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when topGeneSets > 0, the parameter geneSets is specified and if packageTextLabel is ggplot2. |
| topGeneSetsColor | color for the gene sets (used when topGeneSets > 0 and geneSets is specified), black by default Only used when topGeneSets > 0 and the parameter geneSets is specified. |
| includeLegend | logical if TRUE (by default) include a legend, otherwise not |
| includeLineOrigin | if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0 |
| typePlot | type of the plot returned, either 'static' (static) or 'interactive' (potentially interactive) |
| packageInteractivity | if typePlot is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'. |
| figInteractiveSize | vector containing the size of the interactive plot, as [width, height] by default: c(600, 400). This is passed to the width and height parameters of: <ul style="list-style-type: none"> • for plotly plots: the ggplotly function • for ggvis plots: the <code>ggvis::set_options</code> function |
| ggvisAdjustLegend | logical, if TRUE (by default) adjust the legends in ggvis to avoid overlapping legends when multiple legends |
| interactiveTooltip | logical, if TRUE, add hover functionality showing sample annotation (variables used in the plot) in the plot |
| interactiveTooltipExtraVars | name of extra variable(s) (in varLabels of the eset) to add in plotlyEsetPlot to label the samples, empty by default |
| returnAnalysis | logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the topElements element if any, otherwise only the plot object |
| returnEsetPlot | logical, if TRUE return also the esetPlot object |

Value

if returnAnalysis is TRUE, return a list:

- analysis: output of the spectral map analysis, can be given as input to the `esetPlotWrapper` function
 - `dataPlotSamples`: coordinates of the samples
 - `dataPlotGenes`: coordinates of the genes
 - `esetUsed`: expressionSet used in the plot
 - `axisLabels`: axes labels indicating percentage of variance explained by the selected axes
 - `axesContributionsPercentages`: percentages of variance explained by each axis (not only the ones specified in `dim`)
- `topElements`: list with top outlying elements if any, possibly genes, samples and gene sets
- `plot`: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

Lewi, P.J. (1976). Spectral mapping, a technique for classifying biological activity profiles of chemical compounds. *Arzneimittel Forschung (Drug Research)*, 26, 1295–1300

See Also

the function used internally: [mpm](#) and [spectralMap](#) for spectral map in base R graphics

Examples

```
library(ALL)
data(ALL)

## complete example (most of the parameters are optional)
# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white", "dodgerblue2", "darkblue"))(5)[-1],
  "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])
# plot the spectral map
print(esetSpectralMap(eset = ALL,
  title = "Acute lymphoblastic leukemia dataset \n Spectral map complete",
  colorVar = "BT", color = colorPalette,
  shapeVar = "sex", shape = 15:16,
  sizeVar = "age", sizeRange = c(2, 6),
  symmetryAxes = "separate",
  topGenes = 10, topGenesJust = c(1, 0), topGenesCex = 2, topGenesColor = "darkgrey",
  topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
  topSamplesJust = c(1, 0), topSamplesCex = 3)
)

# see vignette for other examples, especially one with gene sets specification
```

esetTsne *plot a t-SNE of an eSet object*

Description

esetTsne reduces the dimension of the data contained in the [eSet](#) via t-Distributed Stochastic Neighbor Embedding with the [Rtsne](#) function and plot the subsequent biplot, possibly with sample annotation contained in the eSet.

Usage

```

esetTsne(
  eset,
  psids = 1:nrow(eset),
  trace = TRUE,
  colorVar = character(),
  color = if (length(colorVar) == 0) "black" else character(),
  shapeVar = character(),
  shape = if (length(shapeVar) == 0) 15 else numeric(),
  sizeVar = character(),
  size = if (length(sizeVar) == 0) {
    ifelse(typePlot[1] == "interactive" &&
      packageInteractivity[1] == "plotly", 20, 2.5)
  } else {
    numeric()
  },
  sizeRange = numeric(),
  alphaVar = character(),
  alpha = if (length(alphaVar) == 0) 1 else numeric(),
  alphaRange = numeric(),
  title = "",
  Rtsne.args = list(perplexity = floor((ncol(eset) - 1)/3), theta = 0.5, dims = 2,
    initial_dims = 50),
  fctTransformDataForInputTsne = NULL,
  symmetryAxes = c("combine", "separate", "none"),
  packageTextLabel = c("ggrepel", "ggplot2"),
  topSamples = 10,
  topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topSamplesVar = character(),
  topSamplesJust = c(0.5, 0.5),
  topSamplesColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),
  packageInteractivity = c("plotly", "ggvis"),
  figInteractiveSize = c(600, 400),
  ggvisAdjustLegend = TRUE,
  interactiveTooltip = TRUE,
  interactiveTooltipExtraVars = character(),
  returnAnalysis = FALSE,

```

```

    returnEsetPlot = FALSE
  )

```

Arguments

| | |
|---|---|
| <code>eset</code> | expressionSet (or SummarizedExperiment) object with data |
| <code>psids</code> | featureNames of genes to include in the plot, all by default |
| <code>trace</code> | logical, if TRUE (by default), print some messages during tsne is running |
| <code>colorVar</code> | name of variable (in varLabels of the eset) used for coloring, empty by default |
| <code>color</code> | character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise |
| <code>shapeVar</code> | name of variable (in varLabels of the eset) used for the shape, empty by default |
| <code>shape</code> | character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise |
| <code>sizeVar</code> | name of variable (in varLabels of the eset) used for the size, empty by default |
| <code>size</code> | character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise |
| <code>sizeRange</code> | size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer' |
| <code>alphaVar</code> | name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case). |
| <code>alpha</code> | character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis. |
| <code>alphaRange</code> | transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot. |
| <code>title</code> | plot title, "" by default |
| <code>Rtsne.args</code> | arguments for the Rtsne function, by default: perplexite parameter = optimal number of neighbours, theta = speed/accuracy trade-off (increase for less accuracy), set to 0.0 for exact TSNE |
| <code>fctTransformDataForInputTsne</code> | function which transform the data in the eSet object before calling the <code>Rtsne</code> function. This should be a function which takes a matrix as input and return a matrix, e.g. the <code>dist</code> function. |
| <code>symmetryAxes</code> | set symmetry for axes, either: <ul style="list-style-type: none"> 'combine' (by default): both axes are symmetric and with the same limits 'separate': each axis is symmetric and has its own limits 'none': axes by default (plot limits) |
| <code>packageTextLabel</code> | package used to label the outlying genes/samples/gene sets, either <code>ggrepel</code> (by default, only used if package <code>ggrepel</code> is available), or <code>ggplot2</code> |

| | |
|--|---|
| <code>topSamples</code> | numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected. If no samples should be annotated, set this parameter to 0. Currently available for static plot. |
| <code>topSamplesCex</code> | cex for sample annotation (used when <code>topSamples > 0</code>) |
| <code>topSamplesVar</code> | variable of the <code>phenoData</code> used to label the samples, by default: empty, the <code>sampleNames</code> are used for labelling (used when <code>topSamples > 0</code>) |
| <code>topSamplesJust</code> | text justification for the samples (used when <code>topSamples > 0</code> and if <code>packageTextLabel</code> is <code>ggplot2</code>), by default: <code>c(0.5, 0.5)</code> so centered |
| <code>topSamplesColor</code> | text color for the samples (used when <code>topSamples > 0</code>), black by default |
| <code>includeLegend</code> | logical if TRUE (by default) include a legend, otherwise not |
| <code>includeLineOrigin</code> | if TRUE (by default) include vertical line at <code>x = 0</code> and horizontal line at <code>y = 0</code> |
| <code>typePlot</code> | type of the plot returned, either 'static' (static) or 'interactive' (potentially interactive) |
| <code>packageInteractivity</code> | if <code>typePlot</code> is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'. |
| <code>figInteractiveSize</code> | vector containing the size of the interactive plot, as [width, height] by default: <code>c(600, 400)</code> . This is passed to the <code>width</code> and <code>height</code> parameters of: <ul style="list-style-type: none"> • for plotly plots: the <code>ggplotly</code> function • for ggvis plots: the <code>ggvis::set_options</code> function |
| <code>ggvisAdjustLegend</code> | logical, if TRUE (by default) adjust the legends in <code>ggvis</code> to avoid overlapping legends when multiple legends |
| <code>interactiveTooltip</code> | logical, if TRUE, add hover functionality showing sample annotation (variables used in the plot) in the plot |
| <code>interactiveTooltipExtraVars</code> | name of extra variable(s) (in <code>varLabels</code> of the <code>eset</code>) to add in <code>plotlyEsetPlot</code> to label the samples, empty by default |
| <code>returnAnalysis</code> | logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the <code>topElements</code> element if any, otherwise only the plot object |
| <code>returnEsetPlot</code> | logical, if TRUE return also the <code>esetPlot</code> object |

Value

if `returnAnalysis` is TRUE, return a list:

- `analysis`: output of the spectral map analysis, whose elements can be given to the `esetPlotWrapper` function
 - `dataPlotSamples`: coordinates of the samples
 - `esetUsed`: expressionSet used in the plot
- `topElements`: list with top outlying elements if any, possibly genes, samples and gene sets
- `plot`: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

L.J.P. van der Maaten and G.E. Hinton (2008). Visualizing High-Dimensional Data Using t-SNE. *Journal of Machine Learning Research*, 2579–2605

See Also

the function used internally: [Rtsne](#) or <http://homepage.tudelft.nl/19j49/t-SNE.html> for further explanations about this technique.

Examples

```
library(ALL)
data(ALL)

## complete example (most of the parameters are optional)

# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white", "dodgerblue2", "darkblue"))(5)[-1],
  "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])

# create tsne
print(esetTsne(eset = ALL,
  title = "Acute lymphoblastic leukemia dataset \n Tsne complete",
  colorVar = "BT", color = colorPalette,
  shapeVar = "sex", shape = 15:16,
  sizeVar = "age", sizeRange = c(2, 6),
  symmetryAxes = "separate",
  topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
  topSamplesJust = c(1, 0), topSamplesCex = 3)
)
```

| | |
|-------------------|---|
| formatManualScale | <i>extend manual scale values if required</i> |
|-------------------|---|

Description

extend manual scale values if required

Usage

```
formatManualScale(x, valVar, nameVar)
```

Arguments

| | |
|---------|--------------------------------------|
| x | data.frame with nameVar |
| valVar | fixed value of variable of aesthetic |
| nameVar | name of variable for aesthetic |

Value

vector of manual scales

Author(s)

Laure Cougnaud

| | |
|--------------|---|
| formatOutput | <i>format output of plotEset function</i> |
|--------------|---|

Description

format output of [plotEset](#) function

Usage

```
formatOutput(res, object, type, returnEsetPlot)
```

Arguments

| | |
|----------------|--|
| res | result of specific plotEset function |
| object | esetPlot object or extended class |
| type | string type of plot |
| returnEsetPlot | logical, should the object be returned in the output function? |

Value

result

Author(s)

Laure Cougnaud

| | |
|---------------|------------------------------------|
| getAxesLimits | <i>generic for get axes limits</i> |
|---------------|------------------------------------|

Description

generic for get axes limits

Usage

```
getAxesLimits(object)
```

```
## S4 method for signature 'esetPlot'  
getAxesLimits(object)
```

Arguments

| | |
|--------|---------------------------------|
| object | plotEset object |
|--------|---------------------------------|

Value

matrix with limits for axes: columns x and y

Author(s)

Laure Cougnaud

| | |
|------------------|--------------------------------------|
| getCoordGeneSets | <i>extract coordinates gene sets</i> |
|------------------|--------------------------------------|

Description

extract coordinates gene sets

Usage

```
getCoordGeneSets(dataPlotGenes, geneSets, esetUsed, geneSetsVar = list())
```

Arguments

| | |
|---------------|--|
| dataPlotGenes | data.frame with two columns 'X' and 'Y' with coordinates for the genes |
| geneSets | geneSets list of gene sets, e.g. gene pathways, output from the 'getGeneSets' function in MLP the genes IDs must correspond to the sampleNames in the eset |
| esetUsed | expressionSet (or SummarizedExperiment) object with data |
| geneSetsVar | variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if NULL the featureNames of the eSet are used |
| ... | Any parameters passed to the getTopElements |

Value

data.frame with two columns 'X' and 'Y' with coordinates for the gene sets

Author(s)

Laure Cougnaud

```
getDataPlotSamplesWithAnnotation
      get sample data for plot
```

Description

get sample data for plot

Usage

```
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'eSetPlot'
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'ggvisEsetPlot'
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'plotlyEsetPlot'
getDataPlotSamplesWithAnnotation(object)
```

Arguments

object [plotEset](#) object

Value

data.frame with 'dataPlotSamples' binded with variables displayed in the plot

Author(s)

Laure Cougnaud

```
getGeneSetsForPlot    get gene sets for plot of eSet object.
```

Description

get and format gene sets to be used as geneSets for the functions: [eSetSpectralMap](#), [eSetLda](#), or [eSetPlotWrapper](#) Use the [getGeneSets](#) function to get the gene sets, combine all databases, and format the gene sets name if required.

Usage

```
getGeneSetsForPlot(
  entrezIdentifiers,
  species = "Human",
  geneSetSource = c("GOBP", "GOMF", "GOCC", "KEGG"),
  useDescription = TRUE,
  trace = TRUE
)
```

Arguments

| | |
|--------------------------------|--|
| <code>entrezIdentifiers</code> | string with Entrez Gene identifiers of the genes of interest |
| <code>species</code> | species to use, given to the getGeneSets function |
| <code>geneSetSource</code> | gene set source, either 'GOBP', 'GOMF', 'GOCC' or 'KEGG'. Multiple choices are available |
| <code>useDescription</code> | logical, if TRUE (by default) use the description to label the gene sets, otherwise use the original gene set identifiers Function 'substr' is used. |
| <code>trace</code> | logical, if TRUE (by default) a few extra information are printed during the process |

Value

list with gene sets, each element is a gene set and contains the ENTREZ IDs of the genes contained in this set. If `useDescription` is:

- FALSE: pathways are labelled with identifiers (Gene Ontology IDs for GOBP, GOMF and GOCC, KEGG IDs for KEGG)
- TRUE: pathways are labelled with gene sets descriptions

Author(s)

Laure Cougnaud

See Also

the function used internally: [getGeneSets](#)

Examples

```
# example dataset
library(ALL)
data(ALL)

# get gene annotation from probe IDs
library("hgu95av2.db")
probeIDs <- featureNames(ALL)
geneInfo <- select(hgu95av2.db, probeIDs, "ENTREZID", "PROBEID")

# get pathway annotation for the genes contained in the ALL dataset (can take a few minutes)
geneSets <- getGeneSetsForPlot(entrezIdentifiers = geneInfo$ENTREZID, species = "Human",
  geneSetSource = 'GOBP',
  useDescription = FALSE, trace = TRUE)
head(geneSets) # returns a pathway list of genes

# gene sets labelled with gene sets description
geneSets <- getGeneSetsForPlot(entrezIdentifiers = geneInfo$ENTREZID, species = "Human",
  geneSetSource = 'GOBP', useDescription = TRUE, trace = TRUE)
head(geneSets) # returns a pathway list of genes

# see also vignette for an example of the use of this function as input for the esetSpectralMap, esetLda or esetP
```

getMethodsInputObjectEsetVis

wrapper to extract useful functions, depending if the object is an ExpressionSet or a SummarizedExperiment.

Description

This returns an error if x is not of the correct class. The package SummarizedExperiment should be available if x is of class SummarizedExperiment.

Usage

```
getMethodsInputObjectEsetVis(x)
```

Arguments

x object

Value

if the object is an ExpressionSet or a SummarizedExperiment, returns a list with the functions specific of the class of x, and equivalent of the ExpressionSet functions: 'sampleNames', 'featureNames', 'fData', 'pData', 'exprs'

- sampleNames: sample names
- featureNames: feature names
- fData: feature annotation
- pData: sample annotation
- exprs: data matrix
- varLabels: sample annotation variables
- fvarLabels: feature annotation variables

Author(s)

Laure Cougnaud

getTopElements

create geom_text object with top genes/sample/pathways

Description

create geom_text object with top genes/sample/pathways

Usage

```

getTopElements(
  top,
  type = c("gene", "sample", "geneSets"),
  var = character(),
  dataPlotGenes = data.frame(),
  dataPlotSamples = data.frame(),
  esetUsed,
  geneSets = list(),
  geneSetsVar = character(),
  geneSetsMaxNChar = numeric()
)

```

Arguments

| | |
|-------------------|--|
| top | numeric, number of top elements |
| type | type of elements to plot, either 'gene', 'sample', or 'geneSets' |
| var | variable used to annotate the elements, only used for 'gene' and 'sample' |
| dataPlotGenes | data.frame with two columns 'X' and 'Y' with coordinates for the genes |
| dataPlotSamples | data.frame with two columns 'X' and 'Y' with coordinates for the samples |
| esetUsed | expressionSet (or SummarizedExperiment) object with data |
| geneSets | list of gene sets, e.g. gene pathways, output from the 'getGeneSets' function in MLP the genes IDs must correspond to the sampleNames in the eset. If several gene sets have the same name, they will be combine to extract the top gene sets. |
| geneSetsVar | variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used |
| geneSetsMaxNChar | maximum number of characters for pathway names, by default keep entire names |
| returnTopElements | logical if TRUE (FALSE by default) return the outlying elements |

Value

Data.frame with coordinates and labels of the top elements

Author(s)

Laure Cougnaud

ggPlotEset

visualize and esetPlot with the 'ggplot2' package

Description

visualize and [esetPlot](#) with the 'ggplot2' package

Usage

`ggPlotEset(object)`

Arguments

`object` object of class `esetPlot`

Value

ggplot object

Author(s)

Laure Cougnaud

`ggplotEsetPlot-class` *a S4 class to represent ggplot plots*

Description

a S4 class to represent ggplot plots

Value

S4 object of class `ggplotEsetPlot`

Slots

`returnTopElements` logical, if TRUE (FALSE by default) return the outlying elements labelled in the plot (if any)

`title` string or expression with plot title, " by default

`xlab` string or expression with label for the x axis

`ylab` string or expression with label for the y axis

Author(s)

Laure Cougnaud

ggvisEsetPlot-class *a S4 class for ggvis plot*

Description

a S4 class for ggvis plot

Value

S4 object of class ggvisEsetPlot

Slots

adjustLegend logical, if TRUE (by default) adjust the legends in ggvis to avoid overlapping legends when multiple legends

alphaRange transparency (alpha) range used in the plot, c(0.1, 1) by default.

Author(s)

Laure Cougnaud

ggvisPlotEset *visualize and [esetPlot](#) with the the 'ggvis' package*

Description

visualize and [esetPlot](#) with the the 'ggvis' package

Usage

```
ggvisPlotEset(object)
```

Arguments

object object of class [esetPlot](#)

Value

ggvis plot object

Author(s)

Laure Cougnaud

| | |
|----------|--|
| plotEset | <i>plot an plotEset object</i> |
|----------|--|

Description

plot an [plotEset](#) object

Usage

```
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'ggplotEsetPlot'
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'ggvisEsetPlot'
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'plotlyEsetPlot'
plotEset(object, returnEsetPlot = FALSE)
```

Arguments

| | |
|----------------|---|
| object | object of class esetPlot |
| returnEsetPlot | logical, if TRUE return also the esetPlot object, such as can be re-use for future call to plotEset |

Value

the plot object if returnEsetPlot is FALSE, otherwise a list with 'plot': the plot object and 'eset-Plot': the [esetPlot](#) object

Author(s)

Laure Cougnaud

| | |
|----------------------|---|
| plotlyEsetPlot-class | <i>a S4 class to represent plotly plots</i> |
|----------------------|---|

Description

a S4 class to represent plotly plots

Value

S4 object of class plotlyEsetPlot

Slots

`returnTopElements` logical, if TRUE (FALSE by default) return the outlying elements labelled in the plot (if any)

`size` specified size(s) (cex) for the points, replicated if needed, used only if `sizeVar` is empty, a factor or character by default: '20' if `sizeVar` is not specified

Author(s)

Laure Cougnaud

`plotlyPlotEset` *visualize and `esetPlot` with the the 'plotly' package*

Description

visualize and `esetPlot` with the the 'plotly' package

Usage

```
plotlyPlotEset(object)
```

Arguments

`object` object of class `esetPlot`

Value

plotly plot

Author(s)

Laure Cougnaud

`plotTopElements` *plot top elements for a static plot*

Description

This create `geom_text` object with top genes/sample/pathways

Usage

```
plotTopElements(
  packageTextLabel = c("ggrepel", "ggplot2"),
  cex = 1,
  just = c(0.5, 0.5),
  color = "black",
  returnTopElements = FALSE,
  ...
)
```

Arguments

| | |
|-------------------|--|
| packageTextLabel | package used to label the outlying genes/samples/gene sets, either 'ggrepel' (by default, only used if package ggrepel is available), or 'ggplot2' |
| cex | cex of text in the plot |
| just | justification of elements in the plot, only use if packageTextLabel is 'ggplot2' |
| color | color for the elements in the plot |
| returnTopElements | logical if TRUE (FALSE by default) return the outlying elements |

Value

- if the elements are present in the data: if returnTopElements is:
 - TRUE: return a list with two arguments:
 - * topElements: string with top elements labelled in the plot
 - * geomText: output of geom_text
 - FALSE: only return the output of geom_text
- if not, return NULL

Author(s)

Laure Cougnaud

| | |
|---------------|--|
| setFixElement | <i>check if the aesthetic is fixed (e.g. color, shape, size 'palette')</i> |
|---------------|--|

Description

check if the aesthetic is fixed (e.g. color, shape, size 'palette')

Usage

```
setFixElement(typeVar, valVar)
```

Arguments

| | |
|---------|--------------------------------------|
| typeVar | name of variable for aesthetic |
| valVar | fixed value of variable of aesthetic |

Value

logical, if TRUE the element is fixed

Author(s)

Laure Cougnaud

| | |
|----------------|--|
| setManualScale | <i>check if manual aesthetic should be set</i> |
|----------------|--|

Description

This is the case only if `typeVar` and `valVar` are specified, and if the variable is not numeric or integer (doesn't work with `ggplot2`)

Usage

```
setManualScale(x, typeVar, valVar)
```

Arguments

| | |
|----------------------|--------------------------------------|
| <code>x</code> | data.frame with <code>typeVar</code> |
| <code>typeVar</code> | name of variable for aesthetic |
| <code>valVar</code> | fixed value of variable of aesthetic |

Value

logical, if TRUE the manual scale should be set

Author(s)

Laure Cougnaud

| | |
|-----------|--|
| simpleCap | <i>capitalize the first letter of a word</i> |
|-----------|--|

Description

capitalize the first letter of a word

Usage

```
simpleCap(x)
```

Arguments

| | |
|----------------|--------|
| <code>x</code> | string |
|----------------|--------|

Value

string with first letter capitalized

| | |
|---------|---|
| varToFm | <i>Get formula for a specific variable, to be used in aesthetic specification in plot_ly.</i> |
|---------|---|

Description

Get formula for a specific variable, to be used in aesthetic specification in [plot_ly](#).

Usage

```
varToFm(var)
```

Arguments

var Character vector with variable to combine. Otherwise with the '+' operator.

Value

[as.formula](#)

Author(s)

Laure Cougnaud

Index

* internal

- characterORexpressionOrCall-class, [2](#)
- esetPlot-class, [7](#)
- esetPlotInteractive-class, [10](#)
- formatManualScale, [24](#)
- formatOutput, [25](#)
- getAxesLimits, [25](#)
- getCoordGeneSets, [26](#)
- getDataPlotSamplesWithAnnotation, [27](#)
- getMethodsInputObjectEsetVis, [29](#)
- getTopElements, [29](#)
- ggPlotEset, [30](#)
- ggvisEsetPlot-class, [32](#)
- ggvisPlotEset, [32](#)
- plotEset, [33](#)
- plotlyEsetPlot-class, [33](#)
- plotlyPlotEset, [34](#)
- plotTopElements, [34](#)
- setFixElement, [35](#)
- setManualScale, [36](#)
- simpleCap, [36](#)
- varToFm, [37](#)

as. formula, [37](#)

characterORexpressionOrCall-class, [2](#)

eSet, [2](#), [10](#), [15](#), [21](#), [27](#)

esetLda, [2](#), [27](#)

esetPlot, [6–8](#), [14](#), [19](#), [23](#), [30–34](#)

esetPlot (esetPlot-class), [7](#)

esetPlot-class, [7](#)

esetPlotInteractive (esetPlotInteractive-class), [10](#)

esetPlotInteractive-class, [10](#)

esetPlotWrapper, [6](#), [10](#), [23](#), [27](#)

esetSpectralMap, [15](#), [27](#)

esetTsne, [21](#)

formatManualScale, [24](#)

formatOutput, [25](#)

getAxesLimits, [25](#)

getAxesLimits, esetPlot-method (getAxesLimits), [25](#)

getCoordGeneSets, [26](#)

getDataPlotSamplesWithAnnotation, [27](#)

getDataPlotSamplesWithAnnotation, esetPlot-method (getDataPlotSamplesWithAnnotation), [27](#)

getDataPlotSamplesWithAnnotation, ggvisEsetPlot-method (getDataPlotSamplesWithAnnotation), [27](#)

getDataPlotSamplesWithAnnotation, plotlyEsetPlot-method (getDataPlotSamplesWithAnnotation), [27](#)

getGeneSets, [27](#), [28](#)

getGeneSetsForPlot, [5](#), [9](#), [13](#), [18](#), [27](#)

getMethodsInputObjectEsetVis, [29](#)

getTopElements, [26](#), [29](#)

ggPlotEset, [30](#)

ggplotEsetPlot (ggplotEsetPlot-class), [31](#)

ggplotEsetPlot-class, [31](#)

ggplotly, [6](#), [14](#), [19](#), [23](#)

ggvisEsetPlot (ggvisEsetPlot-class), [32](#)

ggvisEsetPlot-class, [32](#)

ggvisPlotEset, [32](#)

initialize, esetPlot-method (esetPlot-class), [7](#)

lda, [7](#)

mpm, [15](#), [17](#), [20](#)

plot.mpm, [17](#)

plot_ly, [37](#)

plotEset, [25](#), [27](#), [33](#), [33](#)

plotEset, ggplotEsetPlot-method (plotEset), [33](#)

plotEset, ggvisEsetPlot-method (plotEset), [33](#)

plotEset, plotlyEsetPlot-method (plotEset), [33](#)

plotlyEsetPlot (plotlyEsetPlot-class), [33](#)

plotlyEsetPlot-class, [33](#)
plotlyPlotEset, [34](#)
plotTopElements, [34](#)

Rtsne, [21](#), [22](#), [24](#)

setFixElement, [35](#)
setManualScale, [36](#)
simpleCap, [36](#)
spectralMap, [20](#)

varToFm, [37](#)