

Random Numbers in BiocParallel

*Martin Morgan*¹

¹Martin.Morgan@RoswellPark.org

Edited: 7 September, 2021; Compiled: November 29, 2021

Contents

1	Scope	1
2	Essentials	2
2.1	Use of <code>bplapply()</code> and <code>RNGseed=</code>	2
2.2	Use with <code>bpiterate()</code>	3
2.3	Use with <code>bptry()</code>	4
2.4	Relationship between <code>RNGseed=</code> and <code>set.seed()</code>	5
2.5	<code>bpstart()</code> and random number streams	6
2.6	Relationship between <code>bplapply()</code> and <code>lapply()</code>	6
3	Implementation notes	7
4	<code>sessionInfo()</code>	7

1 Scope

BiocParallel enables use of random number streams in a reproducible manner. This document applies to the following `*Param()`:

- `SerialParam()`: sequential evaluation in a single *R* process.
- `SnowParam()`: parallel evaluation in multiple independent *R* processes.
- `MulticoreParam()`: parallel evaluation in *R* sessions running in forked threads. Not available on Windows.

The `*Param()` can be used for evaluation with:

- `bplapply()`: `lapply()`-like application of a user-supplied function `FUN` to a vector or list of elements `X`.
- `bpiterate()`: apply a user-supplied function `FUN` to an unknown number of elements resulting from successive calls to a user-supplied function `ITER`.

The reproducible random number implementation also supports:

- `bptry()` and the `BPRED0=` argument, for re-evaluation of elements that fail (e.g., because of a bug in `FUN`).

2 Essentials

2.1 Use of `bplapply()` and `RNGseed=`

Attach *BiocParallel* and ensure that the version is greater than 1.27.5

```
library(BiocParallel)
stopifnot(
  packageVersion("BiocParallel") > "1.27.5"
)
```

For reproducible calculation, use the `RNGseed=` argument in any of the `*Param()` constructors.

```
result1 <- bplapply(1:3, runif, BPPARAM = SerialParam(RNGseed = 100))
result1
## [[1]]
## [1] 0.7393338
##
## [[2]]
## [1] 0.8216743 0.7451087
##
## [[3]]
## [1] 0.1962909 0.5226640 0.6857650
```

Repeating the calculation with the same value for `RNGseed=` results in the same result; a different random number seed results in different results.

```
result2 <- bplapply(1:3, runif, BPPARAM = SerialParam(RNGseed = 100))
stopifnot(
  identical(result1, result2)
)

result3 <- bplapply(1:3, runif, BPPARAM = SerialParam(RNGseed = 200))
result3
## [[1]]
## [1] 0.9757768
##
## [[2]]
## [1] 0.6525851 0.6416909
##
## [[3]]
## [1] 0.6710576 0.5895330 0.7686983

stopifnot(
  !identical(result1, result3)
)
```

Results are invariant across `*Param()`

```
result4 <- bplapply(1:3, runif, BPPARAM = SnowParam(RNGseed = 100))
stopifnot(
  identical(result1, result4)
)
```

Random Numbers in BiocParallel

```
)  
  
if (!identical(.Platform$OS.type, "windows")) {  
  result5 <- bplapply(1:3, runif, BPPARAM = MulticoreParam(RNGseed = 100))  
  stopifnot(  
    identical(result1, result5)  
  )  
}
```

Parallel backends can adjust the number of `workers` (processes performing the evaluation) and `tasks` (how elements of `X` are distributed between workers). Results are invariant to these parameters. This is illustrated with `SnowParam()`, but applies also to `MulticoreParam()`.

```
result6 <- bplapply(1:3, runif, BPPARAM = SnowParam(workers = 2, RNGseed = 100))  
result7 <- bplapply(1:3, runif, BPPARAM = SnowParam(workers = 3, RNGseed = 100))  
result8 <- bplapply(  
  1:3, runif,  
  BPPARAM = SnowParam(workers = 2, tasks = 3, RNGseed = 100)  
)  
stopifnot(  
  identical(result1, result6),  
  identical(result1, result7),  
  identical(result1, result8)  
)
```

Subsequent sections illustrate results with `SerialParam()`, but identical results are obtained with `SnowParam()` and `MulticoreParam()`.

2.2 Use with `bpiterate()`

`bpiterate()` allows parallel processing of a 'stream' of data as a series of tasks, with a task consisting of a portion of the overall data. It is useful when the data size is not known or easily partitioned into elements of a vector or list. A real use case might involve iterating through a BAM file, where a task represents successive records (perhaps 100,000 per task) in the file. Here we illustrate with a simple example – iterating through a vector `x = 1:3`

```
ITER_FUN_FACTORY <- function() {  
  x <- 1:3  
  i <- 0L  
  function() {  
    i <<- i + 1L  
    if (i > length(x))  
      return(NULL)  
    x[[i]]  
  }  
}
```

`ITER_FUN_FACTORY()` is used to create a function that, on each invocation, returns the next task (here, an element of `x`; in a real example, perhaps 100000 records from a BAM file). When there are no more tasks, the function returns `NULL`

Random Numbers in BiocParallel

```
ITER <- ITER_FUN_FACTORY()
ITER()
## [1] 1
ITER()
## [1] 2
ITER()
## [1] 3
ITER()
## NULL
```

In our simple example, `bpiterate()` is performing the same computations as `bplapply()` so the results, including the random number streams used by each task in `bpiterate()`, are the same

```
result9 <- bpiterate(
  ITER_FUN_FACTORY(), runif,
  BPPARAM = SerialParam(RNGseed = 100)
)
stopifnot(
  identical(result1, result9)
)
```

2.3 Use with `bptry()`

`bptry()` in conjunction with the `BPREDO=` argument to `bplapply()` or `bpiterate()` allows for graceful recovery from errors. Here a buggy `FUN1()` produces an error for the second element. `bptry()` allows evaluation to continue for other elements of `X`, despite the error. This is shown in the result.

```
FUN1 <- function(i) {
  if (identical(i, 2L)) {
    ## error when evaluating the second element
    stop("i == 2")
  } else runif(i)
}
result10 <- bptry(bplapply(
  1:3, FUN1,
  BPPARAM = SerialParam(RNGseed = 100, stop.on.error = FALSE)
))
result10
## [[1]]
## [1] 0.7393338
##
## [[2]]
## <remote_error in FUN(...): i == 2>
## traceback() available as 'attr(x, "traceback")'
##
```

Random Numbers in BiocParallel

```
## [[3]]
## [1] 0.1962909 0.5226640 0.6857650
##
## attr(,"BPREDSEED")
## [1] 10407 -521219301 319974304 -1596502239 177212014 -800198633
## [7] -1280217748
```

`FUN2()` illustrates the flexibility of `bpttry()` by fixing the bug when `i == 2`, but also generating incorrect results if invoked for previously correct values. The identity of the result to the original computation shows that only the error task is re-computed, and that the random number stream used by the task is identical to the original stream.

```
FUN2 <- function(i) {
  if (identical(i, 2L)) {
    ## the random number stream should be in the same state as the
    ## first time through the loop, and rnorm(i) should return
    ## same result as FUN
    runif(i)
  } else {
    ## if this branch is used, then we are incorrectly updating
    ## already calculated elements -- '0' in the output would
    ## indicate this error
    0
  }
}
result11 <- bplapply(
  1:3, FUN2,
  BPRED0 = result10,
  BPPARAM = SerialParam(RNGseed = 100, stop.on.error = FALSE)
)
stopifnot(
  identical(result1, result11)
)
```

2.4 Relationship between `RNGseed=` and `set.seed()`

The global random number stream (influenced by `set.seed()`) is ignored by *BiocParallel*, and *BiocParallel* does NOT increment the global stream.

```
set.seed(200)
value <- runif(1)

set.seed(200)
result12 <- bplapply(1:3, runif, BPPARAM = SerialParam(RNGseed = 100))
stopifnot(
  identical(result1, result12),
  identical(value, runif(1))
)
```

When `RNGseed=` is not used, an internal stream (not accessible to the user) is used and *BiocParallel* does NOT increment the global stream.

Random Numbers in BiocParallel

```
set.seed(100)
value <- runif(1)

set.seed(100)
result13 <- bplapply(1:3, runif, BPPARAM = SerialParam())
stopifnot(
  !identical(result1, result13),
  identical(value, runif(1))
)
```

2.5 bpstart() and random number streams

In all of the examples so far `*Param()` objects are passed to `bplapply()` or `bpiterate()` in the 'stopped' state. Internally, `bplapply()` and `bpiterate()` invoke `bpstart()` to establish the computational environment (e.g., starting workers for `SnowParam()`). `bpstart()` can be called explicitly, e.g., to allow workers to be used across calls to `bplapply()`.

The cluster random number stream is initiated with `bpstart()`. Thus

```
param <- bpstart(SerialParam(RNGseed = 100))
result16 <- bplapply(1:3, runif, BPPARAM = param)
bpstop(param)
stopifnot(
  identical(result1, result16)
)
```

This allows a second call to `bplapply` to represent a continuation of a random number computation – the second call to `bplapply()` results in different random number streams for each element of X .

```
param <- bpstart(SerialParam(RNGseed = 100))
result16 <- bplapply(1:3, runif, BPPARAM = param)
result17 <- bplapply(1:3, runif, BPPARAM = param)
bpstop(param)
stopifnot(
  identical(result1, result16),
  !identical(result1, result17)
)
```

2.6 Relationship between bplapply() and lapply()

The results from `bplapply()` are different from the results from `lapply()`, even with the same random number seed. This is because correctly implemented parallel random streams require use of a particular random number generator invoked in specific ways for each element of X , as outlined in the Implementation notes section.

```
set.seed(100)
result20 <- lapply(1:3, runif)
stopifnot(
  !identical(result1, result20)
)
```

3 Implementation notes

The implementation uses the L'Ecuyer-CMRG random number generator (see `?RNGkind` and `?parallel::clusterSetRNGStream` for additional details). This random number generates independent streams and substreams of random numbers. In *BiocParallel*, each call to `bpstart()` creates a new stream from the L'Ecuyer-CMRG generator. Each element in `bpapply()` or `bpiterate()` creates a new substream. Each application of FUN is therefore using the L'Ecuyer-CMRG random number generator, with a substream that is independent of the substreams of all other elements.

Within the user-supplied FUN of `bpapply()` or `bpiterate()`, it is a mistake to use `RNGkind()` to set a different random number generator, or to use `set.seed()`. This would in principle compromise the independence of the streams across elements.

4 sessionInfo()

```
## R Under development (unstable) (2021-11-10 r81171)
## Platform: x86_64-pc-linux-gnu (64-bit)
## Running under: Ubuntu 20.04.3 LTS
##
## Matrix products: default
## BLAS: /home/biocbuild/bbs-3.15-bioc/R/lib/libRblas.so
## LAPACK: /home/biocbuild/bbs-3.15-bioc/R/lib/libRlapack.so
##
## locale:
## [1] LC_CTYPE=en_US.UTF-8 LC_NUMERIC=C
## [3] LC_TIME=en_GB LC_COLLATE=C
## [5] LC_MONETARY=en_US.UTF-8 LC_MESSAGES=en_US.UTF-8
## [7] LC_PAPER=en_US.UTF-8 LC_NAME=C
## [9] LC_ADDRESS=C LC_TELEPHONE=C
## [11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C
##
## attached base packages:
## [1] stats4 stats graphics grDevices utils datasets methods
## [8] base
##
## other attached packages:
## [1] TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2
## [2] GenomicFeatures_1.47.3
## [3] AnnotationDbi_1.57.1
## [4] RNAseqData.HNRNPC.bam.chr14_0.33.0
## [5] GenomicAlignments_1.31.2
## [6] VariantAnnotation_1.41.3
## [7] Rsamtools_2.11.0
## [8] Biostrings_2.63.0
## [9] XVector_0.35.0
## [10] SummarizedExperiment_1.25.2
## [11] Biobase_2.55.0
## [12] GenomicRanges_1.47.5
## [13] GenomeInfoDb_1.31.1
```

Random Numbers in BiocParallel

```
## [14] IRanges_2.29.1
## [15] S4Vectors_0.33.5
## [16] MatrixGenerics_1.7.0
## [17] matrixStats_0.61.0
## [18] BiocGenerics_0.41.2
## [19] BiocParallel_1.29.4
##
## loaded via a namespace (and not attached):
## [1] httr_1.4.2          bit64_4.0.5         assertthat_0.2.1
## [4] BiocManager_1.30.16 highr_0.9           BiocFileCache_2.3.0
## [7] base64url_1.4      blob_1.2.2         BSgenome_1.63.3
## [10] GenomeInfoDbData_1.2.7 yaml_2.2.1         progress_1.2.2
## [13] pillar_1.6.4      RSQLite_2.2.8     backports_1.4.0
## [16] lattice_0.20-45   glue_1.5.0        digest_0.6.28
## [19] checkmate_2.0.0   htmltools_0.5.2   Matrix_1.3-4
## [22] XML_3.99-0.8      pkgconfig_2.0.3   biomaRt_2.51.1
## [25] zlibbioc_1.41.0  purrr_0.3.4       snow_0.4-4
## [28] brew_1.0-6        tibble_3.1.6      KEGGREST_1.35.0
## [31] generics_0.1.1   ellipsis_0.3.2    cachem_1.0.6
## [34] withr_2.4.2      magrittr_2.0.1    crayon_1.4.2
## [37] memoise_2.0.1    evaluate_0.14     fs_1.5.0
## [40] fansi_0.5.0      xml2_1.3.2        tools_4.2.0
## [43] data.table_1.14.2 prettyunits_1.1.1  hms_1.1.1
## [46] BiocStyle_2.23.0 BiocIO_1.5.0      lifecycle_1.0.1
## [49] stringr_1.4.0    DelayedArray_0.21.2 compiler_4.2.0
## [52] rlang_0.4.12     debugme_1.1.0     grid_4.2.0
## [55] RCurl_1.98-1.5   rjson_0.2.20      rappdirs_0.3.3
## [58] bitops_1.0-7     rmarkdown_2.11    restfulr_0.0.13
## [61] curl_4.3.2       DBI_1.1.1         R6_2.5.1
## [64] rtracklayer_1.55.2 dplyr_1.0.7       knitr_1.36
## [67] fastmap_1.1.0    bit_4.0.4         utf8_1.2.2
## [70] filelock_1.0.2   stringi_1.7.6     parallel_4.2.0
## [73] Rcpp_1.0.7       vctrs_0.3.8       png_0.1-7
## [76] tidyselect_1.1.1 dbplyr_2.1.1      batchtools_0.9.15
## [79] xfun_0.28
```